
py42

Release py42 v1.25.0

Code42 Software

Jul 27, 2022

CONTENTS

1	User Guides	1
1.1	Getting started with py42	1
1.2	py42 Basics	3
1.3	Executing Searches	6
1.4	Departing Employees	9
1.5	High Risk Employees	9
1.6	Get Active Devices From an Organization	10
1.7	View or Modify device settings	11
1.8	View or Modify organization settings	13
1.9	Configuring Backup Sets	14
1.10	Cases	15
1.11	Trust Settings	16
1.12	V2 File Events	17
1.13	User Risk Profile	18
1.14	Watchlists	19
2	Method Documentation	21
2.1	Alert Rules	21
2.2	Alerts	23
2.3	Archive	33
2.4	Audit Logs	36
2.5	Backup Sets	38
2.6	Cases	39
2.7	Shared Constants	42
2.8	Detection Lists	44
2.9	Devices	49
2.10	Device Settings	52
2.11	Exceptions	54
2.12	File Event Queries - V1 (DEPRECATED)	64
2.13	File Event Queries - V2	105
2.14	Legal Hold	178
2.15	Orgs	182
2.16	Org Settings	184
2.17	Response	186
2.18	Security Data	187
2.19	Shared Query Filters	188
2.20	Trusted Activities	192
2.21	User Risk Profiles	193
2.22	Users	196
2.23	Util	199

2.24 Watchlists	200
3 Features	207
4 Content	209
Python Module Index	211
Index	213

USER GUIDES

1.1 Getting started with py42

- *Licensing*
- *Installation*
- *Authentication*
- *Troubleshooting and Support*

1.1.1 Licensing

This project uses the [MIT License](#).

1.1.2 Installation

You can install py42 from PyPI, from source, or from distribution.

From PyPI

The easiest and most common way is to use `pip`:

```
pip install py42
```

To install a previous version of py42 via `pip`, add the version number. For example, to install version 0.4.1, you would enter:

```
pip install py42==0.4.1
```

Visit the [project history](#) on PyPI to see all published versions.

From source

Alternatively, you can install py42 directly from [source code](#):

```
git clone https://github.com/code42/py42.git
```

When it finishes downloading, from the root project directory, run:

```
python setup.py install
```

From distribution

If you want create a .tar ball for installing elsewhere, run this command from the project's root directory:

```
python setup.py sdist
```

After it finishes building, the .tar ball will be located in the newly created dist directory. To install it, enter:

```
pip install py42-[VERSION].tar.gz
```

1.1.3 Authentication

Important: py42 currently only supports token-based authentication.

To initialize the `py42.sdk.SDKClient`, you must provide your credentials (basic authentication). If you are writing a script, we recommend using a secure password storage library, such as `keyring`, for retrieving passwords. However, subsequent requests use JWT authentication.

If your account uses [two-factor authentication](#), include the time-based one-time password (TOTP) when you initialize the `py42.sdk.SDKClient`. You can also provide a callable object that returns a TOTP. If you pass a callable, it will be called whenever a new TOTP is required to renew the authentication token.

1.1.4 Troubleshooting and support

Debug mode

Debug mode may be useful if you are trying to determine if you are experiencing permissions issues. When debug mode is on, py42 logs HTTP request data to the console's stderr. Use the following as a guide for how to turn on debug mode in py42:

```
import py42.sdk
import py42.settings
import logging

py42.settings.debug.level = logging.DEBUG
```

To provide your own logger, just replace `py42.settings.debug.logger`:

```
custom_logger = logging.getLogger("my_app")
handler = logging.FileHandler("my_app.log")
custom_logger.addHandler(handler)

py42.settings.debug.logger = custom_logger
```

File an issue on GitHub

If you are experiencing an issue with py42, you can create a *New issue* at the [project repository](#). See the [Github guide on creating an issue](#) for more information.

Contact Code42 Support

If you don't have a GitHub account and are experiencing issues, contact [Code42 support](#).

1.1.5 What's next?

Learn the basics by following the py42 *Basics guide*.

1.2 py42 Basics

This guide explains the basic concepts of py42. Learning these basics can help you gain confidence in writing your own scripts.

- *py42 Basics*
 - *Initialization*
 - *Paging*
 - *Py42Response*
 - *Dates*
 - *Exceptions*

The examples from this guide are intended as blanket concepts that apply to other areas in py42. For example, paging over users and devices works the same way as over departing employees and alerts.

1.2.1 Initialization

To use py42, you must initialize the SDK:

```
import py42.sdk

sdk = py42.sdk.from_local_account("https://console.us.code42.com", "my_username", "my_
↳password")
```

If your account uses [two-factor authentication](#), include the time-based one-time password:

```
sdk = py42.sdk.from_local_account("https://console.us.code42.com", "my_username", "my_
↳password", totp="123456")
```

Alternatively, define a function that returns the time-based one-time password:

```
def promptForPassword():
    return input("Please input your authentication code: ")

sdk = py42.sdk.from_local_account("https://console.us.code42.com", "my_username", "my_
↳password", totp=promptForPassword)
```

Alternatively, define a function that returns the auth token based on user's authentication approach

```
import json
import requests
from requests.auth import HTTPBasicAuth
def jwt_provider():
    res = requests.get(
        'https://console.us.code42.com/api/v3/auth/jwt?useBody=true',
        auth=HTTPBasicAuth('username', 'password')
    )
    res_json = json.loads(res.text)
    return res_json['data']['v3_user_token']

sdk_client = py42.sdk.from_jwt_provider("https://console.us.code42.com", jwt_provider)
```

1.2.2 Paging

py42 clients often have a method with the name (or name prefix) `get_all` which handles iterating over pages of response items. Here are some examples:

- `py42.sdk.devices.get_all()`
- `py42.sdk.users.get_all()`
- `py42.sdk.legalhold.get_all_matters()`
- `py42.sdk.orgs.get_all()`

These methods each return a [python generator](#). Looping over the pages returned by the generator gives you access to the actual list of items. Use the code snippet below as an example for working with generators and paging in py42:

```
# Prints the username and notes for all departing employees

pages = sdk.detectionlists.departing_employee.get_all() # pages has 'generator' type
for page in pages: # page has 'Py42Response' type
    employees = page["items"]
    for employee in employees:
        username = employee["userName"]
        notes = employee["notes"]
        print(f"{employee}: {notes}")
```

Each page is a typical py42 response. The next section covers what you can do with `Py42Response` objects.

1.2.3 Py42Response

py42 clients return Py42Response objects which are intentionally similar to `requests.Response` objects. The Py42Response class hides unneeded metadata found on the raw `requests.Response.text` (which is available as `Py42Response.raw_text`), making it easier to get the most useful parts of the response. Also, the object is subscriptable, meaning you can access it with keys or indices (depending on the JSON type underneath data on Code42 API responses):

```
user = response["users"][0]
item = list_response[0]["itemProperty"]
```

To see all the keys on a response, observe its `.text` attribute. By printing the response, you essentially print its text property:

```
# Prints details about the response from a getting a detection list user.

response = sdk.detectionlists.get_user("test.user@example.com")
print(response) # JSON as Dictionary - same as print(response.text)
print(response.raw_text) # Raw API response
print(response.status_code) # 200
cloud_usernames = response["cloudUsernames"]
# if the response might not contain the property you're looking for,
# check to see if it exists with data.get
cloud_usernames = response.data.get("cloudUsernames")
if cloud_usernames:
    print(cloud_usernames)
```

1.2.4 Dates

Most dates in py42 support `POSIX timestamps` for date parameters. As an example, see `:class:sdk.queries.fileevents.filters.event_filter.EventTimestamp` which is used for querying file events by their event timestamp.

```
from datetime import datetime, timedelta

import py42.sdk
import py42.util
from py42.sdk.queries.fileevents.file_event_query import FileEventQuery
from py42.sdk.queries.fileevents.filters.event_filter import EventTimestamp

sdk = py42.sdk.from_local_account("https://console.us.code42.com", "my_username", "my_
↳password")

# Get the epoch date 14 days in the past
query_date = datetime.utcnow() - timedelta(days=14)
query_epoch = (query_date - datetime.utcfromtimestamp(0)).total_seconds()

query = FileEventQuery(EventTimestamp.on_or_after(query_epoch))

response = sdk.securitydata.search_file_events(query)

# Print all the md5 Checksums from every file event within the past 14 days.
```

(continues on next page)

(continued from previous page)

```
file_events = response["fileEvents"]
for event in file_events:
    print(event["md5Checksum"])
```

1.2.5 Exceptions

py42 throws some of its own exceptions when failures occur. py42 exceptions are found in the `py42.sdk.exceptions` module. Some of the available exceptions are:

- `Py42ForbiddenError`: (403) With your currently signed-in account, you don't have the necessary permissions to perform the action you were trying to do.
- `Py42UnauthorizedError`: (401) The username or password is incorrect.
- `Py42InternalServerError`: (500) Likely an unhandled issue on our servers.

For example, you are making a `create_sdk()` function and want to print a more user-friendly message when the provided username or password are incorrect:

```
import keyring
import py42.sdk
from py42.exceptions import Py42UnauthorizedError

def create_sdk(username):
    """Tries to initialize SDK. If unauthorized, prints message and exits."""
    try:
        password = keyring.get_password("my_program", username)
        return py42.sdk.from_local_account("www.authority.example.com", username,
        ↪password)
    except Py42UnauthorizedError:
        print("Invalid username or password.")
        exit(1)
```

1.3 Executing Searches

py42 features a powerful, flexible query system for quickly and easily searching file events and alerts. This guide explains the syntax for building queries and executing searches.

1.3.1 Search File Events

To query for V2 file events, import the required modules and classes and create the SDK:

```
import py42.sdk
from py42.sdk.queries.fileevents.v2 import *
sdk = py42.sdk.from_local_account("https://console.us.code42.com", "my_username", "my_
↪password")
```

V1 events are **DEPRECATED**. If you need to build V1 queries, the corresponding V1 modules can be imported in a similar manner.

```
from py42.sdk.queries.fileevents.v1 import *
```

For more details on updating to V2 file events, see the *V2 File Events Guide*

You must create `query_filter.FilterGroup` objects to conduct searches. Filter groups have a type (in the form of a class), such as `email.Sender`, and an operator (in the form of a function), such as `is_in()`. Some example filter groups look like this:

```
from py42.sdk.queries.fileevents.v2 import *
source_email_filter = source.EmailSender.is_in(["test.user@example.com", "test.
↪ sender@example.com"])
event_action_filter = event.Action.exists()
destination_ip_filter = destination.PrivateIpAddress.eq("127.0.0.1")
```

It is also possible to create `query_filter.FilterGroups` from raw JSON. For example:

```
raw_json = """{"filterClause":"AND","filters":[{"display":null,"value":"P1D","operator":
↪ "WITHIN_THE_LAST","term":"eventTimestamp"}]}"""
json_dict = json.loads(raw_json)
filter_group = FilterGroup.from_dict(json_dict)
```

Important: The filter terms and query objects for file events have changed for V2. Make sure you're using the appropriate modules to construct your queries.

There are two operators when building `file_event_query.FileEventQuery` objects: `any()` and `all()`.

`any()` gets results where at least one of the filters is true and `all()` gets results where all of the filters are true.

```
any_query = FileEventQuery.any(source_email_filter, event_action_filter)
all_query = FileEventQuery.all(event_action_filter, destination_ip_filter)
```

For convenience, the `FileEventQuery` constructor works the same way as `all()`:

```
all_query = FileEventQuery(event_action_filter, destination_ip_filter)
```

You can put filters in an iterable and unpack them (using the `*` operator) in a `FileEventQuery`. This is a common use case for programs that need to conditionally build up filters:

```
# Conditionally appends filters to a list for crafting a query

filter_list = []
if need_trusted:
    filter_list.append(risk.Trusted.is_true())
elif need_user_emails:
    user_email_filter = user.Email.is_in(["foo@example.com", "baz@example.com"])
    filter_list.append(user_email_filter)
# Notice the use of the '*' operator to unpack filter_list
query = FileEventQuery(*filter_list)
```

To execute the search, use `securitydata.SecurityModule.search_file_events()`:

```
# Prints the MD5 hashes of all the events where files were read by browser or other app.
```

(continues on next page)

(continued from previous page)

```

query = FileEventQuery(event.Action.eq(event.Action.APPLICATION_READ))
response = sdk.securitydata.search_file_events(query)
file_events = response["fileEvents"]
for event in file_events:
    print(event["file"]["hash"]["md5"])

```

If the number of events exceeds 10,000 against a query, use `securitydata.SecurityModule.search_all_file_events()`:

```

query = FileEventQuery(event.Action.eq(event.Action.APPLICATION_READ))
response = sdk.securitydata.search_all_file_events(query)
file_events = response["fileEvents"]
for event in file_events:
    print(event["file"]["hash"]["md5"])
while response["nextPgToken"] is not None:
    response = sdk.securitydata.search_all_file_events(query, page_token=response[
↪ "nextPgToken"])
    file_events = response["fileEvents"]
    for event in file_events:
        print(event["file"]["hash"]["md5"])

```

1.3.2 Search Alerts

Alert searches work in a very similar way to file event searches.

To start, import the filters and query object:

```

from py42.sdk.queries.alerts.filters import *
from py42.sdk.queries.alerts.alert_query import AlertQuery

# Create a query for getting all open alerts with severity either 'High' or 'Medium'.

filters = [AlertState.eq(AlertState.OPEN), Severity.is_in([Severity.HIGH, Severity.
↪ MEDIUM])]
query = AlertQuery(*filters)

```

To execute the search, use the `alerts.AlertClient.search()` method:

```

# Prints the actor property from each search result
response = sdk.alerts.search(query)
alerts = response["alerts"]
for alert in alerts:
    print(alert["actor"])

```

1.4 Departing Employees

1.4.1 Add or Remove Users From the Departing Employees List

Use py42 to quickly and easily manage users on the Departing Employees list. This guide describes how to add users to and remove users from the Departing Employees list.

To add a user to the Departing Employees list, all you need to know is the user's Code42 user UID.

To get the user UID based on username:

```
user = sdk.users.get_by_username("username")
uid = user["users"][0]["userId"]
```

`user_id` below refers to the user UID.

```
from py42.exceptions import Py42UserAlreadyAddedError

# Add the departing employee
try:
    response = sdk.detectionlists.departing_employee.add(user_id, departure_date)
except Py42UserAlreadyAddedError:
    print("The user is already on the Departing Employee list.")
```

Important: If the user is already in the Departing Employees list, you will get an `py42.exceptions.Py42UserAlreadyAddedError`.

To remove a user from the Departing Employees list:

```
sdk.detectionlists.departing_employee.remove(user_id)
```

For complete details, see [Departing Employee](#).

1.5 High Risk Employees

1.5.1 Add or Remove Users From the High Risk Employee List

Use py42 to quickly and easily manage users on the High Risk Employee list. This guide describes how to add users to and remove users from the High Risk Employee list.

To add a user to the High Risk Employees list, all you need to know is the user's Code42 user UID.

To get the user UID based on username:

```
user = sdk.users.get_by_username("username")
uid = user["users"][0]["userId"]
```

`user_id` below refers to the user UID.

```
# Add the high risk employee
response = sdk.detectionlists.high_risk_employee.add(user_id)
```

Important: If the user is already in the High Risk Employee list, you will get a `py42.exceptions.Py42UserAlreadyAddedError`.

To remove a user from the High Risk Employee list:

```
sdk.detectionlists.high_risk_employee.remove(user_id)
```

1.5.2 Add or Remove Risk Factors From Users

You can add/remove risk factor tags from a high risk user programmatically using the `add_user_risk_tags()` and `remove_user_risk_tags()` methods in the `detectionlists` module. Both methods take the `user_id` of a high risk employee, and a list of tags that you want to add/remove:

```
from py42.constants import RiskTags

tag_list = [RiskTags.CONTRACT_EMPLOYEE, RiskTags.ELEVATED_ACCESS_PRIVILEGES]

# Add the risk tags
response = sdk.detectionlists.add_user_risk_tags(user_id, tag_list)

# Remove the risk tags
response = sdk.detectionlists.remove_user_risk_tags(user_id, tag_list)
```

Constants for Risk tags are available at [Risk Tags](#)

For complete details, see [High Risk Employee](#).

1.6 Get Active Devices From an Organization

Using py42, you can retrieve information about the active devices in your organization for various use cases. For example, you might want to create a simple report that illustrates how many devices are running each operating system in your Code42 environment. Your user role determines which devices you have access to.

To begin, initialize the SDK:

```
import py42.sdk
sdk = py42.sdk.from_local_account("https://console.us.code42.com", "my_username", "my_
↳password")
```

1.6.1 The `DeviceClient.get_all()` Function

Next, use `py42.sdk.clients.devices.DeviceClient` to search for active devices in your organization. Use the `active` parameter on the `get_all()` method.

The `active` parameter has three different states:

- If `active` is set to `True`, you will only get active devices.
- If `active` is set to `False`, you will only get deactivated devices.
- If you don't use `active`, you will get all devices.

The `get_all()` function returns a generator of pages of devices. The devices returned by `get_all()` are based on the role and permissions of the user authenticating the SDK.

1.6.2 Examples

Here is an example using `get_all()` to get all active devices in your organization(s):

```
# For each active device in your organization, print its GUID and operating system

response = sdk.devices.get_all(active=True)
for page in response:
    devices = page["computers"]
    for device in devices:
        print(f"{device['guid']} - {device['osName']}")
```

As another example, you might have the Cross Org Administrator role and want to get all the active devices for just one of your organizations. First use `orgs.get_all()` to return a list of all current organizations and find the UID of the desired organization. Then use the organization's UID to get information on its devices.

```
# For each active device in the engineering organization, print its GUID and operating
↪ system.

# Assume there is only one org named "Engineering"
for page in sdk.orgs.get_all():
    for org in page["orgs"]:
        if org["orgName"] == "Engineering":
            engineering_org_uid = org["orgUid"]
            break

response = sdk.devices.get_all(active=True, org_uid=engineering_org_uid)
for page in response:
    devices = page["computers"]
    for device in devices:
        print(f"{device['guid']} - {device['osName']}")
```

We got the org UID from the engineering organization and then passed it as a parameter to the method to get all the devices, thus getting all the active devices in the engineering organization.

1.7 View or Modify device settings

Use py42 to easily view and update the settings for devices with the `DeviceSettings` and `IncydrDeviceSettings` objects for Crashplan and Incydr customers, respectively.

The *Device Settings* objects are wrappers around the complex nested dict that the Code42 Computer API endpoint expects, providing helper properties that can be used to get/set values, without having to know the underlying nested structure.

To get started, create a `DeviceSettings` or `IncydrDeviceSettings` object for a given device guid. The `get_settings()` method will create the appropriate object automatically based on the corresponding service running on the device:

```
device_settings = sdk.devices.get_settings(908765043021)
```

Details on which settings can be updated and which are non-modifiable can be found in the method documentation [Device Settings](#). These may differ between services. Some common non-modifiable settings fields are accessible as read-only properties on the object:

```
>>> device_settings.computer_id
12345
>>> device_settings.guid
908765043021
>>> device_settings.org_id
42
>>> device_settings.user_id
494842
>>> device_settings.version
1525200006800
```

And to change settings, in most cases you can just assign new values to the corresponding attribute:

```
>>> device_settings.notes
"A note on this device."
>>> device_settings.notes = "A note on this device."
```

The below section provides more detail on managing backup settings for Crashplan customers.

For convenience and logging purposes, all changes are tracked in the `.changes` property of the `DeviceSettings` objects.

```
>>> device_settings.changes
{'destinations': '{"43": 'PROe Cloud, US <LOCKED>'} -> {'43': 'PROe Cloud, US <LOCKED>',
↪ '632540230984925185': 'PROe Cloud, US - West'}}}
```

Once you’ve made all the desired changes to a `DeviceSettings` object, you can post the changes by passing it to the `sdk.devices.update_settings` method, which returns a `Py42Response` object with the server response:

```
>>> sdk.devices.update_settings(device_settings)
<Py42Response [status=200, data={'active': True, 'address': '192.168.74.144:4247',
↪ 'alertState': 0, 'alertStates': ['OK'], ...}]>
```

1.7.1 Crashplan

Backup settings

The available backup destinations for a device can be found on the read-only `availableDestinations` property:

```
>>> device_settings.available_destinations
{'632540230984925185': 'PROe Cloud, US - West', '43': 'PROe Cloud, US'}
```

Because device backup settings are tied to a given “Backup Set”, of which there could be more than one, the `DeviceSettings.backup_sets` property returns a list of `BackupSet` wrapper classes that help manage backup configuration settings.

```
>>> device_settings.backup_sets
[<BackupSet: id: 1, name: 'Primary - Backup Set'>, <BackupSet: id: 298010138, name:
↪ 'Secondary (large files) - Backup Set'>]
```


See the *Configuring Backup Sets* guide for details on managing backup set settings.

Advanced usage

Because `DeviceSettings` is a subclass of `UserDict` with added attributes/methods to help easily access/modify setting values, the underlying dict that ultimately gets posted to the server is stored on the `.data` attribute of `DeviceSettings` instances, and a `DeviceSettings` object otherwise behaves like a normal dict.

If there is a setting that is not yet implemented by py42 as a helper method/attribute, those values can be manually managed by treating the `DeviceSettings` object as a normal dict.

For example, setting the “backup status email frequency” value to only send every 10 days, via the helper attribute:

```
>>> device_settings.backup_status_email_frequency_days = 10
```

And doing the same thing by setting the value manually on the underlying dict:

```
>>> device_settings["settings"]["serviceBackupConfig"]["backupStatusEmailFreqInMinutes"] =  
↩= "14400"
```

The benefits of the py42 helper attributes/methods is that the values mimic what the Console UI uses (in this case days vs the minutes expected by the API endpoint), so you don’t have to worry about doing conversions yourself. But since the underlying dict is accessible, you aren’t constrained to only what py42 has so far implemented.

Warning: When manually changing values on the underlying dict, those aren’t registered in the `.changes` property and thus won’t be captured in debug logs by the `sdk.devices.update_settings()` method.

1.8 View or Modify organization settings

Use py42 to easily view and update the settings for organizations with the `OrgSettings` object.

The `OrgSettings` object is a wrapper around the complex dicts that the Code42 `Org` and `OrgSettings` API endpoints expect, providing helper properties that can be used to get/set values, without having to know the underlying complexity of the APIs.

To get started, create a `OrgSettings` object for a given `org_id`:

```
org_settings = sdk.orgs.get_settings(org_id)
```

Some common non-modifiable details about the org are accessible as read-only properties:

```
>>> org_settings.org_id  
424345  
>>> org_settings.registration_key  
'XXXX-YYYY-AAAA-BBBB'
```

And to change settings, in most cases you can just assign new values to the appropriate attribute:

```
>>> org_settings.name  
'Admin Test Org'  
>>> org_settings.name = "Admin Production Org"
```

Configuring device backup defaults for an org is very similar to [configuring backup settings for an individual device](#), the `OrgSetting` object has a `.device_defaults` property that contains a `DeviceSettingsDefaults` object providing convenience attributes/methods for configuring defaults for all devices in the org.

```
>>> org_settings.device_defaults.backup_status_email_enabled
True
>>> org_settings.device_defaults.warning_alert_days
7
>>> org_settings.device_defaults.warning_alert_days = 14
```

Backup set configurations are contained in the `.device_defaults.backup_sets` property, and return a list of `BackupSet` wrapper classes for each set configured for the org:

```
>>> org_setting.device_defaults.backup_sets
[<BackupSet: id: 1, name: 'Production Environment - Backup Set'>]
```

See the [Configuring Backup Sets](#) guide for details on managing backup set settings.

Once you’ve made all the desired changes to an `OrgSettings` object, you can post the changes by passing it to the `sdk.orgs.update_settings()` method.

Because there are two endpoints that manage different organization settings values (`/api/Org` and `/api/OrgSettings`), the `sdk.orgs.update_settings()` method might make up to two requests to the server, depending on what `OrgSetting` values were actually modified. Because of the potential for two response values, `orgs.update_settings()` returns a `OrgSettingsResponse` namedtuple with the responses from both endpoints (if applicable), along with an error flag that indicates if any errors occurred. If an error occurred, the `org_response` or `org_settings_response` attributes will contain the `Py42Exception` that was raised instead of the `Py42Response`.

```
>>> sdk.orgs.update_settings(org_settings)
OrgSettingsResponse(error=False, org_response=<Py42Response [status=200, data={'active': True, 'blocked': False, 'classification': 'BASIC', 'configInheritanceCounts': {}, ...}]>, org_settings_response=None)
```

1.9 Configuring Backup Sets

Code42 devices’ backup configurations are managed by “Backup Sets”, which can be configured either at the individual device level, or set as default configurations at the org level.

The `py42.BackupSet` class can be used to view and change the settings of a given backup set.

`BackupSet` instances are automatically constructed by `py42` and attached to their corresponding `DeviceSettings` or `OrgSettings` objects, and stored in the `.backup_sets` properties (`DeviceSettings.backup_sets` or `OrgSettings.device_defaults.backup_sets`).

The following examples will use an individual device’s backup set, but all the methods/attributes are the same when configuring an org device default backup set.

Create a `DeviceSettings` object and get the primary backup set object:

```
>>> device_settings
>>> device_settings.backup_sets
[<BackupSet: id: 1, name: 'Primary - Backup Set'>, <BackupSet: id: 298010138, name:
  ↳ 'Secondary (large files) - Backup Set'>]
>>> bs = device_settings.backup_sets[0]
```

View/update destinations:

```
>>> bs.destinations
{'43': 'PROe Cloud, US <LOCKED>'}
>>>
>>> bs.add_destination(587738803578339329)
>>> bs.remove_destination(43)
>>> bs.destinations
{'632540230984925185': 'PROe Cloud, US - West'}
```

View/update backup file selection/exclusion lists:

```
>>> bs.included_files
['C:/Users/Bob/']
>>> bs.excluded_files
[]
>>>
>>> bs.included_files.append("D:/")
>>> bs.excluded_files.append("C:/Users/Bob/Downloads")
```

You can also replace the existing list with a new one:

```
>>> bs.included_files = ["C:/Users/", "D:/"]
```

View/update filename exclusion patterns:

```
>>> bs.filename_exclusions
['.*/*Photos/']
>>> bs.filename_exclusions.append(".*/*Pictures/")
```

1.10 Cases

Use py42 to quickly and easily manage cases.

1.10.1 Create, View, or Modify Cases

To get started, create a new case.

```
case = sdk.cases.create("new-case")
```

Once you've created a case, or if you're working with an existing one, you can use the case's **number** to view details about that case.

```
# view details about a case
case = sdk.cases.get(case_number)
```

You can also access a case by its **number** to update its details. For example, to update a case's status to **CLOSED**:

```
from py42.constants import CaseStatus

response = sdk.cases.update(case_number, status=CaseStatus.CLOSED)
```

Case statuses can be set to either OPEN or CLOSED. Constants for these statuses are available at [Case Status](#).

1.10.2 View Details for all OPEN Cases

This section describes how to view the details of all cases with an OPEN status.

```
from py42.constants import CaseStatus

response = sdk.cases.get_all(status=CaseStatus.OPEN)

for page in response:
    cases = page["cases"]
    for case in cases:
        print(case)
```

For complete details, see [Cases](#).

1.11 Trust Settings

Use py42 to quickly and easily manage trusted activities and resources, including domains and Slack workspaces.

1.11.1 Create, View, or Modify Trusted Activities

To get started, create a new trusted activity resource.

```
from py42.constants import TrustedActivityType

response = sdk.trustedactivities.create(TrustedActivityType.DOMAIN, "test-domain.com")
```

Constants for the each type of trusted activity are available at [Trusted Activity Type](#)

Once you've created a trusted activity, or if you're working with an existing one, you can use the trusted activity's `resourceId` to view details about it.

```
response = sdk.trustedactivities.get(resource_id)
```

You can also access a trusted activity by its `resourceId` to update its details. For example, to add a description to a trusted activity:

```
response = sdk.trustedactivities.update(resource_id, description="This is a trusted_↵
↵activity.")
```

To clear the description of a trusted activity, pass an empty string `description=""` to the `update()` method.

Important: If you try to create with the same value as an already existing activity, you will get a `py42.exceptions.Py42TrustedActivityConflictError`.

1.11.2 View Details for all Trusted Domains

This section describes how to view the details of all trusted activities of the type DOMAIN.

```
from py42.constants import TrustedActivityType

response = sdk.trustedactivities.get_all(type=TrustedActivityType.DOMAIN)

for page in response:
    resources = page["trustResources"]
    for resource in resources:
        print(resource)
```

For complete details, see *Trusted Activities*.

1.12 V2 File Events

Warning: V1 file events, saved searches, and queries are **deprecated**.

For details on the updated File Event Model, see the V2 File Events API documentation on the [Developer Portal](#).

1.12.1 Querying file events

To query for V2 file events, import the V2 filter modules and FileEventQuery class with:

```
from py42.sdk.queries.fileevents.v2 import *
```

Using the FileEventQuery and filter classes, construct a query and search for file events as detailed in the *Executing Searches Guide*.

1.12.2 Saved Searches

All saved search methods functions have an additional optional use_v2=False argument. If set to True, the saved search module will ingest from the V2 saved search APIs. The use_v2 argument defaults to False and the V1 saved searches are still available.

For example, use the following to view all saved searches with the new V2 apis:

```
import py42.sdk

sdk = py42.sdk.from_local_account("https://console.us.code42.com", "my_username", "my_
↳password")
sdk.securitydata.savedsearches.get(use_v2=True)
```

Retrieving saved searches with V2 settings enabled will retrieve existing V1 saved search queries translated to the V2 model. Existing V1 queries that cannot be properly converted to V2 will be omitted from the response.

1.13 User Risk Profile

A user risk profile is created for each user. Use py42 to manage these user risk profiles.

1.13.1 Update a User Risk Profile

Determine the user ID to manage a user's risk profile. For example, the following code uses the `get_username()` method to find the ID of a user with the username `test.user@code42.com`.

```
response = sdk.userriskprofile.get_username()

user_id = response.data["userId"]
```

Use the user ID with the `update()` method to manage a user risk profiles' `startDate`, `endDate`, and `notes` fields.

The `startDate` and `endDate` arguments expect a format of `YYYY-MM-DD` or a `datetime` object.

The following code updates the departure date of the user risk profile to March 1st, 2025:

```
# update the user risk profile
sdk.userriskprofile.update(user_id, end_date="2025-03-01", notes="Updated the departure_
↳date.")

# view updated user details
py42.util.print_response(sdk.userriskprofile.get(user_id))
```

If you want to clear a field, provide an empty string to the corresponding argument.

For example, the following code will clear the `endDate` and `notes` fields:

```
# clear fields on the user risk profile
sdk.userriskprofile.update(user_id, end_date="", notes="")
```

1.13.2 Manage Cloud Aliases

Each user risk profile starts with a default alias of their code42 username and can have one additional cloud alias. Use the `UserRiskProfileClient` to manage these aliases.

Use `add_cloud_aliases()` to assign additional cloud aliases to a user:

```
user_id = "test-user-123"
cloud_aliases = "test-user@email.com"
sdk.userriskprofile.add_cloud_aliases(user_id, cloud_aliases)

# view updated user cloud aliases
py42.util.print_response(sdk.userriskprofile.get(user_id))
```

Remove cloud aliases in a similar manner using the `delete_cloud_aliases()` method. Provide a list of values to add or remove multiple aliases at once.

```
sdk.userriskprofile.delete_cloud_aliases(user_id, ["test-user@email.com",
↳"username@email.com"])
```

1.14 Watchlists

Use py42 to create and manage watchlists.

Watchlists have replaced the Departing Employees and High Risk Employees detections lists. See the [Code42 support documentation](#) on managing watchlists for more information.

1.14.1 Create a Watchlist

```
from py42.constants import WatchlistType

watchlist = sdk.watchlists.create(WatchlistType.DEPARTING)

# store the id of the new watchlist
watchlist_id = watchlist.data["watchlistId"]
```

Watchlist types are available as constants in the `WatchlistType` class.

1.14.2 View Watchlist Details

There are several methods to view different details about watchlists.

```
import py42.util

# Get information on all current watchlists
response = sdk.watchlists.get_all()

# print all information to the console
for page in response:
    py42.util.print_response(page)
```

Once you have the watchlist's ID, use the following methods to see more details:

```
# To get watchlist details
sdk.watchlists.get(watchlist_id)

# To see all included users
sdk.watchlists.get_all_included_users(watchlist_id)
```

1.14.3 Manage Users on Watchlists

Use the `included_users` methods to manage individual users who are explicitly included on watchlists.

Py42 allows you to reference a watchlist either by its ID or by its type. If adding individual users to a watchlist with the `add_included_users_by_watchlist_type()` method, py42 will create the watchlist for you if it doesn't already exist.

For example, the following code demonstrates two methods to add users to the Departing watchlist:

```
user_ids = ["test-user-123", "test-user-456"]

# METHOD 1: add by watchlist id
sdk.watchlists.add_included_users_by_watchlist_id(user_ids, watchlist_id)

# METHOD 2: add by watchlist type
from py42.constants import WatchlistType

# this method will create the DEPARTING watchlist for you if it doesn't already exist
sdk.watchlists.add_included_users_by_watchlist_type(user_ids, WatchlistType.DEPARTING)

# View your updated watchlist users
sdk.watchlists.get_all_included_users(watchlist_id)
```

The `delete_included_users_by_watchlist_id()` and `delete_included_users_by_watchlist_type()` methods can be used similarly to remove users from a watchlist.

- *Getting Started*
- *Basics*
- *Executing Searches*
- *Departing Employee*
- *High Risk Employee*
- *Get Active Devices From An Organization*
- *Device Settings*
- *Org Settings*
- *Backup Sets*
- *Cases*
- *Trust Settings*
- *V2 File Events*
- *User Risk Profiles*
- *Watchlists*

METHOD DOCUMENTATION

2.1 Alert Rules

class `py42.clients.alertrules.AlertRulesClient`(*alerts_service, alert_rules_service*)

Bases: `object`

[Rest Documentation](#)

add_user(*rule_id, user_id*)

Update alert rule criteria to add a user and all their aliases to an alert rule. A rule's user list can either be inclusive (only the users on the list can generate alerts) or exclusive (everyone can generate alerts, except users on the list). This method will include or exclude based on the rule configuration.

[Rest Documentation](#)

Parameters

- **rule_id** (*str*) – Observer Id of a rule to be updated.
- **user_id** (*str*) – The Code42 `userId` of the user to add to the alert

Returns `py42.response.Py42Response`

property `cloudshare`

A collection of methods for managing cloud sharing alert rules.

Returns `py42.services.alertrules.cloud_share.CloudShareService`

property `exfiltration`

A collection of methods for managing exfiltration alert rules.

Returns `py42.services.alertrules.exfiltration.ExfiltrationService`

property `filetypemismatch`

A collection of methods for managing file type mismatch alert rules.

Returns `py42.services.alertrules.file_type_mismatch.FileTypeMismatchService`

get_all(*sort_key='CreatedAt', sort_direction='DESC'*)

Fetch all available rules.

Parameters

- **sort_key** (*str, optional*) – Sort results based by field. Defaults to 'CreatedAt'.
- **sort_direction** (*str, optional*) – ASC or DESC. Constants available at `py42.constants.SortDirection`. Defaults to "DESC"

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of rules.

Return type generator

get_all_by_name(*rule_name*)

Search for matching rules by name.

Parameters **rule_name** (*str*) – Rule name to search for, case insensitive search.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of rules with the given name.

Return type generator

get_by_observer_id(*observer_id*)

Get the rule with the matching observer ID.

Parameters **observer_id** (*str*) – The observer ID of the rule to return.

Returns `py42.response.Py42Response`

get_page(*sort_key='CreatedAt', sort_direction='DESC', page_num=1, page_size=None*)

Gets a page of alert rules. Note that you can use `page_size` here the same way as other methods that have a `page_size` parameter in py42. However, under the hood, it subtracts one from the given page size in the implementation as the Code42 alerts API expected the start page to be zero while the rest of the Code42 APIs expect the start page to be one.

Parameters

- **sort_key** (*str, optional*) – Sort results based by field. Defaults to “CreatedAt”.
- **sort_direction** (*str, optional*) – ASC or DESC. Constants available at `py42.constants.SortDirection`. Defaults to “DESC”.
- **page_num** (*int, optional*) – The page number to get. Defaults to 1.
- **page_size** (*int, optional*) – The number of items per page. Defaults to `py42.settings.items_per_page`.

Returns `py42.response.Py42Response`

remove_all_users(*rule_id*)

Update alert rule criteria to remove all users the from the alert rule.

[Rest Documentation](#)

Parameters **rule_id** (*str*) – Observer rule Id of a rule to be updated.

Returns `py42.response.Py42Response`

remove_user(*rule_id, user_id*)

Update alert rule criteria to remove a user and all their aliases from an alert rule. A rule’s user list can either be inclusive (only the users on the list can generate alerts) or exclusive (everyone can generate alerts, except users on the list). This method will include or exclude based on the rule configuration.

[Rest Documentation](#)

Parameters

- **rule_id** (*str*) – Observer rule Id of a rule to be updated.
- **user_id** (*str*) – The Code42 `userId` of the user to remove from the alert

Returns *py42.response.Py42Response*

2.1.1 Exfiltration rules

class `py42.services.alertrules.ExfiltrationService(connection, tenant_id)`

Bases: `py42.services.BaseService`

get(*rule_id*)

Fetch exfiltration alert rule by rule id.

Parameters *rule_id* (*str*) – Observer rule Id of a rule to be fetched.

Returns *py42.response.Py42Response*

2.1.2 Cloud share rules

class `py42.services.alertrules.CloudShareService(connection, tenant_id)`

Bases: `py42.services.BaseService`

get(*rule_id*)

Fetch cloud share alert rule by rule id.

Parameters *rule_id* (*str*) – Observer rule Id of a rule to be fetched.

Returns *py42.response.Py42Response*

2.1.3 File type mismatch rules

class `py42.services.alertrules.FileTypeMismatchService(connection, tenant_id)`

Bases: `py42.services.BaseService`

get(*rule_id*)

Fetch File type mismatch alert rules by rule id.

Parameters *rule_id* (*str*) – Observer rule Id of a rule to be fetched.

Returns *py42.response.Py42Response*

2.2 Alerts

class `py42.clients.alerts.AlertsClient(alert_service, alert_rules_client)`

Bases: `object`

A client to expose alert API.

[Rest Documentation](#)

get_aggregate_data(*alert_id*)

Gets alert summary with details about observations.

Parameters *alert_id* (*str*) – Gets the details for the alert with the given ID.

Returns *py42.response.Py42Response*

get_all_alert_details(query)

Helper method that combines `search_all_pages()` and `get_details()` methods to get alert objects with alert “observations” details populated. Returns an iterator of alert detail objects.

Note: automatically overrides the `page_size` property on the query object to limit search to 100 results per page, as that is the max that `get_details()` can request at a time.

Parameters `query` ([py42.sdk.queries.alerts.alert_query.AlertQuery](#)) – An alert query.

Returns An object that iterates over alert detail items.

Return type generator

get_details(alert_ids)

Gets the details for the alerts with the given IDs, including the file event query that, when passed into a search, would result in events that could have triggered the alerts.

[Rest Documentation](#)

Parameters `alert_ids` (`str` or `list[str]`) – The identification number(s) of the alerts for which you want to get details for. Note: The alerts backend accepts a maximum of 100 alerts per request.

Returns A response containing the alert details.

Return type [py42.response.Py42Response](#)

reopen(alert_ids, reason=None)

Reopens the resolved alerts with the given IDs.

Parameters

- **alert_ids** (`str` or `list[str]`) – The identification number(s) for the alerts to reopen. Note: The alerts backend accepts a maximum of 100 alerts per request.
- **reason** (`str`, *optional*) – The reason the alerts are reopened. Defaults to None.

Returns [py42.response.Py42Response](#)

resolve(alert_ids, reason=None)

Resolves the alerts with the given IDs.

Parameters

- **alert_ids** (`str` or `list[str]`) – The identification number(s) for the alerts to resolve. Note: The alerts backend accepts a maximum of 100 alerts per request.
- **reason** (`str`, *optional*) – The reason the alerts are now resolved. Defaults to None.

Returns [py42.response.Py42Response](#)

property rules

A collection of methods for managing alert rules.

Returns `py42.services.alertrules.AlertRulesClient`

search(query, page_num=1, page_size=None)

Searches alerts using the given [py42.sdk.queries.alerts.alert_query.AlertQuery](#).

[Rest Documentation](#)**Parameters**

- **query** ([py42.sdk.queries.alerts.alert_query.AlertQuery](#)) – An alert query. See the [Executing Searches User Guide](#) to learn more about how to construct a query.

- **page_num** (*int, optional*) – The page number to get. Defaults to 1.
- **page_size** (*int, optional*) – The number of items per page. Defaults to `py42.settings.items_per_page`.

Returns A response containing the alerts that match the given query.

Return type `py42.response.Py42Response`

search_all_pages(*query*)

Searches alerts using the given `py42.sdk.queries.alerts.alert_query.AlertQuery`.

Rest Documentation

Parameters **query** (`py42.sdk.queries.alerts.alert_query.AlertQuery`) – An alert query. See the *Executing Searches User Guide* to learn more about how to construct a query.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of alerts that match the given query.

Return type generator

update_note(*alert_id, note*)

Updates an alert's note.

Parameters

- **alert_id** (*str*) – The identification number of an alert to add a note to.
- **note** (*str*) – A note to attach to the alert. Must be less than 2000 characters. Defaults to None.

Returns `py42.response.Py42Response`

update_state(*status, alert_ids, note=None*)

Updates the status of alerts.

Parameters

- **status** (*str*) – Status to set from OPEN, RESOLVED, PENDING, IN_PROGRESS
- **alert_ids** (*str or list[str]*) – The identification number(s) for the alerts to reopen. Note: The alerts backend accepts a maximum of 100 alerts per request.
- **note** (*str, optional*) – A note to attach to the alerts. Must be less than 2000 characters. Defaults to None.

Returns `py42.response.Py42Response`

2.2.1 Filter Classes

The following classes construct filters for file event queries. Each filter class corresponds to an alert detail. Call the appropriate classmethod on your desired filter class with the value you want to match and it will return a `FilterGroup` object that can be passed to `AlertQuery`'s `all()` or `any()` methods to create complex queries that match multiple filter rules.

See *Executing Searches* for more on building search queries.

class `py42.sdk.queries.alerts.filters.alert_filter.Actor`

Bases: `py42.sdk.queries.alerts.util.AlertQueryFilterStringField`

Class that filters alerts based on the username that originated the event(s) that triggered the alert.

classmethod contains(*value*)

Creates a *FilterGroup* for filtering results where the value with key `self._term` contains the given value. Useful for creating CONTAINS filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters *value* (*str*) – The value used to match on.

Returns *FilterGroup*

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod is_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_contains(*value*)

Creates a *FilterGroup* for filtering results where the value with key `self._term` does not contain the given value. Useful for creating DOES_NOT_CONTAIN filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters *value* (*str*) – The value used to exclude on.

Returns *FilterGroup*

classmethod not_eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters *value* (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.alerts.filters.alert_filter.AlertState

Bases: *py42.sdk.queries.query_filter.QueryFilterStringField*, *py42.choices.Choices*

Class that filters alerts based on alert state.

Available options are:

- `AlertState.OPEN`
- `AlertState.DISMISSED`
- `AlertState.PENDING`
- `AlertState.IN_PROGRESS`

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.alerts.filters.alert_filter.DateObserved

Bases: `py42.sdk.queries.alerts.util.AlertQueryFilterTimestampField`

Class that filters alerts based on the timestamp the alert was triggered.

classmethod in_range(start_value, end_value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- **start_value** (*str or int or float or datetime*) – The start value used to filter results.
- **end_value** (*str or int or float or datetime*) – The end value used to filter results.

Returns *FilterGroup*

classmethod on_or_after(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term`` is on or after the provided ``value.

Parameters `value (str or int or float or datetime)` – The value used to filter results.

Returns *FilterGroup*

classmethod `on_or_before(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters `value` (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod `on_same_day(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters `value` (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

class `py42.sdk.queries.alerts.filters.alert_filter.Description`

Bases: `py42.sdk.queries.alerts.util.AlertQueryFilterStringField`

Class that filters alerts based on rule description text.

classmethod `contains(value)`

Creates a *FilterGroup* for filtering results where the value with key `self._term` contains the given value. Useful for creating CONTAINS filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters `value` (*str*) – The value used to match on.

Returns *FilterGroup*

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_contains(value)`

Creates a *FilterGroup* for filtering results where the value with key `self._term` does not contain the given value. Useful for creating DOES_NOT_CONTAIN filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters `value` (*str*) – The value used to exclude on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.alerts.filters.alert_filter.RuleId`

Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`

Class that filters alerts based on rule identifier.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.alerts.filters.alert_filter.RuleName`

Bases: `py42.sdk.queries.alerts.util.AlertQueryFilterStringField`

Class that filters alerts based on rule name.

classmethod `contains(value)`

Creates a *FilterGroup* for filtering results where the value with key `self._term` contains the given value. Useful for creating CONTAINS filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters `value` (*str*) – The value used to match on.

Returns *FilterGroup*

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_contains(value)`

Creates a [FilterGroup](#) for filtering results where the value with key `self._term` does not contain the given value. Useful for creating DOES_NOT_CONTAIN filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters `value` (*str*) – The value used to exclude on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.alerts.filters.alert_filter.RuleSource`

Bases: [py42.sdk.queries.query_filter.QueryFilterStringField](#), `py42.choices.Choices`

Class that filters alerts based on rule source.

Available options are:

- `RuleSource.ALERTING`
- `RuleSource.DEPARTING_EMPLOYEE`
- `RuleSource.HIGH_RISK_EMPLOYEE`

classmethod `choices()`

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (*list*)

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.alerts.filters.alert_filter.RuleType

Bases: *py42.sdk.queries.query_filter.QueryFilterStringField*, *py42.choices.Choices*

Class that filters alerts based on rule type.

Available options are:

- `RuleType.ENDPOINT_EXFILTRATION`
- `RuleType.CLOUD_SHARE_PERMISSIONS`
- `RuleType.FILE_TYPE_MISMATCH`

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.alerts.filters.alert_filter.**Severity**

Bases: *py42.sdk.queries.query_filter.QueryFilterStringField*, *py42.choices.Choices*

Class that filters alerts based on severity.

Available options are:

- Severity.CRITICAL
- Severity.HIGH
- Severity.MODERATE
- Severity.LOW

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod is_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters *value* (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.alerts.alert_query.**AlertQuery**(*args, **kwargs)

Bases: *py42.sdk.queries.BaseQuery*

Helper class for building Code42 Alert queries.

An *AlertQuery* instance's `all()` and `any()` take one or more *FilterGroup* objects to construct a query that can be passed to the `AlertService.search()` method. `all()` returns results that match all of the provided filter criteria, `any()` will return results that match any of the filters.

For convenience, the *AlertQuery* constructor does the same as `all()`.

Usage example:

```
state_filter = AlertState.eq(AlertState.OPEN)
rule_name_filter = RuleName.contains("EmailRule")
query = AlertQuery.all(state_filter, rule_name_filter)
```

2.3 Archive

class `py42.clients.archive.ArchiveClient`(*archive_accessor_factory*, *archive_service*)

Bases: `object`

A module for getting information about backup archives on storage nodes along with functionality for streaming a file from backup.

get_all_by_device_guid(*device_guid*)

Gets archive information for a device.

Parameters *device_guid* (*str*) – The GUID for the device.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of archives.

Return type `generator`

get_all_device_restore_history(*days*, *device_id*)

Gets all restore jobs from the past given days for the device with the given ID.

Parameters

- **days** (*int*) – Number of days of restore history to retrieve.
- **device_id** (*int*) – The identification number of the device to get restore history for.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of restore history.

Return type `generator`

get_all_org_cold_storage_archives(*org_id*, *include_child_orgs=True*,
sort_key='archiveHoldExpireDate', *sort_dir='asc'*)

Returns a detailed list of cold storage archive information for a given org ID.

Parameters

- **org_id** (*str*) – The ID of a Code42 organization.
- **include_child_orgs** (*bool*, *optional*) – Determines whether cold storage information from the Org's children is also returned. Defaults to True.
- **sort_key** (*str*, *optional*) – Sets the property by which the returned results will be sorted. Choose from `archiveHoldExpireDate`, `orgName`, `mountPointName`, `archiveBytes`, and `archiveType`. Defaults to `archiveHoldExpireDate`.
- **sort_dir** (*str*, *optional*) – Sets the order by which `sort_key` should be sorted. Choose from `asc` or `desc`. Defaults to `asc`.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of cold storage archive information.

Return type `generator`

get_all_org_restore_history(*days*, *org_id*)

Gets all restore jobs from the past given days for the organization with the given ID.

Parameters

- **days** (*int*) – Number of days of restore history to retrieve.
- **org_id** (*int*) – The identification number of the organization to get restore history for.

Returns An object that iterates over [py42.response.Py42Response](#) objects that each contain a page of restore history.

Return type generator

get_all_user_restore_history(*days*, *user_id*)

Gets all restore jobs from the past given days for the user with the given ID.

Parameters

- **days** (*int*) – Number of days of restore history to retrieve.
- **user_id** (*int*) – The identification number of the user to get restore history for.

Returns An object that iterates over [py42.response.Py42Response](#) objects that each contain a page of restore history.

Return type generator

get_backup_sets(*device_guid*, *destination_guid*)

Gets all backup set names/identifiers referring to a single destination for a specific device. [Learn more about backup sets.](#)

Parameters

- **device_guid** (*str*) – The GUID of the device to get backup sets for.
- **destination_guid** (*str*) – The GUID of the destination containing the archive to get backup sets for.

Returns A response containing the backup sets.

Return type [py42.response.Py42Response](#)

get_by_archive_guid(*archive_guid*)

Gets single archive information by GUID.

Parameters **archive_guid** (*str*) – The GUID for the archive.

Returns A response containing archive information.

Return type [py42.response.Py42Response](#)

stream_from_backup(*file_paths*, *device_guid*, *destination_guid=None*, *archive_password=None*, *encryption_key=None*, *show_deleted=None*, *file_size_calc_timeout=10*, *backup_set_id=None*)

Streams a file from a backup archive to memory. This method uses the same endpoint as restoring from Console and therefore has all the same considerations.

[Support Documentation](#)**Parameters**

- **file_paths** (*str* or *list of str*) – The path or list of paths to the files or directories in the archive.
- **device_guid** (*str*) – The GUID of the device the file belongs to.

- **destination_guid** (*str, optional*) – The GUID of the destination that stores the backup of the file. If None, it will use the first destination GUID it finds for your device. 'destination_guid' may be useful if the file is missing from one of your destinations or if you want to optimize performance. Defaults to None.
- **archive_password** (*str or None, optional*) – The password for the archive, if password-protected. This is only relevant to users with archive key password security. Defaults to None.
- **encryption_key** (*str or None, optional*) – A custom encryption key for decrypting an archive's file contents, necessary for restoring files. This is only relevant to users with custom key archive security. Defaults to None.
- **show_deleted** (*bool, optional*) – Set to True to include deleted files when restoring a directory. Defaults to None.
- **file_size_calc_timeout** (*int, optional*) – Set to limit the amount of seconds spent calculating file sizes when crafting the request. Set to 0 or None to ignore file sizes altogether. Defaults to 10.
- **backup_set_id** (*str, optional*) – The ID of the backup set restore from (only useful for V3 archives). If not supplied, the default backup set (id=1) will be used if it exists, otherwise the first in the list of existing backup sets will be used.

Returns A response containing the streamed content.

Return type `py42.response.Py42Response`

Usage example:

```
stream_response = sdk.archive.stream_from_backup("/full/path/to/file.txt",
↪ "1234567890")
with open("/path/to/save/file/to", "wb") as f:
    for chunk in stream_response.iter_content(chunk_size=128):
        if chunk:
            f.write(chunk)
```

In certain cases, you will have to unzip the results:

```
import zipfile
with zipfile.ZipFile("downloaded_directory.zip", "r") as zf:
    zf.extractall(".")
```

stream_to_device (*file_paths, device_guid, accepting_device_guid, restore_path, destination_guid=None, archive_password=None, encryption_key=None, show_deleted=None, overwrite_existing_files=False, file_size_calc_timeout=10, backup_set_id=None*)

Streams a file from a backup archive to a specified device.

Parameters

- **file_paths** (*str or list of str*) – The path or list of paths to the files or directories in the archive.
- **device_guid** (*str*) – The GUID of the device the file belongs to.
- **accepting_device_guid** (*str*) – The GUID of the device accepting the restore.
- **restore_path** (*str, optional*) – The path on the accepting device where the restore will be saved. Alternatively, pass in the value `ORIGINAL_LOCATION` to restore the file to the original location, which may be the case if you are replacing a device.

- **destination_guid** (*str, optional*) – The GUID of the destination that stores the backup of the file. If None, it will use the first destination GUID it finds for your device. ‘destination_guid’ may be useful if the file is missing from one of your destinations or if you want to optimize performance. Defaults to None.
- **archive_password** (*str or None, optional*) – The password for the archive, if password-protected. This is only relevant to users with archive key password security. Defaults to None.
- **encryption_key** (*str or None, optional*) – A custom encryption key for decrypting an archive’s file contents, necessary for restoring files. This is only relevant to users with custom key archive security. Defaults to None.
- **show_deleted** (*bool, optional*) – Set to True to include deleted files when restoring a directory. Defaults to None.
- **overwrite_existing_files** (*bool, optional*) – to overwrite any existing files with the restored data. If False (the default), any existing files that match a path being restored will first get renamed.
- **file_size_calc_timeout** (*int, optional*) – Set to limit the amount of seconds spent calculating file sizes when crafting the request. Set to 0 or None to ignore file sizes altogether. Defaults to 10.
- **backup_set_id** (*str, optional*) – The ID of the backup set restore from (only useful for V3 archives). If not supplied, the default backup set (id=1) will be used if it exists, otherwise the first in the list of existing backup sets will be used.

Returns [*py42.response.Py42Response*](#).

update_cold_storage_purge_date(*archive_guid, purge_date*)
Updates the cold storage purge date for a specified archive.

Parameters

- **archive_guid** (*str*) – The identification number of the archive that should be updated
- **purge_date** (*str*) – The date on which the archive should be purged in yyyy-MM-dd format

Returns the response from the ColdStorage API.

Return type [*py42.response.Py42Response*](#)

2.4 Audit Logs

class `py42.clients.auditlogs.AuditLogsClient`(*audit_log_service*)
Bases: `object`

[Rest documentation](#)

get_all(*begin_time=None, end_time=None, event_types=None, user_ids=None, usernames=None, user_ip_addresses=None, affected_user_ids=None, affected_usernames=None, **kwargs*)
Retrieve audit logs, filtered based on given arguments. [Rest Documentation](#)

Parameters

- **begin_time** (*int or float or str or datetime, optional*) – Timestamp in milliseconds or str format “yyyy-MM-dd HH:MM:SS” or a datetime instance. Defaults to None.

- **end_time** (*int or float or str or datetime, optional*) – Timestamp in milliseconds or str format “yyyy-MM-dd HH:MM:SS” or a datetime instance. Defaults to None.
- **event_types** (*str or list, optional*) – A str or list of str of valid event types. Defaults to None.
- **user_ids** (*str or list, optional*) – A str or list of str of Code42 userUids. Defaults to None.
- **usernames** (*str or list, optional*) – A str or list of str of Code42 usernames. Defaults to None.
- **user_ip_addresses** (*str or list, optional*) – A str or list of str of user ip addresses. Defaults to None.
- **affected_user_ids** (*str or list, optional*) – A str or list of str of affected Code42 userUids. Defaults to None.
- **affected_usernames** (*str or list, optional*) – A str or list of str of affected Code42 usernames. Defaults to None.

Returns An object that iterates over [py42.response.Py42Response](#) objects that each contain a page of audit logs.

Return type generator

get_page(*page_num=1, page_size=None, begin_time=None, end_time=None, event_types=None, user_ids=None, usernames=None, user_ip_addresses=None, affected_user_ids=None, affected_usernames=None, **kwargs*)

Retrieve a page of audit logs, filtered based on given arguments.

Note: *page_num* here can be used same way as other methods that have a *page_num* parameter in py42. However, under the hood, it subtracts one from the given *page_num* in the implementation as the Code42 Audit-Logs API expects the start page to be zero. [Rest Documentation](#)

Parameters

- **page_num** (*int, optional*) – The page number to get. Defaults to 1.
- **page_size** (*int, optional*) – The number of items per page. Defaults to `py42.settings.items_per_page`.
- **begin_time** (*int or float or str or datetime, optional*) – Timestamp in milliseconds or str format “yyyy-MM-dd HH:MM:SS” or a datetime instance. Defaults to None.
- **end_time** (*int or float or str or datetime, optional*) – Timestamp in milliseconds or str format “yyyy-MM-dd HH:MM:SS” or a datetime instance. Defaults to None.
- **event_types** (*str or list, optional*) – A str or list of str of valid event types. Defaults to None.
- **user_ids** (*str or list, optional*) – A str or list of str of Code42 userUids. Defaults to None.
- **usernames** (*str or list, optional*) – A str or list of str of Code42 usernames. Defaults to None.
- **user_ip_addresses** (*str or list, optional*) – A str or list of str of user ip addresses. Defaults to None.

- **affected_user_ids**(*str or list, optional*) – A str or list of str of affected Code42 userUids. Defaults to None.
- **affected_usernames**(*str or list, optional*) – A str or list of str of affected Code42 usernames. Defaults to None.

Returns [*py42.response.Py42Response*](#)

2.5 Backup Sets

class `py42.clients.settings.device_settings.BackupSet(settings_manager, backup_set_dict)`

Bases: `collections.UserDict`

Helper class for managing device backup sets and Org device default backup sets.

add_destination(*destination_guid*)

Adds a destination to be used by this backup set. Raises a `Py42Error` if the supplied destination guid is not available to the parent device/org.

Parameters *destination_guid*(*str, int*) – The globally unique identifier of the destination to be added.

property destinations

Returns a dict of the destinations used for backup for the backup set. Dict keys are the destination guides, values are the destination names.

property excluded_files

Returns the list of files/folders excluded from the backup selection. Items can be added/removed from this list via normal list methods, or assigning a new list of files to this attribute to replace the existing one.

property filename_exclusions

Returns the list of regex patterns used to exclude file paths from the backup selection. Items can be added/removed from this list via normal list methods, or assigning a new list of patterns to this attribute to replace the existing one.

property included_files

Returns the list of files/folders included in the backup selection. Items can be added/removed from this list via normal list methods, or assigning a new list of files to this attribute to replace the existing one.

lock_destination(*destination_guid*)

Locks an in-use destination, disallowing the device owner from removing this destination from their backup. Raises a `Py42Error` if the supplied destination guid is not in use on this backup set, or not available to the parent device/org.

property locked

Indicates whether the backup set as a whole is locked. If True, individual settings for this backup set (except for Destination settings), cannot be modified.

remove_destination(*destination_guid*)

Removes a destination from use by this backup set.

Parameters *destination_guid*(*str, int*) – The globally unique identifier of the destination to be removed.

unlock_destination(*destination_guid*)

Unlocks an in-use destination, allowing the device owner to remove this destination from their backup. Raises a [*Py42Error*](#) if the supplied destination guid is not in use on this backup set, or not available to the parent device/org.

2.6 Cases

class `py42.clients.cases.CaseStatus`

Bases: `py42.choices.Choices`

Constants available for setting the status of a case.

- `OPEN`
- `CLOSED`

class `py42.clients.cases.CasesClient(cases_service, cases_file_event_service)`

Bases: `object`

A client to expose cases API.

[Rest documentation](#)

create(*name*, *subject=None*, *assignee=None*, *description=None*, *findings=None*)

Creates a new case. [Rest documentation](#)

Parameters

- **name** (*str*) – Name of the case.
- **subject** (*str*, *optional*) – User UID of a subject of a case.
- **assignee** (*str*, *optional*) – User UID of the assignee.
- **description** (*str*, *optional*) – Description of the case
- **findings** (*str*, *optional*) – Observations of the case.

Returns `py42.response.Py42Response`

export_summary(*case_number*)

Provides case summary to download as a PDF file. [Rest documentation](#)

Parameters **case_number** (*int*) – Case number of the case.

Returns `py42.response.Py42Response`

property `file_events`

A collection of methods for managing file events associated with a given case.

Returns `py42.services.casesfileevents.CasesFileEventsService`

get(*case_number*)

Retrieve case details by case number. [Rest documentation](#)

Parameters **case_number** (*int*) – Case number of the case.

Returns `py42.response.Py42Response`

get_all(*name=None*, *status=None*, *min_create_time=None*, *max_create_time=None*, *min_update_time=None*, *max_update_time=None*, *subject=None*, *assignee=None*, *page_size=100*, *sort_direction='asc'*, *sort_key='number'*, ***kwargs*)

Gets all cases. [Rest documentation](#)

Parameters

- **name** (*str*, *optional*) – Filter results by case name, matches partial names. Defaults to `None`.
- **status** (*str*, *optional*) – Filter results by case status. `OPEN` or `CLOSED`. Defaults to `None`. Constants available at `py42.constants.CaseStatus`.

- **min_create_time** (*str or int or float or datetime, optional*) – Filter results by case creation time, start time. str format %Y-%m-%d %H:%M:%S. Defaults to None.
- **max_create_time** (*str or int or float or datetime, optional*) – Filter results by case creation time, end time. str format %Y-%m-%d %H:%M:%S. Defaults to None.
- **min_update_time** (*str or int or float or datetime, optional*) – Filter results by last updated time, start time. str format %Y-%m-%d %H:%M:%S. Defaults to None.
- **max_update_time** (*str or int or float or datetime, optional*) – Filter results by last updated time, end time. str format %Y-%m-%d %H:%M:%S. Defaults to None.
- **subject** (*str, optional*) – Filter results based on User UID of a subject of a case. Defaults to None.
- **assignee** (*str, optional*) – Filter results based on User UID of an assignee of a case. Defaults to None.
- **page_size** (*int, optional*) – Number of results to return per page. Defaults to 100.
- **sort_direction** (*str, optional*) – The direction on which to sort the response, based on the corresponding sort key. *asc* or *desc*. Defaults to *asc*.
- **sort_key** (*str, optional*) – Values on which the response will be sorted. Defaults to “number”. Available options are *name*, *number*, *createdAt*, *updatedAt*, *status*, *assigneeUsername*, *subjectUsername*.

Returns An object that iterates over [py42.response.Py42Response](#) objects that each contain a page of cases.

Return type generator

get_page(*page_num, name=None, status=None, min_create_time=None, max_create_time=None, min_update_time=None, max_update_time=None, subject=None, assignee=None, page_size=100, sort_direction='asc', sort_key='number', **kwargs*)

Gets individual page of cases. [Rest documentation](#)

Parameters

- **page_num** (*int*) – The page number to request.
- **name** (*str, optional*) – Filter results by case name, matches partial names. Defaults to None.
- **status** (*str, optional*) – Filter results by case status. OPEN or CLOSED. Defaults to None. Constants available at [py42.constants.CaseStatus](#).
- **min_create_time** (*str or int or float or datetime, optional*) – Filter results by case creation time, start time. str format %Y-%m-%d %H:%M:%S. Defaults to None.
- **max_create_time** (*str or int or float or datetime, optional*) – Filter results by case creation time, end time. str format %Y-%m-%d %H:%M:%S. Defaults to None.
- **min_update_time** (*str or int or float or datetime, optional*) – Filter results by last updated time, start time. str format %Y-%m-%d %H:%M:%S. Defaults to None.

- **max_update_time** (*str or int or float or datetime, optional*) – Filter results by last updated time, end time. *str* format *%Y-%m-%d %H:%M:%S*. Defaults to *None*.
- **subject** (*str, optional*) – Filter results based on User UID of a subject of a case. Defaults to *None*.
- **assignee** (*str, optional*) – Filter results based on User UID of an assignee of a case. Defaults to *None*.
- **page_size** (*int, optional*) – Number of results to return per page. Defaults to 100.
- **sort_direction** (*str, optional*) – The direction on which to sort the response, based on the corresponding sort key. *asc* or *desc*. Defaults to *asc*.
- **sort_key** (*str, optional*) – Values on which the response will be sorted. Defaults to “number”. Available options are *name*, *number*, *createdAt*, *updatedAt*, *status*, *assigneeUsername*, *subjectUsername*.

Returns [*py42.response.Py42Response*](#)

update(*case_number*, *name=None*, *subject=None*, *assignee=None*, *description=None*, *findings=None*, *status=None*)

Updates case details for the given case number. [Rest documentation](#)

Parameters

- **case_number** (*int*) – Case number of the case.
- **name** (*str, optional*) – Name of the case. Defaults to *None*.
- **subject** (*str, optional*) – A subject of the case. Defaults to *None*.
- **assignee** (*str, optional*) – User UID of the assignee. Defaults to *None*.
- **description** (*str, optional*) – Description of the case. Defaults to *None*.
- **findings** (*str, optional*) – Notes on the case. Defaults to *None*.
- **status** (*str, optional*) – Status of the case. *OPEN* or *CLOSED*. Defaults to *None*. Constants available at [*py42.constants.CaseStatus*](#).

Returns [*py42.response.Py42Response*](#)

2.6.1 Cases File Events

class `py42.services.casesfileevents.CasesFileEventsService(connection)`

Bases: `py42.services.BaseService`

add(*case_number*, *event_id*)

Adds an event to the case.

Parameters

- **case_number** (*int*) – Case number of the case.
- **event_id** (*str*) – Event id to add to the case.

Returns [*py42.response.Py42Response*](#)

delete(*case_number*, *event_id*)

Deletes an event from the case.

Parameters

- **case_number** (*int*) – Case number of the case.
- **event_id** (*str*) – Event id to remove from case.

Returns [*py42.response.Py42Response*](#)

get(*case_number*, *event_id*)

Gets information of a specified event from the case.

Parameters

- **case_number** (*int*) – Case number of the case.
- **event_id** (*str*) – Event id to fetch from the case.

Returns [*py42.response.Py42Response*](#)

get_all(*case_number*)

Gets all events associated with the given case.

Parameters **case_number** (*int*) – Case number of the case.

Returns [*py42.response.Py42Response*](#)

2.7 Shared Constants

class `py42.constants.SortDirection`

Bases: `py42.choices.Choices`

Constants available to set Code42 request *sort_direction* when sorting returned lists in responses.

- ASC
- DESC

class `py42.constants.CaseStatus`

Bases: `py42.choices.Choices`

Constants available for setting the status of a case.

- OPEN
- CLOSED

class `py42.constants.RiskTags`

Bases: `py42.choices.Choices`

Deprecated. Use [*WatchlistsClient*](#) and [*UserRiskProfileClient*](#) instead. Constants available as risk tags for [*add_user_risk_tags\(\)*](#) and [*remove_user_risk_tags\(\)*](#).

- FLIGHT_RISK
- HIGH_IMPACT_EMPLOYEE
- ELEVATED_ACCESS_PRIVILEGES
- PERFORMANCE_CONCERNS
- SUSPICIOUS_SYSTEM_ACTIVITY
- POOR_SECURITY_PRACTICES
- CONTRACT_EMPLOYEE

class py42.constants.TrustedActivityType

Bases: py42.choices.Choices

Constants available for setting the type of a trusted activity.

- DOMAIN
- SLACK

class py42.constants.DepartingEmployeeFilters

Bases: py42.services.detectionlists._DetectionListFilters, py42.choices.Choices

Deprecated. Use [WatchlistsClient](#) and [UserRiskProfileClient](#) instead. Constants available for filtering Departing Employee search results.

- OPEN
- EXFILTRATION_30_DAYS
- EXFILTRATION_24_HOURS
- LEAVING_TODAY

class py42.constants.HighRiskEmployeeFilters

Bases: py42.services.detectionlists._DetectionListFilters, py42.choices.Choices

Deprecated. Use [WatchlistsClient](#) and [UserRiskProfileClient](#) instead. Constants available for filtering High Risk Employee search results.

- OPEN
- EXFILTRATION_30_DAYS
- EXFILTRATION_24_HOURS

class py42.constants.WatchlistType

Bases: py42.choices.Choices

Constants available for setting the type of watchlist.

- CONTRACT_EMPLOYEE
- DEPARTING_EMPLOYEE
- ELEVATED_ACCESS_PRIVILEGES
- FLIGHT_RISK
- HIGH_IMPACT_EMPLOYEE
- NEW_EMPLOYEE
- PERFORMANCE_CONCERNS
- POOR_SECURITY_PRACTICES
- SUSPICIOUS_SYSTEM_ACTIVITY"

2.8 Detection Lists

Detection lists have been deprecated. Use [Watchlists](#) instead.

```
class py42.clients.detectionlists.DetectionListsClient(user_profile_service,
                                                         departing_employee_service,
                                                         high_risk_employee_service)
```

Bases: object

Deprecated. Use :class: `py42.clients.watchlists.WatchlistsClient` and [UserRiskProfileClient](#) instead. Rest documentation <<https://developer.code42.com/api/#tag/Detection-Lists>>`__

add_user_cloud_alias(user_id, alias)

Deprecated. Use `userriskprofile.add_cloud_aliases()` instead. Add a cloud alias to a user. [Rest Documentation](#)

Parameters

- **user_id** (*str or int*) – The `userId` of the user whose alias you want to update.
- **alias** (*str*) – The alias to be added.

Returns [py42.response.Py42Response](#)

add_user_risk_tags(user_id, tags)

Deprecated. Use `watchlists` instead. Add one or more risk factor tags. [Rest Documentation](#)

Parameters

- **user_id** (*str or int*) – The `userId` of the user whose risk factor tag(s) you want to update.
- **tags** (*str or list of str*) – A single tag or multiple tags in a list to be added. For example: "tag1" or ["tag1", "tag2"].

Constants available at [py42.constants.RiskTags](#)

Returns [py42.response.Py42Response](#)

create_user(username)

Deprecated. Used to create a detection list profile for a user, but now that happens automatically. Thus, this method instead returns the response from an API call that gets the user's profile.

Parameters **username** (*str*) – The Code42 username of the user.

Returns [py42.response.Py42Response](#)

get_user(username)

Deprecated. Use `userriskprofile.get_by_username()` instead. Get user details by username. [Rest Documentation](#)

Parameters **username** (*str*) – The Code42 username of the user.

Returns [py42.response.Py42Response](#)

get_user_by_id(user_id)

Deprecated. Use `userriskprofile.get_by_id()` instead. Get user details by user_id. [Rest Documentation](#)

Parameters **user_id** (*str or int*) – The Code42 `userId` of the user.

Returns [py42.response.Py42Response](#)

refresh_user_scim_attributes(user_id)

Deprecated. Refresh SCIM attributes of a user. [Rest Documentation](#)

Parameters `user_id` (*str or int*) – The `userId` of the user whose attributes you wish to refresh.

Returns `py42.response.Py42Response`

remove_user_cloud_alias(*user_id, alias*)

Deprecated. Use `userriskprofile.delete_cloud_aliases()` instead. Remove a cloud alias from a user. [Rest Documentation](#)

Parameters

- **user_id** (*str or int*) – The `userId` of the user whose alias needs to be removed.
- **alias** (*str*) – The alias to be removed.

Returns `py42.response.Py42Response`

remove_user_risk_tags(*user_id, tags*)

Deprecated. Use `watchlists` instead. Remove one or more risk factor tags. [Rest Documentation](#)

Parameters

- **user_id** (*str or int*) – The `userId` of the user whose risk factor tag(s) needs you want to remove.
- **tags** (*str or list of str*) – A single tag or multiple tags in a list to be removed. For example: "tag1" or ["tag1", "tag2"].

Constants available at `py42.constants.RiskTags`

Returns `py42.response.Py42Response`

update_user_notes(*user_id, notes*)

Deprecated. Use `userriskprofile.update()` instead. Add or update notes related to the user. [Rest Documentation](#)

Parameters

- **user_id** (*str or int*) – The `userId` of the user whose notes you want to update.
- **notes** (*str*) – User profile notes.

Returns `py42.response.Py42Response`

2.8.1 Departing Employees

class `py42.services.detectionlists.departing_employee.DepartingEmployeeFilters`

Bases: `py42.services.detectionlists._DetectionListFilters`, `py42.choices.Choices`

Deprecated. Use `WatchlistsClient` and `UserRiskProfileClient` instead. Constants available for filtering Departing Employee search results.

- OPEN
- EXFILTRATION_30_DAYS
- EXFILTRATION_24_HOURS
- LEAVING_TODAY

class `py42.services.detectionlists.departing_employee.DepartingEmployeeService`(*session,*

user_context,
user_profile_service)

Bases: `py42.services.BaseService`

Deprecated. Use [WatchlistsClient](#) and [UserRiskProfileClient](#) instead. A service for interacting with Code42 Departing Employee APIs.

add(*user_id*, *departure_date=None*)

Deprecated. Use watchlists instead. Adds a user to the Departing Employees list. [REST Documentation](#)

Raises a `Py42UserAlreadyAddedError` when a user already exists in the Departing Employee detection list.

Parameters

- **user_id** (*str or int*) – The Code42 `userId` of the user you want to add to the departing employees list.
- **departure_date** (*str or datetime, optional*) – Date in yyyy-MM-dd format or instance of `datetime`. Date is treated as UTC. Defaults to `None`.

Returns [py42.response.Py42Response](#)

get(*user_id*)

Deprecated. Use `userriskprofile.get_by_id()` instead. Gets departing employee data of a user. [REST Documentation](#)

Parameters **user_id** (*str or int*) – The Code42 `userId` of the user.

Returns [py42.response.Py42Response](#)

get_all(*filter_type='OPEN', sort_key='CREATED_AT', sort_direction='DESC', page_size=100*)

Deprecated. Use `userriskprofile.get_all()`. Gets all Departing Employees.

Parameters

- **filter_type** (*str, optional*) – Constants available at [py42.constants.DepartingEmployeeFilters](#). Defaults to “OPEN”.
- **sort_key** (*str, optional*) – Sort results based by field. Defaults to “CREATED_AT”.
- **sort_direction** (*str, optional*) – ASC or DESC. Defaults to “DESC”.
- **page_size** (*int, optional*) – The number of departing employees to return per page. Defaults to 100.

Returns An object that iterates over [py42.response.Py42Response](#) objects that each contain a page of departing employees.

Return type generator

get_page(*page_num, filter_type='OPEN', sort_key='CREATED_AT', sort_direction='DESC', page_size=100*)

Deprecated. Use `userriskprofile.get_page()` instead. Gets a single page of Departing Employees.

Parameters

- **page_num** (*int*) – The page number to request.
- **filter_type** (*str, optional*) – Constants available at [py42.constants.DepartingEmployeeFilters](#). Defaults to “OPEN”.
- **sort_key** (*str, optional*) – Sort results based by field. Defaults to “CREATED_AT”.
- **sort_direction** (*str, optional*) – ASC or DESC. Defaults to “DESC”.
- **page_size** (*int, optional*) – The number of departing employees to return per page. Defaults to 100.

Returns [py42.response.Py42Response](#)

remove(*user_id*)

Deprecated. Use watchlists instead. Removes a user from the Departing Employees list. [REST Documentation](#)

Parameters *user_id* (*str* or *int*) – The Code42 userUid of the user.

Returns *py42.response.Py42Response*

set_alerts_enabled(*alerts_enabled=True*)

Deprecated. Enable or disable email alerting on Departing Employee exposure events. [REST Documentation](#)

Parameters *alerts_enabled* (*bool*) – Set alerting to on (True) or off (False). Defaults to True.

Returns *py42.response.Py42Response*

update_departure_date(*user_id*, *departure_date*)

Deprecated. Use `userriskprofile.update()` instead. Add or modify details of an existing Departing Employee case. [REST Documentation](#)

Parameters

- **user_id** (*str*) – The Code42 userUid of the user.
- **departure_date** (*str* or *datetime*) – Date in yyyy-MM-dd format or instance of `datetime`. Date is treated as UTC.

Returns *py42.response.Py42Response*

2.8.2 High Risk Employee

class `py42.clients.detectionlists.RiskTags`

Bases: `py42.choices.Choices`

Deprecated. Use [WatchlistsClient](#) and [UserRiskProfileClient](#) instead. Constants available as risk tags for [add_user_risk_tags\(\)](#) and [remove_user_risk_tags\(\)](#).

- FLIGHT_RISK
- HIGH_IMPACT_EMPLOYEE
- ELEVATED_ACCESS_PRIVILEGES
- PERFORMANCE_CONCERNS
- SUSPICIOUS_SYSTEM_ACTIVITY
- POOR_SECURITY_PRACTICES
- CONTRACT_EMPLOYEE

class `py42.services.detectionlists.high_risk_employee.HighRiskEmployeeFilters`

Bases: `py42.services.detectionlists._DetectionListFilters`, `py42.choices.Choices`

Deprecated. Use [WatchlistsClient](#) and [UserRiskProfileClient](#) instead. Constants available for filtering High Risk Employee search results.

- OPEN
- EXFILTRATION_30_DAYS
- EXFILTRATION_24_HOURS

```
class py42.services.detectionlists.high_risk_employee.HighRiskEmployeeService(connection,
                                                                              user_context,
                                                                              user_profile_service)
```

Bases: `py42.services.BaseService`

Deprecated. Use `:class: ~py42.clients.watchlists.WatchlistsClient` and `UserRiskProfileClient` instead. A service for interacting with High Risk Employee APIs.

add(*user_id*)

Deprecated. Use watchlists instead. Adds a user to the High Risk Employee detection list.

Raises a `Py42UserAlreadyAddedError` when a user already exists in the High Risk Employee detection list. [REST Documentation](#)

Parameters *user_id* (*str or int*) – The Code42 `userId` of the user you want to add to the High Risk Employee detection list.

Returns `py42.response.Py42Response`

get(*user_id*)

Deprecated. Use `userriskprofile.get_by_id()` instead. Gets user information. [Rest Documentation](#)

Parameters *user_id* (*str or int*) – The Code42 `userId` of the user has been added to the High Risk Employee detection list.

Returns `py42.response.Py42Response`

get_all(*filter_type='OPEN', sort_key=None, sort_direction=None, page_size=100*)

Deprecated. Use `userriskprofile.get_all()` instead. Searches High Risk Employee list. Filter results by *filter_type*. [Rest Documentation](#)

Parameters

- **filter_type** (*str, optional*) – Constants available at `py42.constants.HighRiskEmployeeFilters`. Defaults to `OPEN`.
- **sort_key** (*str, optional*) – Sort results based by field. Defaults to `None`.
- **sort_direction** (*str, optional*) – `ASC` or `DESC`. Constants available at `py42.constants.SortDirection`. Defaults to `None`.
- **page_size** (*int, optional*) – The number of high risk employees to return per page. Defaults to `100`.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of users.

Return type generator

get_page(*page_num, filter_type='OPEN', sort_key=None, sort_direction=None, page_size=100*)

Deprecated. Use `userriskprofile.get_page()` instead. Gets a single page of High Risk Employees.

Parameters

- **page_num** (*int*) – The page number to request.
- **filter_type** (*str, optional*) – Constants available at `py42.constants.HighRiskEmployeeFilters`. Defaults to `"OPEN"`.
- **sort_key** (*str, optional*) – Sort results based by field. Defaults to `None`.
- **sort_direction** (*str, optional*) – `ASC` or `DESC`. Constants available at `py42.constants.SortDirection`. Defaults to `None`.

- **page_size** (*int*, *optional*) – The number of high risk employees to return per page. Defaults to 100.

Returns [*py42.response.Py42Response*](#)

remove(*user_id*)

Deprecated. Use watchlists instead. Removes a user from the High Risk Employee detection list. [Rest Documentation](#)

Parameters **user_id** (*str* or *int*) – The Code42 *userId* of the user you want to add to the High Risk Employee detection list.

Returns [*py42.response.Py42Response*](#)

set_alerts_enabled(*enabled=True*)

Deprecated. Enables alerts. [Rest Documentation](#)

Parameters **enabled** (*bool*) – Whether to enable alerts for all users.

Returns [*py42.response.Py42Response*](#)

2.9 Devices

class `py42.services.devices.DeviceService(connection)`

Bases: `py42.services.BaseService`

A class to interact with Code42 device/computer APIs.

block(*device_id*)

Blocks a device causing the user not to be able to log in to or restore from Code42 on that device.

Parameters **device_id** (*int*) – The identification number of the device.

Returns [*py42.response.Py42Response*](#)

deactivate(*device_id*)

Deactivates a device, causing backups to stop and archives to go to cold storage.

Parameters **device_id** (*int*) – The identification number of the device.

Returns [*py42.response.Py42Response*](#)

deauthorize(*device_id*)

Deauthorizes the device with the given ID. If used on a cloud connector device, it will remove the authorization token for that account.

Parameters **device_id** (*int*) – The identification number of the device.

Returns [*py42.response.Py42Response*](#)

get_agent_full_disk_access_state(*guid*)

Gets the full disk access status of a device.

Parameters **guid** (*str*) – The globally unique identifier of the device.

Returns A response containing settings information.

Return type [*py42.response.Py42Response*](#)

get_agent_state(*guid*, *property_name*)

Gets the agent state of the device.

Parameters

- **guid** (*str*) – The globally unique identifier of the device.
- **property_name** (*str*) – The name of the property to retrieve (e.g. *fullDiskAccess*).

Returns A response containing settings information.

Return type `py42.response.Py42Response`

get_all (*active=None, blocked=None, org_uid=None, user_uid=None, destination_guid=None, include_backup_usage=None, include_counts=True, q=None, **kwargs*)

Gets all device information.

When no arguments are passed, all records are returned. To filter results, specify respective arguments. For example, to retrieve all active and blocked devices, pass `active=true` and `blocked=true`.

Parameters

- **active** (*bool, optional*) – Filters results by device state. When set to `True`, gets all active devices. When set to `False`, gets all deactivated devices. When set to `None` or excluded, gets all devices regardless of state. Defaults to `None`.
- **blocked** (*bool, optional*) – Filters results by blocked status: `True` or `False`. Defaults to `None`.
- **org_uid** (*int, optional*) – The identification number of an Organization. Defaults to `None`.
- **user_uid** (*int, optional*) – The identification number of a User. Defaults to `None`.
- **destination_guid** (*str or int, optional*) – The globally unique identifier of the storage server that the device back up to. Defaults to `None`.
- **include_backup_usage** (*bool, optional*) – A flag to denote whether to include the destination and its backup stats. Defaults to `None`.
- **include_counts** (*bool, optional*) – A flag to denote whether to include total, warning, and critical counts. Defaults to `True`.
- **q** (*str, optional*) – Searches results flexibly by incomplete GUID, hostname, computer name, etc. Defaults to `None`.

Returns

An object that iterates over `py42.response.Py42Response` objects that each contain a page of devices.

The devices returned by `get_all()` are based on the role and permissions of the user authenticating the py42 SDK.

Return type generator

get_by_guid (*guid, include_backup_usage=None, **kwargs*)

Gets device information by GUID.

Parameters

- **guid** (*str*) – The globally unique identifier of the device.
- **include_backup_usage** (*bool, optional*) – A flag to denote whether to include the destination and its backup stats. Defaults to `None`.

Returns A response containing device information.

Return type `py42.response.Py42Response`

get_by_id(*device_id*, *include_backup_usage=None*, ***kwargs*)

Gets device information by ID.

Parameters

- **device_id** (*int*) – The identification number of the device.
- **include_backup_usage** (*bool*, *optional*) – A flag to denote whether to include the destination and its backup stats. Defaults to None.

Returns A response containing device information.

Return type `py42.response.Py42Response`

get_page(*page_num*, *active=None*, *blocked=None*, *org_uid=None*, *user_uid=None*, *destination_guid=None*, *include_backup_usage=None*, *include_counts=True*, *page_size=None*, *q=None*)

Gets a page of devices.

Parameters

- **page_num** (*int*) – The page number to request.
- **active** (*bool*, *optional*) – Filters results by device state. When set to True, gets all active devices. When set to False, gets all deactivated devices. When set to None or excluded, gets all devices regardless of state. Defaults to None.
- **blocked** (*bool*, *optional*) – Filters results by blocked status: True or False. Defaults to None.
- **org_uid** (*int*, *optional*) – The identification number of an Organization. Defaults to None.
- **user_uid** (*int*, *optional*) – The identification number of a User. Defaults to None.
- **destination_guid** (*str or int*, *optional*) – The globally unique identifier of the storage server that the device back up to. Defaults to None.
- **include_backup_usage** (*bool*, *optional*) – A flag to denote whether to include the destination and its backup stats. Defaults to None.
- **include_counts** (*bool*, *optional*) – A flag to denote whether to include total, warning, and critical counts. Defaults to True.
- **page_size** (*int*, *optional*) – The number of devices to return per page. Defaults to `py42.settings.items_per_page`.
- **q** (*str*, *optional*) – Searches results flexibly by incomplete GUID, hostname, computer name, etc. Defaults to None.

Returns `py42.response.Py42Response`

get_settings(*guid*)

Gets setting data for a device and returns a *DeviceSettings* object for the target device.

Parameters **guid** (*int*, *str*) – The globally unique identifier of the device.

Returns A class to help manage device settings.

Return type `py42.clients.settings.device_settings.DeviceSettings`

reactivate(*device_id*)

Activates a previously deactivated device.

Parameters **device_id** (*int*) – The identification number of the device.

Returns `py42.response.Py42Response`

unlock(*device_id*)

Unlocks a device, permitting a user to be able to login and restore again.

Parameters **device_id** (*int*) – The identification number of the device.

Returns *py42.response.Py42Response*

update_settings(*device_settings*)

Updates a device's settings based on changes to the passed in *DeviceSettings* or *IncydrDeviceSettings* instance. The appropriate instance for each device is returned by the *get_settings()* method.

Parameters **device_settings** (*DeviceSettings* OR *IncydrDeviceSettings*) – An instance of *DeviceSettings* (Crashplan) or *IncydrDeviceSettings* (Incydr) with desired modifications to settings.

Returns A response containing the result of the settings changes.

Return type *py42.response.Py42Response*

upgrade(*guid*)

Instructs a device to upgrade to the latest available version.

Parameters **guid** (*str*) – The globally unique identifier of the device.

Returns A response containing the result of the upgrade request.

Return type *py42.response.Py42Response*

2.10 Device Settings

class *py42.clients.settings.device_settings.IncydrDeviceSettings*(*settings_dict*)

Bases: *collections.UserDict*

Class used to manage individual Incydr devices. These devices have no backup settings and only the **notes** and **external reference** fields are modifiable.

property **computer_id**

Identifier of this device. Read-only.

property **device_id**

Identifier of this device (alias of *.computer_id*). Read only.

external_reference

External reference field for this device.

property **guid**

Globally unique identifier of this device. Read-only.

property **name**

Name of this device. Read-only.

notes

Notes field for this device.

property **org_id**

Identifier of the organization this device belongs to. Read-only.

property **user_id**

Identifier of the user this device belongs to. Read-only.

property **version**

Latest reported Code42 client version number for this device. Read-only.

class `py42.clients.settings.device_settings.DeviceSettings(device_dict)`
 Bases: `py42.clients.settings.device_settings.DeviceSettingsDefaults`

Class used to manage an individual device's settings.

property available_destinations

Returns a dict of destinations available to be used by devices. Dict keys are destination guids and values are destination names.

backup_sets

List of `BackupSet` objects used to manage this device's backup set configurations.

backup_status_email_enabled

Determines if the regularly scheduled backup status email is enabled.

backup_status_email_frequency_days

Determines the frequency of the regularly scheduled backup status email.

property computer_id

Identifier of this device. Read-only.

critical_alert_days

The number of days a device can go without any backup activity before "warning" alert threshold is passed.

critical_email_enabled

Determines if backup "critical" threshold email alerts are configured for this device.

property device_id

Identifier of this device (alias of `.computer_id`). Read only.

external_reference

External reference field for this device.

property guid

Globally unique identifier of this device. Read-only.

property java_memory_heap_max

The maximum memory the client will use on its system

name

Name for this device.

notes

Notes field for this device.

property org_id

Identifier of the organization this device belongs to. Read-only.

property user_id

Identifier of the user this device belongs to. Read-only.

property version

Latest reported Code42 client version number for this device. Read-only.

warning_alert_days

The number of days a device can go without any backup activity before "warning" alert threshold is passed.

warning_email_enabled

Determines if backup "warning" threshold email alerts are configured for this device.

2.11 Exceptions

exception `py42.exceptions.Py42ActiveLegalHoldError(exception, resource, resource_id)`

Bases: `py42.exceptions.Py42BadRequestError`

An exception raised when attempting to deactivate a user or device that is in an active legal hold.

property resource

The user or device resource.

property resource_id

The resource ID.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42ArchiveFileNotFoundError(response, device_guid, file_path)`

Bases: `py42.exceptions.Py42ResponseError`

An exception raised when a resource file is not found or the path is invalid.

property device_guid

The device GUID provided.

property file_path

The file path provided.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42BadRequestError(exception, message=None, *args)`

Bases: `py42.exceptions.Py42HTTPError`

A wrapper to represent an HTTP 400 error.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42BadRestoreRequestError(exception)`

Bases: `py42.exceptions.Py42BadRequestError`

An error raised when the given restore arguments are not compatible and cause a bad request.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42CaseAlreadyHasEventError(exception)`

Bases: `py42.exceptions.Py42BadRequestError`

An error raised when event is already associated to the case.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42CaseNameExistsError**(*exception, case_name*)

Bases: [py42.exceptions.Py42BadRequestError](#)

An error raised when trying to create a case with a name that already exists.

property case_name

The case name.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42ChecksumNotFoundError**(*response, checksum_name, checksum_value*)

Bases: [py42.exceptions.Py42ResponseError](#)

An exception raised when a user-supplied hash could not successfully locate its corresponding resource.

property checksum_name

The checksum name.

property checksum_value

The checksum value.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42CloudAliasCharacterLimitExceededError**

Bases: [py42.exceptions.Py42Error](#)

An exception raised when trying to add a cloud alias to a user that exceeds the max character limit.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42CloudAliasLimitExceededError**(*exception, message=None*)

Bases: [py42.exceptions.Py42BadRequestError](#)

An Exception raised when trying to add a cloud alias to a user when that user already has the max amount of supported cloud aliases.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42ConflictError**(*exception, message=None, *args*)

Bases: [py42.exceptions.Py42HTTPError](#)

A wrapper to represent an HTTP 409 error.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42DescriptionLimitExceededError**(*exception*)

Bases: [py42.exceptions.Py42BadRequestError](#)

An error raised when description of a case exceeds the allowed char length limit.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42DeviceNotConnectedError**(*response*, *device_guid*)

Bases: [py42.exceptions.Py42ResponseError](#)

An exception raised when trying to push a restore to a device that is not connected to an Authority server.

property device_guid

The device GUID.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42Error**

Bases: Exception

A generic, Py42 custom base exception.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42FeatureUnavailableError**(*response*)

Bases: [py42.exceptions.Py42ResponseError](#)

An exception raised when a requested feature is not supported in your Code42 environment.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42ForbiddenError**(*exception*, *message=None*, *args)

Bases: [py42.exceptions.Py42HTTPError](#)

A wrapper to represent an HTTP 403 error.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42HTTPError**(*exception*, *message=None*, *args)

Bases: [py42.exceptions.Py42ResponseError](#)

A base custom class to manage all HTTP errors raised by an API endpoint.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42InternalServerError**(*exception, message=None, *args*)

Bases: [py42.exceptions.Py42HTTPError](#)

A wrapper to represent an HTTP 500 error.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42InvalidArchiveEncryptionKey**(*exception*)

Bases: [py42.exceptions.Py42HTTPError](#)

An exception raised the encryption key for an archive is invalid.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42InvalidArchivePassword**(*exception*)

Bases: [py42.exceptions.Py42HTTPError](#)

An exception raised when the password for unlocking an archive is invalid.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42InvalidCaseUserError**(*exception, user_uid*)

Bases: [py42.exceptions.Py42BadRequestError](#)

An error raised when a case subject or assignee is not a valid user.

property response

The response prior to the error.

property user

The user UID.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42InvalidEmailError**(*email, exception*)

Bases: [py42.exceptions.Py42InternalServerError](#)

An exception raised when trying to set an invalid email as a user's email.

property email

The email being assigned to a user.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42InvalidPageTokenError(exception, page_token)`

Bases: `py42.exceptions.Py42BadRequestError`

An error raised when the page token given is invalid.

property `page_token`

The page token.

property `response`

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42InvalidPasswordError(exception)`

Bases: `py42.exceptions.Py42InternalServerError`

An exception raised when trying to set an invalid password as a user's password.

property `response`

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42InvalidRuleError(exception, rule_id)`

Bases: `py42.exceptions.Py42NotFoundError`

An exception raised when the observer rule ID does not exist.

property `response`

The response prior to the error.

property `rule_id`

The observer rule ID.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42InvalidRuleOperationError(exception, rule_id, source)`

Bases: `py42.exceptions.Py42HTTPError`

An exception raised when trying to add or remove users to a system rule.

property `response`

The response prior to the error.

property `rule_id`

The rule ID.

property `source`

The rule source.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42InvalidUsernameError(exception)`

Bases: `py42.exceptions.Py42InternalServerError`

An exception raised when trying to set an invalid username as a user's username.

property `response`

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42InvalidWatchlistType**(*exception*, *watchlist_type*)

Bases: [py42.exceptions.Py42BadRequestError](#)

An exception raised when an invalid watchlist type is specified.

property response

The response prior to the error.

property watchlist_type

The specified watchlist type.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42LegalHoldAlreadyActiveError**(*exception*, *legal_hold_matter_uid*)

Bases: [py42.exceptions.Py42BadRequestError](#)

An exception raised when trying to activate a Legal Hold Matter that is already active.

property legal_hold_matter_uid

The legal hold matter UID.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42LegalHoldAlreadyDeactivatedError**(*exception*,
legal_hold_matter_uid)

Bases: [py42.exceptions.Py42BadRequestError](#)

An exception raised when trying to deactivate a Legal Hold Matter that is already inactive.

property legal_hold_matter_uid

The legal hold matter UID.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42LegalHoldCriteriaMissingError**(*exception*)

Bases: [py42.exceptions.Py42BadRequestError](#)

An exception raised when a bad request was made to a Legal Hold endpoint.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42LegalHoldNotFoundOrPermissionDeniedError**(*exception*,
resource_uid, *legal_hold_resource='matter'*)

Bases: [py42.exceptions.Py42ForbiddenError](#)

An exception raised when a legal hold matter is inaccessible from your account or the matter ID is not valid.

property response

The response prior to the error.

property uid

The UID of the legal hold resource.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42MFARequiredError**(*exception, message=None*)

Bases: [py42.exceptions.Py42UnauthorizedError](#)

Deprecated: An exception raised when a request requires multi-factor authentication

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42NotFoundError**(*exception, message=None, *args*)

Bases: [py42.exceptions.Py42HTTPError](#)

A wrapper to represent an HTTP 404 error.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42OrgNotFoundError**(*exception, org_uid*)

Bases: [py42.exceptions.Py42BadRequestError](#)

An exception raised when a 400 HTTP error message indicates that an organization was not found.

property org_uid

” The org UID.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42ResponseError**(*response, message, *args*)

Bases: [py42.exceptions.Py42Error](#)

A base custom class to manage all errors raised because of an HTTP response.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.**Py42SessionInitializationError**(*exception*)

Bases: [py42.exceptions.Py42Error](#)

An exception raised when a user connection is invalid. A connection might be invalid due to connection timeout, invalid token, etc.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42StorageSessionInitializationError(exception, message)`

Bases: `py42.exceptions.Py42HTTPError`

An exception raised when the user is not authorized to initialize a storage session. This may occur when trying to restore a file or trying to get events for file activity on removable media, in cloud sync folders, and browser uploads.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42TooManyRequestsError(exception, message=None, *args)`

Bases: `py42.exceptions.Py42HTTPError`

A wrapper to represent an HTTP 429 error.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42TrustedActivityConflictError(exception, value)`

Bases: `py42.exceptions.Py42ConflictError`

An error raised when theres a conflict with a trusted activity domain URL.

property response

The response prior to the error.

property value

The domain, URL or workspace name.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42TrustedActivityIdNotFound(exception, resource_id)`

Bases: `py42.exceptions.Py42NotFoundError`

An exception raised when the trusted activity ID does not exist.

property resource_id

The resource ID.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42TrustedActivityInvalidChangeError(exception)`

Bases: `py42.exceptions.Py42BadRequestError`

An error raised when an invalid change is being made to a trusted activity.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42TrustedActivityInvalidCharacterError(exception)`

Bases: `py42.exceptions.Py42BadRequestError`

An error raised when an invalid character is in a trusted activity value.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42UnableToCreateProfileError(exception, username)`

Bases: `py42.exceptions.Py42BadRequestError`

An error raised when trying to call the method for creating a detection-list user when the user does not exist or is currently awaiting the profile to get created on the back-end. Note: you are no longer able to create detection-list profiles using the API; py42 only returns already existing profiles.

property response

The response prior to the error.

property username

The username of the user.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42UnauthorizedError(exception, message=None, *args)`

Bases: `py42.exceptions.Py42HTTPError`

A wrapper to represent an HTTP 401 error.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42UpdateClosedCaseError(exception)`

Bases: `py42.exceptions.Py42BadRequestError`

An error raised when trying to update a closed case.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42UserAlreadyAddedError(exception, user_id, list_name)`

Bases: `py42.exceptions.Py42BadRequestError`

An exception raised when the user is already added to group or list, such as the Departing Employee list.

property response

The response prior to the error.

property user_id

The user ID.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42UserAlreadyExistsError(exception, message=None)`

Bases: [py42.exceptions.Py42InternalServerError](#)

An exception raised when a user already exists

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42UserNotOnListError(exception, user_id, list_name)`

Bases: [py42.exceptions.Py42NotFoundError](#)

An exception raised when the user is not on a detection list.

property list_name

The list name.

property response

The response prior to the error.

property user_id

The user ID.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42UserRiskProfileNotFound(exception, user_id, identifier='ID')`

Bases: [py42.exceptions.Py42NotFoundError](#)

An exception raised when the user with the given ID for a user risk profile was not found.

property response

The response prior to the error.

property user

The user identifier.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42UsernameMustBeEmailError(exception)`

Bases: [py42.exceptions.Py42InternalServerError](#)

An exception raised when trying to set a non-email as a user's username in a cloud environment.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42WatchlistNotFound(exception, resource_id)`

Bases: [py42.exceptions.Py42NotFoundError](#)

An exception raised when the watchlist with the given ID was not found.

property response

The response prior to the error.

property watchlist_id

The watchlist ID.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42WatchlistOrUserNotFound(exception, watchlist_id, user_id)`

Bases: `py42.exceptions.Py42NotFoundError`

An exception raised when the watchlist ID or the User ID does not exist.

property response

The response prior to the error.

property user_id

The user ID.

property watchlist_id

The watchlist ID.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

`py42.exceptions.raise_py42_error(raised_error)`

Raises the appropriate `py42.exceptions.Py42HttpError` based on the given `HTTPError`'s response status code.

2.12 File Event Queries - V1 (DEPRECATED)

Warning: V1 file events, saved searches, and queries are **deprecated**.

For details on using the new file event data model, see the *V2 File Events User Guide*.

class `py42.sdk.queries.fileevents.file_event_query.FileEventQuery(*args, **kwargs)`

Bases: `py42.sdk.queries.BaseQuery`

Helper class for building V1 Code42 Forensic Search queries.

A `FileEventQuery` instance's `all()` and `any()` take one or more *FilterGroup* objects to construct a query that can be passed to the `FileEventService.search()` method. `all()` returns results that match all of the provided filter criteria, `any()` will return results that match any of the filters.

For convenience, the *FileEventQuery* constructor does the same as `all()`.

Usage example:

```
email_filter = EmailSender.is_in(["test.user@example.com", "test.sender@example.com
↪"])
exposure_filter = ExposureType.exists()
query = FileEventQuery.all(email_filter, exposure_filter)
```

2.12.1 Saved Searches

class `py42.services.savedsearch.SavedSearchService(connection, file_event_service)`

Bases: `py42.services.BaseService`

A service to interact with saved search APIs.

execute(*search_id*, *page_number=None*, *page_size=None*, *use_v2=False*)

Executes a saved search for given search Id, returns up to the first 10,000 events.

Parameters

- **search_id** (*str*) – Unique search Id of the saved search.
- **page_number** (*int*, *optional*) – The consecutive group of results of size *page_size* in the result set to return. Defaults to None.
- **page_size** (*int*, *optional*) – The maximum number of results to be returned. Defaults to None.
- **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns `py42.response.Py42Response`

get(*use_v2=False*)

Fetch details of existing saved searches.

The existing data model for file events and saved searches is deprecated. To use the updated data model for file events, [update your settings](#). Retrieving saved searches with V2 settings enabled will convert existing saved search queries to the V2 data model. Existing V1 queries that cannot be properly converted will be excluded from the response.

Parameters **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns `py42.response.Py42Response`

get_by_id(*search_id*, *use_v2=False*)

Fetch the details of a saved search by its given search Id.

The existing data model for file events and saved searches is deprecated. To use the updated data model for file events, [update your settings](#). Retrieving saved searches with V2 settings enabled will convert existing saved search queries to the V2 data model. Existing V1 queries that cannot be properly converted will be excluded from the response.

Parameters

- **search_id** (*str*) – Unique search Id of the saved search.
- **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns `py42.response.Py42Response`

get_query(*search_id*, *page_number=None*, *page_size=None*, *use_v2=False*)

Get the saved search in form of a query(`py42.sdk.queries.fileevents.file_event_query`).

Parameters

- **search_id** (*str*) – Unique search Id of the saved search.
- **page_number** (*int*, *optional*) – The consecutive group of results of size *page_size* in the result set to return. Defaults to None.
- **page_size** (*int*, *optional*) – The maximum number of results to be returned. Defaults to None.
- **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns `py42.sdk.queries.fileevents.v2.file_event_query.FileEventQuery`

search_file_events(*search_id*, *page_number=None*, *page_size=None*, *use_v2=False*)

Alias method for `execute()`. Executes a saved search for given search Id, returns up to the first 10,000 events.

To view more than the first 10,000 events:

- pass the *search_id* to `get_query()`
- pass the resulting query (`FileEventQuery`) to `search_all_file_events()`, use that method as normal.

Parameters

- **search_id** (*str*) – Unique search Id of the saved search.
- **page_number** (*int*, *optional*) – The consecutive group of results of size *page_size* in the result set to return. Defaults to `None`.
- **page_size** (*int*, *optional*) – The maximum number of results to be returned. Defaults to `None`.
- **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to `False`.

Returns `py42.response.Py42Response`

2.12.2 Filter Classes

The following classes construct filters for file event queries. Each filter class corresponds to a file event detail. Call the appropriate classmethod on your desired filter class with the value you want to match and it will return a `FilterGroup` object that can be passed to `FileEventQuery`'s `all()` or `any()` methods to create complex queries that match multiple filter rules.

Example:

To search for events observed for certain set of documents, you can use the `FileName` and `MD5` filter classes to construct `FilterGroups` that will search for matching filenames or (in case someone renamed the sensitive file) the known MD5 hashes of the files:

```
filename_filter = FileName.is_in(['confidential_plans.docx', 'confidential_plan_
↳ projections.xlsx'])
md5_filter = MD5.is_in(['133765f4fff5e3038b9352a4d14e1532',
↳ 'ea16f0cbfc76f6eba292871f8a8c794b'])
```

See *Executing Searches* for more on building search queries.

Event Filters

util.create_exists_filter_group()

Creates a `FilterGroup` to find events where filter data exists. Useful for creating EXISTS filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters **term** (*str*) – The term of the filter.

Returns `FilterGroup`

util.create_not_exists_filter_group()

Creates a `FilterGroup` to find events where filter data does not exist. Useful for creating DOES_NOT_EXIST filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters **term** (*str*) – The term of the filter.

Returns *FilterGroup*

`util.create_greater_than_filter_group(value)`

Creates a *FilterGroup* for matching file events where the value with key **term** is greater than the given value. Useful for creating GREATER_THAN filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **term** (*str*) – The term of the filter.
- **value** (*str or int*) – The value used to filter file events.

Returns *FilterGroup*

`util.create_less_than_filter_group(value)`

Creates a *FilterGroup* for matching file events where the value with key **term** is less than the given value. Useful for creating LESS_THAN filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **term** (*str*) – The term of the filter.
- **value** (*str or int*) – The value used to filter file events.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.event_filter.EventTimestamp`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterTimestampField`, `py42.choices.Choices`

V1 filter class that filters events based on the timestamp of the event that occurred.

Available event timestamp constants are provided as class attributes, These constants should be used only with class method *within_the_last*:

- `EventTimestamp.FIFTEEN_MINUTES`
- `EventTimestamp.ONE_HOUR`
- `EventTimestamp.THREE_HOURS`
- `EventTimestamp.TWELVE_HOURS`
- `EventTimestamp.ONE_DAY`
- `EventTimestamp.THREE_DAYS`
- `EventTimestamp.SEVEN_DAYS`
- `EventTimestamp.FOURTEEN_DAYS`
- `EventTimestamp.THIRTY_DAYS`

Example:: `filter = EventTimestamp.within_the_last(EventTimestamp.SEVEN_DAYS)`

classmethod `choices()`

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod `in_range(start_value, end_value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- **start_value** (*str or int or float or datetime*) – The start value used to filter results.
- **end_value** (*str or int or float or datetime*) – The end value used to filter results.

Returns [FilterGroup](#)

classmethod `on_or_after(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term`` is on or after the provided ``value.

Parameters **value** (*str or int or float or datetime*) – The value used to filter results.

Returns [FilterGroup](#)

classmethod `on_or_before(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters **value** (*str or int or float or datetime*) – The value used to filter results.

Returns [FilterGroup](#)

classmethod `on_same_day(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters **value** (*str or int or float or datetime*) – The value used to filter results.

Returns [FilterGroup](#)

classmethod `within_the_last(value)`

Returns a [FilterGroup](#) that is useful for finding results where the key `self._term` is a timestamp-related term, such as `EventTimestamp._term`, and value is one of it's accepted values, such as one of the values in `EventTimestamp.choices()`.

Parameters **value** (*str*) – The value used to filter file events.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.filters.event_filter.EventType`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`, `py42.choices.Choices`

V1 filter class that filters file events based on event type.

Available event types are provided as class attributes:

- `EventType.CREATED`
- `EventType.DELETED`
- `EventType.EMAILED`
- `EventType.MODIFIED`
- `EventType.READ_BY_APP`
- `EventType.PRINTED`

Example:

```
filter = EventType.isin([EventType.READ_BY_APP, EventType EMAILED])
```

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_exists()

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod not_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns [FilterGroup](#)

class py42.sdk.queries.fileevents.filters.event_filter.InsertionTimestamp

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterTimestampField`

V1 filter class that filters events based on the timestamp of when the event was actually added to the event store (which can be after the event occurred on the device itself).

`value` must be a POSIX timestamp. (see the [Dates](#) section of the Basics user guide for details on timestamp arguments in py42)

classmethod in_range(start_value, end_value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- **start_value** (*str or int or float or datetime*) – The start value used to filter results.
- **end_value** (*str or int or float or datetime*) – The end value used to filter results.

Returns *FilterGroup***classmethod** **on_or_after**(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term`` is on or after the provided ``value.

Parameters **value** (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup***classmethod** **on_or_before**(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters **value** (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup***classmethod** **on_same_day**(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters **value** (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup***classmethod** **within_the_last**(*value*)

Returns a *FilterGroup* that is useful for finding results where the key `self._term` is a timestamp-related term, such as `EventTimestamp._term`, and `value` is one of its accepted values, such as one of the values in `EventTimestamp.choices()`.

Parameters **value** (*str*) – The value used to filter file events.

Returns *FilterGroup***class** `py42.sdk.queries.fileevents.filters.event_filter.Source`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`, `py42.choices.Choices`

V1 filter class that filters events by event source.

Available source types are provided as class attributes:

- `Source.ENDPOINT`
- `Source.GOOGLE_DRIVE`
- `Source.ONE_DRIVE`
- `Source.BOX`
- `Source.GMAIL`
- `Source.OFFICE_365`

Example:

```
filter = Source.is_in([Source.ENDPOINT, Source.BOX])
```

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.event_filter.MimeTypeMismatch

Bases: *py42.sdk.queries.query_filter.QueryFilterBooleanField*

V1 filter class that filters events by whether or not a file's mime type matches its extension type.

classmethod is_false()

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is False.

Returns *FilterGroup*

classmethod is_true()

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is True.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.event_filter.**OutsideActiveHours**

Bases: [py42.sdk.queries.query_filter.QueryFilterBooleanField](#)

V1 filter class that filters events by whether or not they occurred outside a user's typical working hours

classmethod [is_false\(\)](#)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is False.

Returns [FilterGroup](#)

classmethod [is_true\(\)](#)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is True.

Returns [FilterGroup](#)

File Filters

class py42.sdk.queries.fileevents.filters.file_filter.**FileCategory**

Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField, py42.choices.Choices

V1 filter class that filters events by category of the file observed.

Available file categories are provided as class attributes:

- `FileCategory.AUDIO`
- `FileCategory.DOCUMENT`
- `FileCategory.EXECUTABLE`
- `FileCategory.IMAGE`
- `FileCategory.PDF`
- `FileCategory.PRESENTATION`
- `FileCategory.SCRIPT`
- `FileCategory.SOURCE_CODE`
- `FileCategory.SPREADSHEET`
- `FileCategory.VIDEO`
- `FileCategory.VIRTUAL_DISK_IMAGE`
- `FileCategory.ZIP`

classmethod [choices\(\)](#)

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod [eq\(value\)](#)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod [exists\(\)](#)

Returns a [FilterGroup](#) to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.file_filter.FileName`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by the name of the file observed.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.file_filter.FileOwner

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by the owner of the file observed.

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.file_filter.FilePath

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by path of the file observed.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.file_filter.FileSize`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterComparableField`

V1 filter class that filters events by size of the file observed.

Size value must be bytes.

classmethod `greater_than(value)`

Returns a *FilterGroup* to find events where filter data is greater than the provided value.

Parameters `value (str or int or float)` – The value used to filter file events.

Returns *FilterGroup*

classmethod `less_than(value)`

Returns a *FilterGroup* to find events where filter data is less than than the provided value.

Parameters `value (str or int or float)` – The value used to filter file events.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.file_filter.MD5`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by the MD5 hash of the file observed.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.file_filter.SHA256`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by SHA256 hash of the file observed.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

Device Filters

class py42.sdk.queries.fileevents.filters.device_filter.DeviceUsername

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by the Code42 username of the device that observed the event.

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.filters.device_filter.OSHostname`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by hostname of the device that observed the event.

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod `exists()`

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_exists()`

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.filters.device_filter.PrivateIPAddress`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by private (LAN) IP address of the device that observed the event.

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.device_filter.PublicIPAddress

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by public (WAN) IP address of the device that observed the event.

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists()**

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.device_filter.DeviceSignedInUserName`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by signed in user of the device that observed the event.

classmethod **eq(value)**

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **exists()**

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod **is_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq(value)**

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists()**

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

Cloud Filters

class py42.sdk.queries.fileevents.filters.cloud_filter.**Actor**

Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V1 filter class that filters events by the cloud service username of the event originator (applies to cloud data source events only).

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key self._term is in the provided value_list.

Parameters *value_list* (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term does not equal the provided value.

Parameters *value* (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key self._term is not in the provided value_list.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.cloud_filter.**DirectoryID**

Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V1 filter class that filters events by unique identifier of the cloud drive or folder where the event occurred (applies to cloud data source events only).

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.cloud_filter.Shared`

Bases: `py42.sdk.queries.query_filter.QueryFilterBooleanField`

V1 filter class that filters events by the shared status of the file at the time the event occurred (applies to cloud data source events only).

classmethod is_false()

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is False.

Returns *FilterGroup*

classmethod is_true()

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is True.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.cloud_filter.SharedWith`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by the list of users who had been granted access to the file at the time of the event (applies to cloud data source events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.cloud_filter.SharingTypeAdded`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`, `py42.choices.Choices`

V1 filter class that filters results to include events where a file's sharing permissions were changed to a value that increases exposure (applies to cloud data source events only).

Available options provided as class attributes:

- `SharingTypeAdded.SHARED_VIA_LINK`
- `SharingTypeAdded.IS_PUBLIC`
- `SharingTypeAdded.OUTSIDE_TRUSTED_DOMAIN`

classmethod `choices()`

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (*list*)

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_exists()`

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns [FilterGroup](#)

Exposure Filters

class `py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`, `py42.choices.Choices`

V1 filter class that filters events based on exposure type.

Available options are provided as class attributes:

- `ExposureType.SHARED_VIA_LINK`
- `ExposureType.SHARED_TO_DOMAIN`
- `ExposureType.APPLICATION_READ`
- `ExposureType.CLOUD_STORAGE`
- `ExposureType.REMOVABLE_MEDIA`
- `ExposureType.IS_PUBLIC`

classmethod `choices()`

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (*list*)

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_exists()

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod not_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.filters.exposure_filter.ProcessName`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the process name involved in the exposure (applies to read by browser or other app events only).

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.exposure_filter.ProcessOwner

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the process owner that was involved in the exposure (applies to read by browser or other app events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaName

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the name of the removable media involved in the exposure (applies to removable media events only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaVendor`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the vendor of the removable media device involved in the exposure (applies to removable media events only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_exists()`

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaMediaName`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the name of the removable media (as reported by the vendor/device, usually very similar to `RemovableMediaName`) involved in the exposure (applies to removable media events only).

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod `exists()`

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaVolumeName

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the name of the formatted volume (as reported by the operating system) of the removable media device involved in the exposure (applies to `removable media` events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaPartitionID

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the unique identifier assigned (by the operating system) to the removable media involved in the exposure (applies to `removable media` events only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaSerialNumber`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the serial number of the connected hardware as reported by the operating system (applies to removable media events only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.exposure_filter.SyncDestination

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`, `py42.choices.Choices`

V1 filter class that filters events based on the name of the cloud service the file is synced with (applies to synced to cloud service events only).

Available options are provided as class attributes:

- `SyncDestination.ICLOUD`
- `SyncDestination.BOX`
- `SyncDestination.BOX_DRIVE`
- `SyncDestination.GOOGLE_DRIVE`
- `SyncDestination.GOOGLE_BACKUP_AND_SYNC`
- `SyncDestination.DROPBOX`
- `SyncDestination.ONEDRIVE`

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_exists()`

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.filters.exposure_filter.SyncDestinationUsername`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the username associated with the cloud service the file is synced with (applies to synced to cloud service events only).

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod `exists()`

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_exists()`

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.exposure_filter.TabURL

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on all the URLs of the browser tabs at the time the file contents were read by the browser (applies to `read by browser` or `other app` events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.exposure_filter.WindowTitle

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the name of all the browser tabs or application windows that were open when a browser or other app event occurred (applies to `read by browser` or `other app` events only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

Email Filters

class `py42.sdk.queries.fileevents.filters.email_filter.EmailPolicyName`

Bases: *py42.sdk.queries.query_filter.QueryFilterStringField*

V1 filter class that filters events based on the email DLP policy that detected this file (applies to emails sent via Microsoft Office 365 only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.email_filter.EmailSubject

Bases: *py42.sdk.queries.query_filter.QueryFilterStringField*

V1 filter class that filters events based on the email's subject (applies to email events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.email_filter.EmailRecipients

Bases: *py42.sdk.queries.query_filter.QueryFilterStringField*

V1 filter class that filters events based on the email's recipient list (applies to email events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.email_filter.EmailSender`

Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`

V1 filter class that filters events based on the email's sender (applies to email events only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.email_filter.EmailFrom`

Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`

V1 filter class that filters events based on the display name of the email's sender, as it appears in the "From:" field in the email (applies to email events only).

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns [FilterGroup](#)

Activity Filters

class `py42.sdk.queries.fileevents.filters.activity_filter.TrustedActivity`

Bases: [py42.sdk.queries.query_filter.QueryFilterBooleanField](#)

V1 filter class that filters events based on whether activity can be trusted.

classmethod `is_false()`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is False.

Returns [FilterGroup](#)

classmethod `is_true()`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is True.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.filters.activity_filter.RemoteActivity`

Bases: [py42.sdk.queries.query_filter.QueryFilterBooleanField](#)

V1 filter class that filters events based on whether the activity was remote (took place outside of corporate IP range).

classmethod `is_false()`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is False.

Returns [FilterGroup](#)

classmethod `is_true()`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is True.

Returns *FilterGroup*

Printer Filters

class `py42.sdk.queries.fileevents.filters.print_filter.Printer`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by printer name.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.print_filter.PrintJobName`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by print job name.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

Risk Filters

class py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by risk indicator.

Available options are provided as class attributes:

- `RiskIndicator.CloudDataExposures.PUBLIC_CORPORATE_BOX`
- `RiskIndicator.CloudDataExposures.PUBLIC_CORPORATE_GOOGLE_DRIVE`
- `RiskIndicator.CloudDataExposures.PUBLIC_CORPORATE_ONEDRIVE`
- `RiskIndicator.CloudDataExposures.SENT_CORPORATE_GMAIL`
- `RiskIndicator.CloudDataExposures.SHARED_CORPORATE_BOX`
- `RiskIndicator.CloudDataExposures.SHARED_CORPORATE_GOOGLE_DRIVE`
- `RiskIndicator.CloudDataExposures.SHARED_CORPORATE_ONEDRIVE`
- `RiskIndicator.CloudStorageUploads.AMAZON_DRIVE`
- `RiskIndicator.CloudStorageUploads.BOX`
- `RiskIndicator.CloudStorageUploads.DROPBOX`
- `RiskIndicator.CloudStorageUploads.GOOGLE_DRIVE`

- RiskIndicator.CloudStorageUploads.ICLOUD
- RiskIndicator.CloudStorageUploads.MEGA
- RiskIndicator.CloudStorageUploads.ONEDRIVE
- RiskIndicator.CloudStorageUploads.ZOHO
- RiskIndicator.CodeRepositoryUploads.BITBUCKET
- RiskIndicator.CodeRepositoryUploads.GITHUB
- RiskIndicator.CodeRepositoryUploads.GITLAB
- RiskIndicator.CodeRepositoryUploads.SOURCEFORGE
- RiskIndicator.CodeRepositoryUploads.STASH
- RiskIndicator.EmailServiceUploads.ONESIXTHREE_DOT_COM
- RiskIndicator.EmailServiceUploads.ONETWOSIX_DOT_COM
- RiskIndicator.EmailServiceUploads.AOL
- RiskIndicator.EmailServiceUploads.COMCAST
- RiskIndicator.EmailServiceUploads.GMAIL
- RiskIndicator.EmailServiceUploads.ICLOUD
- RiskIndicator.EmailServiceUploads.MAIL_DOT_COM
- RiskIndicator.EmailServiceUploads.OUTLOOK
- RiskIndicator.EmailServiceUploads.PROTONMAIL
- RiskIndicator.EmailServiceUploads.QQMAIL
- RiskIndicator.EmailServiceUploads.SINA_MAIL
- RiskIndicator.EmailServiceUploads.SOHU_MAIL
- RiskIndicator.EmailServiceUploads.YAHOO
- RiskIndicator.EmailServiceUploads.ZOHO_MAIL
- RiskIndicator.ExternalDevices.AIRDROP
- RiskIndicator.ExternalDevices.REMOVABLE_MEDIA
- RiskIndicator.FileCategories.AUDIO
- RiskIndicator.FileCategories.DOCUMENT
- RiskIndicator.FileCategories.EXECUTABLE
- RiskIndicator.FileCategories.IMAGE
- RiskIndicator.FileCategories.PDF
- RiskIndicator.FileCategories.PRESENTATION
- RiskIndicator.FileCategories.SCRIPT
- RiskIndicator.FileCategories.SOURCE_CODE
- RiskIndicator.FileCategories.SPREADSHEET
- RiskIndicator.FileCategories.VIDEO
- RiskIndicator.FileCategories.VIRTUAL_DISK_IMAGE

- RiskIndicator.FileCategories.ZIP
- RiskIndicator.MessagingServiceUploads.FACEBOOK_MESSENGER
- RiskIndicator.MessagingServiceUploads.MICROSOFT_TEAMS
- RiskIndicator.MessagingServiceUploads.SLACK
- RiskIndicator.MessagingServiceUploads.WHATSAPP
- RiskIndicator.Other.OTHER
- RiskIndicator.Other.UNKNOWN
- RiskIndicator.SocialMediaUploads.FACEBOOK
- RiskIndicator.SocialMediaUploads.LINKEDIN
- RiskIndicator.SocialMediaUploads.REDDIT
- RiskIndicator.SocialMediaUploads.TWITTER
- RiskIndicator.UserBehavior.FILE_MISMATCH
- RiskIndicator.UserBehavior.OFF_HOURS
- RiskIndicator.UserBehavior.REMOTE
- RiskIndicator.UserBehavior.FIRST_DESTINATION_USE
- RiskIndicator.UserBehavior.RARE_DESTINATION_USE

class CloudDataExposures

Bases: py42.choices.Choices

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

class CloudStorageUploads

Bases: py42.choices.Choices

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

class CodeRepositoryUploads

Bases: py42.choices.Choices

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

class EmailServiceUploads

Bases: py42.choices.Choices

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

class ExternalDevices

Bases: py42.choices.Choices

```
classmethod choices()
    Returns attribute values for the given class.
    Returns A list containing the attribute values of the given class.
    Return type (list)

class FileCategories
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class MessagingServiceUploads
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class Other
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class SocialMediaUploads
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class UserBehavior
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the
    provided value.

    Parameters value (str) – The value to match on.

    Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.

    Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in
    the provided value_list.
```

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.risk_filter.RiskSeverity`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`, `py42.choices.Choices`

V1 filter class that filters events by risk severity.

Available options are provided as class attributes:

- `RiskSeverity.LOW`
- `RiskSeverity.MODERATE`
- `RiskSeverity.HIGH`
- `RiskSeverity.CRITICAL`
- `RiskSeverity.NO_RISK_INDICATED`

classmethod `choices()`

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (*list*)

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.risk_filter.RiskScore`

Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`, `py42.sdk.queries.fileevents.util.FileEventFilterComparableField`

V1 filter class that filters events by risk score.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `greater_than(value)`

Returns a *FilterGroup* to find events where filter data is greater than the provided value.

Parameters `value` (*str or int or float*) – The value used to filter file events.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `less_than(value)`

Returns a *FilterGroup* to find events where filter data is less than than the provided value.

Parameters `value` (*str or int or float*) – The value used to filter file events.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

2.13 File Event Queries - V2

For details on using the new file event data model, see the *V2 File Events User Guide*.

class `py42.sdk.queries.fileevents.v2.file_event_query.FileEventQuery(*args, **kwargs)`

Bases: `py42.sdk.queries.BaseQuery`

Helper class for building V2 Code42 Forensic Search queries.

A FileEventQuery instance's `all()` and `any()` take one or more *FilterGroup* objects to construct a query that can be passed to the `FileEventService.search()` method. `all()` returns results that match all of the provided filter criteria, `any()` will return results that match any of the filters.

For convenience, the FileEventQuery constructor does the same as `all()`.

Usage example:

```
email_filter = EmailSender.is_in(["test.user@example.com", "test.sender@example.com
↪"])
exposure_filter = ExposureType.exists()
query = FileEventQuery.all(email_filter, exposure_filter)
```

2.13.1 Saved Searches

Important: Make sure to set the optional argument `use_v2=True` on saved search functions to get V2 file event data and queries.

class `py42.services.savedsearch.SavedSearchService(connection, file_event_service)`

Bases: `py42.services.BaseService`

A service to interact with saved search APIs.

execute(*search_id*, *page_number=None*, *page_size=None*, *use_v2=False*)

Executes a saved search for given search Id, returns up to the first 10,000 events.

Parameters

- **search_id** (*str*) – Unique search Id of the saved search.
- **page_number** (*int*, *optional*) – The consecutive group of results of size *page_size* in the result set to return. Defaults to None.
- **page_size** (*int*, *optional*) – The maximum number of results to be returned. Defaults to None.
- **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns `py42.response.Py42Response`

get(*use_v2=False*)

Fetch details of existing saved searches.

The existing data model for file events and saved searches is deprecated. To use the updated data model for file events, [update your settings](#). Retrieving saved searches with V2 settings enabled will convert existing saved search queries to the V2 data model. Existing V1 queries that cannot be properly converted will be excluded from the response.

Parameters *use_v2* (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns [py42.response.Py42Response](#)

get_by_id(*search_id, use_v2=False*)

Fetch the details of a saved search by its given search Id.

The existing data model for file events and saved searches is deprecated. To use the updated data model for file events, [update your settings](#). Retrieving saved searches with V2 settings enabled will convert existing saved search queries to the V2 data model. Existing V1 queries that cannot be properly converted will be excluded from the response.

Parameters

- **search_id** (*str*) – Unique search Id of the saved search.
- **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns [py42.response.Py42Response](#)

get_query(*search_id, page_number=None, page_size=None, use_v2=False*)

Get the saved search in form of a query([py42.sdk.queries.fileevents.file_event_query](#)).

Parameters

- **search_id** (*str*) – Unique search Id of the saved search.
- **page_number** (*int, optional*) – The consecutive group of results of size *page_size* in the result set to return. Defaults to None.
- **page_size** (*int, optional*) – The maximum number of results to be returned. Defaults to None.
- **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns [py42.sdk.queries.fileevents.v2.file_event_query.FileEventQuery](#)

search_file_events(*search_id, page_number=None, page_size=None, use_v2=False*)

Alias method for [execute\(\)](#). Executes a saved search for given search Id, returns up to the first 10,000 events.

To view more than the first 10,000 events:

- pass the *search_id* to [get_query\(\)](#)
- pass the resulting query ([FileEventQuery](#)) to [search_all_file_events\(\)](#), use that method as normal.

Parameters

- **search_id** (*str*) – Unique search Id of the saved search.
- **page_number** (*int, optional*) – The consecutive group of results of size *page_size* in the result set to return. Defaults to None.
- **page_size** (*int, optional*) – The maximum number of results to be returned. Defaults to None.

- **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns `py42.response.Py42Response`

2.13.2 Filter Classes

The following classes construct filters for file event queries. Each filter class corresponds to a file event detail. Call the appropriate class method on your desired filter class with the value you want to match and it will return a `FilterGroup` object that can be passed to `FileEventQuery`'s `all()` or `any()` methods to create complex queries that match multiple filter rules.

Example:

To search for events observed for certain set of documents, you can use the `file.Name` and `file.MD5` filter classes to construct `FilterGroups` that will search for matching filenames or (in case someone renamed the sensitive file) the known MD5 hashes of the files:

```
from py42.sdk.queries.fileevents.v2 import *
filename_filter = File.Name.is_in(['confidential_plans.docx', 'confidential_plan_
↳ projections.xlsx'])
md5_filter = File.MD5.is_in(['133765f4fff5e3038b9352a4d14e1532',
↳ 'ea16f0cbfc76f6eba292871f8a8c794b'])
```

See [Executing Searches](#) for more on building search queries.

Destination Filters

class `py42.sdk.queries.fileevents.v2.filters.destination.Category`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`, `py42.choices.Choices`

V2 filter class that filters events based on the category of the file event destination.

Available options are provided as class attributes:

- `destination.category.CLOUD_STORAGE`
- `destination.category.DEVICE`
- `destination.category.EMAIL`
- `destination.category.MESSAGING`
- `destination.category.MULTIPLE_POSSIBILITIES`
- `destination.category.SOCIAL_MEDIA`
- `destination.category.SOURCE_CODE_REPOSITORY`
- `destination.category.UNCATEGORIZED`
- `destination.category.UNKNOWN`
- `destination.category.BUSINESS_INTELLIGENCE_TOOLS`
- `destination.category.CIVIL_SERVICES`
- `destination.category.CLOUD_COMPUTING`
- `destination.category.CODING_TOOLS`
- `destination.category.CONTRACT_MANAGEMENT`

- `destination.category.CRM_TOOLS`
- `destination.category.DESIGN_TOOLS`
- `destination.category.E_COMMERCE`
- `destination.category.FILE_CONVERSION_TOOLS`
- `destination.category.FINANCIAL_SERVICES`
- `destination.category.HEALTHCARE_AND_INSURANCE`
- `destination.category.HR_TOOLS`
- `destination.category.IMAGE_HOSTING`
- `destination.category.IT_SERVICES`
- `destination.category.JOB_LISTINGS`
- `destination.category.LEARNING_PLATFORMS`
- `destination.category.MARKETING_TOOLS`
- `destination.category.PDF_MANAGER`
- `destination.category.PHOTO_PRINTING`
- `destination.category.PRODUCTIVITY_TOOLS`
- `destination.category.PROFESSIONAL_SERVICES`
- `destination.category.REAL_ESTATE`
- `destination.category.SALES_TOOLS`
- `destination.category.SEARCH_ENGINE`
- `destination.category.SHIPPING`
- `destination.category.SOFTWARE`
- `destination.category.TRAVEL`
- `destination.category.WEB_HOSTING`

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a [*FilterGroup*](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns [*FilterGroup*](#)

classmethod exists()

Returns a [*FilterGroup*](#) to find events where filter data exists.

Returns [*FilterGroup*](#)

classmethod is_in(value_list)

Returns a [*FilterGroup*](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.destination.EmailRecipients`

Bases: *py42.sdk.queries.query_filter.QueryFilterStringField*

V2 filter class that filters events based on the email's recipient list (applies to email events only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.destination.EmailSubject`

Bases: *py42.sdk.queries.query_filter.QueryFilterStringField*

V2 filter class that filters events based on the email's subject (applies to email events only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.destination.IpAddress`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by public (WAN) IP address of the destination device.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.destination.Name`

Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`

V2 filter class that filters events based on the destination name.

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.destination.OperatingSystem`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the operating system of the destination device.

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.destination.PrintJobName`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by print job name.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.destination.PrintedFilesBackupPath`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the printed file backup path.

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.destination.PrinterName`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by printer name.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.destination.PrivateIpAddress`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by private (LAN) IP address of the destination device.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaBusType

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the bus type of the connected hardware as reported by the operating system (applies to removable media events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaCapacity`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the capacity of the connected hardware as reported by the operating system (applies to `removable media` events only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaMediaName`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the name of the removable media (as reported by the vendor/device, usually very similar to `RemovableMediaName`) involved in the exposure (applies to `removable media` events only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaName

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the name of the removable media involved in the exposure (applies to removable media events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaPartitionID

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the unique identifier assigned (by the operating system) to the removable media involved in the exposure (applies to `removable media` events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaSerialNumber

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the serial number of the connected hardware as reported by the operating system (applies to `removable media` events only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaVendor`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the vendor of the removable media device involved in the exposure (applies to `removable media` events only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_exists()`

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaVolumeName`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the name of the formatted volume (as reported by the operating system) of the removable media device involved in the exposure (applies to `removable media` events only).

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod `exists()`

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_exists()`

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.destination.TabTitleErrors

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on destination tab title errors (for ‘browser or other app’ events).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.destination.TabTitles

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the name of all the browser tabs or application windows that were open when a browser or other app event occurred (applies to read by browser or other app events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **exists()**

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod **is_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq(value)**

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists()**

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.destination.TabUrlErrors`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on destination tab URL Errors (for ‘browser or other app’ events).

classmethod **eq(value)**

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **exists()**

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod **is_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.destination.TabUrls`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on all the URLs of the browser tabs at the time the file contents were read by the browser (applies to `read by browser` or `other app` events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.destination.**UserEmail**
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events by the signed in user email of the destination device.

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key self._term is in the provided value_list.

Parameters *value_list* (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term does not equal the provided value.

Parameters *value* (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key self._term is not in the provided value_list.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

Event Filters

class py42.sdk.queries.fileevents.v2.filters.event.**Action**
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField, py42.choices.Choices

V2 filter class that filters events based on event action.

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (*list*)

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.event.Id`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by event ID.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.event.Inserted

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterTimestampField`

V2 filter class that filters events based on the timestamp of when the event was actually added to the event store (which can be after the event occurred on the device itself).

value must be a POSIX timestamp. (see the *Dates* section of the Basics user guide for details on timestamp arguments in py42)

classmethod in_range(start_value, end_value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- **start_value (str or int or float or datetime)** – The start value used to filter results.
- **end_value (str or int or float or datetime)** – The end value used to filter results.

Returns *FilterGroup*

classmethod on_or_after(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term`` is on or after the provided ``value.

Parameters value (str or int or float or datetime) – The value used to filter results.

Returns *FilterGroup*

classmethod on_or_before(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters value (str or int or float or datetime) – The value used to filter results.

Returns *FilterGroup*

classmethod on_same_day(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters *value* (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod *within_the_last*(*value*)

Returns a *FilterGroup* that is useful for finding results where the key *self._term* is a timestamp-related term, such as *EventTimestamp._term*, and *value* is one of it's accepted values, such as one of the values in *EventTimestamp.choices()*.

Parameters *value* (*str*) – The value used to filter file events.

Returns *FilterGroup*

class *py42.sdk.queries.fileevents.v2.filters.event.Observer*

Bases: *py42.sdk.queries.fileevents.util.FileEventFilterStringField*, *py42.choices.Choices*

V2 filter class that filters events by event observer.

Available event observer types are provided as class attributes:

- *event.Observer.ENDPOINT*
- *event.Observer.GOOGLE_DRIVE*
- *event.Observer.ONE_DRIVE*
- *event.Observer.BOX*
- *event.Observer.GMAIL*
- *event.Observer.OFFICE_365*

Example:: *filter = Event.Observer.is_in([event.Observer.ENDPOINT, event.Observer.BOX])*

classmethod *choices*()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (*list*)

classmethod *eq*(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key *self._term* equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod *exists*()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod *is_in*(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key *self._term* is in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod *not_eq*(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key *self._term* does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists()**

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.event.ShareType`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by share type.

classmethod **eq(value)**

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **exists()**

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod **is_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq(value)**

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists()**

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

File Filters

class py42.sdk.queries.fileevents.v2.filters.file.**Category**

Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField, py42.choices.Choices

V2 filter class that filters events by category of the observed file.

Available file categories are provided as class attributes:

- file.Category.AUDIO
- file.Category.DOCUMENT
- file.Category.EXECUTABLE
- file.Category.IMAGE
- file.Category.PDF
- file.Category.PRESENTATION
- file.Category.SCRIPT
- file.Category.SOURCE_CODE
- file.Category.SPREADSHEET
- file.Category.VIDEO
- file.Category.VIRTUAL_DISK_IMAGE
- file.Category.ZIP

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key self._term equals the provided value.

Parameters value (str) – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key self._term is in the provided value_list.

Parameters value_list (list) – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key self._term does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.file.CategoryByBytes

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters event by the category (by bytes) of the observed file

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.file.CategoryByExtension

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters event by the category (by bytes) of the observed file

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.Classification`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the classification of the observed file.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.file.CloudDriveId

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters event by the cloud drive ID of the observed file.

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.Created`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterTimestampField`

V2 filter class that filters events by the creation timestamp of the observed file.

classmethod `in_range(start_value, end_value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- **start_value** (*str or int or float or datetime*) – The start value used to filter results.
- **end_value** (*str or int or float or datetime*) – The end value used to filter results.

Returns *FilterGroup*

classmethod `on_or_after(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term`` is on or after the provided ``value.

Parameters `value` (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod `on_or_before(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters `value` (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod `on_same_day(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters `value` (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod `within_the_last(value)`

Returns a *FilterGroup* that is useful for finding results where the key `self._term` is a timestamp-related term, such as `EventTimestamp._term`, and `value` is one of it's accepted values, such as one of the values in `EventTimestamp.choices()`.

Parameters `value` (*str*) – The value used to filter file events.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.Directory`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by directory of the observed file.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.file.DirectoryId

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the directory ID of the observed file.

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists()**

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.Id`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the ID of the observed file.

classmethod **eq(value)**

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **exists()**

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod **is_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq(value)**

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists()**

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.MD5`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the MD5 hash of the observed file.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByBytes`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters event by the mime type (by bytes) of the observed file

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByExtension`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters event by the mime type (by extension) of the observed file

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.v2.filters.file.Modified`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterTimestampField`

V2 filter class that filters events by the modification timestamp of the observed file.

classmethod `in_range(start_value, end_value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- **start_value** (*str or int or float or datetime*) – The start value used to filter results.
- **end_value** (*str or int or float or datetime*) – The end value used to filter results.

Returns [FilterGroup](#)

classmethod `on_or_after(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term`` is on or after the provided ``value.

Parameters `value` (*str or int or float or datetime*) – The value used to filter results.

Returns [FilterGroup](#)

classmethod `on_or_before(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters `value` (*str or int or float or datetime*) – The value used to filter results.

Returns [FilterGroup](#)

classmethod `on_same_day(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters `value` (*str or int or float or datetime*) – The value used to filter results.

Returns [FilterGroup](#)

classmethod `within_the_last(value)`

Returns a [FilterGroup](#) that is useful for finding results where the key `self._term` is a timestamp-related term, such as `EventTimestamp._term`, and value is one of it's accepted values, such as one of the values in `EventTimestamp.choices()`.

Parameters `value` (*str*) – The value used to filter file events.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.v2.filters.file.Name`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the name of the observed file.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.Owner`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the owner of the observed file.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.file.SHA256

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by SHA256 hash of the observed file.

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.Size`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterTimestampField`

V2 filter class that filters events by size in bytes of the observed file.

Size value must be bytes.

classmethod `in_range(start_value, end_value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- **start_value** (*str or int or float or datetime*) – The start value used to filter results.
- **end_value** (*str or int or float or datetime*) – The end value used to filter results.

Returns *FilterGroup*

classmethod `on_or_after(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term`` is on or after the provided ``value.

Parameters `value` (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod `on_or_before(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters `value` (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod `on_same_day(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters `value` (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod `within_the_last(value)`

Returns a *FilterGroup* that is useful for finding results where the key `self._term` is a timestamp-related term, such as `EventTimestamp._term`, and value is one of it's accepted values, such as one of the values in `EventTimestamp.choices()`.

Parameters `value` (*str*) – The value used to filter file events.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.Url`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the URL of the observed file.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **exists()**

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod **is_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq(value)**

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists()**

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

Process Filters

class `py42.sdk.queries.fileevents.v2.filters.process.Executable`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the process name involved in the exposure (applies to read by browser or other app events only).

classmethod **eq(value)**

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **exists()**

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod **is_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.process.Owner

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the process owner that was involved in the exposure (applies to read by browser or other app events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

Report Filters

class `py42.sdk.queries.fileevents.v2.filters.report.Count`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`, `py42.sdk.queries.fileevents.util.FileEventFilterComparableField`

V2 filter class that filters events by the record count of the report.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `greater_than(value)`

Returns a *FilterGroup* to find events where filter data is greater than the provided value.

Parameters `value` (*str or int or float*) – The value used to filter file events.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `less_than(value)`

Returns a *FilterGroup* to find events where filter data is less than than the provided value.

Parameters `value` (*str or int or float*) – The value used to filter file events.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.report.**Description**

Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events by the description of the report.

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key self._term is in the provided value_list.

Parameters *value_list* (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term does not equal the provided value.

Parameters *value* (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key self._term is not in the provided value_list.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.report.**Headers**

Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events by the header(s) of the report.

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_exists()`

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.v2.filters.report.ID`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the ID of the report.

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod `exists()`

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_exists()`

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.report.Name`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the name of the report.

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters *value* (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.report.Type`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the type of the report.

Available options are provided as class attributes:

- **attr** `report.Type.AD_HOC`
- **attr** `report.Type.SAVED`

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

Risk Filters

class `py42.sdk.queries.fileevents.v2.filters.risk.Indicators`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the type of risk indicator.

Available options are provided as class attributes:

- `risk.Indicators.FileCategories.AUDIO`
- `risk.Indicators.FileCategories.DOCUMENT`
- `risk.Indicators.FileCategories.EXECUTABLE`
- `risk.Indicators.FileCategories.IMAGE`
- `risk.Indicators.FileCategories.PDF`
- `risk.Indicators.FileCategories.PRESENTATION`
- `risk.Indicators.FileCategories.SCRIPT`
- `risk.Indicators.FileCategories.SOURCE_CODE`

- `risk.Indicators.FileCategories.SPREADSHEET`
- `risk.Indicators.FileCategories.VIDEO`
- `risk.Indicators.FileCategories.VIRTUAL_DISK_IMAGE`
- `risk.Indicators.FileCategories.ZIP`
- `risk.Indicators.UserBehavior.FILE_MISMATCH`
- `risk.Indicators.UserBehavior.OFF_HOURS`
- `risk.Indicators.UserBehavior.REMOTE`
- `risk.Indicators.UserBehavior.FIRST_DESTINATION_USE`
- `risk.Indicators.UserBehavior.RARE_DESTINATION_USE`
- `risk.Indicators.UserBehavior.CONTRACT`
- `risk.Indicators.UserBehavior.DEPARTING`
- `risk.Indicators.UserBehavior.ELEVATED_ACCESS`
- `risk.Indicators.UserBehavior.FLIGHT_RISK`
- `risk.Indicators.UserBehavior.HIGH_IMPACT`
- `risk.Indicators.UserBehavior.HIGH_RISK`
- `risk.Indicators.UserBehavior.PERFORMANCE_CONCERNS`
- `risk.Indicators.UserBehavior.POOR_SECURITY_PRACTICES`
- `risk.Indicators.UserBehavior.SUSPICIOUS_SYSTEM_ACTIVITY`
- `risk.Indicators.CloudStorageUploads.AMAZON_DRIVE`
- `risk.Indicators.CloudStorageUploads.BAIDU_NET_DISK_UPLOAD`
- `risk.Indicators.CloudStorageUploads.BOX`
- `risk.Indicators.CloudStorageUploads.CRASHPLAN_UPLOAD`
- `risk.Indicators.CloudStorageUploads.DRAKE_PORTALS_UPLOAD`
- `risk.Indicators.CloudStorageUploads.DROPBOX`
- `risk.Indicators.CloudStorageUploads.FILE_DOT_IO_UPLOAD`
- `risk.Indicators.CloudStorageUploads.FILESTACK_UPLOAD`
- `risk.Indicators.CloudStorageUploads.GOOGLE_DRIVE`
- `risk.Indicators.CloudStorageUploads.OPEN_TEXT_HIGHTAIL_UPLOAD`
- `risk.Indicators.CloudStorageUploads.ICLOUD`
- `risk.Indicators.CloudStorageUploads.MEGA`
- `risk.Indicators.CloudStorageUploads.ONEDRIVE`
- `risk.Indicators.CloudStorageUploads.SECURE_FIRM_PORTAL_UPLOAD`
- `risk.Indicators.CloudStorageUploads.SHAREFILE_UPLOAD`
- `risk.Indicators.CloudStorageUploads.SMART_VAULT_UPLOAD`
- `risk.Indicators.CloudStorageUploads.SUGAR_SYNC_UPLOAD`
- `risk.Indicators.CloudStorageUploads.WE_TRANSFER_UPLOAD`

- `risk.Indicators.CloudStorageUploads.ZOHO`
- `risk.Indicators.EmailServiceUploads.ONESIXTHREE_DOT_COM`
- `risk.Indicators.EmailServiceUploads.ONETWOSIX_DOT_COM`
- `risk.Indicators.EmailServiceUploads.AOL`
- `risk.Indicators.EmailServiceUploads.COMCAST`
- `risk.Indicators.EmailServiceUploads.FASTMAIL_UPLOAD`
- `risk.Indicators.EmailServiceUploads.GMAIL`
- `risk.Indicators.EmailServiceUploads.GMX_UPLOAD`
- `risk.Indicators.EmailServiceUploads.ICLOUD`
- `risk.Indicators.EmailServiceUploads.LYCOS_UPLOAD`
- `risk.Indicators.EmailServiceUploads.MAIL_DOT_COM_UPLOAD`
- `risk.Indicators.EmailServiceUploads.OUTLOOK`
- `risk.Indicators.EmailServiceUploads.PROTONMAIL`
- `risk.Indicators.EmailServiceUploads.QQMAIL`
- `risk.Indicators.EmailServiceUploads.SINA_MAIL`
- `risk.Indicators.EmailServiceUploads.SOHU_MAIL`
- `risk.Indicators.EmailServiceUploads.TUTANOTA_UPLOAD`
- `risk.Indicators.EmailServiceUploads.YAHOO`
- `risk.Indicators.EmailServiceUploads.ZIX_UPLOAD`
- `risk.Indicators.EmailServiceUploads.ZOHO_MAIL`
- `risk.Indicators.ExternalDevices.AIRDROP`
- `risk.Indicators.ExternalDevices.SALESFORCE_DOWNLOAD`
- `risk.Indicators.ExternalDevices.REMOVABLE_MEDIA`
- `Indicators.CloudDataExposures.PUBLIC_CORPORATE_BOX`
- `Indicators.CloudDataExposures.PUBLIC_CORPORATE_GOOGLE_DRIVE`
- `Indicators.CloudDataExposures.PUBLIC_CORPORATE_ONEDRIVE`
- `Indicators.CloudDataExposures.SENT_CORPORATE_GMAIL`
- `Indicators.CloudDataExposures.SENT_CORPORATE_OFFICE365`
- `Indicators.CloudDataExposures.SHARED_CORPORATE_BOX`
- `Indicators.CloudDataExposures.SHARED_CORPORATE_GOOGLE_DRIVE`
- `Indicators.CloudDataExposures.SHARED_CORPORATE_ONEDRIVE`
- `risk.Indicators.FileConversionToolUploads.CLOUD_CONVERT_UPLOAD`
- `risk.Indicators.FileConversionToolUploads.COMPRESS_JPEG_UPLOAD`
- `risk.Indicators.FileConversionToolUploads.FREE_CONVERT_UPLOAD`
- `risk.Indicators.FileConversionToolUploads.HEIC_TO_JPEG_UPLOAD`
- `risk.Indicators.FileConversionToolUploads.TINY_PNG_UPLOAD`

- risk.Indicators.MessagingServiceUploads.DISCORD_UPLOAD
- risk.Indicators.MessagingServiceUploads.FACEBOOK_MESSENGER
- risk.Indicators.MessagingServiceUploads.GOOGLE_MESSAGES_UPLOAD
- risk.Indicators.MessagingServiceUploads.GOOGLE_CHAT_UPLOAD
- risk.Indicators.MessagingServiceUploads.GOOGLE_HANGOUTS_UPLOAD
- risk.Indicators.MessagingServiceUploads.MICROSOFT_TEAMS
- risk.Indicators.MessagingServiceUploads.SLACK
- risk.Indicators.MessagingServiceUploads.TELEGRAM_UPLOAD
- risk.Indicators.MessagingServiceUploads.WEBEX_UPLOAD
- risk.Indicators.MessagingServiceUploads.WE_CHAT_UPLOAD
- risk.Indicators.MessagingServiceUploads.WHATSAPP
- risk.Indicators.MessagingServiceUploads.ZOOM_UPLOAD
- risk.Indicators.Other.OTHER_DESTINATION
- risk.Indicators.Other.UNKNOWN_DESTINATION
- risk.Indicators.PdfManagerUploads.ADOBE_ACROBAT_UPLOAD
- risk.Indicators.PdfManagerUploads.COMBINE_PDF_UPLOAD
- risk.Indicators.PdfManagerUploads.FREE_PDF_CONVERT_UPLOAD
- risk.Indicators.PdfManagerUploads.I_LOVE_PDF_UPLOAD
- risk.Indicators.PdfManagerUploads.JPG2_PDF_UPLOAD
- risk.Indicators.PdfManagerUploads.PDF24_TOOLS_UPLOAD
- risk.Indicators.PdfManagerUploads.PDF_ESCAPE_UPLOAD
- risk.Indicators.PdfManagerUploads.PDF_FILLER_UPLOAD
- risk.Indicators.PdfManagerUploads.PDF_SIMPLI_UPLOAD
- risk.Indicators.PdfManagerUploads.SEJDA_UPLOAD
- risk.Indicators.PdfManagerUploads.SMALL_PDF_UPLOAD
- risk.Indicators.PdfManagerUploads.SODA_PDF_UPLOAD
- risk.Indicators.ProductivityToolUploads.ADOBE_UPLOAD
- risk.Indicators.ProductivityToolUploads.CANVA_UPLOAD
- risk.Indicators.ProductivityToolUploads.EVERNOTE_UPLOAD
- risk.Indicators.ProductivityToolUploads.FIGMA_UPLOAD
- risk.Indicators.ProductivityToolUploads.GOOGLE_KEEP_UPLOAD
- risk.Indicators.ProductivityToolUploads.GOOGLE_JAMBOARD_UPLOAD
- risk.Indicators.ProductivityToolUploads.IMAGE_COLOR_PICKER_UPLOAD
- risk.Indicators.ProductivityToolUploads.KAPWING_UPLOAD
- risk.Indicators.ProductivityToolUploads.MIRO_UPLOAD
- risk.Indicators.ProductivityToolUploads.MONDAY_UPLOAD

- `risk.Indicators.ProductivityToolUploads.MURAL_UPLOAD`
- `risk.Indicators.ProductivityToolUploads.NOTION_UPLOAD`
- `risk.Indicators.ProductivityToolUploads.OVERLEAF_UPLOAD`
- `risk.Indicators.ProductivityToolUploads.PHOTOPEA_UPLOAD`
- `risk.Indicators.ProductivityToolUploads.PIXLR_UPLOAD`
- `risk.Indicators.ProductivityToolUploads.REMOVE_DOT_BG_UPLOAD`
- `risk.Indicators.ProductivityToolUploads.TRELLO_UPLOAD`
- `risk.Indicators.ProductivityToolUploads.VEED_UPLOAD`
- `risk.Indicators.SocialMediaUploads.FOUR_CHAN_UPLOAD`
- `risk.Indicators.SocialMediaUploads.FACEBOOK`
- `risk.Indicators.SocialMediaUploads.IMGUR_UPLOAD`
- `risk.Indicators.SocialMediaUploads.LINKEDIN`
- `risk.Indicators.SocialMediaUploads.ODNOKLASSNIKI_UPLOAD`
- `risk.Indicators.SocialMediaUploads.OK_UPLOAD`
- `risk.Indicators.SocialMediaUploads.QZONE_UPLOAD`
- `risk.Indicators.SocialMediaUploads.REDDIT`
- `risk.Indicators.SocialMediaUploads.STACK_OVERFLOW_UPLOAD`
- `risk.Indicators.SocialMediaUploads.TUMBLR_UPLOAD`
- `risk.Indicators.SocialMediaUploads.TWITCH_UPLOAD`
- `risk.Indicators.SocialMediaUploads.TWITTER`
- `risk.Indicators.SocialMediaUploads.VIMEO_UPLOAD`
- `risk.Indicators.SocialMediaUploads.VK_UPLOAD`
- `risk.Indicators.SocialMediaUploads.WEIBO_UPLOAD`
- `risk.Indicators.SocialMediaUploads.YOU_TUBE_UPLOAD`
- `risk.Indicators.CodeRepositoryUploads.BITBUCKET_UPLOAD`
- `risk.Indicators.CodeRepositoryUploads.COLABORATORY_UPLOAD`
- `risk.Indicators.CodeRepositoryUploads.GITHUB`
- `risk.Indicators.CodeRepositoryUploads.GITLAB`
- `risk.Indicators.CodeRepositoryUploads.GOOGLE_APPS_SCRIPT_UPLOAD`
- `risk.Indicators.CodeRepositoryUploads.GOOGLE_CLOUD_SHELL_UPLOAD`
- `risk.Indicators.CodeRepositoryUploads.SOURCE_FORGE`
- `risk.Indicators.CodeRepositoryUploads.STASH`
- `risk.Indicators.WebHostingUploads.GIT_HUB_PAGES_UPLOAD`
- `risk.Indicators.WebHostingUploads.GOOGLE_SITES_UPLOAD`
- `risk.Indicators.WebHostingUploads.WIX_UPLOAD`
- `risk.Indicators.WebHostingUploads.WORD_PRESS_UPLOAD`

```

class CloudDataExposures
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class CloudStorageUploads
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class CodeRepositoryUploads
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class EmailServiceUploads
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class ExternalDevices
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class FileCategories
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class FileConversionToolUploads
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class MessagingServiceUploads
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.

```

Returns A list containing the attribute values of the given class.

Return type (list)

class Other

Bases: py42.choices.Choices

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

class PdfManagerUploads

Bases: py42.choices.Choices

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

class ProductivityToolUploads

Bases: py42.choices.Choices

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

class SocialMediaUploads

Bases: py42.choices.Choices

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

class UserBehavior

Bases: py42.choices.Choices

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

class WebHostingUploads

Bases: py42.choices.Choices

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.risk.IndicatorsWeight`

Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`, `py42.sdk.queries.fileevents.util.FileEventFilterComparableField`

V2 filter class that filters events by the risk indicator weight.

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `greater_than(value)`

Returns a *FilterGroup* to find events where filter data is greater than the provided value.

Parameters `value` (*str or int or float*) – The value used to filter file events.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `less_than(value)`

Returns a *FilterGroup* to find events where filter data is less than than the provided value.

Parameters `value` (*str or int or float*) – The value used to filter file events.

Returns *FilterGroup*

classmethod not_eq(*value*)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_in(*value_list*)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.v2.filters.risk.Score`

Bases: [py42.sdk.queries.query_filter.QueryFilterStringField](#), [py42.sdk.queries.fileevents.util.FileEventFilterComparableField](#)

V2 filter class that filters events by risk score.

classmethod eq(*value*)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod greater_than(*value*)

Returns a [FilterGroup](#) to find events where filter data is greater than the provided value.

Parameters **value** (*str or int or float*) – The value used to filter file events.

Returns [FilterGroup](#)

classmethod is_in(*value_list*)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod less_than(*value*)

Returns a [FilterGroup](#) to find events where filter data is less than than the provided value.

Parameters **value** (*str or int or float*) – The value used to filter file events.

Returns [FilterGroup](#)

classmethod not_eq(*value*)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_in(*value_list*)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.risk.**Severity**

Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField, py42.choices.Choices

V2 filter class that filters events by risk severity.

Available options are provided as class attributes:

- risk.Severity.LOW
- risk.Severity.MODERATE
- risk.Severity.HIGH
- risk.Severity.CRITICAL
- risk.Severity.NO_RISK_INDICATED

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key self._term is in the provided value_list.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key self._term is not in the provided value_list.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.risk.TrustReason`

Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`, `py42.choices.Choices`

V2 filter class that filters events based on the trust reason for the activity.

Available options are provided as class attributes:

- **attr** `risk.TrustReason.TRUSTED_DOMAIN_BROWSER_URL`
- **attr** `risk.TrustReason.TRUSTED_BROWSER_URL_PATH`
- **attr** `risk.TrustReason.TRUSTED_DOMAIN_BROWSER_TAB_TITLE`
- **attr** `risk.TrustReason.TRUSTED_BROWSER_TAB_INFOS`
- **attr** `risk.TrustReason.TRUSTED_DOMAIN_EMAIL_RECIPIENT`
- **attr** `risk.TrustReason.TRUSTED_DOMAIN_CLOUD_SYNC_USERNAME`
- **attr** `risk.TrustReason.TRUSTED_SLACK_WORKSPACE`
- **attr** `risk.TrustReason.EVENT_PAIRING_SERVICE_MATCH`
- **attr** `risk.TrustReason.EVENT_PAIRING_SERVICE_ENDPOINT_MATCH`
- **attr** `risk.TrustReason.DOWNLOAD_TO_A_MANAGED_DEVICE`
- **attr** `risk.TrustReason.SHARED_WITH_TRUSTED_USERS`

classmethod `choices()`

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.risk.Trusted

Bases: *py42.sdk.queries.query_filter.QueryFilterBooleanField*

V2 filter class that filters events based on whether activity can be trusted.

classmethod is_false()

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is False.

Returns *FilterGroup*

classmethod is_true()

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is True.

Returns *FilterGroup*

Source Filters

class py42.sdk.queries.fileevents.v2.filters.source.Category

Bases: *py42.sdk.queries.fileevents.util.FileEventFilterStringField*, *py42.choices.Choices*

V2 filter class that filters events based on source category.

Available options are provided as class attributes:

- `source.Category.BUSINESS_TOOLS`
- `source.Category.CLOUD_STORAGE`
- `source.Category.DEVICE`
- `source.Category.EMAIL`
- `source.Category.MESSAGING`
- `source.Category.MULTIPLE_POSSIBILITIES`
- `source.Category.SOCIAL_MEDIA`
- `source.Category.SOURCE_CODE_REPOSITORY`
- `source.Category.UNCATEGORIZED`
- `source.Category.UNKNOWN`
- `source.category.BUSINESS_INTELLIGENCE_TOOLS`
- `source.category.CIVIL_SERVICES`
- `source.category.CLOUD_COMPUTING`
- `source.category.CODING_TOOLS`
- `source.category.CONTRACT_MANAGEMENT`
- `source.category.CRM_TOOLS`
- `source.category.DESIGN_TOOLS`
- `source.category.E_COMMERCE`
- `source.category.FILE_CONVERSION_TOOLS`
- `source.category.FINANCIAL_SERVICES`
- `source.category.HEALTHCARE_AND_INSURANCE`

- `source.category.HR_TOOLS`
- `source.category.IMAGE_HOSTING`
- `source.category.IT_SERVICES`
- `source.category.JOB_LISTINGS`
- `source.category.LEARNING_PLATFORMS`
- `source.category.MARKETING_TOOLS`
- `source.category.PDF_MANAGER`
- `source.category.PHOTO_PRINTING`
- `source.category.PRODUCTIVITY_TOOLS`
- `source.category.PROFESSIONAL_SERVICES`
- `source.category.REAL_ESTATE`
- `source.category.SALES_TOOLS`
- `source.category.SEARCH_ENGINE`
- `source.category.SHIPPING`
- `source.category.SOFTWARE`
- `source.category.TRAVEL`
- `source.category.WEB_HOSTING`

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.source.Domain`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the domain of the source device.

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.source.EmailFrom`

Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`

V2 filter class that filters events based on the display name of the email's sender, as it appears in the "From:" field in the email (applies to email events only).

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.v2.filters.source.EmailSender`

Bases: [py42.sdk.queries.query_filter.QueryFilterStringField](#)

V2 filter class that filters events based on the email's sender (applies to email events only).

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.source.**IpAddress**

Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events by public (WAN) IP address of the source device.

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key self._term is in the provided value_list.

Parameters *value_list* (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term does not equal the provided value.

Parameters *value* (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key self._term is not in the provided value_list.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.source.**Name**

Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events based on source name.

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_exists()`

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.v2.filters.source.OperatingSystem`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the operating system of the source device.

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod `exists()`

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_exists()`

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.source.PrivateIpAddress`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by private (LAN) IP address of the source device.

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters *value* (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBusType`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the bus type of the connected hardware as reported by the operating system (applies to removable media events only).

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **exists()**

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod **is_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq(value)**

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists()**

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCapacity`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the capacity of the connected hardware as reported by the operating system (applies to `removable media` events only).

classmethod **eq(value)**

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **exists()**

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod **is_in(value_list)**

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaMediaName`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the name of the removable media (as reported by the vendor/device, usually very similar to `RemovableMediaName`) involved in the exposure (applies to removable media events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaName`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the name of the removable media involved in the exposure (applies to removable media events only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaPartitionID`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the unique identifier assigned (by the operating system) to the removable media involved in the exposure (applies to removable media events only).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_exists()

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod not_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns [FilterGroup](#)

class py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaSerialNumber

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the serial number of the connected hardware as reported by the operating system (applies to `removable media` events only).

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVendor

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the vendor of the removable media device involved in the exposure (applies to removable media events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters value (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVolumeName

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the name of the formatted volume (as reported by the operating system) of the removable media device involved in the exposure (applies to `removable media` events only).

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod `exists()`

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_exists()`

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on source tab title errors (for ‘browser or other app’ events).

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod `exists()`

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.source.TabTitles`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on source tab titles (for ‘browser or other app’ events).

classmethod `eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns *FilterGroup*

classmethod `exists()`

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key *self._term* is not in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.source.TabUrlErrors

Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events based on source tab URL Errors (for ‘browser or other app’ events).

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key *self._term* equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key *self._term* is in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key *self._term* does not equal the provided value.

Parameters *value* (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key *self._term* is not in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.source.TabUrls

Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events based on source tab URLs (for ‘browser or other app’ events).

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key *self._term* equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters value_list (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters value_list (list) – The list of values to exclude on.

Returns *FilterGroup*

Timestamp Filters

class py42.sdk.queries.fileevents.v2.filters.timestamp.Timestamp

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterTimestampField`, `py42.choices.Choices`

V2 filter class that filters events based on the timestamp of the event that occurred.

Available event timestamp constants are provided as class attributes, These constants should be used only with class method *within_the_last*:

- `timestamp.Timestamp.FIFTEEN_MINUTES`
- `timestamp.Timestamp.ONE_HOUR`
- `timestamp.Timestamp.THREE_HOURS`
- `timestamp.Timestamp.TWELVE_HOURS`
- `timestamp.Timestamp.ONE_DAY`
- `timestamp.Timestamp.THREE_DAYS`
- `timestamp.Timestamp.SEVEN_DAYS`
- `timestamp.Timestamp.FOURTEEN_DAYS`
- `timestamp.Timestamp.THIRTY_DAYS`

Example:: filter = timestamp.Timestamp.within_the_last(EventTimestamp.SEVEN_DAYS)

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod in_range(start_value, end_value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- **start_value** (*str or int or float or datetime*) – The start value used to filter results.
- **end_value** (*str or int or float or datetime*) – The end value used to filter results.

Returns *FilterGroup*

classmethod on_or_after(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term`` is on or after the provided ``value.

Parameters value (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod on_or_before(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters value (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod on_same_day(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters value (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod within_the_last(value)

Returns a *FilterGroup* that is useful for finding results where the key `self._term` is a timestamp-related term, such as `EventTimestamp._term`, and value is one of it's accepted values, such as one of the values in `EventTimestamp.choices()`.

Parameters value (*str*) – The value used to filter file events.

Returns *FilterGroup*

User Filters

class py42.sdk.queries.fileevents.v2.filters.user.DeviceUid

Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events by the device UID of the actor.

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key *self._term* equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key *self._term* is in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key *self._term* does not equal the provided value.

Parameters *value* (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key *self._term* is not in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.user.Email

Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events by the Code42 user email of the actor.

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key *self._term* equals the provided value.

Parameters *value* (*str*) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_exists()`

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod `not_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.v2.filters.user.Id`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the Code42 user ID of the actor.

classmethod `eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (*str*) – The value to match on.

Returns [FilterGroup](#)

classmethod `exists()`

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod `is_in(value_list)`

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (*list*) – The list of values to match on.

Returns [FilterGroup](#)

classmethod `not_eq(value)`

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (*str*) – The value to exclude on.

Returns [FilterGroup](#)

classmethod `not_exists()`

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in**(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

2.14 Legal Hold

class `py42.services.legalhold.LegalHoldService`(*connection*)

Bases: `py42.services.BaseService`

A service for interacting with Code42 Legal Hold APIs.

The LegalHoldService provides the ability to manage Code42 Legal Hold Policies and Matters. It can: - Create, view, and list all existing Policies. - Create, view, deactivate, reactivate, and list all existing Matters. - Add/remove Custodians from a Matter.

add_to_matter(*user_uid*, *legal_hold_uid*)

Add a user (Custodian) to a Legal Hold Matter.

Parameters

- **user_uid** (*str*) – The identifier of the user.
- **legal_hold_uid** (*str*) – The identifier of the Legal Hold Matter.

Returns *py42.response.Py42Response*

create_matter(*name*, *hold_policy_uid*, *description=None*, *notes=None*, *hold_ext_ref=None*)

Creates a new, active Legal Hold Matter.

Parameters

- **name** (*str*) – The name of the new Legal Hold Matter.
- **hold_policy_uid** (*str*) – The identifier of the Preservation Policy that will apply to this Matter.
- **description** (*str*, *optional*) – An optional description of the Matter. Defaults to None.
- **notes** (*str*, *optional*) – Optional notes information. Defaults to None.
- **hold_ext_ref** (*str*, *optional*) – Optional external reference information. Defaults to None.

Returns *py42.response.Py42Response*

create_policy(*name*, *policy=None*)

Creates a new Legal Hold Preservation Policy.

Parameters

- **name** (*str*) – The name of the new Policy.
- **policy** (*dict*, *optional*) – The desired Preservation Policy settings as a dict. Defaults to None (where the server-default backup set is used).

Returns *py42.response.Py42Response*

deactivate_matter(*legal_hold_uid*)

Deactivates and closes a Legal Hold Matter.

Parameters **legal_hold_uid** (*str*) – The identifier of the Legal Hold Matter.

Returns *py42.response.Py42Response*

get_all_events(*legal_hold_uid=None, min_event_date=None, max_event_date=None*)

Gets an individual page of Legal Hold events.

Parameters

- **legal_hold_uid** (*str, optional*) – Find LegalHoldEvents for the Legal Hold Matter with this unique identifier. Defaults to None.
- **min_event_date** (*str or int or float or datetime, optional*) – Find LegalHoldEvents whose eventDate is equal to or after this time. E.g. yyyy-MM-dd HH:MM:SS. Defaults to None.
- **max_event_date** (*str or int or float or datetime, optional*) – Find LegalHoldEvents whose eventDate is equal to or before this time. E.g. yyyy-MM-dd HH:MM:SS. Defaults to None.

Returns An object that iterates over *py42.response.Py42Response* objects that each contain a page of LegalHoldEvent objects.

Return type generator

get_all_matter_custodians(*legal_hold_uid=None, user_uid=None, user=None, active=True*)

Gets all Legal Hold memberships.

Each user (Custodian) who has been added to a Legal Hold Matter is returned by the server as a LegalHoldMembership object in the response body. If the object's active state is "INACTIVE", they have been removed from the Matter and are no longer subject to the Legal Hold retention rules. Users can be Custodians of multiple Legal Holds at once (and thus would be part of multiple LegalHoldMembership objects).

Parameters

- **legal_hold_uid** (*str, optional*) – Find LegalHoldMemberships for the Legal Hold Matter with this unique identifier. Defaults to None.
- **user_uid** (*str, optional*) – Find LegalHoldMemberships for the user with this identifier. Defaults to None.
- **user** (*str, optional*) – Find LegalHoldMemberships by flexibly searching on username, email, extUserRef, or last name. Will find partial matches. Defaults to None.
- **active** (*bool or None, optional*) – Find LegalHoldMemberships by their active state. True returns active LegalHoldMemberships, False returns inactive LegalHoldMemberships, None returns all LegalHoldMemberships regardless of state. Defaults to True.

Returns An object that iterates over *py42.response.Py42Response* objects that each contain a page of LegalHoldMembership objects.

Return type generator

get_all_matters(*creator_user_uid=None, active=True, name=None, hold_ext_ref=None*)

Gets all existing Legal Hold Matters.

Parameters

- **creator_user_uid** (*str, optional*) – Find Matters by the identifier of the user who created them. Defaults to None.

- **active** (*bool or None, optional*) – Find Matters by their active state. True returns active Matters, False returns inactive Matters, None returns all Matters regardless of state. Defaults to True.
- **name** (*str, optional*) – Find Matters with a ‘name’ that either equals or contains this value. Defaults to None.
- **hold_ext_ref** (*str, optional*) – Find Matters having a matching external reference field. Defaults to None.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of Legal Hold Matters.

Return type generator

get_custodians_page(*page_num, legal_hold_membership_uid=None, legal_hold_uid=None, user_uid=None, user=None, active=True, page_size=None*)

Gets an individual page of Legal Hold memberships. One of the following optional args is required to determine which custodians to retrieve:

legal_hold_membership_uid, legal_hold_uid, user_uid, user

Parameters

- **page_num** (*int*) – The page number to request.
- **legal_hold_membership_uid** (*str, optional*) – Find LegalHoldMemberships with a specific membership UID. Defaults to None.
- **legal_hold_uid** (*str, optional*) – Find LegalHoldMemberships for the Legal Hold Matter with this unique identifier. Defaults to None.
- **user_uid** (*str, optional*) – Find LegalHoldMemberships for the user with this identifier. Defaults to None.
- **user** (*str, optional*) – Find LegalHoldMemberships by flexibly searching on username, email, extUserRef, or last name. Will find partial matches. Defaults to None.
- **active** (*bool or None, optional*) – Find LegalHoldMemberships by their active state. True returns active LegalHoldMemberships, False returns inactive LegalHoldMemberships, None returns all LegalHoldMemberships regardless of state. Defaults to True.
- **page_size** (*int, optional*) – The size of the page. Defaults to `py42.settings.items_per_page`.

Return type `py42.response.Py42Response`

get_events_page(*legal_hold_uid=None, min_event_date=None, max_event_date=None, page_num=1, page_size=None*)

Gets an individual page of Legal Hold events.

Parameters

- **legal_hold_uid** (*str, optional*) – Find LegalHoldEvents for the Legal Hold Matter with this unique identifier. Defaults to None.
- **min_event_date** (*str or int or float or datetime, optional*) – Find LegalHoldEvents whose eventDate is equal to or after this time. E.g. yyyy-MM-dd HH:MM:SS. Defaults to None.
- **max_event_date** (*str or int or float or datetime, optional*) – Find LegalHoldEvents whose eventDate is equal to or before this time. E.g. yyyy-MM-dd HH:MM:SS. Defaults to None.

- **page_num** (*int*) – The page number to request. Defaults to 1.
- **page_size** (*int, optional*) – The size of the page. Defaults to `py42.settings.items_per_page`.

Return type `py42.response.Py42Response`

get_matter_by_uid(*legal_hold_uid*)

Gets a single Legal Hold Matter.

Parameters **legal_hold_uid** (*str*) – The identifier of the Legal Hold Matter.

Returns A response containing the Matter.

Return type `py42.response.Py42Response`

get_matters_page(*page_num, creator_user_uid=None, active=True, name=None, hold_ext_ref=None, page_size=None*)

Gets a page of existing Legal Hold Matters.

Parameters

- **page_num** (*int*) – The page number to request.
- **creator_user_uid** (*str, optional*) – Find Matters by the identifier of the user who created them. Defaults to None.
- **active** (*bool or None, optional*) – Find Matters by their active state. True returns active Matters, False returns inactive Matters, None returns all Matters regardless of state. Defaults to True.
- **name** (*str, optional*) – Find Matters with a ‘name’ that either equals or contains this value. Defaults to None.
- **hold_ext_ref** (*str, optional*) – Find Matters having a matching external reference field. Defaults to None.
- **page_size** (*int, optional*) – The number of legal hold items to return per page. Defaults to `py42.settings.items_per_page`.

Return type `py42.response.Py42Response`

get_policy_by_uid(*legal_hold_policy_uid*)

Gets a single Preservation Policy.

Parameters **legal_hold_policy_uid** (*str*) – The identifier of the Preservation Policy.

Returns A response containing the Policy.

Return type `py42.response.Py42Response`

get_policy_list()

Gets a list of existing Preservation Policies.

Returns A response containing the list of Policies.

Return type `py42.response.Py42Response`

reactivate_matter(*legal_hold_uid*)

Reactivates and re-opens a closed Matter.

Parameters **legal_hold_uid** (*str*) – The identifier of the Legal Hold Matter.

Returns `py42.response.Py42Response`

remove_from_matter(*legal_hold_membership_uid*)

Remove a user (Custodian) from a Legal Hold Matter.

Parameters `legal_hold_membership_uid (str)` – The identifier of the LegalHoldMembership representing the Custodian to Matter relationship.

Returns `py42.response.Py42Response`

2.15 Orgs

class `py42.services.orgs.OrgService(connection)`

Bases: `py42.services.BaseService`

A service for interacting with Code42 organization APIs.

Use the OrgService to create and retrieve organizations. You can also use it to block and deactivate organizations.

block(`org_id`)

Blocks the organization with the given org ID as well as its child organizations. A blocked organization will not allow any of its users or devices to log in. New registrations will be rejected and all currently logged in clients will be logged out. Backups continue for any devices that are still active.

Parameters `org_id (int)` – An ID for an organization.

Returns `py42.response.Py42Response`

create_org(`org_name, org_ext_ref=None, notes=None, parent_org_uid=None`)

Creates a new organization.

Parameters

- **org_name** (`str`) – The name of the new organization.
- **org_ext_ref** (`str, optional`) – External reference information, such as a serial number, asset tag, employee ID, or help desk issue ID. Defaults to None.
- **notes** (`str, optional`) – Descriptive information about the organization. Defaults to None.
- **parent_org_uid** (`int, optional`) – The org UID for the parent organization. Defaults to None.

Returns `py42.response.Py42Response`

deactivate(`org_id`)

Deactivates the organization with the given ID, including all users, plans, and devices. Backups stop and archives move to cold storage.

Parameters `org_id (int)` – An ID for an organization.

Returns `py42.response.Py42Response`

get_agent_full_disk_access_states(`org_id`)

Gets the full disk access status for devices in an org.

Parameters `org_id (str)` – The org's identifier.

Returns A response containing settings information.

Return type `py42.response.Py42Response`

get_agent_state(`org_id, property_name`)

Gets the agent state of the devices in the org.

Parameters

- **org_id** (*str*) – The org’s identifier.
- **property_name** (*str*) – The name of the property to retrieve (e.g. *fullDiskAccess*).

Returns A response containing settings information.

Return type `py42.response.Py42Response`

get_all(***kwargs*)

Gets all organizations.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of organizations.

Return type generator

get_by_id(*org_id*, ***kwargs*)

Gets the organization with the given ID.

Parameters **org_id** (*int*) – An ID for an organization.

Returns A response containing the organization.

Return type `py42.response.Py42Response`

get_by_uid(*org_uid*, ***kwargs*)

Gets the organization with the given UID.

Parameters **org_uid** (*str*) – A UID for an organization.

Returns A response containing the organization.

Return type `py42.response.Py42Response`

get_current(***kwargs*)

Gets the organization for the currently signed-in user.

Returns A response containing the organization for the currently signed-in user.

Return type `py42.response.Py42Response`

get_page(*page_num*, *page_size=None*, ***kwargs*)

Gets an individual page of organizations.

Parameters

- **page_num** (*int*) – The page number to request.
- **page_size** (*int*, *optional*) – The number of organizations to return per page. Defaults to `py42.settings.items_per_page`.
- **kwargs** (*dict*, *optional*) – Additional advanced-user arguments. Defaults to None.

Returns `py42.response.Py42Response`

get_settings(*org_id*)

Gets setting data for an org and returns an *OrgSettingsManager* for the target org.

Parameters **org_id** (*int*, *str*) – The identifier of the org.

Returns A class to help manage org settings.

Return type `py42.clients._settings_managers.OrgSettings`

reactivate(*org_id*)

Reactivates the organization with the given ID. Backups are *not* restarted automatically.

Parameters **org_id** (*int*) – An ID for an organization.

Returns *py42.response.Py42Response*

unblock(*org_id*)

Removes a block, if one exists, on an organization and its descendants with the given ID. All users in the organization remain blocked until they are unblocked individually.

Parameters *org_id* (*int*) – An ID for an organization.

Returns *py42.response.Py42Response*

update_settings(*org_settings*)

Updates an org's settings based on changes to the passed in *OrgSettings* instance.

Parameters *org_settings* (*OrgSettings*) – An *OrgSettings* instance with desired modifications to settings.

Returns A namedtuple containing the result of the setting change api calls.

Return type *py42.services.orgs.OrgSettings*

2.16 Org Settings

class *py42.clients.settings.org_settings.OrgSettings*(*org_settings*, *t_settings*)

Bases: *collections.UserDict*

Class used to manage an Organization's settings.

archive_hold_days

Number of days backup archives are held in cold storage after deactivation or destination removal from any devices in this Org.

backup_alert_recipient_emails

List of email addresses that organization backup alert emails get sent to (org admin users get these automatically).

backup_critical_email_days

The number of days devices in this org can go without any backup before "critical" alerts get sent to org admins.

backup_warning_email_days

The number of days devices in this org can go without any backup before "warning" alerts get sent to org admins.

endpoint_monitoring_background_priority_enabled

Determines if devices in this org have reduced priority in some IO bound tasks. If enabled, devices may see improved general device performance at the expense of some Code42 backup/security tasks taking longer.

property endpoint_monitoring_browser_and_applications_enabled

Determines if browser and other application activity endpoint monitoring event capturing is enabled for this org.

property endpoint_monitoring_cloud_sync_enabled

Determines if cloud sync endpoint monitoring event capturing is enabled for this org.

endpoint_monitoring_custom_applications_mac

List of additional applications the Code42 client monitors for file exfiltration activity.

See [Support Documentation](#) for more details.

endpoint_monitoring_custom_applications_win

List of additional applications the Code42 client monitors for file exfiltration activity.

See [Support Documentation](#) for more details.

property endpoint_monitoring_enabled

Determines if endpoint monitoring settings are enabled for this org.

Disabling this property also disables “removable media”, “cloud sync”, “browser and application monitoring” and “printer detection” properties.

endpoint_monitoring_file_exfiltration_detection_exclusions

File types and file paths to exclude from file exfiltration detection.

See [Support Documentation](#) for more details on the shape of the body this setting expects.

property endpoint_monitoring_file_metadata_collection_enabled

Determines if file metadata collection is enabled for this org.

endpoint_monitoring_file_metadata_collection_exclusions

File types and file paths to exclude from file metadata collection.

See [Support Documentation](#) for more details on the shape of the body this setting expects.

endpoint_monitoring_file_metadata_ingest_scan_enabled

Determines if file metadata collection does an initial full scan when first enabled on devices.

endpoint_monitoring_file_metadata_scan_enabled

Determines if file metadata collection regular full scans are enabled for this org.

property endpoint_monitoring_printer_detection_enabled

Determines if printer endpoint monitoring event capturing is enabled for this org.

property endpoint_monitoring_removable_media_enabled

Determines if removable media endpoint monitoring event capturing is enabled for this org.

external_reference

External reference field for this Org.

maximum_user_subscriptions

Number of users allowed to consume a license in this Org. Set to -1 for unlimited.

notes

Notes field for this Org.

org_backup_quota

Backup storage quota (in GB) for this organization. Set to -1 for unlimited.

property org_id

The identifier for the org.

org_name

Name for this Org.

property packets

The setting packets for any modifications to be posted to the /api/v1/OrgSettings endpoint.

quota_settings_inherited

Determines if Org Quota settings (*maximum_user_subscriptions*, *org_backup_quota*, *user_backup_quota*, *archive_hold_days*) are inherited from parent organization.

Modifying one of the Org Quota attributes automatically sets this attribute to *False*.

property registration_key

The registration key for the org.

reporting_settings_inherited

Determines if Org Reporting settings (*backup_warning_email_days*, *backup_critical_email_days*, *backup_alert_recipient_emails*) are inherited from parent organization.

Modifying one of the Org Reporting attributes automatically sets this attribute to *False*.

user_backup_quota

Backup storage quota (in GB) for each user in this organization. Set to -1 for unlimited.

web_restore_admin_limit

Limit (in MB) to amount of data restorable by admin users via web restore.

web_restore_enabled

Determines if web restores are enabled for devices in this org.

web_restore_user_limit

Limit (in MB) to amount of data restorable by non-admin users via web restore.

class `py42.clients.settings.device_settings.DeviceSettingsDefaults(device_dict, org_settings)`

Bases: `collections.UserDict`

Class used for managing an Organization's Device Default settings. Also acts as a base class for *DeviceSettings* to manage individual device settings.

property available_destinations

Returns a dict of destinations available to be used by devices. Dict keys are destination guids and values are destination names.

backup_status_email_enabled

Determines if the regularly scheduled backup status email is enabled.

backup_status_email_frequency_days

Determines the frequency of the regularly scheduled backup status email.

critical_alert_days

The number of days a device can go without any backup activity before "warning" alert threshold is passed.

critical_email_enabled

Determines if backup "critical" threshold email alerts are configured for this device.

warning_alert_days

The number of days a device can go without any backup activity before "warning" alert threshold is passed.

warning_email_enabled

Determines if backup "warning" threshold email alerts are configured for this device.

2.17 Response

class `py42.response.Py42Response(requests_response)`

Bases: `object`

property encoding

The encoding used to decode the response text.

property headers

A case-insensitive dictionary of response headers.

iter_content(chunk_size=1, decode_unicode=False)

Iterates over the response data. When *stream=True* is set on the request, this avoids reading the content at once into memory for large responses.

Parameters

- **chunk_size** (*int, optional*) – The number of bytes it should read into memory. A value of None will function differently depending on the value of *stream*. *stream=True* will read data as it arrives in whatever size the chunks are received. If *stream=False*, data is returned as a single chunk. This is not necessarily the length of each item. Defaults to 1.
- **decode_unicode** (*bool, optional*) – If True, content will be decoded using the best available encoding based on the response. Defaults to False.

property raw_text

The `response.Response.text` property. It contains raw metadata that is not included in the `Py42Response.text` property.

property status_code

An integer code of the response HTTP Status, e.g. 404 or 200.

property text

The more useful parts of the HTTP response dumped into a dictionary.

property url

The final URL location of response.

2.18 Security Data

Warning: V1 file events, saved searches, and queries are **deprecated**.

For details on using the new file event data model, see the [V2 File Events User Guide](#).

class `py42.clients.securitydata.SecurityDataClient`(*file_event_service, preservation_data_service, saved_search_service, storage_service_factory*)

Bases: `object`

property savedsearches

A collection of methods related to retrieving forensic search data.

Returns `class: py42.services.savedsearch.SavedSearchService`

search_all_file_events(*query, page_token=""*)

Searches for all file events, returning a page of events with a token in the response to retrieve next page. [REST Documentation](#)

Parameters

- **query** (*str* or `py42.sdk.queries.fileevents.v2.file_event_query.FileEventQuery`) – The file event query to filter search results.
- **page_token** (*str, optional*) – A token used to indicate the starting point for additional page results. For the first page, do not pass `page_token`. For all consecutive pages, pass the token from the previous response from field `nextPgToken`. Defaults to empty string.

Returns A response containing a page of events.

Return type `py42.response.Py42Response`

search_file_events(*query*)

Searches for file events, returns up to the first 10,000 events. [REST Documentation](#)

Parameters **query** (str or `py42.sdk.queries.fileevents.v2.file_event_query.FileEventQuery`) – The file event query to filter search results.

Returns A response containing the first 10,000 events.

Return type `py42.response.Py42Response`

stream_file_by_md5(*checksum*)

Stream file based on MD5 checksum.

Parameters **checksum** (str) – MD5 hash of the file.

Returns Returns a stream of the requested file.

stream_file_by_sha256(*checksum*)

Stream file based on SHA256 checksum.

Parameters **checksum** (str) – SHA256 hash of the file.

Returns Returns a stream of the requested file.

2.19 Shared Query Filters

class `py42.sdk.queries.query_filter.FilterGroup`(*filter_list*, *filter_clause*='AND')

Bases: object

Class for constructing a logical sub-group of related filters from a list of `QueryFilter` objects. Takes a list of `QueryFilter` objects and combines them logically using the passed in filter clause (AND or OR).

When `str()` is called on a `FilterGroup` instance, the combined filter items are transformed into a JSON string to be used as part of a Forensic Search or Alert query.

When `dict()` is called on a `FilterGroup` instance, the combined filter items are transformed into the Python *dict* equivalent of their JSON representation. This can be useful for programmatically manipulating a `FilterGroup` after it's been created.

property **filter_clause**

The clause joining the filters, such as AND or OR.

property **filter_list**

The list of `QueryFilter` objects in this group.

classmethod **from_dict**(*_dict*)

Creates an instance of `FilterGroup` from the values found in `_dict`. `_dict` must contain keys `filters` and `filterClause`.

Parameters **_dict** (*dict*) – A dictionary containing keys `term`, `operator`, and `value`.

Returns `FilterGroup`

class `py42.sdk.queries.query_filter.QueryFilter`(*term*, *operator*, *value*=None)

Bases: object

Class for constructing a single filter object for use in a search query.

When `str()` is called on a `QueryFilter` instance, the (`term`, `operator`, `value`) attribute combination is transformed into a JSON string to be used as part of a Forensic Search or Alert query.

When `dict()` is called on a `QueryFilter` instance, the (`term`, `operator`, `value`) attribute combination is transformed into the Python *dict* equivalent of their JSON representation. This can be useful for programmatically manipulating a `QueryFilter` after it's been created.

classmethod `from_dict(_dict)`

Creates an instance of `QueryFilter` from the values found in `_dict`. `_dict` must contain keys `term`, `operator`, and `value`.

Parameters `_dict (dict)` – A dictionary containing keys `term`, `operator`, and `value`.

Returns `QueryFilter`

property `operator`

The operator between `term` and `value`, such as `IS` or `IS_NOT`.

property `term`

The term of the filter, such as `actor` or `sharedWith`.

property `value`

The value used to filter results.

class `py42.sdk.queries.query_filter.QueryFilterBooleanField`

Bases: `object`

Helper class for creating filters where the search value is a boolean.

classmethod `is_false()`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` is `False`.

Returns `FilterGroup`

classmethod `is_true()`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` is `True`.

Returns `FilterGroup`

class `py42.sdk.queries.query_filter.QueryFilterStringField`

Bases: `object`

Helper class for creating filters where the search value is a string.

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `is_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

`class py42.sdk.queries.query_filter.QueryFilterTimestampField`

Bases: object

Helper class for creating filters where the search value is a timestamp.

classmethod `in_range(start_value, end_value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- **start_value** (*str or int or float or datetime*) – The start value used to filter results.
- **end_value** (*str or int or float or datetime*) – The end value used to filter results.

Returns *FilterGroup*

classmethod `on_or_after(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term`` is on or after the provided ``value.

Parameters **value** (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod `on_or_before(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters **value** (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod `on_same_day(value)`

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters **value** (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_eq_filter_group(term, value)`

“Creates a *FilterGroup* for filtering results where the value with key `term` equals the given value. Useful for creating IS filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **term** – (str): The term of the filter, such as `actor` or `sharedWith`.
- **value** (str) – The value used to match on.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_filter_group(query_filter_list, filter_clause)`

Creates a *FilterGroup* object. Useful for programmatically crafting query filters, such as filters not yet defined in py42. Alternatively, if you want to create custom filter groups with already defined operators (such as *IS* or *IS_IN*), see the other methods in this module, such as `create_eq_filter_group()`.

Parameters

- **query_filter_list** (*list*) – a list of *QueryFilter* objects.

- **filter_clause** (*str*) – The clause joining the filters, such as AND or OR.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_in_range_filter_group(term, start_value, end_value)`

“Creates a *FilterGroup* for filtering results where the value with key *term* is in the given range. Examples include values describing dates. Useful for creating a combination of ON_OR_AFTER and ON_OR_BEFORE filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **term** – (*str*): The term of the filter, such as `eventTimestamp`.
- **start_value** (*str or int*) – The start value used to filter results.
- **end_value** (*str or int*) – The end value used to filter results.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_is_in_filter_group(term, value_list)`

“Creates a *FilterGroup* for filtering results where the value with key *term* is one of several values. Useful for creating IS_IN filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **term** – (*str*): The term of the filter, such as `actor` or `sharedWith`.
- **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_not_eq_filter_group(term, value)`

“Creates a *FilterGroup* for filtering results where the value with key *term* does not equal the given value. Useful for creating IS_NOT filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **term** – (*str*): The term of the filter, such as `actor` or `sharedWith`.
- **value** (*str*) – The value used to exclude on.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_not_in_filter_group(term, value_list)`

“Creates a *FilterGroup* for filtering results where the value with key *term* is not one of several values. Useful for creating NOT_IN filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **term** – (*str*): The term of the filter, such as `actor` or `sharedWith`.
- **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_on_or_after_filter_group(term, value)`

“Creates a *FilterGroup* for filtering results where the value with key *term* is on or after the given value. Examples include values describing dates. Useful for creating ON_OR_AFTER filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **term** – (*str*): The term of the filter, such as `eventTimestamp`.
- **value** (*str or int*) – The value used to filter results.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_on_or_before_filter_group(term, value)`

“Creates a [FilterGroup](#) for filtering results where the value with key `term` is on or before the given value. Examples include values describing dates. Useful for creating ON_OR_BEFORE filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **term** (*str*) – The term of the filter, such as `eventTimestamp`.
- **value** (*str or int*) – The value used to filter results.

Returns [FilterGroup](#)

`py42.sdk.queries.query_filter.create_query_filter(term, operator, value=None)`

Creates a [QueryFilter](#) object. Useful for programmatically crafting query filters, such as filters not yet defined in py42.

Parameters

- **term** (*str*) – The term of the filter, such as `actor` or `sharedWith`.
- **operator** (*str*) – The operator between `term` and `value`, such as `IS` or `IS_NOT`.
- **value** (*str*) – The value used to filter results.

Returns [QueryFilter](#)

`py42.sdk.queries.query_filter.create_within_the_last_filter_group(term, value)`

Returns a [FilterGroup](#) that is useful for finding results where the key `term` is an `EventTimestamp._term` and the value is one of the `EventTimestamp` attributes as `value`.

Parameters **value** (*str*) – `EventTimestamp` attribute.

Returns [FilterGroup](#)

2.20 Trusted Activities

class `py42.clients.trustedactivities.TrustedActivityType`

Bases: `py42.choices.Choices`

Constants available for setting the type of a trusted activity.

- `DOMAIN`
- `SLACK`

class `py42.clients.trustedactivities.TrustedActivitiesClient(trusted_activities_service)`

Bases: `object`

A client to expose the trusted activities/data preferences API

[Rest documentation](#)

create(*type, value, description=None*)

Gets all trusted activities with the given type. [Rest documentation](#)

Parameters

- **type** (*str*) – Type of the trusted activity. Constants available at [py42.constants.TrustedActivityType](#).
- **value** (*str*) – The URL of the domain or name of the Slack workspace.
- **description** (*str, optional*) – Description of the trusted activity.

Returns `py42.response.Py42Response`

delete(*id*)

Deletes a trusted activity by given resource number. [Rest documentation](#)

Parameters *id* (*int*) – Resource number of the trusted activity or domain.

Returns `py42.response.Py42Response`

get(*id*)

Retrieve trusted activity details by given resource number. [Rest documentation](#)

Parameters *id* (*int*) – Resource number of the trusted activity or domain.

Returns `py42.response.Py42Response`

get_all(*type=None, page_size=None*)

Gets all trusted activities. [Rest documentation](#)

Parameters

- **type** (*str, optional*) – Type of the trusted activity. Defaults to None. Constants available at `py42.constants.TrustedActivityType`.
- **page_size** (*int, optional*) – Number of results to return per page. Defaults to 100.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of cases.

Return type generator

update(*id, value=None, description=None*)

Updates trusted activity details by given resource number. [Rest documentation](#)

Parameters

- **id** (*int*) – Resource number of the trusted activity.
- **value** (*str, optional*) – The URL of the domain or name of the Slack workspace.
- **description** (*str, optional*) – Description of the trusted activity.

Returns `py42.response.Py42Response`

2.21 User Risk Profiles

class `py42.clients.userriskprofile.UserRiskProfileClient`(*user_risk_profile_service*)

Bases: object

A client to expose the user risk profile API.

[Rest Documentation](#)

add_cloud_aliases(*user_id, cloud_alias*)

Add cloud aliases to a user risk profile.

Parameters

- **user_id** (*str*) – The user UID.
- **cloud_alias** (*str or list(str)*) – The alias(es) to add to the user risk profile. Each user starts with a default alias of their code42 username and can have one additional cloud alias.

Returns `py42.response.Py42Response`

delete_cloud_aliases(*user_id*, *cloud_aliases*)

Delete cloud aliases from a user risk profile.

Parameters

- **user_id** (*str*) – The user UID.
- **cloud_aliases** (*str* or *list(str)*) – The alias(es) to remove from the user risk profile. Each user starts with a default alias of their code42 username and can have one additional cloud alias.

Returns [*py42.response.Py42Response*](#)

get_all(*manager_id=None*, *title=None*, *division=None*, *department=None*, *employment_type=None*, *country=None*, *region=None*, *locality=None*, *active=None*, *deleted=None*, *support_user=None*)

Get all user risk profiles.

Parameters

- **manager_id** (*str*, *optional*) – Matches users whose manager has the given Code42 user UID. Defaults to None
- **title** (*str*, *optional*) – Matches users with the given job title. Defaults to None
- **division** (*str*, *optional*) – Matches users in the given division. Defaults to None
- **department** (*str*, *optional*) – Matches users in the given department. Defaults to None
- **employment_type** (*str*, *optional*) – Matches users with the given employment type. Defaults to None
- **country** (*str*, *optional*) – Matches users in the given country. Defaults to None
- **region** (*str*, *optional*) – Matches users the given region (state). Defaults to None
- **locality** (*str*, *optional*) – Matches users in the given locality (city). Defaults to None
- **active** (*boolean*, *optional*) – Matches users by whether the user is active. Defaults to None
- **deleted** (*boolean*, *optional*) – Matches users by whether the user is deleted. Defaults to None
- **support_user** (*boolean*, *optional*) – Matches users by whether the user is a support user. Defaults to None

Returns An object that iterates over [*py42.response.Py42Response*](#) objects that each contain a page of user risk profiles.

Return type generator

get_by_id(*user_id*)

Get a user risk profile by a user UID.

Parameters **user_id** (*str*) – A unique user UID.

Returns [*py42.response.Py42Response*](#)

get_by_username(*username*)

Get a user risk profile by username.

Parameters **username** (*str*) – A username.

Returns [*py42.response.Py42Response*](#)

get_page(*page_num=1, page_size=None, manager_id=None, title=None, division=None, department=None, employment_type=None, country=None, region=None, locality=None, active=None, deleted=None, support_user=None*)

Get a page of user risk profiles.

Parameters

- **page_num** (*integer, optional*) – The desired page of user risk profile results to retrieve. Defaults to None
- **page_size** (*integer, optional*) – The desired number of results per page. Defaults to None
- **manager_id** (*str, optional*) – Matches users whose manager has the given Code42 user UID. Defaults to None
- **title** (*str, optional*) – Matches users with the given job title. Defaults to None
- **division** (*str, optional*) – Matches users in the given division. Defaults to None
- **department** (*str, optional*) – Matches users in the given department. Defaults to None
- **employment_type** (*str, optional*) – Matches users with the given employment type. Defaults to None
- **country** (*str, optional*) – Matches users in the given country. Defaults to None
- **region** (*str, optional*) – Matches users the given region (state). Defaults to None
- **locality** (*str, optional*) – Matches users in the given locality (city). Defaults to None
- **active** (*boolean, optional*) – Matches users by whether the user is active. Defaults to None
- **deleted** (*boolean, optional*) – Matches users by whether the user is deleted. Defaults to None
- **support_user** (*boolean, optional*) – Matches users by whether the user is a support user. Defaults to None

Returns [*py42.response.Py42Response*](#)

update(*user_id, start_date=None, end_date=None, notes=None*)

Update a user risk profile.

For each arg, if None is provided, the value will not be updated. Pass an empty string if you want to clear that value from the profile.

Parameters

- **user_id** (*str*) – The UID of the user to update.
- **start_date** (*str or datetime, optional*) – The start date of the user risk profile to be updated. Expects format of 'YYYY-MM-DD' or instance of datetime. Defaults to None.
- **end_date** (*str or datetime, optional*) – The departure date of the user risk profile to be updated. Expects format of 'YYYY-MM-DD' or instance of datetime. Defaults to None.
- **notes** (*str, optional*) – The notes field of the user risk profile to be updated. Defaults to None

Returns [*py42.response.Py42Response*](#)

2.22 Users

class `py42.services.users.UserService(connection)`

Bases: `py42.services.BaseService`

A service for interacting with Code42 user APIs. Use the `UserService` to create and retrieve users. You can also use it to block and deactivate users.

add_role(*user_id*, *role_name*)

Adds a role to a user.

Parameters

- **user_id** (*int*) – An ID for a user.
- **role_name** (*str*) – The name of the role to assign to the user.

Returns `py42.response.Py42Response`

block(*user_id*)

Blocks the user with the given ID. A blocked user is not allowed to log in or restore files. Backups will continue if the user is still active.

Parameters **user_id** (*int*) – An ID for a user.

Returns `py42.response.Py42Response`

change_org_assignment(*user_id*, *org_id*)

Assigns a user to a different organization.

Parameters

- **user_id** (*int*) – An ID for a user.
- **org_id** (*int*) – An ID for the organization to move the user to.

Returns `py42.response.Py42Response`

create_user(*org_uid*, *username*, *email*, *password=None*, *first_name=None*, *last_name=None*, *notes=None*)

Creates a new user. WARNING: If the provided username already exists for a user, it will be updated in the database instead.

Parameters

- **org_uid** (*str*) – The org UID for the organization the new user belongs to.
- **username** (*str*) – The username for the new user.
- **email** (*str*) – The email for the new user.
- **password** (*str*, *optional*) – The password for the new user. Defaults to None.
- **first_name** (*str*, *optional*) – The first name for the new user. Defaults to None.
- **last_name** (*str*, *optional*) – The last name for the new user. Defaults to None.
- **notes** (*str*, *optional*) – Descriptive information about the user. Defaults to None.

Returns `py42.response.Py42Response`

deactivate(*user_id*, *block_user=None*)

Deactivates the user with the given user ID. Backups discontinue for a deactivated user, and their archives go to cold storage.

Parameters

- **user_id** (*int*) – An ID for a user.

- **block_user** (*bool*, *optional*) – Blocks the user upon deactivation. Defaults to None.

Returns [py42.response.Py42Response](#)

get_all (*active=None*, *email=None*, *org_uid=None*, *role_id=None*, *q=None*, ***kwargs*)

Gets all users.

Parameters

- **active** (*bool*, *optional*) – True gets active users only, and false gets deactivated users only. Defaults to None.
- **email** (*str*, *optional*) – Limits users to only those with this email. Defaults to None.
- **org_uid** (*str*, *optional*) – Limits users to only those in the organization with this org UID. Defaults to None.
- **role_id** (*int*, *optional*) – Limits users to only those with a given role ID. Defaults to None.
- **q** (*str*, *optional*) – A generic query filter that searches across name, username, and email. Defaults to None.

Returns An object that iterates over [py42.response.Py42Response](#) objects that each contain a page of users.

Return type generator

get_available_roles()

Report the list of roles that are available for the authenticated user to assign to other users.

Returns [py42.response.Py42Response](#)

get_by_id (*user_id*, ***kwargs*)

Gets the user with the given ID. [Rest Documentation](#)

Parameters **user_id** (*int*) – An ID for a user.

Returns A response containing the user.

Return type [py42.response.Py42Response](#)

get_by_uid (*user_uid*, ***kwargs*)

Gets the user with the given UID.

Parameters **user_uid** (*str*) – A UID for a user.

Returns A response containing the user.

Return type [py42.response.Py42Response](#)

get_by_username (*username*, ***kwargs*)

Gets the user with the given username.

Parameters **username** (*str* or *unicode*) – A username for a user.

Returns A response containing the user.

Return type [py42.response.Py42Response](#)

get_current (***kwargs*)

Gets the currently signed in user.

Returns A response containing the user.

Return type [py42.response.Py42Response](#)

get_page(*page_num*, *active=None*, *email=None*, *org_uid=None*, *role_id=None*, *page_size=None*, *q=None*, ***kwargs*)

Gets an individual page of users.

Parameters

- **page_num** (*int*) – The page number to request.
- **active** (*bool*, *optional*) – True gets active users only, and false gets deactivated users only. Defaults to None.
- **email** (*str*, *optional*) – Limits users to only those with this email. Defaults to None.
- **org_uid** (*str*, *optional*) – Limits users to only those in the organization with this org UID. Defaults to None.
- **role_id** (*int*, *optional*) – Limits users to only those with a given role ID. Defaults to None.
- **page_size** (*int*, *optional*) – The number of items on the page. Defaults to `py42.settings.items_per_page`.
- **q** (*str*, *optional*) – A generic query filter that searches across name, username, and email. Defaults to None.

Returns `py42.response.Py42Response`

get_roles(*user_id*)

Return the list of roles that are currently assigned to the given user.

Parameters **user_id** (*int*) – An ID for a user.

Returns `py42.response.Py42Response`

get_scim_data_by_uid(*user_uid*)

Returns SCIM data such as division, department, and title for a given user.

Parameters **user_uid** (*str*) – A Code42 user uid.

Returns `py42.response.Py42Response`

reactivate(*user_id*, *unblock_user=None*)

Reactivates the user with the given ID.

Parameters

- **user_id** (*int*) – An ID for a user.
- **unblock_user** (*bool*, *optional*) – Whether or not to unblock the user. Defaults to None.

Returns `py42.response.Py42Response`

remove_role(*user_id*, *role_name*)

Removes a role from a user.

Parameters

- **user_id** (*int*) – An ID for a user.
- **role_name** (*str*) – The name of the role to unassign from the user.

Returns `py42.response.Py42Response`

unblock(*user_id*)

Removes a block, if one exists, on the user with the given user ID. Unblocked users are allowed to log in and restore.

Parameters `user_id (int)` – An ID for a user.

Returns `py42.response.Py42Response`

update_user(`user_uid, username=None, email=None, password=None, first_name=None, last_name=None, notes=None, archive_size_quota_bytes=None`)

Updates an existing user.

Parameters

- **user_uid** (`str or int`) – A Code42 user UID.
- **username** (`str, optional`) – The username to which the user’s username will be changed. Defaults to None.
- **email** (`str, optional`) – The email to which the user’s email will be changed. Defaults to None.
- **password** (`str, optional`) – The password to which the user’s password will be changed. Defaults to None.
- **first_name** (`str, optional`) – The first name to which the user’s first name will be changed. Defaults to None.
- **last_name** (`str, optional`) – The last name to which the user’s last name will be changed. Defaults to None.
- **notes** (`str, optional`) – Descriptive information about the user. Defaults to None.
- **archive_size_quota_bytes** (`int, optional`) – The quota in bytes that limits the user’s archive size. Defaults to None.

Returns `py42.response.Py42Response`

class `py42.usercontext.UserContext(administration_client)`

Bases: object

An object representing the currently logged in user.

get_current_tenant_id()

Gets the currently signed in user’s tenant ID.

2.23 Util

`py42.util.convert_datetime_to_timestamp_str(date)`

Converts the given datetime to a formatted date str. The format matches strftime directives `%Y-%m-%dT%H:%M:%S.%f`.

Parameters `date (datetime)` – The datetime object to convert.

Returns A str representing the given date. Example output looks like ‘2020-03-25T15:29:04.465Z’.

Return type (str)

`py42.util.convert_timestamp_to_str(timestamp)`

Converts the given POSIX timestamp to a date str. The format matches strftime directives `%Y-%m-%dT%H:%M:%S.%f`.

Parameters `timestamp (float or int)` – A POSIX timestamp.

Returns A str representing the given timestamp. Example output looks like ‘2020-03-25T15:29:04.465Z’.

Return type (str)

`py42.util.format_json(json_string)`

Converts a minified JSON str to a prettified JSON str.

Parameters `json_string` (str) – A str representing minified JSON.

Returns A str representing prettified JSON.

Return type (str)

`py42.util.get_attribute_values_from_class(cls)`

Returns attribute values for the given class.

Parameters `cls` (class) – The class to obtain attributes from.

Returns A list containing the attribute values of the given class.

Return type (list)

`py42.util.print_response(response, label=None)`

Prints a [py42.response.Py42Response](#) as prettified JSON. If unable to load, it prints the given response.

Parameters

- **response** ([py42.response.Py42Response](#)) – The response to print.
- **label** (str, optional) – A label at the beginning of the printed text. Defaults to None.

2.24 Watchlists

class `py42.clients.watchlists.WatchlistType`

Bases: `py42.choices.Choices`

Constants available for setting the type of watchlist.

- `CONTRACT_EMPLOYEE`
- `DEPARTING_EMPLOYEE`
- `ELEVATED_ACCESS_PRIVILEGES`
- `FLIGHT_RISK`
- `HIGH_IMPACT_EMPLOYEE`
- `NEW_EMPLOYEE`
- `PERFORMANCE_CONCERNS`
- `POOR_SECURITY_PRACTICES`
- `SUSPICIOUS_SYSTEM_ACTIVITY`

class `py42.clients.watchlists.WatchlistsClient(watchlists_service)`

Bases: `object`

A client to expose the watchlists API.

[Rest Documentation](#)

add_included_users_by_watchlist_id(`user_ids`, `watchlist_id`)

Explicitly include users on a watchlist.

Parameters

- **user_ids** (*list(str)*) – A list of user IDs to add to the watchlist
- **watchlist_id** (*str*) – A unique watchlist ID.

Returns *py42.response.Py42Response*

add_included_users_by_watchlist_type(*user_ids*, *watchlist_type*)

Explicitly include users on a watchlist.

Parameters

- **user_ids** (*list(str)*) – A list of user IDs to add to the watchlist
- **watchlist_type** (*str*) – Type of watchlist. Constants available at *py42.constants.WatchlistType*.

Returns *py42.response.Py42Response*

create(*watchlist_type*)

Create a new watchlist.

Parameters **watchlist_type** (*str*) – Type of watchlist. Constants available at *py42.constants.WatchlistType*.

Returns *py42.response.Py42Response*

delete(*watchlist_id*)

Delete a watchlist.

Parameters **watchlist_id** (*str*) – A unique watchlist ID.

Returns *py42.response.Py42Response*

get(*watchlist_id*)

Get a watchlist.

Parameters **watchlist_id** (*str*) – A unique watchlist ID.

Returns *py42.response.Py42Response*

get_all()

Get all watchlists.

Returns An object that iterates over *py42.response.Py42Response* objects that each contain a page of watchlists.

Return type generator

get_all_included_users(*watchlist_id*)

Get all users explicitly included on a watchlist.

Parameters **watchlist_id** (*str*) – A unique watchlist ID.

Returns An object that iterates over *py42.response.Py42Response* objects that each contain a page of included users that match the given query.

Return type generator

get_all_watchlist_members(*watchlist_id*)

Get all members of a watchlist.

Parameters **watchlist_id** (*str*) – A unique watchlist ID.

Returns An object that iterates over *py42.response.Py42Response* objects that each contain a page of watchlist members.

Return type generator

get_watchlist_member(*watchlist_id*, *user_id*)

Get a member of a watchlist.

Parameters

- **watchlist_id** (*str*) – A unique watchlist ID.
- **user_id** (*str*) – A unique user ID.

Returns [*py42.response.Py42Response*](#)

remove_included_users_by_watchlist_id(*user_ids*, *watchlist_id*)

Remove users that are explicitly included on a watchlist.

Parameters

- **user_ids** (*list(str)*) – A list of user IDs to remove from the watchlist
- **watchlist_id** (*str*) – A unique watchlist ID.

Returns [*py42.response.Py42Response*](#)

remove_included_users_by_watchlist_type(*user_ids*, *watchlist_type*)

Remove users that are explicitly included on a watchlist.

Parameters

- **user_ids** (*list(str)*) – A list of user IDs to remove from the watchlist
- **watchlist_type** (*str*) – Type of watchlist. Constants available at [*py42.constants.WatchlistType*](#).

Returns [*py42.response.Py42Response*](#)

The main SDK object by which all other methods are accessed is created by calling `py42.sdk.from_local_account` or `py42.sdk.from_jwt_provider`. For example:

```
import py42.sdk

sdk = py42.sdk.from_local_account("console.us.code42.com", "john.doe@example.com", "my_pw")
# access properties on 'sdk' to explore all the available methods
```

Important: *py42* only supports token-based authentication.

Explore the complete public documentation for *py42* below.

- [*Alerts*](#)
- [*Alert Rules*](#)
- [*Archive*](#)
- [*Audit Logs*](#)
- [*Backup Sets*](#)
- [*Cases*](#)
- [*Constants*](#)
- [*Detection Lists*](#)
- [*Devices*](#)

- *Device Settings*
- *Exceptions*
- *(DEPRECATED) File Event Queries - V1*
- *File Event Queries - V2*
- *Legal Hold*
- *Orgs*
- *Org Settings*
- *Response*
- *Security Data*
- *Shared Query Filters*
- *Trusted Activities*
- *Users*
- *User Risk Profiles*
- *Util*
- *Watchlists*

`py42.sdk.from_jwt_provider(host_address, jwt_provider)`

Creates a *SDKClient* object for accessing the Code42 REST APIs using a custom auth mechanism. User can use any authentication mechanism like that returns a JSON Web token on authentication which would then be used for all subsequent requests.

Parameters

- **host_address** (*str*) – The domain name of the Code42 instance being authenticated to, e.g. console.us.code42.com
- **jwt_provider** (*function*) – A function that accepts no parameters and on execution returns a JSON web token string.

Returns *py42.sdk.SDKClient*

`py42.sdk.from_local_account(host_address, username, password, totp=None)`

Creates a *SDKClient* object for accessing the Code42 REST APIs using the supplied credentials. This method supports only accounts created within the Code42 console or using the APIs (including py42). Username/passwords that are based on Active Directory, Okta, or other Identity providers cannot be used with this method.

Parameters

- **host_address** (*str*) – The domain name of the Code42 instance being authenticated to, e.g. console.us.code42.com
- **username** (*str*) – The username of the authenticating account.
- **password** (*str*) – The password of the authenticating account.
- **totp** (*callable or str, optional*) – The time-based one-time password of the authenticating account. Include only if the account uses Code42's two-factor authentication. Defaults to None.

Returns *py42.sdk.SDKClient*

class `py42.sdk.SDKClient`(*main_connection, auth*)

Bases: `object`

property alerts

A collection of methods related to retrieving and updating alerts rules.

Returns `py42.clients.alertrules.AlertRulesClient`

property archive

A collection of methods for accessing Code42 storage archives. Useful for doing web-restores or finding a file on an archive.

Returns `py42.clients.archive.ArchiveClient`

property auditlogs

A collection of methods for retrieving audit logs.

Returns `py42.clients.auditlogs.AuditLogsClient`

property cases

A collection of methods and properties for managing cases and file events associated with the case.

Returns `py42.clients.cases.CaseClient`

property detectionlists

A collection of properties each containing methods for managing specific detection lists, such as departing employees.

Returns `py42.clients.detectionlists.DetectionListsClient`

property devices

A collection of methods for retrieving or updating data about devices in the Code42 environment.

Returns `py42.services.devices.DeviceService`

classmethod `from_jwt_provider`(*host_address, jwt_provider*)

Creates a `SDKClient` object for accessing the Code42 REST APIs using a custom auth mechanism.

User can use any authentication mechanism like that returns a JSON Web token on authentication which would then be used for all subsequent requests.

Parameters

- **host_address** (*str*) – The domain name of the Code42 instance being authenticated to, e.g. `console.us.code42.com`
- **jwt_provider** (*function*) – A function that accepts no parameters and on execution returns a
- **string**. (*JSON web token*) –

Returns `py42.sdk.SDKClient`

classmethod `from_local_account`(*host_address, username, password, totp=None*)

Creates a `SDKClient` object for accessing the Code42 REST APIs using the supplied credentials. This method supports only accounts created within the Code42 console or using the APIs (including py42). Username/passwords that are based on Active Directory, Okta, or other Identity providers should use the `from_jwt_provider` method.

Parameters

- **host_address** (*str*) – The domain name of the Code42 instance being authenticated to, e.g. `console.us.code42.com`

- **username** (*str*) – The username of the authenticating account.
- **password** (*str*) – The password of the authenticating account.
- **totp** (*callable or str, optional*) – The time-based one-time password of the authenticating account. Include only if the account uses Code42's two-factor authentication. Defaults to None.

Returns *py42.sdk.SDKClient*

property legalhold

A collection of methods for retrieving and updating legal-hold matters, policies, and custodians.

Returns *py42.services.legalhold.LegalHoldService*

property loginconfig

A collection of methods related to getting information about the login configuration of user accounts.

Returns *py42.clients.loginconfig.LoginConfigurationClient*.

property orgs

A collection of methods for retrieving or updating data about organizations in the Code42 environment.

Returns *py42.services.orgs.OrgService*

property securitydata

A collection of methods and properties for getting security data such as:

- File events
- Security plan information

Returns *py42.clients.securitydata.SecurityDataClient*

property serveradmin

A collection of methods for getting server information for on-premise environments and tenant information for cloud environments.

Returns *py42.services.administration.AdministrationService*

property trustedactivities

A collection of methods and properties for managing trusted domains.

Returns *py42.clients.trustedactivities.TrustedActivitiesClient*

property usercontext

A collection of methods related to getting information about the currently logged in user, such as the tenant ID.

Returns *py42.usercontext.UserContext*

property userriskprofile

A collection of methods and properties for managing user risk profiles.

Returns *py42.clients.userriskprofile.UserRiskProfileClient*

property users

A collection of methods for retrieving or updating data about users in the Code42 environment.

Returns *py42.services.users.UserService*

property watchlists

A collection of methods and properties for managing watchlists.

Returns `py42.clients.watchlists.WatchlistsClient`

py42 is a Python wrapper around the Code42 REST APIs that also provides several utility methods. Use py42 to develop your own tools for working with Code42 data while avoiding the overhead of session / authentication management.

FEATURES

- Managing users, organizations, and devices.
- Searching file events, alerts and auditlogs.
- Adding/Removing employees from detection lists.
- Managing cases.

CONTENT

- *User Guides*
- *Method Documentation*

PYTHON MODULE INDEX

p

- py42.exceptions, 54
- py42.sdk, 203
- py42.sdk.queries.alerts.filters.alert_filter,
25
- py42.sdk.queries.fileevents.v2.filters.destination,
107
- py42.sdk.queries.fileevents.v2.filters.event,
124
- py42.sdk.queries.fileevents.v2.filters.file,
129
- py42.sdk.queries.fileevents.v2.filters.process,
142
- py42.sdk.queries.fileevents.v2.filters.report,
144
- py42.sdk.queries.fileevents.v2.filters.risk,
148
- py42.sdk.queries.fileevents.v2.filters.source,
159
- py42.sdk.queries.fileevents.v2.filters.timestamp,
174
- py42.sdk.queries.fileevents.v2.filters.user,
176
- py42.sdk.queries.query_filter, 188
- py42.util, 199

A

Action (class in `py42.sdk.queries.fileevents.v2.filters.event`), 124
Actor (class in `py42.sdk.queries.alerts.filters.alert_filter`), 25
Actor (class in `py42.sdk.queries.fileevents.filters.cloud_filter`), 81
add() (`py42.services.casesfileevents.CasesFileEventsService` method), 41
add() (`py42.services.detectionlists.departing_employee.DepartingEmployeeService` method), 46
add() (`py42.services.detectionlists.high_risk_employee.HighRiskEmployeeService` method), 48
add_cloud_aliases() (`py42.clients.userriskprofile.UserRiskProfileClient` method), 193
add_destination() (`py42.clients.settings.device_settings.BackupSet` method), 38
add_included_users_by_watchlist_id() (`py42.clients.watchlists.WatchlistsClient` method), 200
add_included_users_by_watchlist_type() (`py42.clients.watchlists.WatchlistsClient` method), 201
add_role() (`py42.services.users.UserService` method), 196
add_to_matter() (`py42.services.legalhold.LegalHoldService` method), 178
add_user() (`py42.clients.alertrules.AlertRulesClient` method), 21
add_user_cloud_alias() (`py42.clients.detectionlists.DetectionListsClient` method), 44
add_user_risk_tags() (`py42.clients.detectionlists.DetectionListsClient` method), 44
AlertQuery (class in `py42.sdk.queries.alerts.alert_query`), 32
AlertRulesClient (class in `py42.clients.alertrules`), 21
alerts (`py42.sdk.SDKClient` property), 204
AlertsClient (class in `py42.clients.alerts`), 23
AlertState (class in `py42.sdk.queries.alerts.filters.alert_filter`), 26
archive (`py42.sdk.SDKClient` property), 204
archive_hold_days (`py42.clients.settings.org_settings.OrgSettings` attribute), 184
ArchiveClient (class in `py42.clients.archive`), 33
auditlogs (`py42.sdk.SDKClient` property), 204
AuditLogsClient (class in `py42.clients.auditlogs`), 36
available_destinations (`py42.clients.settings.device_settings.DeviceSettings` attribute), 53
available_destinations (`py42.clients.settings.device_settings.DeviceSettingsDefaults` property), 186

B

backup_alert_recipient_emails (`py42.clients.settings.org_settings.OrgSettings` attribute), 184
backup_critical_email_days (`py42.clients.settings.org_settings.OrgSettings` attribute), 184
backup_sets (`py42.clients.settings.device_settings.DeviceSettings` attribute), 53
backup_status_email_enabled (`py42.clients.settings.device_settings.DeviceSettings` attribute), 53
backup_status_email_enabled (`py42.clients.settings.device_settings.DeviceSettingsDefaults` attribute), 186
backup_status_email_frequency_days (`py42.clients.settings.device_settings.DeviceSettings` attribute), 53
backup_status_email_frequency_days (`py42.clients.settings.device_settings.DeviceSettingsDefaults` attribute), 186
backup_warning_email_days (`py42.clients.settings.org_settings.OrgSettings` attribute), 184
BackupSet (class in `py42.clients.settings.device_settings`), 38
block() (`py42.services.devices.DeviceService` method), 49

block() (py42.services.orgs.OrgService method), 182
 block() (py42.services.users.UserService method), 196

C

case_name (py42.exceptions.Py42CaseNameExistsError property), 55
 cases (py42.sdk.SDKClient property), 204
 CasesClient (class in py42.clients.cases), 39
 CasesFileEventsService (class in py42.services.casesfileevents), 41
 CaseStatus (class in py42.clients.cases), 39
 CaseStatus (class in py42.constants), 42
 Category (class in py42.sdk.queries.fileevents.v2.filters.destination), 107
 Category (class in py42.sdk.queries.fileevents.v2.filters.file), 129
 Category (class in py42.sdk.queries.fileevents.v2.filters.sources), 159
 CategoryByBytes (class in py42.sdk.queries.fileevents.v2.filters.file), 130
 CategoryByExtension (class in py42.sdk.queries.fileevents.v2.filters.file), 130
 change_org_assignment() (py42.services.users.UserService method), 196
 checksum_name (py42.exceptions.Py42ChecksumNotFoundError property), 55
 checksum_value (py42.exceptions.Py42ChecksumNotFoundError property), 55
 choices() (py42.sdk.queries.alerts.filters.alert_filter.AlertState class method), 26
 choices() (py42.sdk.queries.alerts.filters.alert_filter.RuleSource class method), 30
 choices() (py42.sdk.queries.alerts.filters.alert_filter.RuleType class method), 31
 choices() (py42.sdk.queries.alerts.filters.alert_filter.Severity class method), 32
 choices() (py42.sdk.queries.fileevents.filters.cloud_filter.SharingType class method), 83
 choices() (py42.sdk.queries.fileevents.filters.event_filter.EventTimestamp class method), 67
 choices() (py42.sdk.queries.fileevents.filters.event_filter.EventType class method), 69
 choices() (py42.sdk.queries.fileevents.filters.event_filter.Source class method), 71
 choices() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType class method), 84
 choices() (py42.sdk.queries.fileevents.filters.exposure_filter.SyncDestination class method), 91
 choices() (py42.sdk.queries.fileevents.filters.file_filter.FileCategory class method), 72
 choices() (py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.CloudData class method), 101
 choices() (py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.CodeRepository class method), 101
 choices() (py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.EmailService class method), 101
 choices() (py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.ExternalData class method), 101
 choices() (py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.FileCategory class method), 102
 choices() (py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.Messaging class method), 102
 choices() (py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.Other class method), 102
 choices() (py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.SocialMedia class method), 102
 choices() (py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.User class method), 102
 choices() (py42.sdk.queries.fileevents.filters.risk_filter.RiskSeverity class method), 103
 choices() (py42.sdk.queries.fileevents.v2.filters.destination.Category class method), 108
 choices() (py42.sdk.queries.fileevents.v2.filters.event.Action class method), 124
 choices() (py42.sdk.queries.fileevents.v2.filters.event.Observer class method), 127
 choices() (py42.sdk.queries.fileevents.v2.filters.file.Category class method), 129
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.CloudData class method), 153
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.CloudStorage class method), 153
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.CodeRepository class method), 153
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.EmailService class method), 153
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.ExternalData class method), 153
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.FileCategory class method), 153
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.FileConversion class method), 153
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.Messaging class method), 153
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.Other class method), 154
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.PdfManagement class method), 154
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.Productivity class method), 154
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.SocialMedia class method), 154

choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.UserPy42.sdk.queries.query_filter), 191
 class method), 154 create_is_in_filter_group() (in module
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.WebPy42.sdk.queries.query_filter), 191
 class method), 154 create_less_than_filter_group()
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Severity (py42.sdk.queries.fileevents.util method),
 class method), 157 67
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.TrustPcreate_matter() (py42.services.legalhold.LegalHoldService
 class method), 158 method), 178
 choices() (py42.sdk.queries.fileevents.v2.filters.source.Ccreate_not_eq_filter_group() (in module
 class method), 160 py42.sdk.queries.query_filter), 191
 choices() (py42.sdk.queries.fileevents.v2.filters.timestampCcreate_not_exists_filter_group()
 class method), 175 (py42.sdk.queries.fileevents.util method),
 Classification (class in 66
 py42.sdk.queries.fileevents.v2.filters.file), create_not_in_filter_group() (in module
 131 py42.sdk.queries.query_filter), 191
 CloudDriveId (class in create_on_or_after_filter_group() (in module
 py42.sdk.queries.fileevents.v2.filters.file), py42.sdk.queries.query_filter), 191
 132 create_on_or_before_filter_group() (in module
 cloudshare (py42.clients.alertrules.AlertRulesClient py42.sdk.queries.query_filter), 191
 property), 21 create_org() (py42.services.orgs.OrgService method),
 CloudShareService (class in py42.services.alertrules), 182
 23 create_policy() (py42.services.legalhold.LegalHoldService
 computer_id (py42.clients.settings.device_settings.DeviceSettings method), 178
 property), 53 create_query_filter() (in module
 computer_id (py42.clients.settings.device_settings.IncydrDeviceSettingspy42.sdk.queries.query_filter), 192
 property), 52 create_user() (py42.clients.detectionlists.DetectionListsClient
 contains() (py42.sdk.queries.alerts.filters.alert_filter.Actor method), 44
 class method), 25 create_user() (py42.services.users.UserService
 contains() (py42.sdk.queries.alerts.filters.alert_filter.Description method), 196
 class method), 28 create_within_the_last_filter_group() (in mod-
 contains() (py42.sdk.queries.alerts.filters.alert_filter.RuleName ule py42.sdk.queries.query_filter), 192
 class method), 29 Created (class in py42.sdk.queries.fileevents.v2.filters.file),
 convert_datetime_to_timestamp_str() (in module 133
 py42.util), 199 critical_alert_days
 convert_timestamp_to_str() (in module py42.util), (py42.clients.settings.device_settings.DeviceSettings
 199 attribute), 53
 Count (class in py42.sdk.queries.fileevents.v2.filters.report),critical_alert_days
 144 (py42.clients.settings.device_settings.DeviceSettingsDefaults
 create() (py42.clients.cases.CasesClient method), 39 attribute), 186
 create() (py42.clients.trustedactivities.TrustedActivitiesClcreate_critical_email_enabled
 method), 192 (py42.clients.settings.device_settings.DeviceSettings
 create() (py42.clients.watchlists.WatchlistsClient attribute), 53
 method), 201 critical_email_enabled
 create_eq_filter_group() (in module (py42.clients.settings.device_settings.DeviceSettingsDefaults
 py42.sdk.queries.query_filter), 190 attribute), 186
 create_exists_filter_group()
 (py42.sdk.queries.fileevents.util method),
 66 D
 create_filter_group() (in module DateObserved (class in
 py42.sdk.queries.query_filter), 190 py42.sdk.queries.alerts.filters.alert_filter),
 27
 create_greater_than_filter_group()
 (py42.sdk.queries.fileevents.util method),
 67 deactivate() (py42.services.devices.DeviceService
 create_in_range_filter_group() (in module method), 49
 182 deactivate() (py42.services.orgs.OrgService method),

deactivate() (py42.services.users.UserService method), 196
 deactivate_matter() (py42.services.legalhold.LegalHoldService method), 178
 deauthorize() (py42.services.devices.DeviceService method), 49
 delete() (py42.clients.trustedactivities.TrustedActivitiesClient method), 193
 delete() (py42.clients.watchlists.WatchlistsClient method), 201
 delete() (py42.services.casesfileevents.CasesFileEventsService method), 41
 delete_cloud_aliases() (py42.clients.userriskprofile.UserRiskProfileClient method), 194
 DepartingEmployeeFilters (class in py42.constants), 43
 DepartingEmployeeFilters (class in py42.services.detectionlists.departing_employee), 45
 DepartingEmployeeService (class in py42.services.detectionlists.departing_employee), 45
 Description (class in py42.sdk.queries.alerts.filters.alert_filter), 28
 Description (class in py42.sdk.queries.fileevents.v2.filters.report), 145
 destinations (py42.clients.settings.device_settings.BackupSet property), 38
 detectionlists (py42.sdk.SDKClient property), 204
 DetectionListsClient (class in py42.clients.detectionlists), 44
 device_guid (py42.exceptions.Py42ArchiveFileNotFoundEmail property), 54
 device_guid (py42.exceptions.Py42DeviceNotConnectedError property), 56
 device_id (py42.clients.settings.device_settings.DeviceSettings property), 53
 device_id (py42.clients.settings.device_settings.IncydrDeviceSettings property), 52
 devices (py42.sdk.SDKClient property), 204
 DeviceService (class in py42.services.devices), 49
 DeviceSettings (class in py42.clients.settings.device_settings), 52
 DeviceSettingsDefaults (class in py42.clients.settings.device_settings), 186
 DeviceSignedInUserName (class in py42.sdk.queries.fileevents.filters.device_filter), 80
 DeviceUid (class in py42.sdk.queries.fileevents.v2.filters.user), 176
 DeviceUsername (class in py42.sdk.queries.fileevents.filters.device_filter), 77
 Directory (class in py42.sdk.queries.fileevents.v2.filters.file), 133
 DirectoryID (class in py42.sdk.queries.fileevents.filters.cloud_filter), 81
 DirectoryId (class in py42.sdk.queries.fileevents.v2.filters.file), 134
 Domain (class in py42.sdk.queries.fileevents.v2.filters.source), 161
E
 Email (class in py42.sdk.queries.fileevents.v2.filters.user), 176
 email (py42.exceptions.Py42InvalidEmailError property), 57
 EmailFrom (class in py42.sdk.queries.fileevents.filters.email_filter), 96
 EmailFrom (class in py42.sdk.queries.fileevents.v2.filters.source), 161
 EmailPolicyName (class in py42.sdk.queries.fileevents.filters.email_filter), 94
 EmailRecipients (class in py42.sdk.queries.fileevents.filters.email_filter), 95
 EmailRecipients (class in py42.sdk.queries.fileevents.v2.filters.destination), 109
 EmailSender (class in py42.sdk.queries.fileevents.filters.email_filter), 96
 EmailSender (class in py42.sdk.queries.fileevents.v2.filters.source), 162
 EmailSubject (class in py42.sdk.queries.fileevents.filters.email_filter), 95
 EmailSubject (class in py42.sdk.queries.fileevents.v2.filters.destination), 109
 encoding (py42.response.Py42Response property), 186
 endpoint_monitoring_background_priority_enabled (py42.clients.settings.org_settings.OrgSettings attribute), 184
 endpoint_monitoring_browser_and_applications_enabled (py42.clients.settings.org_settings.OrgSettings property), 184
 endpoint_monitoring_cloud_sync_enabled (py42.clients.settings.org_settings.OrgSettings property), 184

endpoint_monitoring_custom_applications_mac (py42.clients.settings.org_settings.OrgSettings attribute), 184	eq() (py42.sdk.queries.fileevents.filters.device_filter.DeviceSignedInUserNa class method), 80
endpoint_monitoring_custom_applications_win (py42.clients.settings.org_settings.OrgSettings attribute), 184	eq() (py42.sdk.queries.fileevents.filters.device_filter.DeviceUsername class method), 77
endpoint_monitoring_enabled (py42.clients.settings.org_settings.OrgSettings property), 185	eq() (py42.sdk.queries.fileevents.filters.device_filter.OSTHostname class method), 78
endpoint_monitoring_file_exfiltration_detection_exclusions (py42.clients.settings.org_settings.OrgSettings attribute), 185	eq() (py42.sdk.queries.fileevents.filters.device_filter.PrivateIPAddress class method), 78
endpoint_monitoring_file_metadata_collection_enabled (py42.clients.settings.org_settings.OrgSettings property), 185	eq() (py42.sdk.queries.fileevents.filters.device_filter.PublicIPAddress class method), 79
endpoint_monitoring_file_metadata_collection_exclusions (py42.clients.settings.org_settings.OrgSettings attribute), 185	eq() (py42.sdk.queries.fileevents.filters.email_filter.EmailFrom class method), 97
endpoint_monitoring_file_metadata_ingest_scan_enabled (py42.clients.settings.org_settings.OrgSettings attribute), 185	eq() (py42.sdk.queries.fileevents.filters.email_filter.EmailPolicyName class method), 94
endpoint_monitoring_file_metadata_scan_enabled (py42.clients.settings.org_settings.OrgSettings attribute), 185	eq() (py42.sdk.queries.fileevents.filters.email_filter.EmailRecipients class method), 95
endpoint_monitoring_printer_detection_enabled (py42.clients.settings.org_settings.OrgSettings property), 185	eq() (py42.sdk.queries.fileevents.filters.email_filter.EmailSender class method), 96
endpoint_monitoring_removable_media_enabled (py42.clients.settings.org_settings.OrgSettings property), 185	eq() (py42.sdk.queries.fileevents.filters.email_filter.EmailSubject class method), 95
eq() (py42.sdk.queries.alerts.filters.alert_filter.Actor class method), 26	eq() (py42.sdk.queries.fileevents.filters.event_filter.EventType class method), 69
eq() (py42.sdk.queries.alerts.filters.alert_filter.AlertState class method), 27	eq() (py42.sdk.queries.fileevents.filters.event_filter.Source class method), 71
eq() (py42.sdk.queries.alerts.filters.alert_filter.Description class method), 28	eq() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType class method), 84
eq() (py42.sdk.queries.alerts.filters.alert_filter.RuleId class method), 29	eq() (py42.sdk.queries.fileevents.filters.exposure_filter.ProcessName class method), 85
eq() (py42.sdk.queries.alerts.filters.alert_filter.RuleName class method), 29	eq() (py42.sdk.queries.fileevents.filters.exposure_filter.ProcessOwner class method), 86
eq() (py42.sdk.queries.alerts.filters.alert_filter.RuleSource class method), 30	eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaMe class method), 88
eq() (py42.sdk.queries.alerts.filters.alert_filter.RuleType class method), 31	eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaNa class method), 87
eq() (py42.sdk.queries.alerts.filters.alert_filter.Severity class method), 32	eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaPa class method), 89
eq() (py42.sdk.queries.fileevents.filters.cloud_filter.Actor class method), 81	eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaSer class method), 90
eq() (py42.sdk.queries.fileevents.filters.cloud_filter.Directory class method), 81	eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaVer class method), 87
eq() (py42.sdk.queries.fileevents.filters.cloud_filter.SharedVolum class method), 82	eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaVo class method), 89
eq() (py42.sdk.queries.fileevents.filters.cloud_filter.SharingType class method), 83	eq() (py42.sdk.queries.fileevents.filters.exposure_filter.SyncDestination class method), 91
	eq() (py42.sdk.queries.fileevents.filters.exposure_filter.SyncDestinationUse class method), 92
	eq() (py42.sdk.queries.fileevents.filters.exposure_filter.TabURL class method), 93
	eq() (py42.sdk.queries.fileevents.filters.exposure_filter.WindowTitle class method), 93
	eq() (py42.sdk.queries.fileevents.filters.file_filter.FileCategory class method), 72
	eq() (py42.sdk.queries.fileevents.filters.file_filter.FileName class method), 73

eq() (py42.sdk.queries.fileevents.filters.file_filter.FileOwner class method), 74
 eq() (py42.sdk.queries.fileevents.filters.file_filter.FilePath class method), 74
 eq() (py42.sdk.queries.fileevents.filters.file_filter.MD5 class method), 75
 eq() (py42.sdk.queries.fileevents.filters.file_filter.SHA256 class method), 76
 eq() (py42.sdk.queries.fileevents.filters.print_filter.Printer class method), 98
 eq() (py42.sdk.queries.fileevents.filters.print_filter.PrintJobName class method), 98
 eq() (py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator class method), 102
 eq() (py42.sdk.queries.fileevents.filters.risk_filter.RiskScore class method), 104
 eq() (py42.sdk.queries.fileevents.filters.risk_filter.RiskSeverity class method), 103
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.Category class method), 108
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.EmailByCip class method), 109
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.EmailSubject class method), 109
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.IpAddress class method), 110
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.Name class method), 111
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.OperationSystem class method), 111
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.Printed class method), 113
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.Printer class method), 113
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.PrintedName class method), 112
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.PrivateAddress class method), 114
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.RemoveByFile class method), 115
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.RemoveByFile class method), 116
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.RemoveByFile class method), 116
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.RemoveByFile class method), 117
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.RemoveByFile class method), 118
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.RemoveByFile class method), 119
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.RemoveByFile class method), 119
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.RemoveByFile class method), 120
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.TabTitleErrors class method), 121
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.TabTitles class method), 121
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.TabUrlErrors class method), 122
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.TabUrls class method), 123
 eq() (py42.sdk.queries.fileevents.v2.filters.destination.UserEmail class method), 124
 eq() (py42.sdk.queries.fileevents.v2.filters.event.Action class method), 124
 eq() (py42.sdk.queries.fileevents.v2.filters.event.Id class method), 125
 eq() (py42.sdk.queries.fileevents.v2.filters.event.Observer class method), 127
 eq() (py42.sdk.queries.fileevents.v2.filters.event.ShareType class method), 128
 eq() (py42.sdk.queries.fileevents.v2.filters.file.Category class method), 129
 eq() (py42.sdk.queries.fileevents.v2.filters.file.CategoryByBytes class method), 130
 eq() (py42.sdk.queries.fileevents.v2.filters.file.CategoryByExtension class method), 130
 eq() (py42.sdk.queries.fileevents.v2.filters.file.Classification class method), 131
 eq() (py42.sdk.queries.fileevents.v2.filters.file.CloudDriveId class method), 132
 eq() (py42.sdk.queries.fileevents.v2.filters.file.Directory class method), 133
 eq() (py42.sdk.queries.fileevents.v2.filters.file.DirectoryId class method), 134
 eq() (py42.sdk.queries.fileevents.v2.filters.file.Id class method), 135
 eq() (py42.sdk.queries.fileevents.v2.filters.file.MD5 class method), 136
 eq() (py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByBytes class method), 136
 eq() (py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByExtension class method), 137
 eq() (py42.sdk.queries.fileevents.v2.filters.file.Name class method), 138
 eq() (py42.sdk.queries.fileevents.v2.filters.file.Owner class method), 139
 eq() (py42.sdk.queries.fileevents.v2.filters.file.SHA256 class method), 140
 eq() (py42.sdk.queries.fileevents.v2.filters.file.Url class method), 141
 eq() (py42.sdk.queries.fileevents.v2.filters.process.Executable class method), 142
 eq() (py42.sdk.queries.fileevents.v2.filters.process.Owner class method), 143
 eq() (py42.sdk.queries.fileevents.v2.filters.report.Count class method), 144

eq() (py42.sdk.queries.fileevents.v2.filters.report.Description class method), 145

eq() (py42.sdk.queries.fileevents.v2.filters.report.Headers class method), 145

eq() (py42.sdk.queries.fileevents.v2.filters.report.ID class method), 146

eq() (py42.sdk.queries.fileevents.v2.filters.report.Name class method), 147

eq() (py42.sdk.queries.fileevents.v2.filters.report.Type class method), 147

eq() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators class method), 154

eq() (py42.sdk.queries.fileevents.v2.filters.risk.IndicatorsWeight class method), 155

eq() (py42.sdk.queries.fileevents.v2.filters.risk.Score class method), 156

eq() (py42.sdk.queries.fileevents.v2.filters.risk.Severity class method), 157

eq() (py42.sdk.queries.fileevents.v2.filters.risk.TrustReason class method), 158

eq() (py42.sdk.queries.fileevents.v2.filters.source.Category class method), 160

eq() (py42.sdk.queries.fileevents.v2.filters.source.Domain class method), 161

eq() (py42.sdk.queries.fileevents.v2.filters.source.EmailFrom class method), 161

eq() (py42.sdk.queries.fileevents.v2.filters.source.EmailSender class method), 162

eq() (py42.sdk.queries.fileevents.v2.filters.source.IpAddress class method), 163

eq() (py42.sdk.queries.fileevents.v2.filters.source.Name class method), 163

eq() (py42.sdk.queries.fileevents.v2.filters.source.OperatingSystem class method), 164

eq() (py42.sdk.queries.fileevents.v2.filters.source.PrivateIpAddress class method), 165

eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBusType class method), 165

eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCapacity class method), 166

eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaMediaName class method), 167

eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaName class method), 168

eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaPartitionId class method), 168

eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaSerialNumber class method), 169

eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVendor class method), 170

eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVolumeId class method), 171

eq() (py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors class method), 171

eq() (py42.sdk.queries.fileevents.v2.filters.source.TabTitles class method), 172

eq() (py42.sdk.queries.fileevents.v2.filters.source.TabUrlErrors class method), 173

eq() (py42.sdk.queries.fileevents.v2.filters.source.TabUrls class method), 173

eq() (py42.sdk.queries.fileevents.v2.filters.user.DeviceUid class method), 176

eq() (py42.sdk.queries.fileevents.v2.filters.user.Email class method), 176

eq() (py42.sdk.queries.fileevents.v2.filters.user.Id class method), 177

eq() (py42.sdk.queries.query_filter.QueryFilterStringField class method), 189

EventTimestamp (class in py42.sdk.queries.fileevents.filters.event_filter), 67

EventType (class in py42.sdk.queries.fileevents.filters.event_filter), 68

excluded_files (py42.clients.settings.device_settings.BackupSet property), 38

Executable (class in py42.sdk.queries.fileevents.v2.filters.process), 142

execute() (py42.services.savedsearch.SavedSearchService method), 65

exfiltration (py42.clients.alertrules.AlertRulesClient property), 21

ExfiltrationService (class in py42.services.alertrules), 23

exists() (py42.sdk.queries.fileevents.filters.cloud_filter.Actor class method), 81

exists() (py42.sdk.queries.fileevents.filters.cloud_filter.DirectoryID class method), 81

exists() (py42.sdk.queries.fileevents.filters.cloud_filter.SharedWith class method), 82

exists() (py42.sdk.queries.fileevents.filters.cloud_filter.SharingTypeAdded class method), 83

exists() (py42.sdk.queries.fileevents.filters.device_filter.DeviceSignedInUser class method), 80

exists() (py42.sdk.queries.fileevents.filters.device_filter.DeviceUsername class method), 77

exists() (py42.sdk.queries.fileevents.filters.device_filter.OSTHostname class method), 78

exists() (py42.sdk.queries.fileevents.filters.device_filter.PrivateIPAddress class method), 79

exists() (py42.sdk.queries.fileevents.filters.device_filter.PublicIPAddress class method), 79

exists() (py42.sdk.queries.fileevents.filters.event_filter.EventType class method), 69

exists() (py42.sdk.queries.fileevents.filters.event_filter.Source class method), 71

exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType class method), 84

exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ProcessName class method), 84

class method), 85
 exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureFilter, class method), 86
 exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureFilter, class method), 88
 exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureFilter, class method), 87
 exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureFilter, class method), 90
 exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureFilter, class method), 90
 exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureFilter, class method), 87
 exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureFilter, class method), 89
 exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureFilter, class method), 91
 exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureFilter, class method), 92
 exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureFilter, class method), 93
 exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureFilter, class method), 94
 exists() (py42.sdk.queries.fileevents.filters.file_filter.FileCategoryFilter, class method), 72
 exists() (py42.sdk.queries.fileevents.filters.file_filter.FileNameFilter, class method), 73
 exists() (py42.sdk.queries.fileevents.filters.file_filter.FileOwnerFilter, class method), 74
 exists() (py42.sdk.queries.fileevents.filters.file_filter.FilePermissionsFilter, class method), 75
 exists() (py42.sdk.queries.fileevents.filters.file_filter.MD5Filter, class method), 76
 exists() (py42.sdk.queries.fileevents.filters.file_filter.SHA256Filter, class method), 76
 exists() (py42.sdk.queries.fileevents.filters.print_filter.PriorityFilter, class method), 98
 exists() (py42.sdk.queries.fileevents.filters.print_filter.PriorityFilter, class method), 99
 exists() (py42.sdk.queries.fileevents.filters.risk_filter.RiskScoreFilter, class method), 102
 exists() (py42.sdk.queries.fileevents.filters.risk_filter.RiskScoreFilter, class method), 103
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.Existing(), class method), 108
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.Existing(), class method), 110
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.Existing(), class method), 111
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.Existing(), class method), 113
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.Existing(), class method), 114
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.Existing(), class method), 112
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.PrivateIpAddress(), class method), 114
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia(), class method), 115
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia(), class method), 116
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia(), class method), 116
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia(), class method), 117
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia(), class method), 118
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia(), class method), 119
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia(), class method), 119
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia(), class method), 120
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.TabTitleErrors(), class method), 121
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.TabTitles(), class method), 122
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.TabUrlErrors(), class method), 122
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.TabUrls(), class method), 123
 exists() (py42.sdk.queries.fileevents.v2.filters.destination.UserEmail(), class method), 124
 exists() (py42.sdk.queries.fileevents.v2.filters.event.Action(), class method), 125
 exists() (py42.sdk.queries.fileevents.v2.filters.event.Id(), class method), 125
 exists() (py42.sdk.queries.fileevents.v2.filters.event.Observer(), class method), 127
 exists() (py42.sdk.queries.fileevents.v2.filters.event.ShareType(), class method), 128
 exists() (py42.sdk.queries.fileevents.v2.filters.file.Category(), class method), 129
 exists() (py42.sdk.queries.fileevents.v2.filters.file.CategoryByBytes(), class method), 130
 exists() (py42.sdk.queries.fileevents.v2.filters.file.CategoryByExtension(), class method), 131
 exists() (py42.sdk.queries.fileevents.v2.filters.file.Classification(), class method), 131
 exists() (py42.sdk.queries.fileevents.v2.filters.file.CloudDriveId(), class method), 132
 exists() (py42.sdk.queries.fileevents.v2.filters.file.Directory(), class method), 134
 exists() (py42.sdk.queries.fileevents.v2.filters.file.DirectoryId(), class method), 134
 exists() (py42.sdk.queries.fileevents.v2.filters.file.Id(), class method), 135
 exists() (py42.sdk.queries.fileevents.v2.filters.file.MD5(), class method), 135

class method), 136
 exists() (py42.sdk.queries.fileevents.v2.filters.file.MimeTypeExists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaSe
 class method), 136
 exists() (py42.sdk.queries.fileevents.v2.filters.file.MimeTypeExists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaSe
 class method), 137
 exists() (py42.sdk.queries.fileevents.v2.filters.file.NameExists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVo
 class method), 139
 exists() (py42.sdk.queries.fileevents.v2.filters.file.OwnerExists() (py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors
 class method), 139
 exists() (py42.sdk.queries.fileevents.v2.filters.file.SHA256Exists() (py42.sdk.queries.fileevents.v2.filters.source.TabTitles
 class method), 140
 exists() (py42.sdk.queries.fileevents.v2.filters.file.UrlExists() (py42.sdk.queries.fileevents.v2.filters.source.TabUrlErrors
 class method), 142
 exists() (py42.sdk.queries.fileevents.v2.filters.process.ExecutableExists() (py42.sdk.queries.fileevents.v2.filters.source.TabUrls
 class method), 142
 exists() (py42.sdk.queries.fileevents.v2.filters.process.OwnerExists() (py42.sdk.queries.fileevents.v2.filters.user.DeviceUid
 class method), 143
 exists() (py42.sdk.queries.fileevents.v2.filters.report.CountExists() (py42.sdk.queries.fileevents.v2.filters.user.Email
 class method), 144
 exists() (py42.sdk.queries.fileevents.v2.filters.report.DescriptionExists() (py42.sdk.queries.fileevents.v2.filters.user.Id
 class method), 145
 exists() (py42.sdk.queries.fileevents.v2.filters.report.HeaderExists() (py42.sdk.queries.fileevents.v2.filters.user.Id
 class method), 145
 exists() (py42.sdk.queries.fileevents.v2.filters.report.IDExists() (py42.clients.cases.CasesClient
 class method), 146
 exists() (py42.sdk.queries.fileevents.v2.filters.report.NameExists() (py42.clients.cases.CasesClient
 class method), 147
 exists() (py42.sdk.queries.fileevents.v2.filters.report.TypeExists() (py42.clients.cases.CasesClient
 class method), 148
 exists() (py42.sdk.queries.fileevents.v2.filters.risk.IndicatorsExists() (py42.clients.cases.CasesClient
 class method), 154
 exists() (py42.sdk.queries.fileevents.v2.filters.risk.SeverityExists() (py42.clients.cases.CasesClient
 class method), 157
 exists() (py42.sdk.queries.fileevents.v2.filters.source.CategoryExists() (py42.clients.cases.CasesClient property),
 class method), 160
 exists() (py42.sdk.queries.fileevents.v2.filters.source.DomainExists() (py42.clients.cases.CasesClient property),
 class method), 161
 exists() (py42.sdk.queries.fileevents.v2.filters.source.IpAddressExists() (py42.exceptions.Py42ArchiveFileNotFoundError
 class method), 163
 exists() (py42.sdk.queries.fileevents.v2.filters.source.NameExists() (py42.sdk.queries.fileevents.filters.file_filter), 72
 class method), 163
 exists() (py42.sdk.queries.fileevents.v2.filters.source.OperatingSystemExists() (py42.sdk.queries.fileevents.file_event_query),
 class method), 164
 exists() (py42.sdk.queries.fileevents.v2.filters.source.PrivateIpAddressExists() (py42.sdk.queries.fileevents.filters.file_filter),
 class method), 165
 exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBuildTypeExists() (py42.clients.settings.device_settings.BackupSet
 class method), 166
 exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCapacityExists() (py42.clients.settings.device_settings.BackupSet
 class method), 166
 exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaNameExists() (py42.sdk.queries.fileevents.filters.file_filter),
 class method), 167
 exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaPathExists() (py42.sdk.queries.fileevents.filters.file_filter),
 class method), 168
 exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaPartitionIDExists() (py42.sdk.queries.fileevents.filters.file_filter),
 class method), 168

filetypeismatch (py42.clients.alertrules.AlertRulesClient property), 21
 FileTypeMismatchService (class in py42.services.alertrules), 23
 filter_clause (py42.sdk.queries.query_filter.FilterGroup property), 188
 filter_list (py42.sdk.queries.query_filter.FilterGroup property), 188
 FilterGroup (class in py42.sdk.queries.query_filter), 188
 format_json() (in module py42.util), 200
 from_dict() (py42.sdk.queries.query_filter.FilterGroup class method), 188
 from_dict() (py42.sdk.queries.query_filter.QueryFilter class method), 188
 from_jwt_provider() (in module py42.sdk), 203
 from_jwt_provider() (py42.sdk.SDKClient class method), 204
 from_local_account() (in module py42.sdk), 203
 from_local_account() (py42.sdk.SDKClient class method), 204

G

get() (py42.clients.cases.CasesClient method), 39
 get() (py42.clients.trustedactivities.TrustedActivitiesClient method), 193
 get() (py42.clients.watchlists.WatchlistsClient method), 201
 get() (py42.services.alertrules.CloudShareService method), 23
 get() (py42.services.alertrules.ExfiltrationService method), 23
 get() (py42.services.alertrules.FileTypeMismatchService method), 23
 get() (py42.services.casesfileevents.CasesFileEventsService method), 42
 get() (py42.services.detectionlists.departing_employee.DepartingEmployeeService method), 46
 get() (py42.services.detectionlists.high_risk_employee.HighRiskEmployeeService method), 48
 get() (py42.services.savedsearch.SavedSearchService method), 65
 get_agent_full_disk_access_state() (py42.services.devices.DeviceService method), 49
 get_agent_full_disk_access_states() (py42.services.orgs.OrgService method), 182
 get_agent_state() (py42.services.devices.DeviceService method), 49
 get_agent_state() (py42.services.orgs.OrgService method), 182
 get_aggregate_data() (py42.clients.alerts.AlertsClient method), 23
 get_all() (py42.clients.alertrules.AlertRulesClient method), 21
 get_all() (py42.clients.auditlogs.AuditLogsClient method), 36
 get_all() (py42.clients.cases.CasesClient method), 39
 get_all() (py42.clients.trustedactivities.TrustedActivitiesClient method), 193
 get_all() (py42.clients.userriskprofile.UserRiskProfileClient method), 194
 get_all() (py42.clients.watchlists.WatchlistsClient method), 201
 get_all() (py42.services.casesfileevents.CasesFileEventsService method), 42
 get_all() (py42.services.detectionlists.departing_employee.DepartingEmployeeService method), 46
 get_all() (py42.services.detectionlists.high_risk_employee.HighRiskEmployeeService method), 48
 get_all() (py42.services.devices.DeviceService method), 50
 get_all() (py42.services.orgs.OrgService method), 183
 get_all() (py42.services.users.UserService method), 197
 get_all_alert_details() (py42.clients.alerts.AlertsClient method), 23
 get_all_by_device_guid() (py42.clients.archive.ArchiveClient method), 33
 get_all_by_name() (py42.clients.alertrules.AlertRulesClient method), 22
 get_all_device_restore_history() (py42.clients.archive.ArchiveClient method), 33
 get_all_events() (py42.services.legalhold.LegalHoldService method), 179
 get_all_included_users() (py42.clients.watchlists.WatchlistsClient method), 201
 get_all_matter_custodians() (py42.services.legalhold.LegalHoldService method), 179
 get_all_matters() (py42.services.legalhold.LegalHoldService method), 179
 get_all_org_cold_storage_archives() (py42.clients.archive.ArchiveClient method), 33
 get_all_org_restore_history() (py42.clients.archive.ArchiveClient method), 33
 get_all_user_restore_history() (py42.clients.archive.ArchiveClient method), 34
 get_all_watchlist_members()

(py42.clients.watchlists.WatchlistsClient method), 201
 get_attribute_values_from_class() (in module py42.util), 200
 get_available_roles() (py42.services.users.UserService method), 197
 get_backup_sets() (py42.clients.archive.ArchiveClient method), 34
 get_by_archive_guid() (py42.clients.archive.ArchiveClient method), 34
 get_by_guid() (py42.services.devices.DeviceService method), 50
 get_by_id() (py42.clients.userriskprofile.UserRiskProfileClient method), 194
 get_by_id() (py42.services.devices.DeviceService method), 50
 get_by_id() (py42.services.orgs.OrgService method), 183
 get_by_id() (py42.services.savedsearch.SavedSearchService method), 65
 get_by_id() (py42.services.users.UserService method), 197
 get_by_observer_id() (py42.clients.alertrules.AlertRulesClient method), 22
 get_by_uid() (py42.services.orgs.OrgService method), 183
 get_by_uid() (py42.services.users.UserService method), 197
 get_by_username() (py42.clients.userriskprofile.UserRiskProfileClient method), 194
 get_by_username() (py42.services.users.UserService method), 197
 get_current() (py42.services.orgs.OrgService method), 183
 get_current() (py42.services.users.UserService method), 197
 get_current_tenant_id() (py42.usercontext.UserContext method), 199
 get_custodians_page() (py42.services.legalhold.LegalHoldService method), 180
 get_details() (py42.clients.alerts.AlertsClient method), 24
 get_events_page() (py42.services.legalhold.LegalHoldService method), 180
 get_matter_by_uid() (py42.services.legalhold.LegalHoldService method), 181
 get_matters_page() (py42.services.legalhold.LegalHoldService method), 181
 get_page() (py42.clients.alertrules.AlertRulesClient method), 22
 get_page() (py42.clients.auditlogs.AuditLogsClient method), 37
 get_page() (py42.clients.cases.CasesClient method), 40
 get_page() (py42.clients.userriskprofile.UserRiskProfileClient method), 194
 get_page() (py42.services.detectionlists.departing_employee.DepartingEmployeeClient method), 46
 get_page() (py42.services.detectionlists.high_risk_employee.HighRiskEmployeeClient method), 48
 get_page() (py42.services.devices.DeviceService method), 51
 get_page() (py42.services.orgs.OrgService method), 183
 get_page() (py42.services.users.UserService method), 197
 get_policy_by_uid() (py42.services.legalhold.LegalHoldService method), 181
 get_policy_list() (py42.services.legalhold.LegalHoldService method), 181
 get_query() (py42.services.savedsearch.SavedSearchService method), 65
 get_roles() (py42.services.users.UserService method), 198
 get_scim_data_by_uid() (py42.services.users.UserService method), 198
 get_settings() (py42.services.devices.DeviceService method), 51
 get_settings() (py42.services.orgs.OrgService method), 183
 get_user() (py42.clients.detectionlists.DetectionListsClient method), 44
 get_user_by_id() (py42.clients.detectionlists.DetectionListsClient method), 44
 get_watchlist_member() (py42.clients.watchlists.WatchlistsClient method), 201
 greater_than() (py42.sdk.queries.fileevents.filters.file_filter.FileSize class method), 75
 greater_than() (py42.sdk.queries.fileevents.filters.risk_filter.RiskScore class method), 104
 greater_than() (py42.sdk.queries.fileevents.v2.filters.report.Count class method), 144
 greater_than() (py42.sdk.queries.fileevents.v2.filters.risk.IndicatorsWeight class method), 155
 greater_than() (py42.sdk.queries.fileevents.v2.filters.risk.Score class method), 156
 guid() (py42.clients.settings.device_settings.DeviceSettings property), 53
 guid() (py42.clients.settings.device_settings.IncydrDeviceSettings property), 52

H

Headers (class in py42.sdk.queries.fileevents.v2.filters.report), 145	Indicators.EmailServiceUploads (class in py42.sdk.queries.fileevents.v2.filters.risk), 153
headers (py42.response.Py42Response property), 186	Indicators.ExternalDevices (class in py42.sdk.queries.fileevents.v2.filters.risk), 153
HighRiskEmployeeFilters (class in py42.constants), 43	Indicators.FileCategories (class in py42.sdk.queries.fileevents.v2.filters.risk), 153
HighRiskEmployeeFilters (class in py42.services.detectionlists.high_risk_employee), 47	Indicators.FileConversionToolUploads (class in py42.sdk.queries.fileevents.v2.filters.risk), 153
HighRiskEmployeeService (class in py42.services.detectionlists.high_risk_employee), 47	Indicators.MessagingServiceUploads (class in py42.sdk.queries.fileevents.v2.filters.risk), 153
I	Indicators.Other (class in py42.sdk.queries.fileevents.v2.filters.risk), 154
Id (class in py42.sdk.queries.fileevents.v2.filters.event), 125	Indicators.PdfManagerUploads (class in py42.sdk.queries.fileevents.v2.filters.risk), 154
Id (class in py42.sdk.queries.fileevents.v2.filters.file), 135	Indicators.ProductivityToolUploads (class in py42.sdk.queries.fileevents.v2.filters.risk), 154
ID (class in py42.sdk.queries.fileevents.v2.filters.report), 146	Indicators.SocialMediaUploads (class in py42.sdk.queries.fileevents.v2.filters.risk), 154
Id (class in py42.sdk.queries.fileevents.v2.filters.user), 177	Indicators.UserBehavior (class in py42.sdk.queries.fileevents.v2.filters.risk), 154
in_range() (py42.sdk.queries.alerts.filters.alert_filter.DateObserved class method), 27	Indicators.WebHostingUploads (class in py42.sdk.queries.fileevents.v2.filters.risk), 154
in_range() (py42.sdk.queries.fileevents.filters.event_filter.EventTimestamp class method), 67	Indicators.Weight (class in py42.sdk.queries.fileevents.v2.filters.risk), 155
in_range() (py42.sdk.queries.fileevents.filters.event_filter.InsertionTimestamp class method), 69	Inserted (class in py42.sdk.queries.fileevents.v2.filters.event), 126
in_range() (py42.sdk.queries.fileevents.v2.filters.event.Inserted class method), 126	InsertionTimestamp (class in py42.sdk.queries.fileevents.filters.event_filter), 69
in_range() (py42.sdk.queries.fileevents.v2.filters.file.Created class method), 133	IpAddress (class in py42.sdk.queries.fileevents.v2.filters.destination), 110
in_range() (py42.sdk.queries.fileevents.v2.filters.file.Modified class method), 138	IpAddress (class in py42.sdk.queries.fileevents.v2.filters.source), 163
in_range() (py42.sdk.queries.fileevents.v2.filters.file.Size class method), 141	is_false() (py42.sdk.queries.fileevents.filters.activity_filter.RemoteActivity class method), 97
in_range() (py42.sdk.queries.fileevents.v2.filters.timestamp.Timestamp class method), 175	is_false() (py42.sdk.queries.fileevents.filters.activity_filter.TrustedActivity class method), 97
in_range() (py42.sdk.queries.query_filter.QueryFilterTimestampField class method), 190	is_false() (py42.sdk.queries.fileevents.filters.cloud_filter.Shared class method), 82
included_files (py42.clients.settings.device_settings.BackupSet property), 38	is_false() (py42.sdk.queries.fileevents.filters.event_filter.MimeTypeMismatch class method), 71
IncydrDeviceSettings (class in py42.clients.settings.device_settings), 52	is_false() (py42.sdk.queries.fileevents.filters.event_filter.OutsideActiveHours class method), 72
Indicators (class in py42.sdk.queries.fileevents.v2.filters.risk), 148	is_false() (py42.sdk.queries.fileevents.v2.filters.risk.Trusted class method), 159
Indicators.CloudDataExposures (class in py42.sdk.queries.fileevents.v2.filters.risk), 152	
Indicators.CloudStorageUploads (class in py42.sdk.queries.fileevents.v2.filters.risk), 153	
Indicators.CodeRepositoryUploads (class in py42.sdk.queries.fileevents.v2.filters.risk), 153	

`is_false()` (`py42.sdk.queries.query_filter.QueryFilterBookmarksFilter` class method), 189
`is_in()` (`py42.sdk.queries.alerts.filters.alert_filter.Actor` class method), 26
`is_in()` (`py42.sdk.queries.alerts.filters.alert_filter.AlertStatus` class method), 27
`is_in()` (`py42.sdk.queries.alerts.filters.alert_filter.Description` class method), 28
`is_in()` (`py42.sdk.queries.alerts.filters.alert_filter.RuleId` class method), 29
`is_in()` (`py42.sdk.queries.alerts.filters.alert_filter.RuleName` class method), 29
`is_in()` (`py42.sdk.queries.alerts.filters.alert_filter.RuleSource` class method), 30
`is_in()` (`py42.sdk.queries.alerts.filters.alert_filter.RuleType` class method), 31
`is_in()` (`py42.sdk.queries.alerts.filters.alert_filter.Severity` class method), 32
`is_in()` (`py42.sdk.queries.fileevents.filters.cloud_filter.Actor` class method), 81
`is_in()` (`py42.sdk.queries.fileevents.filters.cloud_filter.DirectoryId` class method), 82
`is_in()` (`py42.sdk.queries.fileevents.filters.cloud_filter.ShareLink` class method), 83
`is_in()` (`py42.sdk.queries.fileevents.filters.cloud_filter.SharingType` class method), 83
`is_in()` (`py42.sdk.queries.fileevents.filters.device_filter.DeviceSignature` class method), 80
`is_in()` (`py42.sdk.queries.fileevents.filters.device_filter.DeviceUsed` class method), 77
`is_in()` (`py42.sdk.queries.fileevents.filters.device_filter.OS` class method), 78
`is_in()` (`py42.sdk.queries.fileevents.filters.device_filter.PrivateIP` class method), 79
`is_in()` (`py42.sdk.queries.fileevents.filters.device_filter.PublicIP` class method), 79
`is_in()` (`py42.sdk.queries.fileevents.filters.email_filter.EmailFrom` class method), 97
`is_in()` (`py42.sdk.queries.fileevents.filters.email_filter.EmailTo` class method), 94
`is_in()` (`py42.sdk.queries.fileevents.filters.email_filter.EmailReplyTo` class method), 96
`is_in()` (`py42.sdk.queries.fileevents.filters.email_filter.EmailCc` class method), 96
`is_in()` (`py42.sdk.queries.fileevents.filters.email_filter.EmailSubject` class method), 95
`is_in()` (`py42.sdk.queries.fileevents.filters.event_filter.EventType` class method), 69
`is_in()` (`py42.sdk.queries.fileevents.filters.event_filter.Source` class method), 71
`is_in()` (`py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType` class method), 85
`is_in()` (`py42.sdk.queries.fileevents.filters.exposure_filter.ProcessOwner` class method), 86
`is_in()` (`py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMedia` class method), 88
`is_in()` (`py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaSize` class method), 87
`is_in()` (`py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaUsage` class method), 90
`is_in()` (`py42.sdk.queries.fileevents.filters.exposure_filter.SyncDestination` class method), 91
`is_in()` (`py42.sdk.queries.fileevents.filters.exposure_filter.SyncDestinationType` class method), 92
`is_in()` (`py42.sdk.queries.fileevents.filters.exposure_filter.TabURL` class method), 93
`is_in()` (`py42.sdk.queries.fileevents.filters.exposure_filter.WindowTitle` class method), 94
`is_in()` (`py42.sdk.queries.fileevents.filters.file_filter.FileCategory` class method), 73
`is_in()` (`py42.sdk.queries.fileevents.filters.file_filter.FileName` class method), 73
`is_in()` (`py42.sdk.queries.fileevents.filters.file_filter.FileOwner` class method), 74
`is_in()` (`py42.sdk.queries.fileevents.filters.file_filter.FilePath` class method), 75
`is_in()` (`py42.sdk.queries.fileevents.filters.file_filter.MD5` class method), 76
`is_in()` (`py42.sdk.queries.fileevents.filters.file_filter.SHA256` class method), 76
`is_in()` (`py42.sdk.queries.fileevents.filters.print_filter.Printer` class method), 98
`is_in()` (`py42.sdk.queries.fileevents.filters.print_filter.PrintJobName` class method), 99
`is_in()` (`py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator` class method), 102
`is_in()` (`py42.sdk.queries.fileevents.filters.risk_filter.RiskScore` class method), 104
`is_in()` (`py42.sdk.queries.fileevents.filters.risk_filter.RiskSeverity` class method), 103
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.Category` class method), 108
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.EmailRecipients` class method), 109
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.EmailSubject` class method), 110
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.IpAddress` class method), 110
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.Name` class method), 111

`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.OpeningSystem` class method), 112
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessId` class method), 113
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 114
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessIdName` class method), 112
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 114
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 115
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 116
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 117
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 117
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 118
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 119
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 119
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 120
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 121
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 122
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 122
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 123
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.ProcessName` class method), 124
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.event.Action` class method), 125
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.event.Id` class method), 125
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.event.Observers` class method), 127
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.event.ShareType` class method), 128
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Category` class method), 129
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Category` class method), 130
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Category` class method), 131
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Classification` class method), 131
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.CloudDrive` class method), 132
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Directory` class method), 134
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.DirectoryId` class method), 134
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Id` class method), 135
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.MD5` class method), 136
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByBytes` class method), 136
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByExtension` class method), 137
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Name` class method), 139
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Owner` class method), 139
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.SHA256` class method), 140
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Url` class method), 142
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.process.Executable` class method), 142
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.process.Owner` class method), 143
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.report.Count` class method), 144
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.report.Description` class method), 145
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.report.Headers` class method), 145
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.report.ID` class method), 146
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.report.Name` class method), 147
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.report.Type` class method), 148
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.risk.Indicators` class method), 155
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.risk.IndicatorsWeight` class method), 155
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.risk.Score` class method), 156
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.risk.Severity` class method), 157
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.risk.TrustReason` class method), 158
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.source.Category` class method), 160
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.source.Domain` class method), 161
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.source.EmailFrom` class method), 162
`is_in()` (`py42.sdk.queries.fileevents.v2.filters.source.EmailSender` class method), 162

[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.IpAddress` class method), 163
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.Name` class method), 163
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.OperativeSystem` class method), 164
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.PrivateIpAddress` class method), 165
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBusType` class method), 166
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCapacity` class method), 166
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaName` class method), 167
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaPartitionID` class method), 169
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaSerialNumber` class method), 169
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVendor` class method), 170
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVolumeName` class method), 171
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors` class method), 171
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.TabTitles` class method), 172
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.TabUrlsErrors` class method), 173
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.source.TabUrls` class method), 174
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.user.DeviceUid` class method), 176
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.user.Email` class method), 176
[is_in\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.user.Id` class method), 177
[is_in\(\)](#) (`py42.sdk.queries.query_filter.QueryFilterStringField` class method), 189
[is_true\(\)](#) (`py42.sdk.queries.fileevents.filters.activity_filter.RemoteActivity` class method), 97
[is_true\(\)](#) (`py42.sdk.queries.fileevents.filters.activity_filter.TrustedActivity` class method), 97
[is_true\(\)](#) (`py42.sdk.queries.fileevents.filters.cloud_filter.Shared` class method), 82
[is_true\(\)](#) (`py42.sdk.queries.fileevents.filters.event_filter.MimeTypeMismatch` class method), 71
[is_true\(\)](#) (`py42.sdk.queries.fileevents.filters.event_filter.OutsideActiveHours` class method), 72
[is_true\(\)](#) (`py42.sdk.queries.fileevents.v2.filters.risk.Trusted` class method), 159
[is_true\(\)](#) (`py42.sdk.queries.query_filter.QueryFilterBooleanField` class method), 189

[iter_content\(\)](#) (`py42.response.Py42Response` method), 186
[JavaMemoryHeapMax](#) (`py42.clients.settings.device_settings.DeviceSettings` property), 53
[LegalHoldMatterUids](#) (`py42.exceptions.Py42LegalHoldAlreadyActiveError` property), 59
[LegalHoldMatterUids](#) (`py42.exceptions.Py42LegalHoldAlreadyDeactivatedError` property), 59
[LegalHold](#) (`py42.sdk.SDKClient` property), 205
[LegalHoldService](#) (class in `py42.services.legalhold`), 178
[LessThan](#) (`py42.sdk.queries.fileevents.filters.file_filter.FileSize` class method), 75
[LessThan](#) (`py42.sdk.queries.fileevents.filters.risk_filter.RiskScore` class method), 104
[LessThan](#) (`py42.sdk.queries.fileevents.v2.filters.report.Count` class method), 144
[LessThan](#) (`py42.sdk.queries.fileevents.v2.filters.risk.IndicatorsWeight` class method), 155
[LessThan](#) (`py42.sdk.queries.fileevents.v2.filters.risk.Score` class method), 156
[ListName](#) (`py42.exceptions.Py42UserNotOnListError` property), 63
[LockDestination](#) (`py42.clients.settings.device_settings.BackupSet` method), 38
[Locked](#) (`py42.clients.settings.device_settings.BackupSet` property), 38
[Loginconfig](#) (`py42.sdk.SDKClient` property), 205

M
[MaximumUserSubscriptions](#) (`py42.clients.settings.org_settings.OrgSettings` attribute), 185
[MD5](#) (class in `py42.sdk.queries.fileevents.filters.file_filter`), 75
[MD5](#) (class in `py42.sdk.queries.fileevents.v2.filters.file`), 135
[MimeTypeByBytes](#) (class in `py42.sdk.queries.fileevents.v2.filters.file`), 136
[MimeTypeByExtension](#) (class in `py42.sdk.queries.fileevents.v2.filters.file`), 137
[MimeTypeMismatch](#) (class in `py42.sdk.queries.fileevents.filters.event_filter`), 71

Modified (class in py42.sdk.queries.fileevents.v2.filters.file)not_eq() (py42.sdk.queries.alerts.filters.alert_filter.RuleId
138 class method), 29

module not_eq() (py42.sdk.queries.alerts.filters.alert_filter.RuleName
class method), 30

py42.exceptions, 54 not_eq() (py42.sdk.queries.alerts.filters.alert_filter.RuleSource
class method), 31

py42.sdk, 203 not_eq() (py42.sdk.queries.alerts.filters.alert_filter.RuleType
class method), 31

py42.sdk.queries.alerts.filters.alert_filter, 25 not_eq() (py42.sdk.queries.alerts.filters.alert_filter.Severity
class method), 32

py42.sdk.queries.fileevents.v2.filters.destination, 107 not_eq() (py42.sdk.queries.fileevents.filters.cloud_filter.Actor
class method), 81

py42.sdk.queries.fileevents.v2.filters.event, 124 not_eq() (py42.sdk.queries.fileevents.filters.cloud_filter.DirectoryID
class method), 82

py42.sdk.queries.fileevents.v2.filters.file, 129 not_eq() (py42.sdk.queries.fileevents.filters.cloud_filter.SharedWith
class method), 83

py42.sdk.queries.fileevents.v2.filters.process, 142 not_eq() (py42.sdk.queries.fileevents.filters.cloud_filter.SharingTypeAddress
class method), 84

py42.sdk.queries.fileevents.v2.filters.report, 144 not_eq() (py42.sdk.queries.fileevents.filters.device_filter.DeviceSignedInU
class method), 80

py42.sdk.queries.fileevents.v2.filters.risk, 148 not_eq() (py42.sdk.queries.fileevents.filters.device_filter.DeviceUsername
class method), 77

py42.sdk.queries.fileevents.v2.filters.source, 159 not_eq() (py42.sdk.queries.fileevents.filters.device_filter.OSHostname
class method), 78

py42.sdk.queries.fileevents.v2.filters.timestamp, 174 not_eq() (py42.sdk.queries.fileevents.filters.device_filter.PrivateIPAddress
class method), 79

py42.sdk.queries.fileevents.v2.filters.user, 176 not_eq() (py42.sdk.queries.fileevents.filters.device_filter.PublicIPAddress
class method), 79

py42.sdk.queries.query_filter, 188 not_eq() (py42.sdk.queries.fileevents.filters.email_filter.EmailFrom
class method), 97

py42.util, 199 not_eq() (py42.sdk.queries.fileevents.filters.email_filter.EmailPolicyName
class method), 95

N not_eq() (py42.sdk.queries.fileevents.filters.email_filter.EmailRecipients
class method), 96

Name (class in py42.sdk.queries.fileevents.v2.filters.destination), 111 not_eq() (py42.sdk.queries.fileevents.filters.email_filter.EmailSender
class method), 96

Name (class in py42.sdk.queries.fileevents.v2.filters.file), 138 not_eq() (py42.sdk.queries.fileevents.filters.email_filter.EmailSubject
class method), 95

Name (class in py42.sdk.queries.fileevents.v2.filters.report), 147 not_eq() (py42.sdk.queries.fileevents.filters.event_filter.EventType
class method), 69

Name (class in py42.sdk.queries.fileevents.v2.filters.source), 163 not_eq() (py42.sdk.queries.fileevents.filters.event_filter.Source
class method), 71

name (py42.clients.settings.device_settings.DeviceSettings
attribute), 53 not_eq() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType
class method), 85

name (py42.clients.settings.device_settings.IncydrDeviceSettings
property), 52 not_eq() (py42.sdk.queries.fileevents.filters.exposure_filter.ProcessName
class method), 85

not_contains() (py42.sdk.queries.alerts.filters.alert_filter.Actor
class method), 26 not_eq() (py42.sdk.queries.fileevents.filters.exposure_filter.ProcessOwner
class method), 86

not_contains() (py42.sdk.queries.alerts.filters.alert_filter.Description
class method), 28 not_eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMedia
class method), 88

not_contains() (py42.sdk.queries.alerts.filters.alert_filter.RuleName
class method), 30 not_eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMedia
class method), 87

not_eq() (py42.sdk.queries.alerts.filters.alert_filter.Actor
class method), 26 not_eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMedia
class method), 90

not_eq() (py42.sdk.queries.alerts.filters.alert_filter.AlertState
class method), 27

not_eq() (py42.sdk.queries.alerts.filters.alert_filter.Description
class method), 28

`not_eq()` (`py42.sdk.queries.fileevents.filters.exposure_filter.Md5SkriptView` class method), 91
`not_eq()` (`py42.sdk.queries.fileevents.filters.exposure_filter.Md5SkriptView` class method), 91
`not_eq()` (`py42.sdk.queries.fileevents.filters.exposure_filter.Md5SkriptView` class method), 88
`not_eq()` (`py42.sdk.queries.fileevents.filters.exposure_filter.Md5SkriptView` class method), 89
`not_eq()` (`py42.sdk.queries.fileevents.filters.exposure_filter.Md5SkriptView` class method), 92
`not_eq()` (`py42.sdk.queries.fileevents.filters.exposure_filter.Md5SkriptView` class method), 92
`not_eq()` (`py42.sdk.queries.fileevents.filters.exposure_filter.Md5SkriptView` class method), 93
`not_eq()` (`py42.sdk.queries.fileevents.filters.exposure_filter.Md5SkriptView` class method), 94
`not_eq()` (`py42.sdk.queries.fileevents.filters.file_filter.FileCategory` class method), 73
`not_eq()` (`py42.sdk.queries.fileevents.filters.file_filter.FileName` class method), 73
`not_eq()` (`py42.sdk.queries.fileevents.filters.file_filter.FilePath` class method), 74
`not_eq()` (`py42.sdk.queries.fileevents.filters.file_filter.FilePath` class method), 75
`not_eq()` (`py42.sdk.queries.fileevents.filters.file_filter.MD5` class method), 76
`not_eq()` (`py42.sdk.queries.fileevents.filters.file_filter.SHA256` class method), 77
`not_eq()` (`py42.sdk.queries.fileevents.filters.print_filter.PrintName` class method), 98
`not_eq()` (`py42.sdk.queries.fileevents.filters.print_filter.PrintName` class method), 99
`not_eq()` (`py42.sdk.queries.fileevents.filters.risk_filter.RiskScore` class method), 103
`not_eq()` (`py42.sdk.queries.fileevents.filters.risk_filter.RiskScore` class method), 104
`not_eq()` (`py42.sdk.queries.fileevents.filters.risk_filter.RiskScore` class method), 104
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.Connection` class method), 109
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.Connection` class method), 109
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.Connection` class method), 110
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.Connection` class method), 110
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.Connection` class method), 111
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.Connection` class method), 112
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.Connection` class method), 113
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.Connection` class method), 114
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.Connection` class method), 112
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.PrivateIpAddress` class method), 115
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia` class method), 115
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia` class method), 116
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia` class method), 117
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia` class method), 117
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia` class method), 118
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia` class method), 119
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia` class method), 120
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia` class method), 120
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.TabTitleErrors` class method), 121
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.TabTitles` class method), 122
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.TabUrlErrors` class method), 122
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.TabUrls` class method), 123
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.destination.UserEmail` class method), 124
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.event.Action` class method), 125
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.event.Id` class method), 126
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.event.Observer` class method), 127
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.event.ShareType` class method), 128
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.Category` class method), 129
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.CategoryByBytes` class method), 130
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.CategoryByExtension` class method), 131
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.Classification` class method), 132
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.CloudDriveId` class method), 132
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.Directory` class method), 134
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.DirectoryId` class method), 134
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.Id` class method), 135
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.MD5` class method), 136

`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByFile` class method), 137
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByFile` class method), 137
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.Name` class method), 139
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.Owner` class method), 140
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.SHA256` class method), 140
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.file.Url` class method), 142
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.process.ExternalId` class method), 143
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.process.Owner` class method), 143
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.report.Count` class method), 144
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.report.Description` class method), 145
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.report.Headline` class method), 146
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.report.ID` class method), 146
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.report.Name` class method), 147
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.report.Type` class method), 148
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.risk.Indicator` class method), 155
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.risk.IndicatorWeight` class method), 155
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.risk.Score` class method), 156
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.risk.Severity` class method), 157
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.risk.TrustReason` class method), 158
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.Category` class method), 160
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.Domain` class method), 161
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.EmailFrom` class method), 162
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.EmailTo` class method), 162
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.IpAddress` class method), 163
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.Name` class method), 164
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.OpeningHours` class method), 164
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.PrivateAddress` class method), 165
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaByFile` class method), 166
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCategory` class method), 166
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaMedia` class method), 167
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaName` class method), 168
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaParent` class method), 169
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaSeries` class method), 169
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVersion` class method), 170
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVolume` class method), 171
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors` class method), 172
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.TabTitles` class method), 172
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.TabUrlErrors` class method), 173
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.source.TabUrls` class method), 174
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.user.DeviceUid` class method), 176
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.user.Email` class method), 177
`not_eq()` (`py42.sdk.queries.fileevents.v2.filters.user.Id` class method), 177
`not_eq()` (`py42.sdk.queries.query_filter.QueryFilterStringField` class method), 189
`not_exists()` (`py42.sdk.queries.fileevents.filters.cloud_filter.Actor` class method), 81
`not_exists()` (`py42.sdk.queries.fileevents.filters.cloud_filter.DirectoryID` class method), 82
`not_exists()` (`py42.sdk.queries.fileevents.filters.cloud_filter.SharedWith` class method), 83
`not_exists()` (`py42.sdk.queries.fileevents.filters.cloud_filter.SharingType` class method), 84
`not_exists()` (`py42.sdk.queries.fileevents.filters.device_filter.DeviceSignature` class method), 80
`not_exists()` (`py42.sdk.queries.fileevents.filters.device_filter.DeviceUser` class method), 77
`not_exists()` (`py42.sdk.queries.fileevents.filters.device_filter.OSType` class method), 78
`not_exists()` (`py42.sdk.queries.fileevents.filters.device_filter.PrivateIPAd` class method), 79
`not_exists()` (`py42.sdk.queries.fileevents.filters.device_filter.PublicIPAd` class method), 80
`not_exists()` (`py42.sdk.queries.fileevents.filters.event_filter.EventType` class method), 69
`not_exists()` (`py42.sdk.queries.fileevents.filters.event_filter.Source` class method), 71

`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.file.Id` `not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMedia`
class method), 135 class method), 168
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.file.MimeType` `not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMedia`
class method), 136 class method), 169
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.file.MinOffset` `not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMedia`
class method), 137 class method), 170
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.file.MinOffsetSize` `not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMedia`
class method), 137 class method), 170
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.file.Name` `not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMedia`
class method), 139 class method), 171
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.file.Owner` `not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors`
class method), 140 class method), 172
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.file.SHA256` `not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source.TabTitles`
class method), 140 class method), 172
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.file.Url` `not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source.TabUrlErrors`
class method), 142 class method), 173
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.processing` `not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source.TabUrls`
class method), 143 class method), 174
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.processing` `not_exists()` (`py42.sdk.queries.fileevents.v2.filters.user.DeviceUid`
class method), 143 class method), 176
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.report` `not_exists()` (`py42.sdk.queries.fileevents.v2.filters.user.Email`
class method), 144 class method), 177
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.report` `not_exists()` (`py42.sdk.queries.fileevents.v2.filters.user.Id`
class method), 145 class method), 177
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.report` `not_exists()` (`py42.sdk.queries.alerts.filters.alert_filter.Actor`
class method), 146 class method), 26
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.report` `not_exists()` (`py42.sdk.queries.alerts.filters.alert_filter.AlertState`
class method), 146 class method), 27
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.report` `not_exists()` (`py42.sdk.queries.alerts.filters.alert_filter.Description`
class method), 147 class method), 28
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.report` `not_exists()` (`py42.sdk.queries.alerts.filters.alert_filter.RuleId`
class method), 148 class method), 29
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.risk` `not_exists()` (`py42.sdk.queries.alerts.filters.alert_filter.RuleName`
class method), 155 class method), 30
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.risk` `not_exists()` (`py42.sdk.queries.alerts.filters.alert_filter.RuleSource`
class method), 157 class method), 31
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source` `not_exists()` (`py42.sdk.queries.alerts.filters.alert_filter.RuleType`
class method), 160 class method), 31
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source` `not_exists()` (`py42.sdk.queries.alerts.filters.alert_filter.Severity`
class method), 161 class method), 32
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source` `not_exists()` (`py42.sdk.queries.fileevents.filters.cloud_filter.Actor`
class method), 163 class method), 81
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source` `not_exists()` (`py42.sdk.queries.fileevents.filters.cloud_filter.DirectoryID`
class method), 164 class method), 82
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source` `not_exists()` (`py42.sdk.queries.fileevents.filters.cloud_filter.SharedWith`
class method), 164 class method), 83
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source` `not_exists()` (`py42.sdk.queries.fileevents.filters.cloud_filter.SharingTypeAdded`
class method), 165 class method), 84
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source` `not_exists()` (`py42.sdk.queries.fileevents.filters.device_filter.DeviceSignedInU`
class method), 166 class method), 80
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source` `not_exists()` (`py42.sdk.queries.fileevents.filters.device_filter.DeviceUsername`
class method), 167 class method), 77
`not_exists()` (`py42.sdk.queries.fileevents.v2.filters.source` `not_exists()` (`py42.sdk.queries.fileevents.filters.device_filter.OSTHostname`
class method), 167 class method), 78

`not_in()` (py42.sdk.queries.fileevents.filters.device_filter.PriorityIndicator class method), 79
`not_in()` (py42.sdk.queries.fileevents.filters.device_filter.PrintJob class method), 77
`not_in()` (py42.sdk.queries.fileevents.filters.device_filter.PrintJobName class method), 80
`not_in()` (py42.sdk.queries.fileevents.filters.device_filter.Printer class method), 98
`not_in()` (py42.sdk.queries.fileevents.filters.email_filter.EmailFilter class method), 97
`not_in()` (py42.sdk.queries.fileevents.filters.print_filter.PrintJobName class method), 99
`not_in()` (py42.sdk.queries.fileevents.filters.print_filter.Printer class method), 103
`not_in()` (py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator class method), 103
`not_in()` (py42.sdk.queries.fileevents.filters.risk_filter.RiskScore class method), 105
`not_in()` (py42.sdk.queries.fileevents.filters.risk_filter.RiskSeverity class method), 104
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.Category class method), 109
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.EmailRecipient class method), 109
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.EmailSubject class method), 110
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.IpAddress class method), 111
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.Name class method), 111
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.OperatingSystem class method), 112
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.PrintedFilesBase class method), 113
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.PrinterName class method), 114
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.PrintJobName class method), 113
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.PrivateIpAddress class method), 115
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia class method), 115
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia class method), 116
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia class method), 117
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia class method), 118
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia class method), 118
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia class method), 119
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia class method), 120
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia class method), 121
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.TabTitleErrors class method), 121
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.TabTitles class method), 122
`not_in()` (py42.sdk.queries.fileevents.v2.filters.destination.TabUrlErrors class method), 123

`not_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.HostUrl` class method), 123
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.destination.HostFile` class method), 124
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.event.Action` class method), 125
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.event.Id` class method), 126
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.event.Observed` class method), 128
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.event.ShareType` class method), 128
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Category` class method), 130
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.CategoryByBin` class method), 130
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.CategoryByExtension` class method), 131
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Classification` class method), 132
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.CloudDrive` class method), 132
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Directory` class method), 134
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.DirectoryId` class method), 135
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Id` class method), 135
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.MD5` class method), 136
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.MimeType` class method), 137
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByExtension` class method), 137
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Name` class method), 139
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Owner` class method), 140
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.SHA256` class method), 140
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.file.Url` class method), 142
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.process.Executable` class method), 143
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.process.Owner` class method), 143
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.report.Count` class method), 144
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.report.Description` class method), 145
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.report.Headline` class method), 146
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.report.ID` class method), 147
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.report.Name` class method), 147
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.report.Type` class method), 148
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.risk.Indicators` class method), 155
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.risk.IndicatorsWeight` class method), 156
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.risk.Score` class method), 156
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.risk.Severity` class method), 157
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.risk.TrustReason` class method), 158
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.Category` class method), 161
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.Domain` class method), 161
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.EmailFrom` class method), 162
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.EmailSender` class method), 162
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.IpAddress` class method), 163
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.Name` class method), 164
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.OperatingSystem` class method), 165
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.PrivateIpAddress` class method), 165
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBus` class method), 166
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCapacity` class method), 167
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaMedia` class method), 167
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaName` class method), 168
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaPath` class method), 169
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaSerial` class method), 170
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVersion` class method), 170
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVolume` class method), 171
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors` class method), 172
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.TabTitles` class method), 172
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.TabUrlErrors` class method), 173
`not_in()` (`py42.sdk.queries.fileevents.v2.filters.source.TabUrls` class method), 174

not_in() (py42.sdk.queries.fileevents.v2.filters.user.DeviceId on_same_day() (py42.sdk.queries.alerts.filters.alert_filter.DateObserved
 class method), 176 class method), 28
 not_in() (py42.sdk.queries.fileevents.v2.filters.user.Email on_same_day() (py42.sdk.queries.fileevents.filters.event_filter.EventTime
 class method), 177 class method), 68
 not_in() (py42.sdk.queries.fileevents.v2.filters.user.Id on_same_day() (py42.sdk.queries.fileevents.filters.event_filter.InsertionTime
 class method), 178 class method), 70
 not_in() (py42.sdk.queries.query_filter.QueryFilterStringField on_same_day() (py42.sdk.queries.fileevents.v2.filters.event.Inserted
 class method), 189 class method), 126
 notes (py42.clients.settings.device_settings.DeviceSettings on_same_day() (py42.sdk.queries.fileevents.v2.filters.file.Created
 attribute), 53 class method), 133
 notes (py42.clients.settings.device_settings.IncydrDeviceSettings on_same_day() (py42.sdk.queries.fileevents.v2.filters.file.Modified
 attribute), 52 class method), 138
 notes (py42.clients.settings.org_settings.OrgSettings at- on_same_day() (py42.sdk.queries.fileevents.v2.filters.file.Size
 tribute), 185 class method), 141
 on_same_day() (py42.sdk.queries.fileevents.v2.filters.timestamp.Timestamp
 class method), 175
O
 Observer (class in py42.sdk.queries.fileevents.v2.filters.event on_same_day() (py42.sdk.queries.query_filter.QueryFilterTimestampField
 127 class method), 190
 on_or_after() (py42.sdk.queries.alerts.filters.alert_filter.DateObserved (class in
 class method), 27 py42.sdk.queries.fileevents.v2.filters.destination),
 111
 on_or_after() (py42.sdk.queries.fileevents.filters.event_filter.EventTimestamp
 class method), 68 OperatingSystem (class in
 on_or_after() (py42.sdk.queries.fileevents.filters.event_filter.InsertionTimestamp py42.sdk.queries.fileevents.v2.filters.source),
 class method), 70 164
 on_or_after() (py42.sdk.queries.fileevents.v2.filters.event_insertion operator (py42.sdk.queries.query_filter.QueryFilter
 class method), 126 property), 189
 on_or_after() (py42.sdk.queries.fileevents.v2.filters.file.Created org_backup_quota (py42.clients.settings.org_settings.OrgSettings
 class method), 133 attribute), 185
 on_or_after() (py42.sdk.queries.fileevents.v2.filters.file.Modified org_id (py42.clients.settings.device_settings.DeviceSettings
 class method), 138 property), 53
 on_or_after() (py42.sdk.queries.fileevents.v2.filters.file.Size org_id (py42.clients.settings.device_settings.IncydrDeviceSettings
 class method), 141 property), 52
 on_or_after() (py42.sdk.queries.fileevents.v2.filters.timestamp.Timestamp org_id (py42.clients.settings.org_settings.OrgSettings
 class method), 175 property), 185
 on_or_after() (py42.sdk.queries.query_filter.QueryFilterTimestampField org_name (py42.clients.settings.org_settings.OrgSettings
 class method), 190 attribute), 185
 on_or_before() (py42.sdk.queries.alerts.filters.alert_filter.DateObserved org_uid (py42.exceptions.Py42OrgNotFoundError
 class method), 27 property), 60
 on_or_before() (py42.sdk.queries.fileevents.filters.event_filter.EventTimestamp org (py42.sdk.SDKClient property), 205
 class method), 68 OrgService (class in py42.services.orgs), 182
 on_or_before() (py42.sdk.queries.fileevents.filters.event_filter.InsertionTimestamp OrgSettings (class in
 class method), 70 py42.clients.settings.org_settings), 184
 on_or_before() (py42.sdk.queries.fileevents.v2.filters.event_insertion OSHostname (class in py42.sdk.queries.fileevents.filters.device_filter),
 class method), 126 78
 on_or_before() (py42.sdk.queries.fileevents.v2.filters.file.Created OutsideActiveHours (class in
 class method), 133 py42.sdk.queries.fileevents.filters.event_filter),
 71
 on_or_before() (py42.sdk.queries.fileevents.v2.filters.file.Modified Owner (class in py42.sdk.queries.fileevents.v2.filters.file),
 class method), 138 139
 on_or_before() (py42.sdk.queries.fileevents.v2.filters.file.Size Owner (class in py42.sdk.queries.fileevents.v2.filters.process),
 class method), 141 143
 on_or_before() (py42.sdk.queries.fileevents.v2.filters.timestamp.Timestamp
 class method), 175
 on_or_before() (py42.sdk.queries.query_filter.QueryFilterTimestampField
 class method), 190

P

packets (py42.clients.settings.org_settings.OrgSettings

property), 185
 page_token (py42.exceptions.Py42InvalidPageTokenError
 property), 58
 print_response() (in module py42.util), 200
 PrintedFilesBackupPath (class in py42.sdk.queries.fileevents.v2.filters.destination),
 113
 Printer (class in py42.sdk.queries.fileevents.filters.print_filter), module, 188
 98
 PrinterName (class in py42.sdk.queries.fileevents.v2.filters.destination),
 113
 PrintJobName (class in py42.sdk.queries.fileevents.filters.print_filter),
 98
 PrintJobName (class in py42.sdk.queries.fileevents.v2.filters.destination),
 112
 PrivateIPAddress (class in py42.sdk.queries.fileevents.filters.device_filter),
 78
 PrivateIpAddress (class in py42.sdk.queries.fileevents.v2.filters.destination),
 114
 PrivateIpAddress (class in py42.sdk.queries.fileevents.v2.filters.source),
 165
 ProcessName (class in py42.sdk.queries.fileevents.filters.exposure_filter),
 85
 ProcessOwner (class in py42.sdk.queries.fileevents.filters.exposure_filter),
 86
 PublicIPAddress (class in py42.sdk.queries.fileevents.filters.device_filter),
 79
 py42.exceptions
 module, 54
 py42.sdk
 module, 203
 py42.sdk.queries.alerts.filters.alert_filter
 module, 25
 py42.sdk.queries.fileevents.v2.filters.destination
 module, 107
 py42.sdk.queries.fileevents.v2.filters.event
 module, 124
 py42.sdk.queries.fileevents.v2.filters.file
 module, 129
 py42.sdk.queries.fileevents.v2.filters.process
 module, 142
 py42.sdk.queries.fileevents.v2.filters.report
 module, 144
 py42.sdk.queries.fileevents.v2.filters.risk
 module, 148
 py42.sdk.queries.fileevents.v2.filters.source
 module, 159
 py42.sdk.queries.fileevents.v2.filters.timestamp
 module, 174
 py42.sdk.queries.fileevents.v2.filters.user
 module, 176
 py42.sdk.queries.query_filter
 py42.util
 module, 199
 Py42ActiveLegalHoldError, 54
 Py42ArchiveFileNotFoundError, 54
 Py42BadRequestError, 54
 Py42BadRestoreRequestError, 54
 Py42CaseAlreadyHasEventError, 54
 Py42CaseNameExistsError, 55
 Py42ChecksumNotFoundError, 55
 Py42CloudAliasCharacterLimitExceededError, 55
 Py42CloudAliasLimitExceededError, 55
 Py42ConflictError, 55
 Py42DescriptionLimitExceededError, 56
 Py42DeviceNotConnectedError, 56
 Py42Error, 56
 Py42FeatureUnavailableError, 56
 Py42ForbiddenError, 56
 Py42HTTPError, 56
 Py42InternalServerError, 57
 Py42InvalidArchiveEncryptionKey, 57
 Py42InvalidArchivePassword, 57
 Py42InvalidCaseUserError, 57
 Py42InvalidEmailError, 57
 Py42InvalidPageTokenError, 57
 Py42InvalidPasswordError, 58
 Py42InvalidRuleError, 58
 Py42InvalidRuleOperationError, 58
 Py42InvalidUsernameError, 58
 Py42InvalidWatchlistType, 59
 Py42LegalHoldAlreadyActiveError, 59
 Py42LegalHoldAlreadyDeactivatedError, 59
 Py42LegalHoldCriteriaMissingError, 59
 Py42LegalHoldNotFoundOrPermissionDeniedError,
 59
 Py42MFARequiredError, 60
 Py42NotFoundError, 60
 Py42OrgNotFoundError, 60
 Py42Response (class in py42.response), 186
 Py42ResponseError, 60
 Py42SessionInitializationError, 60
 Py42StorageSessionInitializationError, 60
 Py42TooManyRequestsError, 61
 Py42TrustedActivityConflictError, 61
 Py42TrustedActivityIdNotFound, 61
 Py42TrustedActivityInvalidChangeError, 61
 Py42TrustedActivityInvalidCharacterError, 61

Py42UnableToCreateProfileError, 62
 Py42UnauthorizedError, 62
 Py42UpdateClosedCaseError, 62
 Py42UserAlreadyAddedError, 62
 Py42UserAlreadyExistsError, 62
 Py42UsernameMustBeEmailError, 63
 Py42UserNotOnListError, 63
 Py42UserRiskProfileNotFound, 63
 Py42WatchlistNotFound, 63
 Py42WatchlistOrUserNotFound, 64

Q

QueryFilter (class in *py42.sdk.queries.query_filter*), 188
 QueryFilterBooleanField (class in *py42.sdk.queries.query_filter*), 189
 QueryFilterStringField (class in *py42.sdk.queries.query_filter*), 189
 QueryFilterTimestampField (class in *py42.sdk.queries.query_filter*), 190
 quota_settings_inherited (*py42.clients.settings.org_settings.OrgSettings* attribute), 185

R

raise_py42_error() (in module *py42.exceptions*), 64
 raw_text (*py42.response.Py42Response* property), 187
 reactivate() (*py42.services.devices.DeviceService* method), 51
 reactivate() (*py42.services.orgs.OrgService* method), 183
 reactivate() (*py42.services.users.UserService* method), 198
 reactivate_matter() (*py42.services.legalhold.LegalHoldService* method), 181
 refresh_user_scim_attributes() (*py42.clients.detectionlists.DetectionListsClient* method), 44
 registration_key (*py42.clients.settings.org_settings.OrgSettings* property), 185
 RemoteActivity (class in *py42.sdk.queries.fileevents.filters.activity_filter*), 97
 RemovableMediaBusType (class in *py42.sdk.queries.fileevents.v2.filters.destination*), 115
 RemovableMediaBusType (class in *py42.sdk.queries.fileevents.v2.filters.source*), 165
 RemovableMediaCapacity (class in *py42.sdk.queries.fileevents.v2.filters.destination*), 116

RemovableMediaCapacity (class in *py42.sdk.queries.fileevents.v2.filters.source*), 166
 RemovableMediaMediaName (class in *py42.sdk.queries.fileevents.filters.exposure_filter*), 88
 RemovableMediaMediaName (class in *py42.sdk.queries.fileevents.v2.filters.destination*), 116
 RemovableMediaMediaName (class in *py42.sdk.queries.fileevents.v2.filters.source*), 167
 RemovableMediaName (class in *py42.sdk.queries.fileevents.filters.exposure_filter*), 86
 RemovableMediaName (class in *py42.sdk.queries.fileevents.v2.filters.destination*), 117
 RemovableMediaName (class in *py42.sdk.queries.fileevents.v2.filters.source*), 168
 RemovableMediaPartitionID (class in *py42.sdk.queries.fileevents.filters.exposure_filter*), 89
 RemovableMediaPartitionID (class in *py42.sdk.queries.fileevents.v2.filters.destination*), 118
 RemovableMediaPartitionID (class in *py42.sdk.queries.fileevents.v2.filters.source*), 168
 RemovableMediaSerialNumber (class in *py42.sdk.queries.fileevents.filters.exposure_filter*), 90
 RemovableMediaSerialNumber (class in *py42.sdk.queries.fileevents.v2.filters.destination*), 118
 RemovableMediaSerialNumber (class in *py42.sdk.queries.fileevents.v2.filters.source*), 169
 RemovableMediaVendor (class in *py42.sdk.queries.fileevents.filters.exposure_filter*), 87
 RemovableMediaVendor (class in *py42.sdk.queries.fileevents.v2.filters.destination*), 119
 RemovableMediaVendor (class in *py42.sdk.queries.fileevents.v2.filters.source*), 170
 RemovableMediaVolumeName (class in *py42.sdk.queries.fileevents.filters.exposure_filter*), 89
 RemovableMediaVolumeName (class in *py42.sdk.queries.fileevents.v2.filters.destination*), 120

RemovableMediaVolumeName (class in response (py42.exceptions.Py42ChecksumNotFoundError
 py42.sdk.queries.fileevents.v2.filters.source), property), 55
 170 response (py42.exceptions.Py42CloudAliasLimitExceededError
 remove() (py42.services.detectionlists.departing_employee.DepartingEmployeeService
 method), 46 response (py42.exceptions.Py42ConflictError prop-
 remove() (py42.services.detectionlists.high_risk_employee.HighRiskEmployeeService
 method), 49 response (py42.exceptions.Py42DescriptionLimitExceededError
 remove_all_users() (py42.clients.alertrules.AlertRulesClient property), 56
 method), 22 response (py42.exceptions.Py42DeviceNotConnectedError
 remove_destination() response (py42.exceptions.Py42FeatureUnavailableError
 (py42.clients.settings.device_settings.BackupSet property), 56
 method), 38 response (py42.exceptions.Py42ForbiddenError prop-
 remove_from_matter() response (py42.exceptions.Py42HTTPError property),
 (py42.services.legalhold.LegalHoldService 56
 method), 181 response (py42.exceptions.Py42InternalServerError
 remove_included_users_by_watchlist_id() property), 57
 (py42.clients.watchlists.WatchlistsClient response (py42.exceptions.Py42InvalidArchiveEncryptionKey
 method), 202 property), 57
 remove_included_users_by_watchlist_type() response (py42.exceptions.Py42InvalidArchivePassword
 (py42.clients.watchlists.WatchlistsClient property), 57
 method), 202 response (py42.exceptions.Py42InvalidCaseUserError
 remove_role() (py42.services.users.UserService property), 57
 method), 198 response (py42.exceptions.Py42InvalidEmailError
 remove_user() (py42.clients.alertrules.AlertRulesClient property), 57
 method), 22 response (py42.exceptions.Py42InvalidPageTokenError
 remove_user_cloud_alias() response (py42.exceptions.Py42InvalidPasswordError
 (py42.clients.detectionlists.DetectionListsClient property), 58
 method), 45 response (py42.exceptions.Py42InvalidRuleError prop-
 remove_user_risk_tags() response (py42.exceptions.Py42InvalidRuleOperationError
 (py42.clients.detectionlists.DetectionListsClient property), 58
 method), 45 response (py42.exceptions.Py42InvalidUsernameError
 reopen() (py42.clients.alerts.AlertsClient method), 24 property), 58
 reporting_settings_inherited response (py42.exceptions.Py42InvalidWatchlistType
 (py42.clients.settings.org_settings.OrgSettings property), 59
 attribute), 185 response (py42.exceptions.Py42LegalHoldAlreadyActiveError
 resolve() (py42.clients.alerts.AlertsClient method), 24 property), 59
 resource (py42.exceptions.Py42ActiveLegalHoldError response (py42.exceptions.Py42LegalHoldAlreadyDeactivatedError
 property), 54 property), 59
 resource_id (py42.exceptions.Py42ActiveLegalHoldError response (py42.exceptions.Py42LegalHoldCriteriaMissingError
 property), 54 property), 59
 resource_id (py42.exceptions.Py42TrustedActivityIdNotFound response (py42.exceptions.Py42LegalHoldNotFoundOrPermissionDenied
 property), 61 property), 59
 response (py42.exceptions.Py42ActiveLegalHoldError response (py42.exceptions.Py42MFARequiredError
 property), 54 property), 60
 response (py42.exceptions.Py42ArchiveFileNotFoundError response (py42.exceptions.Py42NotFoundError prop-
 property), 54 property), 60
 response (py42.exceptions.Py42BadRequestError prop- response (py42.exceptions.Py42OrgNotFoundError
 erty), 54 property), 60
 response (py42.exceptions.Py42BadRestoreRequestError response (py42.exceptions.Py42ResponseError prop-
 property), 54 erty), 60
 response (py42.exceptions.Py42CaseAlreadyHasEventError response (py42.exceptions.Py42ResponseError prop-
 property), 54 erty), 60
 response (py42.exceptions.Py42CaseNameExistsError response (py42.exceptions.Py42ResponseError prop-
 property), 55 erty), 60

response (py42.exceptions.Py42StorageSessionInitializationError in py42.sdk.queries.fileevents.filters.risk_filter),
 property), 61 102
 response (py42.exceptions.Py42TooManyRequestsError RiskIndicator.Other (class in
 property), 61 py42.sdk.queries.fileevents.filters.risk_filter),
 response (py42.exceptions.Py42TrustedActivityConflictError 102
 property), 61 RiskIndicator.SocialMediaUploads (class in
 response (py42.exceptions.Py42TrustedActivityIdNotFound py42.sdk.queries.fileevents.filters.risk_filter),
 property), 61 102
 response (py42.exceptions.Py42TrustedActivityInvalidChangeRiskIndicator.UserBehavior (class in
 property), 61 py42.sdk.queries.fileevents.filters.risk_filter),
 response (py42.exceptions.Py42TrustedActivityInvalidCharacterError 102
 property), 62 RiskScore (class in py42.sdk.queries.fileevents.filters.risk_filter),
 response (py42.exceptions.Py42UnableToCreateProfileError 104
 property), 62 RiskSeverity (class in
 response (py42.exceptions.Py42UnauthorizedError py42.sdk.queries.fileevents.filters.risk_filter),
 property), 62 103
 response (py42.exceptions.Py42UpdateClosedCaseError RiskTags (class in py42.clients.detectionlists), 47
 property), 62 RiskTags (class in py42.constants), 42
 response (py42.exceptions.Py42UserAlreadyAddedError rule_id (py42.exceptions.Py42InvalidRuleError prop-
 property), 62 erty), 58
 response (py42.exceptions.Py42UserAlreadyExistsError rule_id (py42.exceptions.Py42InvalidRuleOperationError
 property), 63 property), 58
 response (py42.exceptions.Py42UsernameMustBeEmailError RuleId (class in py42.sdk.queries.alerts.filters.alert_filter),
 property), 63 29
 response (py42.exceptions.Py42UserNotOnListError RuleName (class in py42.sdk.queries.alerts.filters.alert_filter),
 property), 63 29
 response (py42.exceptions.Py42UserRiskProfileNotFound rules (py42.clients.alerts.AlertsClient property), 24
 property), 63 RuleSource (class in py42.sdk.queries.alerts.filters.alert_filter),
 response (py42.exceptions.Py42WatchlistNotFound 30
 property), 63 RuleType (class in py42.sdk.queries.alerts.filters.alert_filter),
 response (py42.exceptions.Py42WatchlistOrUserNotFound 31
 property), 64

S

RiskIndicator (class in
 py42.sdk.queries.fileevents.filters.risk_filter),
 99
 RiskIndicator.CloudDataExposures (class in
 py42.sdk.queries.fileevents.filters.risk_filter),
 101
 RiskIndicator.CloudStorageUploads (class in
 py42.sdk.queries.fileevents.filters.risk_filter),
 101
 RiskIndicator.CodeRepositoryUploads (class in
 py42.sdk.queries.fileevents.filters.risk_filter),
 101
 RiskIndicator.EmailServiceUploads (class in
 py42.sdk.queries.fileevents.filters.risk_filter),
 101
 RiskIndicator.ExternalDevices (class in
 py42.sdk.queries.fileevents.filters.risk_filter),
 101
 RiskIndicator.FileCategories (class in
 py42.sdk.queries.fileevents.filters.risk_filter),
 102
 RiskIndicator.MessagingServiceUploads (class

savedsearches (py42.clients.securitydata.SecurityDataClient
 property), 187
 SavedSearchService (class in
 py42.services.savedsearch), 65
 Score (class in py42.sdk.queries.fileevents.v2.filters.risk),
 156
 SDKClient (class in py42.sdk), 203
 search() (py42.clients.alerts.AlertsClient method), 24
 search_all_file_events()
 (py42.clients.securitydata.SecurityDataClient
 method), 187
 search_all_pages() (py42.clients.alerts.AlertsClient
 method), 25
 search_file_events()
 (py42.clients.securitydata.SecurityDataClient
 method), 187
 search_file_events()
 (py42.services.savedsearch.SavedSearchService
 method), 66
 securitydata (py42.sdk.SDKClient property), 205

SecurityDataClient (class in **T**
 py42.clients.securitydata), 187
 serveradmin (py42.sdk.SDKClient property), 205
 set_alerts_enabled()
 (py42.services.detectionlists.departing_employee.DepartingEmployeeService
 method), 47
 set_alerts_enabled()
 (py42.services.detectionlists.high_risk_employee.HighRiskEmployeeService
 method), 49
 Severity (class in py42.sdk.queries.alerts.filters.alert_filter),
 32
 Severity (class in py42.sdk.queries.fileevents.v2.filters.risk),
 157
 SHA256 (class in py42.sdk.queries.fileevents.filters.file_filter),
 76
 SHA256 (class in py42.sdk.queries.fileevents.v2.filters.file),
 140
 Shared (class in py42.sdk.queries.fileevents.filters.cloud_filter),
 82
 SharedWith (class in py42.sdk.queries.fileevents.filters.cloud_filter),
 82
 ShareType (class in py42.sdk.queries.fileevents.v2.filters.event),
 128
 SharingTypeAdded (class in
 py42.sdk.queries.fileevents.filters.cloud_filter),
 83
 Size (class in py42.sdk.queries.fileevents.v2.filters.file),
 141
 SortDirection (class in py42.constants), 42
 Source (class in py42.sdk.queries.fileevents.filters.event_filter),
 70
 source (py42.exceptions.Py42InvalidRuleOperationError
 property), 58
 status_code (py42.response.Py42Response property),
 187
 stream_file_by_md5()
 (py42.clients.securitydata.SecurityDataClient
 method), 188
 stream_file_by_sha256()
 (py42.clients.securitydata.SecurityDataClient
 method), 188
 stream_from_backup()
 (py42.clients.archive.ArchiveClient method),
 34
 stream_to_device() (py42.clients.archive.ArchiveClient
 method), 35
 SyncDestination (class in **U**
 py42.sdk.queries.fileevents.filters.exposure_filter),
 91
 SyncDestinationUsername (class in
 py42.sdk.queries.fileevents.filters.exposure_filter),
 92

TabTitleErrors (class in
 py42.sdk.queries.fileevents.v2.filters.destination),
 121
 TabTitleErrors (class in
 py42.sdk.queries.fileevents.v2.filters.source),
 171
 TabTitles (class in py42.sdk.queries.fileevents.v2.filters.destination),
 121
 TabTitles (class in py42.sdk.queries.fileevents.v2.filters.source),
 172
 TabURL (class in py42.sdk.queries.fileevents.filters.exposure_filter),
 93
 TabUrlErrors (class in
 py42.sdk.queries.fileevents.v2.filters.destination),
 122
 TabUrlErrors (class in
 py42.sdk.queries.fileevents.v2.filters.source),
 173
 TabURLs (class in py42.sdk.queries.fileevents.v2.filters.destination),
 123
 TabURLs (class in py42.sdk.queries.fileevents.v2.filters.source),
 173
 term (py42.sdk.queries.query_filter.QueryFilter prop-
 erty), 189
 text (py42.response.Py42Response property), 187
 Timestamp (class in py42.sdk.queries.fileevents.v2.filters.timestamp),
 174
 Trusted (class in py42.sdk.queries.fileevents.v2.filters.risk),
 159
 trustedactivities (py42.sdk.SDKClient property),
 205
 TrustedActivitiesClient (class in
 py42.clients.trustedactivities), 192
 TrustedActivity (class in
 py42.sdk.queries.fileevents.filters.activity_filter),
 97
 TrustedActivityType (class in
 py42.clients.trustedactivities), 192
 TrustedActivityType (class in py42.constants), 42
 TrustReason (class in
 py42.sdk.queries.fileevents.v2.filters.risk),
 158
 Type (class in py42.sdk.queries.fileevents.v2.filters.report),
 147

uid (py42.exceptions.Py42LegalHoldNotFoundOrPermissionDeniedError
 property), 60
 unblock() (py42.services.devices.DeviceService
 method), 51
 unblock() (py42.services.orgs.OrgService method), 184
 unblock() (py42.services.users.UserService method),
 198

unlock_destination() (py42.clients.settings.device_settings.BackupSet method), 38
 update() (py42.clients.cases.CasesClient method), 41
 update() (py42.clients.trustedactivities.TrustedActivitiesClient method), 193
 update() (py42.clients.userriskprofile.UserRiskProfileClient method), 195
 update_cold_storage_purge_date() (py42.clients.archive.ArchiveClient method), 36
 update_departure_date() (py42.services.detectionlists.departing_employee.DepartingEmployeeService method), 47
 update_note() (py42.clients.alerts.AlertsClient method), 25
 update_settings() (py42.services.devices.DeviceService method), 52
 update_settings() (py42.services.orgs.OrgService method), 184
 update_state() (py42.clients.alerts.AlertsClient method), 25
 update_user() (py42.services.users.UserService method), 199
 update_user_notes() (py42.clients.detectionlists.DetectionListsClient method), 45
 upgrade() (py42.services.devices.DeviceService method), 52
 Url (class in py42.sdk.queries.fileevents.v2.filters.file), 141
 url (py42.response.Py42Response property), 187
 user (py42.exceptions.Py42InvalidCaseUserError property), 57
 user (py42.exceptions.Py42UserRiskProfileNotFound property), 63
 user_backup_quota (py42.clients.settings.org_settings.OrgSettings attribute), 186
 user_id (py42.clients.settings.device_settings.DeviceSettings property), 53
 user_id (py42.clients.settings.device_settings.IncydrDeviceSettings property), 52
 user_id (py42.exceptions.Py42UserAlreadyAddedError property), 62
 user_id (py42.exceptions.Py42UserNotOnListError property), 63
 user_id (py42.exceptions.Py42WatchlistOrUserNotFound property), 64
 UserContext (class in py42.usercontext), 199
 usercontext (py42.sdk.SDKClient property), 205
 UserEmail (class in py42.sdk.queries.fileevents.v2.filters.destination), 124
 username (py42.exceptions.Py42UnableToCreateProfileError property), 62
 userriskprofile (py42.sdk.SDKClient property), 205
 UserRiskProfileClient (class in py42.clients.userriskprofile), 193
 users (py42.sdk.SDKClient property), 205
 UserService (class in py42.services.users), 196
V
 value (py42.exceptions.Py42TrustedActivityConflictError property), 61
 value (py42.sdk.queries.query_filter.QueryFilter property), 189
 version (py42.clients.settings.device_settings.DeviceSettings property), 36
 version (py42.clients.settings.device_settings.IncydrDeviceSettings property), 52
W
 warning_alert_days (py42.clients.settings.device_settings.DeviceSettings attribute), 53
 warning_alert_days (py42.clients.settings.device_settings.DeviceSettings attribute), 186
 warning_email_enabled (py42.clients.settings.device_settings.DeviceSettings attribute), 53
 warning_email_enabled (py42.clients.settings.device_settings.DeviceSettingsDefaults attribute), 186
 watchlist_id (py42.exceptions.Py42WatchlistNotFound property), 63
 watchlist_id (py42.exceptions.Py42WatchlistOrUserNotFound property), 64
 watchlist_type (py42.exceptions.Py42InvalidWatchlistType property), 59
 watchlists (py42.sdk.SDKClient property), 205
 WatchlistsClient (class in py42.clients.watchlists), 200
 WatchlistType (class in py42.clients.watchlists), 200
 WatchlistType (class in py42.constants), 43
 web_restore_admin_limit (py42.clients.settings.org_settings.OrgSettings attribute), 186
 web_restore_enabled (py42.clients.settings.org_settings.OrgSettings attribute), 186
 web_restore_user_limit (py42.clients.settings.org_settings.OrgSettings attribute), 186
 WindowTitle (class in py42.sdk.queries.fileevents.filters.exposure_filter), 93
 with_traceback() (py42.exceptions.Py42ActiveLegalHoldError method), 54
 with_traceback() (py42.exceptions.Py42ArchiveFileNotFoundError method), 54

`with_traceback()` (`py42.exceptions.Py42BadRequestError` with `with_traceback()` (`py42.exceptions.Py42LegalHoldCriteriaMissingError`
`method`), 54 `method`), 59
`with_traceback()` (`py42.exceptions.Py42BadRestoreRequestError` with `with_traceback()` (`py42.exceptions.Py42LegalHoldNotFoundOrPermissionsError`
`method`), 54 `method`), 60
`with_traceback()` (`py42.exceptions.Py42CaseAlreadyHasEvidenceError` with `with_traceback()` (`py42.exceptions.Py42MFARequiredError`
`method`), 55 `method`), 60
`with_traceback()` (`py42.exceptions.Py42CaseNameExistsError` with `with_traceback()` (`py42.exceptions.Py42NotFoundError`
`method`), 55 `method`), 60
`with_traceback()` (`py42.exceptions.Py42ChecksumNotFound` with `with_traceback()` (`py42.exceptions.Py42OrgNotFoundError`
`method`), 55 `method`), 60
`with_traceback()` (`py42.exceptions.Py42CloudAliasChannelLimitError` with `with_traceback()` (`py42.exceptions.Py42ResponseError`
`method`), 55 `method`), 60
`with_traceback()` (`py42.exceptions.Py42CloudAliasLimitExceededError` with `with_traceback()` (`py42.exceptions.Py42SessionInitializationError`
`method`), 55 `method`), 60
`with_traceback()` (`py42.exceptions.Py42ConflictError` with `with_traceback()` (`py42.exceptions.Py42StorageSessionInitializationError`
`method`), 55 `method`), 61
`with_traceback()` (`py42.exceptions.Py42DescriptionLimitExceededError` with `with_traceback()` (`py42.exceptions.Py42TooManyRequestsError`
`method`), 56 `method`), 61
`with_traceback()` (`py42.exceptions.Py42DeviceNotConnectedError` with `with_traceback()` (`py42.exceptions.Py42TrustedActivityConflictError`
`method`), 56 `method`), 61
`with_traceback()` (`py42.exceptions.Py42Error` with `with_traceback()` (`py42.exceptions.Py42TrustedActivityIdNotFound`
`method`), 56 `method`), 61
`with_traceback()` (`py42.exceptions.Py42FeatureUnavailableError` with `with_traceback()` (`py42.exceptions.Py42TrustedActivityInvalidChangeEvent`
`method`), 56 `method`), 61
`with_traceback()` (`py42.exceptions.Py42ForbiddenError` with `with_traceback()` (`py42.exceptions.Py42TrustedActivityInvalidCharacter`
`method`), 56 `method`), 62
`with_traceback()` (`py42.exceptions.Py42HTTPError` with `with_traceback()` (`py42.exceptions.Py42UnableToCreateProfileError`
`method`), 56 `method`), 62
`with_traceback()` (`py42.exceptions.Py42InternalServerError` with `with_traceback()` (`py42.exceptions.Py42UnauthorizedError`
`method`), 57 `method`), 62
`with_traceback()` (`py42.exceptions.Py42InvalidArchiveEvent` with `with_traceback()` (`py42.exceptions.Py42UpdateClosedCaseError`
`method`), 57 `method`), 62
`with_traceback()` (`py42.exceptions.Py42InvalidArchivePairingError` with `with_traceback()` (`py42.exceptions.Py42UserAlreadyAddedError`
`method`), 57 `method`), 62
`with_traceback()` (`py42.exceptions.Py42InvalidCaseUser` with `with_traceback()` (`py42.exceptions.Py42UserAlreadyExistsError`
`method`), 57 `method`), 63
`with_traceback()` (`py42.exceptions.Py42InvalidEmailError` with `with_traceback()` (`py42.exceptions.Py42UsernameMustBeEmailError`
`method`), 57 `method`), 63
`with_traceback()` (`py42.exceptions.Py42InvalidPageTokenError` with `with_traceback()` (`py42.exceptions.Py42UserNotOnListError`
`method`), 58 `method`), 63
`with_traceback()` (`py42.exceptions.Py42InvalidPasswordError` with `with_traceback()` (`py42.exceptions.Py42UserRiskProfileNotFound`
`method`), 58 `method`), 63
`with_traceback()` (`py42.exceptions.Py42InvalidRuleError` with `with_traceback()` (`py42.exceptions.Py42WatchlistNotFound`
`method`), 58 `method`), 63
`with_traceback()` (`py42.exceptions.Py42InvalidRuleOperationError` with `with_traceback()` (`py42.exceptions.Py42WatchlistOrUserNotFound`
`method`), 58 `method`), 64
`with_traceback()` (`py42.exceptions.Py42InvalidUsernameError` with `within_the_last()` (`py42.sdk.queries.fileevents.filters.event_filter.EventFilter`
`method`), 58 `class method`), 68
`with_traceback()` (`py42.exceptions.Py42InvalidWatchlistType` with `within_the_last()` (`py42.sdk.queries.fileevents.filters.event_filter.InsertionFilter`
`method`), 59 `class method`), 70
`with_traceback()` (`py42.exceptions.Py42LegalHoldAlreadyExistsError` with `within_the_last()` (`py42.sdk.queries.fileevents.v2.filters.event.InsertedEventFilter`
`method`), 59 `class method`), 127
`with_traceback()` (`py42.exceptions.Py42LegalHoldAlreadyExistsError` with `within_the_last()` (`py42.sdk.queries.fileevents.v2.filters.file.CreatedFileFilter`
`method`), 59 `class method`), 133

`within_the_last()` (*py42.sdk.queries.fileevents.v2.filters.file.Modified*
class method), [138](#)

`within_the_last()` (*py42.sdk.queries.fileevents.v2.filters.file.Size*
class method), [141](#)

`within_the_last()` (*py42.sdk.queries.fileevents.v2.filters.timestamp.Timestamp*
class method), [175](#)