
py42

Release py42 v1.25.1

Code42 Software

Sep 07, 2022

CONTENTS

1	User Guides	1
1.1	Getting started with py42	1
1.2	py42 Basics	3
1.3	Executing Searches	6
1.4	Departing Employees	9
1.5	High Risk Employees	9
1.6	Get Active Devices From an Organization	10
1.7	View or Modify device settings	11
1.8	View or Modify organization settings	13
1.9	Configuring Backup Sets	14
1.10	Cases	15
1.11	Trust Settings	16
1.12	V2 File Events	17
1.13	User Risk Profile	18
1.14	Watchlists	19
2	Method Documentation	21
2.1	Alert Rules	21
2.2	Alerts	23
2.3	Archive	33
2.4	Audit Logs	36
2.5	Backup Sets	38
2.6	Cases	39
2.7	Shared Constants	42
2.8	Detection Lists	44
2.9	Devices	49
2.10	Device Settings	52
2.11	Exceptions	54
2.12	File Event Queries - V1 (DEPRECATED)	64
2.13	File Event Queries - V2	105
2.14	Legal Hold	178
2.15	Orgs	182
2.16	Org Settings	184
2.17	Response	186
2.18	Security Data	187
2.19	Shared Query Filters	188
2.20	Trusted Activities	192
2.21	User Risk Profiles	193
2.22	Users	196
2.23	Util	199

2.24 Watchlists	200
3 Features	207
4 Content	209
Python Module Index	211
Index	213

USER GUIDES

1.1 Getting started with py42

- *Licensing*
- *Installation*
- *Authentication*
- *Troubleshooting and Support*

1.1.1 Licensing

This project uses the [MIT License](#).

1.1.2 Installation

You can install py42 from PyPI, from source, or from distribution.

From PyPI

The easiest and most common way is to use pip:

```
pip install py42
```

To install a previous version of py42 via pip, add the version number. For example, to install version 0.4.1, you would enter:

```
pip install py42==0.4.1
```

Visit the [project history](#) on PyPI to see all published versions.

From source

Alternatively, you can install py42 directly from [source code](#):

```
git clone https://github.com/code42/py42.git
```

When it finishes downloading, from the root project directory, run:

```
python setup.py install
```

From distribution

If you want create a .tar ball for installing elsewhere, run this command from the project's root directory:

```
python setup.py sdist
```

After it finishes building, the .tar ball will be located in the newly created dist directory. To install it, enter:

```
pip install py42-[VERSION].tar.gz
```

1.1.3 Authentication

Important: py42 currently only supports token-based authentication.

To initialize the `py42.sdk.SDKClient`, you must provide your credentials (basic authentication). If you are writing a script, we recommend using a secure password storage library, such as `keyring`, for retrieving passwords. However, subsequent requests use JWT authentication.

If your account uses [two-factor authentication](#), include the time-based one-time password (TOTP) when you initialize the `py42.sdk.SDKClient`. You can also provide a callable object that returns a TOTP. If you pass a callable, it will be called whenever a new TOTP is required to renew the authentication token.

1.1.4 Troubleshooting and support

Debug mode

Debug mode may be useful if you are trying to determine if you are experiencing permissions issues. When debug mode is on, py42 logs HTTP request data to the console's stderr. Use the following as a guide for how to turn on debug mode in py42:

```
import py42.sdk
import py42.settings
import logging

py42.settings.debug.level = logging.DEBUG
```

To provide your own logger, just replace `py42.settings.debug.logger`:

```
custom_logger = logging.getLogger("my_app")
handler = logging.FileHandler("my_app.log")
custom_logger.addHandler(handler)

py42.settings.debug.logger = custom_logger
```

File an issue on GitHub

If you are experiencing an issue with py42, you can create a *New issue* at the project repository. See the [Github guide on creating an issue](#) for more information.

Contact Code42 Support

If you don't have a GitHub account and are experiencing issues, contact [Code42 support](#).

1.1.5 What's next?

Learn the basics by following the py42 [Basics guide](#).

1.2 py42 Basics

This guide explains the basic concepts of py42. Learning these basics can help you gain confidence in writing your own scripts.

- *py42 Basics*
 - *Initialization*
 - *Paging*
 - *Py42Response*
 - *Dates*
 - *Exceptions*

The examples from this guide are intended as blanket concepts that apply to other areas in py42. For example, paging over users and devices works the same way as over departing employees and alerts.

1.2.1 Initialization

To use py42, you must initialize the SDK:

```
import py42.sdk

sdk = py42.sdk.from_local_account("https://console.us.code42.com", "my_username", "my_
˓password")
```

If your account uses two-factor authentication, include the time-based one-time password:

```
 sdk = py42.sdk.from_local_account("https://console.us.code42.com", "my_username", "my_
˓password", totp="123456")
```

Alternatively, define a function that returns the time-based one-time password:

```
def promptForPassword():
    return input("Please input your authentication code: ")

sdk = py42.sdk.from_local_account("https://console.us.code42.com", "my_username", "my_
˓password", totp=promptForPassword)
```

Alternatively, define a function that returns the auth token based on user's authentication approach

```
import json
import requests
from requests.auth import HTTPBasicAuth
def jwt_provider():
    res = requests.get(
        'https://console.us.code42.com/api/v3/auth/jwt?useBody=true',
        auth=HTTPBasicAuth('username', 'password')
    )
    res_json = json.loads(res.text)
    return res_json['data']['v3_user_token']

sdk_client = py42.sdk.from_jwt_provider("https://console.us.code42.com", jwt_provider)
```

1.2.2 Paging

py42 clients often have a method with the name (or name prefix) `get_all` which handles iterating over pages of response items. Here are some examples:

- `py42.sdk.devices.get_all()`
- `py42.sdk.users.get_all()`
- `py42.sdk.legalhold.get_all_matters()`
- `py42.sdk.orgs.get_all()`

These methods each return a [python generator](#). Looping over the pages returned by the generator gives you access to the actual list of items. Use the code snippet below as an example for working with generators and paging in py42:

```
# Prints the username and notes for all departing employees

pages = sdk.detectionlists.departing_employee.get_all()  # pages has 'generator' type
for page in pages:  # page has 'Py42Response' type
    employees = page["items"]
    for employee in employees:
        username = employee["user_name"]
        notes = employee["notes"]
        print(f"{employee}: {notes}")
```

Each page is a typical py42 response. The next section covers what you can do with Py42Response objects.

1.2.3 Py42Response

py42 clients return Py42Response objects which are intentionally similar to `requests.Response` objects. The `Py42Response` class hides unneeded metadata found on the raw `requests.Response.text` (which is available as `Py42Response.raw_text`), making it easier to get the most useful parts of the response. Also, the object is subscriptable, meaning you can access it with keys or indices (depending on the JSON type underneath data on Code42 API responses):

```
user = response["users"][0]
item = list_response[0]["itemProperty"]
```

To see all the keys on a response, observe its `.text` attribute. By printing the response, you essentially print its `text` property:

```
# Prints details about the response from a getting a detection list user.

response = sdk.detectionlists.get_user("test.user@example.com")
print(response) # JSON as Dictionary - same as print(response.text)
print(response.raw_text) # Raw API response
print(response.status_code) # 200
cloud_usernames = response["cloudUsernames"]
# if the response might not contain the property you're looking for,
# check to see if it exists with data.get
cloud_usernames = response.data.get("cloudUsernames")
if cloud_usernames:
    print(cloud_usernames)
```

1.2.4 Dates

Most dates in py42 support `POSIX timestamps` for date parameters. As an example, see `:class:sdk.queries.fileevents.filters.event_filter.EventTimestamp` which is used for querying file events by their event timestamp.

```
from datetime import datetime, timedelta

import py42.sdk
import py42.util
from py42.sdk.queries.fileevents.file_event_query import FileEventQuery
from py42.sdk.queries.filters.event_filter import EventTimestamp

sdk = py42.sdk.from_local_account("https://console.us.code42.com", "my_username", "my_
˓password")

# Get the epoch date 14 days in the past
query_date = datetime.utcnow() - timedelta(days=14)
query_epoch = (query_date - datetime.utcfromtimestamp(0)).total_seconds()

query = FileEventQuery(EventTimestamp.on_or_after(query_epoch))

response = sdk.securitydata.search_file_events(query)

# Print all the md5 Checksums from every file event within the past 14 days.
```

(continues on next page)

(continued from previous page)

```
file_events = response["fileEvents"]
for event in file_events:
    print(event["md5Checksum"])
```

1.2.5 Exceptions

py42 throws some of its own exceptions when failures occur. py42 exceptions are found in the `py42.sdk.exceptions` module. Some of the available exceptions are:

- `Py42ForbiddenError`: (403) With your currently signed-in account, you don't have the necessary permissions to perform the action you were trying to do.
- `Py42UnauthorizedError`: (401) The username or password is incorrect.
- `Py42InternalServerError`: (500) Likely an unhandled issue on our servers.

For example, you are making a `create_sdk()` function and want to print a more user-friendly message when the provided username or password are incorrect:

```
import keyring
import py42.sdk
from py42.exceptions import Py42UnauthorizedError

def create_sdk(username):
    """Tries to initialize SDK. If unauthorized, prints message and exits."""
    try:
        password = keyring.get_password("my_program", username)
        return py42.sdk.from_local_account("www.authority.example.com", username, password)
    except Py42UnauthorizedError:
        print("Invalid username or password.")
        exit(1)
```

1.3 Executing Searches

py42 features a powerful, flexible query system for quickly and easily searching file events and alerts. This guide explains the syntax for building queries and executing searches.

1.3.1 Search File Events

To query for V2 file events, import the required modules and classes and create the SDK:

```
import py42.sdk
from py42.sdk.queries.fileevents.v2 import *
sdk = py42.sdk.from_local_account("https://console.us.code42.com", "my_username", "my_password")
```

V1 events are **DEPRECATED**. If you need to build V1 queries, the corresponding V1 modules can be imported in a similar manner.

```
from py42.sdk.queries.fileevents.v1 import *
```

For more details on updating to V2 file events, see the [V2 File Events Guide](#)

You must create `query_filter.FilterGroup` objects to conduct searches. Filter groups have a type (in the form of a class), such as `email.Sender`, and an operator (in the form of a function), such as `is_in()`. Some example filter groups look like this:

```
from py42.sdk.queries.fileevents.v2 import *
source_email_filter = source.EmailSender.is_in(["test.user@example.com", "test.
˓→sender@example.com"])
event_action_filter = event.Action.exists()
destination_ip_filter = destination.PrivateIpAddress.eq("127.0.0.1")
```

It is also possible to create `query_filter.FilterGroups` from raw JSON. For example:

```
raw_json = """>{"filterClause": "AND", "filters": [{"display": null, "value": "P1D", "operator": "
˓→WITHIN_THE_LAST", "term": "eventTimestamp"}]}"""
json_dict = json.loads(raw_json)
filter_group = FilterGroup.from_dict(json_dict)
```

Important: The filter terms and query objects for file events have changed for V2. Make sure you're using the appropriate modules to construct your queries.

There are two operators when building `file_event_query.FileEventQuery` objects: `any()` and `all()`.

`any()` gets results where at least one of the filters is true and `all()` gets results where all of the filters are true.

```
any_query = FileEventQuery.any(source_email_filter, event_action_filter)
all_query = FileEventQuery.all(event_action_filter, destination_ip_filter)
```

For convenience, the `FileEventQuery` constructor works the same way as `all()`:

```
all_query = FileEventQuery(event_action_filter, destination_ip_filter)
```

You can put filters in an iterable and unpack them (using the `*` operator) in a `FileEventQuery`. This is a common use case for programs that need to conditionally build up filters:

```
# Conditionally appends filters to a list for crafting a query

filter_list = []
if need_trusted:
    filter_list.append(risk.Trusted.is_true())
elif need_user_emails:
    user_email_filter = user.Email.is_in(["foo@example.com", "baz@example.com"])
    filter_list.append(user_email_filter)
# Notice the use of the '*' operator to unpack filter_list
query = FileEventQuery(*filter_list)
```

To execute the search, use `securitydata.SecurityModule.search_file_events()`:

```
# Prints the MD5 hashes of all the events where files were read by browser or other app.
```

(continues on next page)

(continued from previous page)

```
query = FileEventQuery(event.Action.eq(event.Action.APPLICATION_READ))
response = sdk.securitydata.search_file_events(query)
file_events = response["fileEvents"]
for event in file_events:
    print(event["file"]["hash"]["md5"])
```

If the number of events exceeds 10,000 against a query, use `securitydata.SecurityModule.search_all_file_events()`:

```
query = FileEventQuery(event.Action.eq(event.Action.APPLICATION_READ))
response = sdk.securitydata.search_all_file_events(query)
file_events = response["fileEvents"]
for event in file_events:
    print(event["file"]["hash"]["md5"])
while response["nextPgToken"] is not None:
    response = sdk.securitydata.search_all_file_events(query, page_token=response[
    "nextPgToken"])
    file_events = response["fileEvents"]
    for event in file_events:
        print(event["file"]["hash"]["md5"])
```

1.3.2 Search Alerts

Alert searches work in a very similar way to file event searches.

To start, import the filters and query object:

```
from py42.sdk.queries.alerts.filters import *
from py42.sdk.queries.alert_query import AlertQuery

# Create a query for getting all open alerts with severity either 'High' or 'Medium'.

filters = [AlertState.eq(AlertState.OPEN), Severity.is_in([Severity.HIGH, Severity.
    ↪MEDIUM])]
query = AlertQuery(*filters)
```

To execute the search, use the `alerts.AlertClient.search()` method:

```
# Prints the actor property from each search result
response = sdk.alerts.search(query)
alerts = response["alerts"]
for alert in alerts:
    print(alert["actor"])
```

1.4 Departing Employees

1.4.1 Add or Remove Users From the Departing Employees List

Use py42 to quickly and easily manage users on the Departing Employees list. This guide describes how to add users to and remove users from the Departing Employees list.

To add a user to the Departing Employees list, all you need to know is the user's Code42 user UID.

To get the user UID based on username:

```
user = sdk.users.get_by_username("username")
uid = user["users"][0]["userUid"]
```

user_id below refers to the user UID.

```
from py42.exceptions import Py42UserAlreadyAddedError

# Add the departing employee
try:
    response = sdk.detectionlists.departing_employee.add(user_id, departure_date)
except Py42UserAlreadyAddedError:
    print("The user is already on the Departing Employee list.")
```

Important: If the user is already in the Departing Employees list, you will get an `py42.exceptions.Py42UserAlreadyAddedError`.

To remove a user from the Departing Employees list:

```
sdk.detectionlists.departing_employee.remove(user_id)
```

For complete details, see *Departing Employee*.

1.5 High Risk Employees

1.5.1 Add or Remove Users From the High Risk Employee List

Use py42 to quickly and easily manage users on the High Risk Employee list. This guide describes how to add users to and remove users from the High Risk Employee list.

To add a user to the High Risk Employees list, all you need to know is the user's Code42 user UID.

To get the user UID based on username:

```
user = sdk.users.get_by_username("username")
uid = user["users"][0]["userUid"]
```

user_id below refers to the user UID.

```
# Add the high risk employee
response = sdk.detectionlists.high_risk_employee.add(user_id)
```

Important: If the user is already in the High Risk Employee list, you will get a `py42.exceptions.Py42UserAlreadyAddedError`.

To remove a user from the High Risk Employee list:

```
sdk.detectionlists.high_risk_employee.remove(user_id)
```

1.5.2 Add or Remove Risk Factors From Users

You can add/remove risk factor tags from a high risk user programmatically using the `add_user_risk_tags()` and `remove_user_risk_tags()` methods in the `detectionlists` module. Both methods take the `user_id` of a high risk employee, and a list of tags that you want to add/remove:

```
from py42.constants import RiskTags

tag_list = [RiskTags.CONTRACT_EMPLOYEE, RiskTags.ELEVATED_ACCESS_PRIVILEGES]

# Add the risk tags
response = sdk.detectionlists.add_user_risk_tags(user_id, tag_list)

# Remove the risk tags
response = sdk.detectionlists.remove_user_risk_tags(user_id, tag_list)
```

Constants for Risk tags are available at [Risk Tags](#)

For complete details, see [High Risk Employee](#).

1.6 Get Active Devices From an Organization

Using py42, you can retrieve information about the active devices in your organization for various use cases. For example, you might want to create a simple report that illustrates how many devices are running each operating system in your Code42 environment. Your user role determines which devices you have access to.

To begin, initialize the SDK:

```
import py42.sdk
sdk = py42.sdk.from_local_account("https://console.us.code42.com", "my_username", "my_
˓→password")
```

1.6.1 The DeviceClient.get_all() Function

Next, use `py42.sdk.clients.devices.DeviceClient` to search for active devices in your organization. Use the `active` parameter on the `get_all()` method.

The `active` parameter has three different states:

- If `active` is set to `True`, you will only get active devices.
- If `active` is set to `False`, you will only get deactivated devices.
- If you don't use `active`, you will get all devices.

The `get_all()` function returns a generator of pages of devices. The devices returned by `get_all()` are based on the role and permissions of the user authenticating the SDK.

1.6.2 Examples

Here is an example using `get_all()` to get all active devices in your organization(s):

```
# For each active device in your organization, print its GUID and operating system

response = sdk.devices.get_all(active=True)
for page in response:
    devices = page["computers"]
    for device in devices:
        print(f"{device['guid']} - {device['osName']}")
```

As another example, you might have the Cross Org Administrator role and want to get all the active devices for just one of your organizations. First use `orgs.get_all()` to return a list of all current organizations and find the UID of the desired organization. Then use the organization's UID to get information on its devices.

```
# For each active device in the engineering organization, print its GUID and operating system.

# Assume there is only one org named "Engineering"
for page in sdk.orgs.get_all():
    for org in page["orgs"]:
        if org["orgName"] == "Engineering":
            engineering_org_uid = org["orgUid"]
            break

response = sdk.devices.get_all(active=True, org_uid=engineering_org_uid)
for page in response:
    devices = page["computers"]
    for device in devices:
        print(f"{device['guid']} - {device['osName']}")
```

We got the org UID from the engineering organization and then passed it as a parameter to the method to get all the devices, thus getting all the active devices in the engineering organization.

1.7 View or Modify device settings

Use py42 to easily view and update the settings for devices with the `DeviceSettings` and `IncydrDeviceSettings` objects for Crashplan and Incydr customers, respectively.

The `Device Settings` objects are wrappers around the complex nested dict that the Code42 Computer API endpoint expects, providing helper properties that can be used to get/set values, without having to know the underlying nested structure.

To get started, create a `DeviceSettings` or `IncydrDeviceSettings` object for a given device guid. The `get_settings()` method will create the appropriate object automatically based on the corresponding service running on the device:

```
device_settings = sdk.devices.get_settings(908765043021)
```

Details on which settings can be updated and which are non-modifiable can be found in the method documentation [Device Settings](#). These may differ between services. Some common non-modifiable settings fields are accessible as read-only properties on the object:

```
>>> device_settings.computer_id  
12345  
>>> device_settings.guid  
908765043021  
>>> device_settings.org_id  
42  
>>> device_settings.user_id  
494842  
>>> device_settings.version  
1525200006800
```

And to change settings, in most cases you can just assign new values to the corresponding attribute:

```
>>> device_settings.notes  
"A note on this device."  
>>> device_settings.notes = "A note on this device."
```

The below section provides more detail on managing backup settings for Crashplan customers.

For convenience and logging purposes, all changes are tracked in the .changes property of the DeviceSettings objects.

```
>>> device_settings.changes  
{'destinations': {"43": 'PROe Cloud, US <LOCKED>', '632540230984925185': 'PROe Cloud, US - West'}}}
```

Once you've made all the desired changes to a DeviceSettings object, you can post the changes by passing it to the sdk.devices.update_settings method, which returns a Py42Response object with the server response:

```
>>> sdk.devices.update_settings(device_settings)  
<Py42Response [status=200, data={'active': True, 'address': '192.168.74.144:4247',  
'alertState': 0, 'alertStates': ['OK'], ...}]>
```

1.7.1 Crashplan

Backup settings

The available backup destinations for a device can be found on the read-only availableDestinations property:

```
>>> device_settings.available_destinations  
{'632540230984925185': 'PROe Cloud, US - West', '43': 'PROe Cloud, US'}
```

Because device backup settings are tied to a given “Backup Set”, of which there could be more than one, the DeviceSettings.backup_sets property returns a list of BackupSet wrapper classes that help manage backup configuration settings.

```
>>> device_settings.backup_sets  
[<BackupSet: id: 1, name: 'Primary - Backup Set'>, <BackupSet: id: 298010138, name:  
'Secondary (large files) - Backup Set'>]
```

See the [Configuring Backup Sets](#) guide for details on managing backup set settings.

Advanced usage

Because `DeviceSettings` is a subclass of `UserDict` with added attributes/methods to help easily access/modify setting values, the underlying dict that ultimately gets posted to the server is stored on the `.data` attribute of `DeviceSettings` instances, and a `DeviceSettings` object otherwise behaves like a normal dict.

If there is a setting that is not yet implemented by py42 as a helper method/attribute, those values can be manually managed by treating the `DeviceSettings` object as a normal dict.

For example, setting the “backup status email frequency” value to only send every 10 days, via the helper attribute:

```
>>> device_settings.backup_status_email_frequency_days = 10
```

And doing the same thing by setting the value manually on the underlying dict:

```
>>> device_settings["settings"]["serviceBackupConfig"]["backupStatusEmailFreqInMinutes"]  
=> "14400"
```

The benefits of the py42 helper attributes/methods is that the values mimic what the Console UI uses (in this case days vs the minutes expected by the API endpoint), so you don’t have to worry about doing conversions yourself. But since the underlying dict is accessible, you aren’t constrained to only what py42 has so far implemented.

Warning: When manually changing values on the underlying dict, those aren’t registered in the `.changes` property and thus won’t be captured in debug logs by the `sdk.devices.update_settings()` method.

1.8 View or Modify organization settings

Use py42 to easily view and update the settings for organizations with the `OrgSettings` object.

The `OrgSettings` object is a wrapper around the complex dicts that the Code42 Org and OrgSettings API endpoints expect, providing helper properties that can be used to get/set values, without having to know the underlying complexity of the APIs.

To get started, create a `OrgSettings` object for a given `org_id`:

```
org_settings = sdk.orgs.get_settings(org_id)
```

Some common non-modifiable details about the org are accessible as read-only properties:

```
>>> org_settings.org_id  
424345  
>>> org_settings.registration_key  
'XXXX-YYYY-AAAA-BBBB'
```

And to change settings, in most cases you can just assign new values to the appropriate attribute:

```
>>> org_settings.name  
'Admin Test Org'  
>>> org_settings.name = "Admin Production Org"
```

Configuring device backup defaults for an org is very similar to [configuring backup settings for an individual device](#), the OrgSetting object has a .device_defaults property that contains a DeviceSettingsDefaults object providing convenience attributes/methods for configuring defaults for all devices in the org.

```
>>> org_settings.device_defaults.backup_status_email_enabled  
True  
>>> org_settings.device_defaults.warning_alert_days  
7  
>>> org_settings.device_defaults.warning_alert_days = 14
```

Backup set configurations are contained in the .device_defaults.backup_sets property, and return a list of BackupSet wrapper classes for each set configured for the org:

```
>>> org_setting.device_defaults.backup_sets  
[<BackupSet: id: 1, name: 'Production Environment - Backup Set'>]
```

See the [Configuring Backup Sets](#) guide for details on managing backup set settings.

Once you've made all the desired changes to an OrgSettings object, you can post the changes by passing it to the sdk.orgs.update_settings() method.

Because there are two endpoints that manage different organization settings values (/api/Org and /api/OrgSettings), the sdk.orgs.update_settings() method might make up to two requests to the server, depending on what OrgSetting values were actually modified. Because of the potential for two response values, orgs.update_settings() returns a OrgSettingsResponse namedtuple with the responses from both endpoints (if applicable), along with an error flag that indicates if any errors occurred. If an error occurred, the org_response or org_settings_response attributes will contain the Py42Exception that was raised instead of the Py42Response.

```
>>> sdk.orgs.update_settings(org_settings)  
OrgSettingsResponse(error=False, org_response=<Py42Response [status=200, data={'active':  
    ↪ True, 'blocked': False, 'classification': 'BASIC', 'configInheritanceCounts': {}, ...}  
    ↪ >, org_settings_response=None)
```

1.9 Configuring Backup Sets

Code42 devices' backup configurations are managed by "Backup Sets", which can be configured either at the individual device level, or set as default configurations at the org level.

The py42 BackupSet class can be used to view and change the settings of a given backup set.

BackupSet instances are automatically constructed by py42 and attached to their corresponding DeviceSettings or OrgSettings objects, and stored in the .backup_sets properties (DeviceSettings.backup_sets or OrgSettings.device_defaults.backup_sets).

The following examples will use an individual device's backup set, but all the methods/attributes are the same when configuring an org device default backup set.

Create a DeviceSettings object and get the primary backup set object:

```
>>> device_settings  
>>> device_settings.backup_sets  
[<BackupSet: id: 1, name: 'Primary - Backup Set'>, <BackupSet: id: 298010138, name:  
    ↪ 'Secondary (large files) - Backup Set'>]  
>>> bs = device_settings.backup_sets[0]
```

View/update destinations:

```
>>> bs.destinations
{'43': 'PROe Cloud, US <LOCKED>'}
>>>
>>> bs.add_destination(587738803578339329)
>>> bs.remove_destination(43)
>>> bs.destinations
{'632540230984925185': 'PROe Cloud, US - West'}
```

View/update backup file selection/exclusion lists:

```
>>> bs.included_files
['C:/Users/Bob/']
>>> bs.excluded_files
[]
>>>
>>> bs.included_files.append("D:/")
>>> bs.excluded_files.append("C:/Users/Bob/Downloads")
```

You can also replace the existing list with a new one:

```
>>> bs.included_files = ["C:/Users/", "D:/"]
```

View/update filename exclusion patterns:

```
>>> bs.filename_exclusions
['.*/Photos/']
>>> bs.filename_exclusions.append(".*/Pictures/")
```

1.10 Cases

Use py42 to quickly and easily manage cases.

1.10.1 Create, View, or Modify Cases

To get started, create a new case.

```
case = sdk.cases.create("new-case")
```

Once you've created a case, or if you're working with an existing one, you can use the case's `number` to view details about that case.

```
# view details about a case
case = sdk.cases.get(case_number)
```

You can also access a case by its `number` to update its details. For example, to update a case's status to CLOSED:

```
from py42.constants import CaseStatus

response = sdk.cases.update(case_number, status=CaseStatus.CLOSED)
```

Case statuses can be set to either OPEN or CLOSED. Constants for these statuses are available at [Case Status](#).

1.10.2 View Details for all OPEN Cases

This section describes how to view the details of all cases with an OPEN status.

```
from py42.constants import CaseStatus

response = sdk.cases.get_all(status=CaseStatus.OPEN)

for page in response:
    cases = page["cases"]
    for case in cases:
        print(case)
```

For complete details, see [Cases](#).

1.11 Trust Settings

Use py42 to quickly and easily manage trusted activities and resources, including domains and Slack workspaces.

1.11.1 Create, View, or Modify Trusted Activities

To get started, create a new trusted activity resource.

```
from py42.constants import TrustedActivityType

response = sdk.trustedactivities.create(TrustedActivityType.DOMAIN, "test-domain.com")
```

Constants for each type of trusted activity are available at [Trusted Activity Type](#)

Once you've created a trusted activity, or if you're working with an existing one, you can use the trusted activity's resourceId to view details about it.

```
response = sdk.trustedactivities.get(resource_id)
```

You can also access a trusted activity by its resourceId to update its details. For example, to add a description to a trusted activity:

```
response = sdk.trustedactivities.update(resource_id, description="This is a trusted_
activity.")
```

To clear the description of a trusted activity, pass an empty string `description=""` to the `update()` method.

Important: If you try to create with the same value as an already existing activity, you will get a `py42.exceptions.Py42TrustedActivityConflictError`.

1.11.2 View Details for all Trusted Domains

This section describes how to view the details of all trusted activities of the type DOMAIN.

```
from py42.constants import TrustedActivityType

response = sdk.trustedactivities.get_all(type=TrustedActivityType.DOMAIN)

for page in response:
    resources = page["trustResources"]
    for resource in resources:
        print(resource)
```

For complete details, see *Trusted Activities*.

1.12 V2 File Events

Warning: V1 file events, saved searches, and queries are **deprecated**.

For details on the updated File Event Model, see the V2 File Events API documentation on the [Developer Portal](#).

1.12.1 Querying file events

To query for V2 file events, import the V2 filter modules and `FileEventQuery` class with:

```
from py42.sdk.queries.fileevents.v2 import *
```

Using the `FileEventQuery` and filter classes, construct a query and search for file events as detailed in the [Executing Searches Guide](#).

1.12.2 Saved Searches

All saved search methods functions have an additional optional `use_v2=False` argument. If set to True, the saved search module will ingest from the V2 saved search APIs. The `use_v2` argument defaults to False and the V1 saved searches are still available.

For example, use the following to view all saved searches with the new V2 apis:

```
import py42.sdk

sdk = py42.sdk.from_local_account("https://console.us.code42.com", "my_username", "my_
˓→password")
sdk.securitydata.savedsearches.get(use_v2=True)
```

Retrieving saved searches with V2 settings enabled will retrieve existing V1 saved search queries translated to the V2 model. Existing V1 queries that cannot be properly converted to V2 will be omitted from the response.

1.13 User Risk Profile

A user risk profile is created for each user. Use py42 to manage these user risk profiles.

1.13.1 Update a User Risk Profile

Determine the user ID to manage a user's risk profile. For example, the following code uses the `get_username()` method to find the ID of a user with the username `test.user@code42.com`.

```
response = sdk.userriskprofile.get_username()  
  
user_id = response.data["userId"]
```

Use the user ID with the `update()` method to manage a user risk profiles' `startDate`, `endDate`, and `notes` fields.

The `startDate` and `endDate` arguments expect a format of `YYYY-MM-DD` or a `datetime` object.

The following code updates the departure date of the user risk profile to March 1st, 2025:

```
# update the user risk profile  
sdk.userriskprofile.update(user_id, end_date="2025-03-01", notes="Updated the departure date.")  
  
# view updated user details  
py42.util.print_response(sdk.userriskprofile.get(user_id))
```

If you want to clear a field, provide an empty string to the corresponding argument.

For example, the following code will clear the `endDate` and `notes` fields:

```
# clear fields on the user risk profile  
sdk.userriskprofile.update(user_id, end_date="", notes="")
```

1.13.2 Manage Cloud Aliases

Each user risk profile starts with a default alias of their code42 username and can have one additional cloud alias. Use the `UserRiskProfileClient` to manage these aliases.

Use `add_cloud_aliases()` to assign additional cloud aliases to a user:

```
user_id = "test-user-123"  
cloud_aliases = "test-user@email.com"  
sdk.userriskprofile.add_cloud_aliases(user_id, cloud_aliases)  
  
# view updated user cloud aliases  
py42.util.print_response(sdk.userriskprofile.get(user_id))
```

Remove cloud aliases in a similar manner using the `delete_cloud_aliases()` method. Provide a list of values to add or remove multiple aliases at once.

```
sdk.userriskprofile.delete_cloud_aliases(user_id, ["test-user@email.com",  
"username@email.com"])
```

1.14 Watchlists

Use py42 to create and manage watchlists.

Watchlists have replaced the Departing Employees and High Risk Employees detections lists. See the [Code42 support documentation](#) on managing watchlists for more information.

1.14.1 Create a Watchlist

```
from py42.constants import WatchlistType

watchlist = sdk.watchlists.create(WatchlistType.DEPARTING)

# store the id of the new watchlist
watchlist_id = watchlist.data["watchlistId"]
```

Watchlist types are available as constants in the `WatchlistType` class.

1.14.2 View Watchlist Details

There are several methods to view different details about watchlists.

```
import py42.util

# Get information on all current watchlists
response = sdk.watchlists.get_all()

# print all information to the console
for page in response:
    py42.util.print_response(page)
```

Once you have the watchlist's ID, use the following methods to see more details:

```
# To get watchlist details
sdk.watchlists.get(watchlist_id)

# To see all included users
sdk.watchlists.get_all_included_users(watchlist_id)
```

1.14.3 Manage Users on Watchlists

Use the `included_users` methods to manage individual users who are explicitly included on watchlists.

Py42 allows you to reference a watchlist either by its ID or by its type. If adding individual users to a watchlist with the `add_included_users_by_watchlist_type()` method, py42 will create the watchlist for you if it doesn't already exist.

For example, the following code demonstrates two methods to add users to the Departing watchlist:

```
user_ids = ["test-user-123", "test-user-456"]

# METHOD 1: add by watchlist id
sdk.watchlists.add_included_users_by_watchlist_id(user_ids, watchlist_id)

# METHOD 2: add by watchlist type
from py42.constants import WatchlistType

# this method will create the DEPARTING watchlist for you if it doesn't already exist
sdk.watchlists.add_included_users_by_watchlist_type(user_ids, WatchlistType.DEPARTING)

# View your updated watchlist users
sdk.watchlists.get_all_included_users(watchlist_id)
```

The `delete_included_users_by_watchlist_id()` and `delete_included_users_by_watchlist_type()` methods can be used similarly to remove users from a watchlist.

- [*Getting Started*](#)
- [*Basics*](#)
- [*Executing Searches*](#)
- [*Departing Employee*](#)
- [*High Risk Employee*](#)
- [*Get Active Devices From An Organization*](#)
- [*Device Settings*](#)
- [*Org Settings*](#)
- [*Backup Sets*](#)
- [*Cases*](#)
- [*Trust Settings*](#)
- [*V2 File Events*](#)
- [*User Risk Profiles*](#)
- [*Watchlists*](#)

METHOD DOCUMENTATION

2.1 Alert Rules

```
class py42.clients.alertrules.AlertRulesClient(alerts_service, alert_rules_service)  
Bases: object
```

Rest Documentation

add_user(rule_id, user_id)

Update alert rule criteria to add a user and all their aliases to an alert rule. A rule's user list can either be inclusive (only the users on the list can generate alerts) or exclusive (everyone can generate alerts, except users on the list). This method will include or exclude based on the rule configuration.

Rest Documentation

Parameters

- **rule_id** (*str*) – Observer Id of a rule to be updated.
- **user_id** (*str*) – The Code42 userUid of the user to add to the alert

Returns *py42.response.Py42Response*

property cloudshare

A collection of methods for managing cloud sharing alert rules.

Returns *py42.services.alertrules.cloud_share.CloudShareService*

property exfiltration

A collection of methods for managing exfiltration alert rules.

Returns *py42.services.alertrules.exfiltration.ExfiltrationService*

property filetypeismatch

A collection of methods for managing file type mismatch alert rules.

Returns *py42.services.alertrules.file_type_mismatch.FileTypeMismatchService*

get_all(sort_key='CreatedAt', sort_direction='DESC')

Fetch all available rules.

Parameters

- **sort_key** (*str, optional*) – Sort results based by field. Defaults to ‘CreatedAt’.
- **sort_direction** (*str, optional*) – ASC or DESC. Constants available at *py42.constants.SortDirection*. Defaults to “DESC”

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of rules.

Return type generator

get_all_by_name(`rule_name`)

Search for matching rules by name.

Parameters `rule_name` (`str`) – Rule name to search for, case insensitive search.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of rules with the given name.

Return type generator

get_by_observer_id(`observer_id`)

Get the rule with the matching observer ID.

Parameters `observer_id` (`str`) – The observer ID of the rule to return.

Returns `py42.response.Py42Response`

get_page(`sort_key='CreatedAt', sort_direction='DESC', page_num=1, page_size=None`)

Gets a page of alert rules. Note that you can use `page_size` here the same way as other methods that have a `page_size` parameter in py42. However, under the hood, it subtracts one from the given page size in the implementation as the Code42 alerts API expected the start page to be zero while the rest of the Code42 APIs expect the start page to be one.

Parameters

- `sort_key` (`str, optional`) – Sort results based by field. Defaults to “CreatedAt”.
- `sort_direction` (`str, optional`) – ASC or DESC. Constants available at `py42.constants.SortDirection`. Defaults to “DESC”.
- `page_num` (`int, optional`) – The page number to get. Defaults to 1.
- `page_size` (`int, optional`) – The number of items per page. Defaults to `py42.settings.items_per_page`.

Returns `py42.response.Py42Response`

remove_all_users(`rule_id`)

Update alert rule criteria to remove all users the from the alert rule.

Rest Documentation

Parameters `rule_id` (`str`) – Observer rule Id of a rule to be updated.

Returns `py42.response.Py42Response`

remove_user(`rule_id, user_id`)

Update alert rule criteria to remove a user and all their aliases from an alert rule. A rule’s user list can either be inclusive (only the users on the list can generate alerts) or exclusive (everyone can generate alerts, except users on the list). This method will include or exclude based on the rule configuration.

Rest Documentation

Parameters

- `rule_id` (`str`) – Observer rule Id of a rule to be updated.
- `user_id` (`str`) – The Code42 userUid of the user to remove from the alert

Returns `py42.response.Py42Response`

2.1.1 Exfiltration rules

```
class py42.services.alertrules.ExfiltrationService(connection, tenant_id)
Bases: py42.services.BaseService
```

get(rule_id)

Fetch exfiltration alert rule by rule id.

Parameters `rule_id (str)` – Observer rule Id of a rule to be fetched.

Returns `py42.response.Py42Response`

2.1.2 Cloud share rules

```
class py42.services.alertrules.CloudShareService(connection, tenant_id)
Bases: py42.services.BaseService
```

get(rule_id)

Fetch cloud share alert rule by rule id.

Parameters `rule_id (str)` – Observer rule Id of a rule to be fetched.

Returns `py42.response.Py42Response`

2.1.3 File type mismatch rules

```
class py42.services.alertrules.FileTypeMismatchService(connection, tenant_id)
Bases: py42.services.BaseService
```

get(rule_id)

Fetch File type mismatch alert rules by rule id.

Parameters `rule_id (str)` – Observer rule Id of a rule to be fetched.

Returns `py42.response.Py42Response`

2.2 Alerts

```
class py42.clients.alerts.AlertsClient(alert_service, alert_rules_client)
Bases: object
```

A client to expose alert API.

[Rest Documentation](#)

get_aggregate_data(alert_id)

Gets alert summary with details about observations.

Parameters `alert_id (str)` – Gets the details for the alert with the given ID.

Returns `py42.response.Py42Response`

get_all_alert_details(query)

Helper method that combines `search_all_pages()` and `get_details()` methods to get alert objects with alert “observations” details populated. Returns an iterator of alert detail objects.

Note: automatically overrides the `page_size` property on the query object to limit search to 100 results per page, as that is the max that `get_details()` can request at a time.

Parameters `query` (`py42.sdk.queries.alerts.alert_query.AlertQuery`) – An alert query.

Returns An object that iterates over alert detail items.

Return type generator

get_details(alert_ids)

Gets the details for the alerts with the given IDs, including the file event query that, when passed into a search, would result in events that could have triggered the alerts.

Rest Documentation

Parameters `alert_ids` (`str or list[str]`) – The identification number(s) of the alerts for which you want to get details for. Note: The alerts backend accepts a maximum of 100 alerts per request.

Returns A response containing the alert details.

Return type `py42.response.Py42Response`

reopen(alert_ids, reason=None)

Reopens the resolved alerts with the given IDs.

Parameters

- `alert_ids` (`str or list[str]`) – The identification number(s) for the alerts to reopen.
Note: The alerts backend accepts a maximum of 100 alerts per request.
- `reason` (`str, optional`) – The reason the alerts are reopened. Defaults to None.

Returns `py42.response.Py42Response`

resolve(alert_ids, reason=None)

Resolves the alerts with the given IDs.

Parameters

- `alert_ids` (`str or list[str]`) – The identification number(s) for the alerts to resolve.
Note: The alerts backend accepts a maximum of 100 alerts per request.
- `reason` (`str, optional`) – The reason the alerts are now resolved. Defaults to None.

Returns `py42.response.Py42Response`

property rules

A collection of methods for managing alert rules.

Returns `py42.services.alertrules.AlertRulesClient`

search(query, page_num=1, page_size=None)

Searches alerts using the given `py42.sdk.queries.alerts.alert_query.AlertQuery`.

Rest Documentation

Parameters

- `query` (`py42.sdk.queries.alerts.alert_query.AlertQuery`) – An alert query.
See the [Executing Searches User Guide](#) to learn more about how to construct a query.

- **page_num** (*int, optional*) – The page number to get. Defaults to 1.
- **page_size** (*int, optional*) – The number of items per page. Defaults to `py42.settings.items_per_page`.

Returns A response containing the alerts that match the given query.

Return type `py42.response.Py42Response`

search_all_pages(*query*)

Searches alerts using the given `py42.sdk.queries.alerts.alert_query.AlertQuery`.

Rest Documentation

Parameters **query** (`py42.sdk.queries.alerts.alert_query.AlertQuery`) – An alert query. See the [Executing Searches User Guide](#) to learn more about how to construct a query.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of alerts that match the given query.

Return type generator

update_note(*alert_id, note*)

Updates an alert's note.

Parameters

- **alert_id** (*str*) – The identification number of an alert to add a note to.
- **note** (*str*) – A note to attach to the alert. Must be less than 2000 characters. Defaults to None.

Returns `py42.response.Py42Response`

update_state(*status, alert_ids, note=None*)

Updates the status of alerts.

Parameters

- **status** (*str*) – Status to set from OPEN, RESOLVED, PENDING, IN_PROGRESS
- **alert_ids** (*str or List[str]*) – The identification number(s) for the alerts to reopen. Note: The alerts backend accepts a maximum of 100 alerts per request.
- **note** (*str, optional*) – A note to attach to the alerts. Must be less than 2000 characters. Defaults to None.

Returns `py42.response.Py42Response`

2.2.1 Filter Classes

The following classes construct filters for file event queries. Each filter class corresponds to an alert detail. Call the appropriate classmethod on your desired filter class with the value you want to match and it will return a `FilterGroup` object that can be passed to `AlertQuery`'s `all()` or `any()` methods to create complex queries that match multiple filter rules.

See [Executing Searches](#) for more on building search queries.

class `py42.sdk.queries.alerts.filters.alert_filter.Actor`

Bases: `py42.sdk.queries.alerts.util.AlertQueryFilterStringField`

Class that filters alerts based on the username that originated the event(s) that triggered the alert.

classmethod contains(*value*)

Creates a *FilterGroup* for filtering results where the value with key `self._term` contains the given value. Useful for creating CONTAINS filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters `value (str)` – The value used to match on.

Returns *FilterGroup*

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod is_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_contains(*value*)

Creates a *FilterGroup* for filtering results where the value with key `self._term` does not contain the given value. Useful for creating DOES_NOT_CONTAIN filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters `value (str)` – The value used to exclude on.

Returns *FilterGroup*

classmethod not_eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.alerts.filters.alert_filter.AlertState`

Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`, `py42.choices.Choices`

Class that filters alerts based on alert state.

Available options are:

- `AlertState.OPEN`
- `AlertState.DISMISSED`
- `AlertState.PENDING`
- `AlertState.IN_PROGRESS`

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.alerts.filters.alert_filter.DateObserved

Bases: `py42.sdk.queries.alerts.util.AlertQueryFilterTimestampField`

Class that filters alerts based on the timestamp the alert was triggered.

classmethod in_range(start_value, end_value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- `start_value (str or int or float or datetime)` – The start value used to filter results.
- `end_value (str or int or float or datetime)` – The end value used to filter results.

Returns *FilterGroup*

classmethod on_or_after(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term`` is on or after the provided ``value``.

Parameters `value (str or int or float or datetime)` – The value used to filter results.

Returns *FilterGroup*

```
classmethod on_or_before(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term is on or before the provided value.

    Parameters value (str or int or float or datetime) – The value used to filter results.

    Returns FilterGroup

classmethod on_same_day(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term is within the same calendar day as the provided value.

    Parameters value (str or int or float or datetime) – The value used to filter results.

    Returns FilterGroup

class py42.sdk.queries.alerts.filters.alert_filter.Description
    Bases: py42.sdk.queries.alerts.util.AlertQueryFilterStringField

    Class that filters alerts based on rule description text.

    classmethod contains(value)
        Creates a FilterGroup for filtering results where the value with key self._term contains the given value. Useful for creating CONTAINS filters that are not yet supported in py42 or programmatically crafting filter groups.

        Parameters value (str) – The value used to match on.

        Returns FilterGroup

    classmethod eq(value)
        Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

        Parameters value (str) – The value to match on.

        Returns FilterGroup

    classmethod is_in(value_list)
        Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.

        Parameters value_list (list) – The list of values to match on.

        Returns FilterGroup

    classmethod not_contains(value)
        Creates a FilterGroup for filtering results where the value with key self._term does not contain the given value. Useful for creating DOES_NOT_CONTAIN filters that are not yet supported in py42 or programmatically crafting filter groups.

        Parameters value (str) – The value used to exclude on.

        Returns FilterGroup

    classmethod not_eq(value)
        Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.

        Parameters value (str) – The value to exclude on.

        Returns FilterGroup
```

classmethod not_in(value_list)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.alerts.filters.alert_filter.RuleId`
Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`

Class that filters alerts based on rule identifier.

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.alerts.filters.alert_filter.RuleName`
Bases: `py42.sdk.queries.alerts.util.AlertQueryFilterStringField`

Class that filters alerts based on rule name.

classmethod contains(value)

Creates a *FilterGroup* for filtering results where the value with key `self._term` contains the given value. Useful for creating CONTAINS filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters `value` (`str`) – The value used to match on.

Returns *FilterGroup*

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns *FilterGroup*

classmethod not_contains(value)

Creates a *FilterGroup* for filtering results where the value with key `self._term` does not contain the given value. Useful for creating DOES_NOT_CONTAIN filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters `value` (`str`) – The value used to exclude on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.alerts.filters.alert_filter.RuleSource`

Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`, `py42.choices.Choices`

Class that filters alerts based on rule source.

Available options are:

- `RuleSource.ALERTING`
- `RuleSource.DEPARTING_EMPLOYEE`
- `RuleSource.HIGH_RISK_EMPLOYEE`

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (`list`)

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.alerts.filters.alert_filter.RuleType`
Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`, `py42.choices.Choices`
Class that filters alerts based on rule type.

Available options are:

- `RuleType.ENDPOINT_EXFILTRATION`
- `RuleType.CLOUD_SHARE_PERMISSIONS`
- `RuleType.FILE_TYPE_MISMATCH`

classmethod **choices**()
Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (*list*)

classmethod **eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **is_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

```
class py42.sdk.queries.alerts.filters.alert_filter.Severity
    Bases: py42.sdk.queries.query_filter.QueryFilterStringField, py42.choices.Choices
```

Class that filters alerts based on severity.

Available options are:

- Severity.CRITICAL
- Severity.HIGH
- Severity.MODERATE
- Severity.LOW

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term equals the provided value.

Parameters **value** (str) – The value to match on.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key self._term is in the provided value_list.

Parameters **value_list** (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key self._term does not equal the provided value.

Parameters **value** (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key self._term is not in the provided value_list.

Parameters **value_list** (list) – The list of values to exclude on.

Returns *FilterGroup*

```
class py42.sdk.queries.alerts.alert_query.AlertQuery(*args, **kwargs)
```

Bases: py42.sdk.queries.BaseQuery

Helper class for building Code42 Alert queries.

An AlertQuery instance's all() and any() take one or more *FilterGroup* objects to construct a query that can be passed to the AlertService.search() method. all() returns results that match all of the provided filter criteria, any() will return results that match any of the filters.

For convenience, the *AlertQuery* constructor does the same as all().

Usage example:

```
state_filter = AlertState.eq(AlertState.OPEN)
rule_name_filter = RuleName.contains("EmailRule")
query = AlertQuery.all(state_filter, rule_name_filter)
```

2.3 Archive

Important: You must be using py42 to version 1.25.1 or higher to use the `archive.stream_from_backup()` or `archive.stream_to_device()` methods.

class `py42.clients.archive.ArchiveClient(archive_accessor_factory, archive_service)`
 Bases: `object`

A module for getting information about backup archives on storage nodes along with functionality for streaming a file from backup.

get_all_by_device_guid(device_guid)
 Gets archive information for a device.

Parameters `device_guid (str)` – The GUID for the device.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of archives.

Return type generator

get_all_device_restore_history(days, device_id)
 Gets all restore jobs from the past given days for the device with the given ID.

Parameters

- `days (int)` – Number of days of restore history to retrieve.
- `device_id (int)` – The identification number of the device to get restore history for.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of restore history.

Return type generator

get_all_org_cold_storage_archives(org_id, include_child_orgs=True, sort_key='archiveHoldExpireDate', sort_dir='asc')

Returns a detailed list of cold storage archive information for a given org ID.

Parameters

- `org_id (str)` – The ID of a Code42 organization.
- `include_child_orgs (bool, optional)` – Determines whether cold storage information from the Org's children is also returned. Defaults to True.
- `sort_key (str, optional)` – Sets the property by which the returned results will be sorted. Choose from `archiveHoldExpireDate`, `orgName`, `mountPointName`, `archiveBytes`, and `archiveType`. Defaults to `archiveHoldExpireDate`.
- `sort_dir (str, optional)` – Sets the order by which `sort_key` should be sorted. Choose from `asc` or `desc`. Defaults to `asc`.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of cold storage archive information.

Return type generator

get_all_org_restore_history(*days*, *org_id*)

Gets all restore jobs from the past given days for the organization with the given ID.

Parameters

- **days** (*int*) – Number of days of restore history to retrieve.
- **org_id** (*int*) – The identification number of the organization to get restore history for.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of restore history.

Return type generator

get_all_user_restore_history(*days*, *user_id*)

Gets all restore jobs from the past given days for the user with the given ID.

Parameters

- **days** (*int*) – Number of days of restore history to retrieve.
- **user_id** (*int*) – The identification number of the user to get restore history for.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of restore history.

Return type generator

get_backup_sets(*device_guid*, *destination_guid*)

Gets all backup set names/identifiers referring to a single destination for a specific device. [Learn more about backup sets](#).

Parameters

- **device_guid** (*str*) – The GUID of the device to get backup sets for.
- **destination_guid** (*str*) – The GUID of the destination containing the archive to get backup sets for.

Returns A response containing the backup sets.

Return type `py42.response.Py42Response`

get_by_archive_guid(*archive_guid*)

Gets single archive information by GUID.

Parameters `archive_guid` (*str*) – The GUID for the archive.

Returns A response containing archive information.

Return type `py42.response.Py42Response`

stream_from_backup(*file_paths*, *device_guid*, *destination_guid=None*, *archive_password=None*, *encryption_key=None*, *show_deleted=None*, *file_size_calc_timeout=10*, *backup_set_id=None*)

Streams a file from a backup archive to memory. This method uses the same endpoint as restoring from Console and therefore has all the same considerations.

[Support Documentation](#)

Parameters

- **file_paths** (*str or list of str*) – The path or list of paths to the files or directories in the archive.
- **device_guid** (*str*) – The GUID of the device the file belongs to.
- **destination_guid** (*str, optional*) – The GUID of the destination that stores the backup of the file. If None, it will use the first destination GUID it finds for your device. ‘destination_guid’ may be useful if the file is missing from one of your destinations or if you want to optimize performance. Defaults to None.
- **archive_password** (*str or None, optional*) – The password for the archive, if password-protected. This is only relevant to users with archive key password security. Defaults to None.
- **encryption_key** (*str or None, optional*) – A custom encryption key for decrypting an archive’s file contents, necessary for restoring files. This is only relevant to users with custom key archive security. Defaults to None.
- **show_deleted** (*bool, optional*) – Set to True to include deleted files when restoring a directory. Defaults to None.
- **file_size_calc_timeout** (*int, optional*) – Set to limit the amount of seconds spent calculating file sizes when crafting the request. Set to 0 or None to ignore file sizes altogether. Defaults to 10.
- **backup_set_id** (*str, optional*) – The ID of the backup set restore from (only useful for V3 archives). If not supplied, the default backup set (id=1) will be used if it exists, otherwise the first in the list of existing backup sets will be used.

Returns A response containing the streamed content.

Return type `py42.response.Py42Response`

Usage example:

```
stream_response = sdk.archive.stream_from_backup("/full/path/to/file.txt",
                                               "1234567890")
with open("/path/to/save/file/to", "wb") as f:
    for chunk in stream_response.iter_content(chunk_size=128):
        if chunk:
            f.write(chunk)
```

In certain cases, you will have to unzip the results:

```
import zipfile
with zipfile.ZipFile("downloaded_directory.zip", "r") as zf:
    zf.extractall(".")
```

stream_to_device(*file_paths, device_guid, accepting_device_guid, restore_path, destination_guid=None, archive_password=None, encryption_key=None, show_deleted=None, overwrite_existing_files=False, file_size_calc_timeout=10, backup_set_id=None*)

Streams a file from a backup archive to a specified device.

Parameters

- **file_paths** (*str or list of str*) – The path or list of paths to the files or directories in the archive.
- **device_guid** (*str*) – The GUID of the device the file belongs to.
- **accepting_device_guid** (*str*) – The GUID of the device accepting the restore.

- **restore_path** (*str, optional*) – The path on the accepting device where the restore will be saved. Alternatively, pass in the value ORIGINAL_LOCATION to restore the file to the original location, which may be the case if you are replacing a device.
- **destination_guid** (*str, optional*) – The GUID of the destination that stores the backup of the file. If None, it will use the first destination GUID it finds for your device. ‘destination_guid’ may be useful if the file is missing from one of your destinations or if you want to optimize performance. Defaults to None.
- **archive_password** (*str or None, optional*) – The password for the archive, if password-protected. This is only relevant to users with archive key password security. Defaults to None.
- **encryption_key** (*str or None, optional*) – A custom encryption key for decrypting an archive’s file contents, necessary for restoring files. This is only relevant to users with custom key archive security. Defaults to None.
- **show_deleted** (*bool, optional*) – Set to True to include deleted files when restoring a directory. Defaults to None.
- **overwrite_existing_files** (*bool, optional*) – to overwrite any existing files with the restored data. If False (the default), any existing files that match a path being restored will first get renamed.
- **file_size_calc_timeout** (*int, optional*) – Set to limit the amount of seconds spent calculating file sizes when crafting the request. Set to 0 or None to ignore file sizes altogether. Defaults to 10.
- **backup_set_id** (*str, optional*) – The ID of the backup set restore from (only useful for V3 archives). If not supplied, the default backup set (id=1) will be used if it exists, otherwise the first in the list of existing backup sets will be used.

Returns `py42.response.Py42Response`.

update_cold_storage_purge_date(*archive_guid, purge_date*)

Updates the cold storage purge date for a specified archive.

Parameters

- **archive_guid** (*str*) – The identification number of the archive that should be updated
- **purge_date** (*str*) – The date on which the archive should be purged in yyyy-MM-dd format

Returns the response from the ColdStorage API.

Return type `py42.response.Py42Response`

2.4 Audit Logs

class `py42.clients.auditlogs.AuditLogsClient(audit_log_service)`

Bases: `object`

Rest documentation

get_all(*begin_time=None, end_time=None, event_types=None, user_ids=None, usernames=None, user_ip_addresses=None, affected_user_ids=None, affected_usernames=None, **kwargs*)

Retrieve audit logs, filtered based on given arguments. [Rest Documentation](#)

Parameters

- **begin_time** (*int or float or str or datetime, optional*) – Timestamp in milliseconds or str format “yyyy-MM-dd HH:MM:SS” or a datetime instance. Defaults to None.
- **end_time** (*int or float or str or datetime, optional*) – Timestamp in milliseconds or str format “yyyy-MM-dd HH:MM:SS” or a datetime instance. Defaults to None.
- **event_types** (*str or list, optional*) – A str or list of str of valid event types. Defaults to None.
- **user_ids** (*str or list, optional*) – A str or list of str of Code42 userUids. Defaults to None.
- **usernames** (*str or list, optional*) – A str or list of str of Code42 usernames. Defaults to None.
- **user_ip_addresses** (*str or list, optional*) – A str or list of str of user ip addresses. Defaults to None.
- **affected_user_ids** (*str or list, optional*) – A str or list of str of affected Code42 userUids. Defaults to None.
- **affected_usernames** (*str or list, optional*) – A str or list of str of affected Code42 usernames. Defaults to None.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of audit logs.

Return type generator

```
get_page(page_num=1, page_size=None, begin_time=None, end_time=None, event_types=None, user_ids=None, usernames=None, user_ip_addresses=None, affected_user_ids=None, affected_usernames=None, **kwargs)
```

Retrieve a page of audit logs, filtered based on given arguments.

Note: *page_num* here can be used same way as other methods that have a *page_num* parameter in py42. However, under the hood, it subtracts one from the given *page_num* in the implementation as the Code42 Audit-Logs API expects the start page to be zero. [Rest Documentation](#)

Parameters

- **page_num** (*int, optional*) – The page number to get. Defaults to 1.
- **page_size** (*int, optional*) – The number of items per page. Defaults to `py42.settings.items_per_page`.
- **begin_time** (*int or float or str or datetime, optional*) – Timestamp in milliseconds or str format “yyyy-MM-dd HH:MM:SS” or a datetime instance. Defaults to None.
- **end_time** (*int or float or str or datetime, optional*) – Timestamp in milliseconds or str format “yyyy-MM-dd HH:MM:SS” or a datetime instance. Defaults to None.
- **event_types** (*str or list, optional*) – A str or list of str of valid event types. Defaults to None.
- **user_ids** (*str or list, optional*) – A str or list of str of Code42 userUids. Defaults to None.
- **usernames** (*str or list, optional*) – A str or list of str of Code42 usernames. Defaults to None.

- **user_ip_addresses** (*str or list, optional*) – A str or list of str of user ip addresses. Defaults to None.
- **affected_user_ids** (*str or list, optional*) – A str or list of str of affected Code42 userUids. Defaults to None.
- **affected_usernames** (*str or list, optional*) – A str or list of str of affected Code42 usernames. Defaults to None.

Returns `py42.response.Py42Response`

2.5 Backup Sets

class `py42.clients.settings.device_settings.BackupSet(settings_manager, backup_set_dict)`

Bases: `collections.UserDict`

Helper class for managing device backup sets and Org device default backup sets.

add_destination(*destination_guid*)

Adds a destination to be used by this backup set. Raises a `Py42Error` if the supplied destination guid is not available to the parent device/org.

Parameters `destination_guid(str, int)` – The globally unique identifier of the destination to be added.

property destinations

Returns a dict of the destinations used for backup for the backup set. Dict keys are the destination guids, values are the destination names.

property excluded_files

Returns the list of files/folders excluded from the backup selection. Items can be added/removed from this list via normal list methods, or assigning a new list of files to this attribute to replace the existing one.

property filename_exclusions

Returns the list of regex patterns used to exclude file paths from the backup selection. Items can be added/removed from this list via normal list methods, or assigning a new list of patterns to this attribute to replace the existing one.

property included_files

Returns the list of files/folders included in the backup selection. Items can be added/removed from this list via normal list methods, or assigning a new list of files to this attribute to replace the existing one.

lock_destination(*destination_guid*)

Locks an in-use destination, disallowing the device owner from removing this destination from their backup. Raises a `Py42Error` if the supplied destination guid is not in use on this backup set, or not available to the parent device/org.

property locked

Indicates whether the backup set as a whole is locked. If True, individual settings for this backup set (except for Destination settings), cannot be modified.

remove_destination(*destination_guid*)

Removes a destination from use by this backup set.

Parameters `destination_guid(str, int)` – The globally unique identifier of the destination to be removed.

unlock_destination(destination_guid)

Unlocks an in-use destination, allowing the device owner to remove this destination from their backup.
Raises a [Py42Error](#) if the supplied destination guid is not in use on this backup set, or not available to the parent device/org.

2.6 Cases

class py42.clients.cases.CaseStatus

Bases: `py42.choices.Choices`

Constants available for setting the status of a case.

- OPEN
- CLOSED

class py42.clients.cases.CasesClient(cases_service, cases_file_event_service)

Bases: `object`

A client to expose cases API.

[Rest documentation](#)

create(name, subject=None, assignee=None, description=None, findings=None)

Creates a new case. [Rest documentation](#)

Parameters

- **name** (`str`) – Name of the case.
- **subject** (`str, optional`) – User UID of a subject of a case.
- **assignee** (`str, optional`) – User UID of the assignee.
- **description** (`str, optional`) – Description of the case
- **findings** (`str, optional`) – Observations of the case.

Returns `py42.response.Py42Response`

export_summary(case_number)

Provides case summary to download as a PDF file. [Rest documentation](#)

Parameters `case_number` (`int`) – Case number of the case.

Returns `py42.response.Py42Response`

property file_events

A collection of methods for managing file events associated with a given case.

Returns `py42.services.casesfileevents.CasesFileEventsService`

get(case_number)

Retrieve case details by case number. [Rest documentation](#)

Parameters `case_number` (`int`) – Case number of the case.

Returns `py42.response.Py42Response`

get_all(name=None, status=None, min_create_time=None, max_create_time=None, min_update_time=None, max_update_time=None, subject=None, assignee=None, page_size=100, sort_direction='asc', sort_key='number', **kwargs)

Gets all cases. [Rest documentation](#)

Parameters

- **name** (*str, optional*) – Filter results by case name, matches partial names. Defaults to None.
- **status** (*str, optional*) – Filter results by case status. OPEN or CLOSED. Defaults to None. Constants available at [py42.constants.CaseStatus](#).
- **min_create_time** (*str or int or float or datetime, optional*) – Filter results by case creation time, start time. str format %Y-%m-%d %H:%M:%S. Defaults to None.
- **max_create_time** (*str or int or float or datetime, optional*) – Filter results by case creation time, end time. str format %Y-%m-%d %H:%M:%S. Defaults to None.
- **min_update_time** (*str or int or float or datetime, optional*) – Filter results by last updated time, start time. str format %Y-%m-%d %H:%M:%S. Defaults to None.
- **max_update_time** (*str or int or float or datetime, optional*) – Filter results by last updated time, end time. str format %Y-%m-%d %H:%M:%S. Defaults to None.
- **subject** (*str, optional*) – Filter results based on User UID of a subject of a case. Defaults to None.
- **assignee** (*str, optional*) – Filter results based on User UID of an assignee of a case. Defaults to None.
- **page_size** (*int, optional*) – Number of results to return per page. Defaults to 100.
- **sort_direction** (*str, optional*) – The direction on which to sort the response, based on the corresponding sort key. *asc* or *desc*. Defaults to *asc*.
- **sort_key** (*str, optional*) – Values on which the response will be sorted. Defaults to “number”. Available options are *name*, *number*, *createdAt*, *updatedAt*, *status*, *assigneeUsername*, *subjectUsername*.

Returns An object that iterates over [py42.response.Py42Response](#) objects that each contain a page of cases.

Return type generator

```
get_page(page_num, name=None, status=None, min_create_time=None, max_create_time=None,  
        min_update_time=None, max_update_time=None, subject=None, assignee=None, page_size=100,  
        sort_direction='asc', sort_key='number', **kwargs)
```

Gets individual page of cases. [Rest documentation](#)

Parameters

- **page_num** (*int*) – The page number to request.
- **name** (*str, optional*) – Filter results by case name, matches partial names. Defaults to None.
- **status** (*str, optional*) – Filter results by case status. OPEN or CLOSED. Defaults to None. Constants available at [py42.constants.CaseStatus](#).
- **min_create_time** (*str or int or float or datetime, optional*) – Filter results by case creation time, start time. str format %Y-%m-%d %H:%M:%S. Defaults to None.

- **max_create_time** (*str or int or float or datetime, optional*) – Filter results by case creation time, end time. str format %Y-%m-%d %H:%M:%S. Defaults to None.
- **min_update_time** (*str or int or float or datetime, optional*) – Filter results by last updated time, start time. str format %Y-%m-%d %H:%M:%S. Defaults to None.
- **max_update_time** (*str or int or float or datetime, optional*) – Filter results by last updated time, end time. str format %Y-%m-%d %H:%M:%S. Defaults to None.
- **subject** (*str, optional*) – Filter results based on User UID of a subject of a case. Defaults to None.
- **assignee** (*str, optional*) – Filter results based on User UID of an assignee of a case. Defaults to None.
- **page_size** (*int, optional*) – Number of results to return per page. Defaults to 100.
- **sort_direction** (*str, optional*) – The direction on which to sort the response, based on the corresponding sort key. *asc* or *desc*. Defaults to *asc*.
- **sort_key** (*str, optional*) – Values on which the response will be sorted. Defaults to “number”. Available options are *name*, *number*, *createdAt*, *updatedAt*, *status*, *assigneeUsername*, *subjectUsername*.

Returns `py42.response.Py42Response`

update(*case_number, name=None, subject=None, assignee=None, description=None, findings=None, status=None*)

Updates case details for the given case number. [Rest documentation](#)

Parameters

- **case_number** (*int*) – Case number of the case.
- **name** (*str, optional*) – Name of the case. Defaults to None.
- **subject** (*str, optional*) – A subject of the case. Defaults to None.
- **assignee** (*str, optional*) – User UID of the assignee. Defaults to None.
- **description** (*str, optional*) – Description of the case. Defaults to None.
- **findings** (*str, optional*) – Notes on the case. Defaults to None.
- **status** (*str, optional*) – Status of the case. OPEN or CLOSED. Defaults to None. Constants available at `py42.constants.CaseStatus`.

Returns `py42.response.Py42Response`

2.6.1 Cases File Events

class `py42.services.casesfileevents.CasesFileEventsService`(*connection*)

Bases: `py42.services BaseService`

add(*case_number, event_id*)

Adds an event to the case.

Parameters

- **case_number** (*int*) – Case number of the case.

- **event_id** (*str*) – Event id to add to the case.

Returns *py42.response.Py42Response*

delete(*case_number*, *event_id*)

Deletes an event from the case.

Parameters

- **case_number** (*int*) – Case number of the case.
- **event_id** (*str*) – Event id to remove from case.

Returns *py42.response.Py42Response*

get(*case_number*, *event_id*)

Gets information of a specified event from the case.

Parameters

- **case_number** (*int*) – Case number of the case.
- **event_id** (*str*) – Event id to fetch from the case.

Returns *py42.response.Py42Response*

get_all(*case_number*)

Gets all events associated with the given case.

Parameters **case_number** (*int*) – Case number of the case.

Returns *py42.response.Py42Response*

2.7 Shared Constants

class *py42.constants.SortDirection*

Bases: *py42.choices.Choices*

Constants available to set Code42 request *sort_direction* when sorting returned lists in responses.

- ASC
- DESC

class *py42.constants.CaseStatus*

Bases: *py42.choices.Choices*

Constants available for setting the status of a case.

- OPEN
- CLOSED

class *py42.constants.RiskTags*

Bases: *py42.choices.Choices*

Deprecated. Use *WatchlistsClient* and *UserRiskProfileClient* instead. Constants available as risk tags for *add_user_risk_tags()* and *remove_user_risk_tags()*.

- FLIGHT_RISK
- HIGH_IMPACT_EMPLOYEE
- ELEVATED_ACCESS_PRIVILEGES
- PERFORMANCE_CONCERN

- SUSPICIOUS_SYSTEM_ACTIVITY
- POOR_SECURITY_PRACTICES
- CONTRACT_EMPLOYEE

class py42.constants.TrustedActivityType

Bases: py42.choices.Choices

Constants available for setting the type of a trusted activity.

- DOMAIN
- SLACK

class py42.constants.DepartingEmployeeFilters

Bases: py42.services.detectionlists._DetectionListFilters, py42.choices.Choices

Deprecated. Use [WatchlistsClient](#) and [UserRiskProfileClient](#) instead. Constants available for filtering Departing Employee search results.

- OPEN
- EXFILTRATION_30_DAYS
- EXFILTRATION_24_HOURS
- LEAVING_TODAY

class py42.constants.HighRiskEmployeeFilters

Bases: py42.services.detectionlists._DetectionListFilters, py42.choices.Choices

Deprecated. Use [WatchlistsClient](#) and [UserRiskProfileClient](#) instead. Constants available for filtering High Risk Employee search results.

- OPEN
- EXFILTRATION_30_DAYS
- EXFILTRATION_24_HOURS

class py42.constants.WatchlistType

Bases: py42.choices.Choices

Constants available for setting the type of watchlist.

- CONTRACT_EMPLOYEE
- DEPARTING_EMPLOYEE
- ELEVATED_ACCESS_PRIVILEGES
- FLIGHT_RISK
- HIGH_IMPACT_EMPLOYEE
- NEW_EMPLOYEE
- PERFORMANCE_CONCERNs
- POOR_SECURITY_PRACTICES
- SUSPICIOUS_SYSTEM_ACTIVITY”

2.8 Detection Lists

Detection lists have been deprecated. Use [Watchlists](#) instead.

```
class py42.clients.detectionlists.DetectionListsClient(user_profile_service,
                                                       departing_employee_service,
                                                       high_risk_employee_service)
```

Bases: object

Deprecated. Use :class:`~py42.clients.watchlists.WatchlistsClient` and [UserRiskProfileClient](#) instead. Rest documentation <<https://developer.code42.com/api/#tag/Detection-Lists>>`__

add_user_cloud_alias(user_id, alias)

Deprecated. Use `userriskprofile.add_cloud_aliases()` instead. Add a cloud alias to a user. [Rest Documentation](#)

Parameters

- **user_id** (*str or int*) – The userUid of the user whose alias you want to update.
- **alias** (*str*) – The alias to be added.

Returns `py42.response.Py42Response`

add_user_risk_tags(user_id, tags)

Deprecated. Use `watchlists` instead. Add one or more risk factor tags. [Rest Documentation](#)

Parameters

- **user_id** (*str or int*) – The userUid of the user whose risk factor tag(s) you want to update.
- **tags** (*str or list of str*) – A single tag or multiple tags in a list to be added. For example: "tag1" or ["tag1", "tag2"].

Constants available at `py42.constants.RiskTags`

Returns `py42.response.Py42Response`

create_user(username)

Deprecated. Used to create a detection list profile for a user, but now that happens automatically. Thus, this method instead returns the response from an API call that gets the user's profile.

Parameters **username** (*str*) – The Code42 username of the user.

Returns `py42.response.Py42Response`

get_user(username)

Deprecated. Use `userriskprofile.get_by_username()` instead. Get user details by username. [Rest Documentation](#)

Parameters **username** (*str*) – The Code42 username of the user.

Returns `py42.response.Py42Response`

get_user_by_id(user_id)

Deprecated. Use `userriskprofile.get_by_id()` instead. Get user details by user_id. [Rest Documentation](#)

Parameters **user_id** (*str or int*) – The Code42 userId of the user.

Returns `py42.response.Py42Response`

refresh_user_scim_attributes(user_id)

Deprecated. Refresh SCIM attributes of a user. [Rest Documentation](#)

Parameters `user_id (str or int)` – The userUid of the user whose attributes you wish to refresh.

Returns `py42.response.Py42Response`

remove_user_cloud_alias(`user_id, alias`)

Deprecated. Use `userriskprofile.delete_cloud_aliases()` instead. Remove a cloud alias from a user. [Rest Documentation](#)

Parameters

- `user_id (str or int)` – The userUid of the user whose alias needs to be removed.
- `alias (str)` – The alias to be removed.

Returns `py42.response.Py42Response`

remove_user_risk_tags(`user_id, tags`)

Deprecated. Use watchlists instead. Remove one or more risk factor tags. [Rest Documentation](#)

Parameters

- `user_id (str or int)` – The userUid of the user whose risk factor tag(s) needs you want to remove.
- `tags (str or list of str)` – A single tag or multiple tags in a list to be removed. For example: "tag1" or ["tag1", "tag2"].

Constants available at `py42.constants.RiskTags`

Returns `py42.response.Py42Response`

update_user_notes(`user_id, notes`)

Deprecated. Use `userriskprofile.update()` instead. Add or update notes related to the user. [Rest Documentation](#)

Parameters

- `user_id (str or int)` – The userUid of the user whose notes you want to update.
- `notes (str)` – User profile notes.

Returns `py42.response.Py42Response`

2.8.1 Departing Employees

```
class py42.services.detectionlists.departing_employee.DepartingEmployeeFilters
Bases: py42.services.detectionlists._DetectionListFilters, py42.choices.Choices

Deprecated. Use WatchlistsClient and UserRiskProfileClient instead. Constants available for filtering Departing Employee search results.

    • OPEN
    • EXFILTRATION_30_DAYS
    • EXFILTRATION_24_HOURS
    • LEAVING_TODAY

class py42.services.detectionlists.departing_employee.DepartingEmployeeService(session,
                                user_context,
                                user_profile_service)
Bases: py42.services BaseService
```

Deprecated. Use `WatchlistsClient` and `UserRiskProfileClient` instead. A service for interacting with Code42 Departing Employee APIs.

add(`user_id`, `departure_date=None`)

Deprecated. Use watchlists instead. Adds a user to the Departing Employees list. [REST Documentation](#)

Raises a `Py42UserAlreadyAddedError` when a user already exists in the Departing Employee detection list.

Parameters

- `user_id` (`str or int`) – The Code42 userUid of the user you want to add to the departing employees list.
- `departure_date` (`str or datetime, optional`) – Date in yyyy-MM-dd format or instance of datetime. Date is treated as UTC. Defaults to None.

Returns `py42.response.Py42Response`

get(`user_id`)

Deprecated. Use `userriskprofile.get_by_id()` instead. Gets departing employee data of a user. [REST Documentation](#)

Parameters `user_id` (`str or int`) – The Code42 userUid of the user.

Returns `py42.response.Py42Response`

get_all(`filter_type='OPEN'`, `sort_key='CREATED_AT'`, `sort_direction='DESC'`, `page_size=100`)

Deprecated. Use `userriskprofile.get_all()`. Gets all Departing Employees.

Parameters

- `filter_type` (`str, optional`) – Constants available at `py42.constants.DepartingEmployeeFilters`. Defaults to “OPEN”.
- `sort_key` (`str, optional`) – Sort results based by field. Defaults to “CREATED_AT”.
- `sort_direction` (`str, optional`) – ASC or DESC. Defaults to “DESC”.
- `page_size` (`int, optional`) – The number of departing employees to return per page. Defaults to 100.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of departing employees.

Return type generator

get_page(`page_num`, `filter_type='OPEN'`, `sort_key='CREATED_AT'`, `sort_direction='DESC'`, `page_size=100`)

Deprecated. Use `userriskprofile.get_page()` instead. Gets a single page of Departing Employees.

Parameters

- `page_num` (`int`) – The page number to request.
- `filter_type` (`str, optional`) – Constants available at `py42.constants.DepartingEmployeeFilters`. Defaults to “OPEN”.
- `sort_key` (`str, optional`) – Sort results based by field. Defaults to “CREATED_AT”.
- `sort_direction` (`str, optional`) – ASC or DESC. Defaults to “DESC”.
- `page_size` (`int, optional`) – The number of departing employees to return per page. Defaults to 100.

Returns `py42.response.Py42Response`

`remove(user_id)`

Deprecated. Use watchlists instead. Removes a user from the Departing Employees list. REST Documentation

Parameters `user_id(str or int)` – The Code42 userUid of the user.

Returns `py42.response.Py42Response`

`set_alerts_enabled(alerts_enabled=True)`

Deprecated. Enable or disable email alerting on Departing Employee exposure events. REST Documentation

Parameters `alerts_enabled(bool)` – Set alerting to on (True) or off (False). Defaults to True.

Returns `py42.response.Py42Response`

`update_departure_date(user_id, departure_date)`

Deprecated. Use `userriskprofile.update()` instead. Add or modify details of an existing Departing Employee case. REST Documentation

Parameters

- `user_id(str)` – The Code42 userUid of the user.
- `departure_date(str or datetime)` – Date in yyyy-MM-dd format or instance of date-time. Date is treated as UTC.

Returns `py42.response.Py42Response`

2.8.2 High Risk Employee

`class py42.clients.detectionlists.RiskTags`

Bases: `py42.choices.Choices`

Deprecated. Use `WatchlistsClient` and `UserRiskProfileClient` instead. Constants available as risk tags for `add_user_risk_tags()` and `remove_user_risk_tags()`.

- FLIGHT_RISK
- HIGH_IMPACT_EMPLOYEE
- ELEVATED_ACCESS_PRIVILEGES
- PERFORMANCE_CONCERNS
- SUSPICIOUS_SYSTEM_ACTIVITY
- POOR_SECURITY_PRACTICES
- CONTRACT_EMPLOYEE

`class py42.services.detectionlists.high_risk_employee.HighRiskEmployeeFilters`

Bases: `py42.services.detectionlists._DetectionListFilters, py42.choices.Choices`

Deprecated. Use `WatchlistsClient` and `UserRiskProfileClient` instead. Constants available for filtering High Risk Employee search results.

- OPEN
- EXFILTRATION_30_DAYS
- EXFILTRATION_24_HOURS

```
class py42.services.detectionlists.high_risk_employee.HighRiskEmployeeService(connection,
                                user_context,
                                user_profile_service)

Bases: py42.services BaseService

Deprecated. Use :class:`~py42.clients.watchlists.WatchlistsClient` and UserRiskProfileClient instead. A service for interacting with High Risk Employee APIs.

add(user_id)
    Deprecated. Use watchlists instead. Adds a user to the High Risk Employee detection list.

    Raises a Py42UserAlreadyAddedError when a user already exists in the High Risk Employee detection list. REST Documentation

    Parameters user_id (str or int) – The Code42 userUid of the user you want to add to the High Risk Employee detection list.

    Returns py42.response.Py42Response

get(user_id)
    Deprecated. Use userriskprofile.get_by_id() instead. Gets user information. Rest Documentation

    Parameters user_id (str or int) – The Code42 userUid of the user has been added to the High Risk Employee detection list.

    Returns py42.response.Py42Response

get_all(filter_type='OPEN', sort_key=None, sort_direction=None, page_size=100)
    Deprecated. Use userriskprofile.get_all() instead. Searches High Risk Employee list. Filter results by filter_type. Rest Documentation

    Parameters
        • filter_type (str, optional) – Constants available at py42.constants.HighRiskEmployeeFilters. Defaults to OPEN.
        • sort_key (str, optional) – Sort results based by field. Defaults to None.
        • sort_direction (str, optional) – ASC or DESC. Constants available at py42.constants.SortDirection. Defaults to None.
        • page_size (int, optional) – The number of high risk employees to return per page. Defaults to 100.

    Returns An object that iterates over py42.response.Py42Response objects that each contain a page of users.

    Return type generator

get_page(page_num, filter_type='OPEN', sort_key=None, sort_direction=None, page_size=100)
    Deprecated. Use userriskprofile.get_page() instead. Gets a single page of High Risk Employees.

    Parameters
        • page_num (int) – The page number to request.
        • filter_type (str, optional) – Constants available at py42.constants.HighRiskEmployeeFilters. Defaults to “OPEN”.
        • sort_key (str, optional) – Sort results based by field. Defaults to None.
        • sort_direction (str, optional) – ASC or DESC. Constants available at py42.constants.SortDirection. Defaults to None.
```

- **page_size** (*int, optional*) – The number of high risk employees to return per page.
Defaults to 100.

Returns `py42.response.Py42Response`

remove(*user_id*)

Deprecated. Use watchlists instead. Removes a user from the High Risk Employee detection list. [Rest Documentation](#)

Parameters **user_id** (*str or int*) – The Code42 userUid of the user you want to add to the High Risk Employee detection list.

Returns `py42.response.Py42Response`

set_alerts_enabled(*enabled=True*)

Deprecated. Enables alerts. [Rest Documentation](#)

Parameters **enabled** (*bool*) – Whether to enable alerts for all users.

Returns `py42.response.Py42Response`

2.9 Devices

class `py42.services.devices.DeviceService`(*connection*)

Bases: `py42.services BaseService`

A class to interact with Code42 device/computer APIs.

block(*device_id*)

Blocks a device causing the user not to be able to log in to or restore from Code42 on that device.

Parameters **device_id** (*int*) – The identification number of the device.

Returns `py42.response.Py42Response`

deactivate(*device_id*)

Deactivates a device, causing backups to stop and archives to go to cold storage.

Parameters **device_id** (*int*) – The identification number of the device.

Returns `py42.response.Py42Response`

deauthorize(*device_id*)

Deauthorizes the device with the given ID. If used on a cloud connector device, it will remove the authorization token for that account.

Parameters **device_id** (*int*) – The identification number of the device.

Returns `py42.response.Py42Response`

get_agent_full_disk_access_state(*guid*)

Gets the full disk access status of a device.

Parameters **guid** (*str*) – The globally unique identifier of the device.

Returns A response containing settings information.

Return type `py42.response.Py42Response`

get_agent_state(*guid, property_name*)

Gets the agent state of the device.

Parameters

- **guid (str)** – The globally unique identifier of the device.
- **property_name (str)** – The name of the property to retrieve (e.g. *fullDiskAccess*).

Returns A response containing settings information.

Return type `py42.response.Py42Response`

get_all(*active=None*, *blocked=None*, *org_uid=None*, *user_uid=None*, *destination_guid=None*, *include_backup_usage=None*, *include_counts=True*, *q=None*, ***kwargs*)

Gets all device information.

When no arguments are passed, all records are returned. To filter results, specify respective arguments. For example, to retrieve all active and blocked devices, pass *active=true* and *blocked=true*.

Parameters

- **active (bool, optional)** – Filters results by device state. When set to True, gets all active devices. When set to False, gets all deactivated devices. When set to None or excluded, gets all devices regardless of state. Defaults to None.
- **blocked (bool, optional)** – Filters results by blocked status: True or False. Defaults to None.
- **org_uid (int, optional)** – The identification number of an Organization. Defaults to None.
- **user_uid (int, optional)** – The identification number of a User. Defaults to None.
- **destination_guid (str or int, optional)** – The globally unique identifier of the storage server that the device back up to. Defaults to None.
- **include_backup_usage (bool, optional)** – A flag to denote whether to include the destination and its backup stats. Defaults to None.
- **include_counts (bool, optional)** – A flag to denote whether to include total, warning, and critical counts. Defaults to True.
- **q (str, optional)** – Searches results flexibly by incomplete GUID, hostname, computer name, etc. Defaults to None.

Returns

An object that iterates over `py42.response.Py42Response` objects that each contain a page of devices.

The devices returned by `get_all()` are based on the role and permissions of the user authenticating the py42 SDK.

Return type generator

get_by_guid(*guid*, *include_backup_usage=None*, ***kwargs*)

Gets device information by GUID.

Parameters

- **guid (str)** – The globally unique identifier of the device.
- **include_backup_usage (bool, optional)** – A flag to denote whether to include the destination and its backup stats. Defaults to None.

Returns A response containing device information.

Return type `py42.response.Py42Response`

get_by_id(*device_id*, *include_backup_usage=None*, ***kwargs*)

Gets device information by ID.

Parameters

- **device_id** (*int*) – The identification number of the device.
- **include_backup_usage** (*bool, optional*) – A flag to denote whether to include the destination and its backup stats. Defaults to None.

Returns A response containing device information.

Return type `py42.response.Py42Response`

get_page(*page_num*, *active=None*, *blocked=None*, *org_uid=None*, *user_uid=None*, *destination_guid=None*, *include_backup_usage=None*, *include_counts=True*, *page_size=None*, *q=None*)

Gets a page of devices.

Parameters

- **page_num** (*int*) – The page number to request.
- **active** (*bool, optional*) – Filters results by device state. When set to True, gets all active devices. When set to False, gets all deactivated devices. When set to None or excluded, gets all devices regardless of state. Defaults to None.
- **blocked** (*bool, optional*) – Filters results by blocked status: True or False. Defaults to None.
- **org_uid** (*int, optional*) – The identification number of an Organization. Defaults to None.
- **user_uid** (*int, optional*) – The identification number of a User. Defaults to None.
- **destination_guid** (*str or int, optional*) – The globally unique identifier of the storage server that the device back up to. Defaults to None.
- **include_backup_usage** (*bool, optional*) – A flag to denote whether to include the destination and its backup stats. Defaults to None.
- **include_counts** (*bool, optional*) – A flag to denote whether to include total, warning, and critical counts. Defaults to True.
- **page_size** (*int, optional*) – The number of devices to return per page. Defaults to `py42.settings.items_per_page`.
- **q** (*str, optional*) – Searches results flexibly by incomplete GUID, hostname, computer name, etc. Defaults to None.

Returns `py42.response.Py42Response`

get_settings(*guid*)

Gets setting data for a device and returns a *DeviceSettings* object for the target device.

Parameters `guid (int, str)` – The globally unique identifier of the device.

Returns A class to help manage device settings.

Return type `py42.clients.settings.device_settings.DeviceSettings`

reactivate(*device_id*)

Activates a previously deactivated device.

Parameters `device_id (int)` – The identification number of the device.

Returns `py42.response.Py42Response`

```
unblock(device_id)
    Unblocks a device, permitting a user to be able to login and restore again.

    Parameters device_id (int) – The identification number of the device.

    Returns py42.response.Py42Response

update_settings(device_settings)
    Updates a device's settings based on changes to the passed in DeviceSettings or IncydrDeviceSettings instance. The appropriate instance for each device is returned by the get_settings() method.

    Parameters device_settings (DeviceSettings OR IncydrDeviceSettings) – An instance of DeviceSettings (Crashplan) or IncydrDeviceSettings (Incydr) with desired modifications to settings.

    Returns A response containing the result of the settings changes.

    Return type py42.response.Py42Response

upgrade(guid)
    Instructs a device to upgrade to the latest available version.

    Parameters guid (str) – The globally unique identifier of the device.

    Returns A response containing the result of the upgrade request.

    Return type py42.response.Py42Response
```

2.10 Device Settings

```
class py42.clients.settings.device_settings.IncydrDeviceSettings(settings_dict)
    Bases: collections.UserDict

    Class used to manage individual Incydr devices. These devices have no backup settings and only the notes and external_reference fields are modifiable.

    property computer_id
        Identifier of this device. Read-only.

    property device_id
        Identifier of this device (alias of .computer_id). Read only.

    external_reference
        External reference field for this device.

    property guid
        Globally unique identifier of this device. Read-only.

    property name
        Name of this device. Read-only.

    notes
        Notes field for this device.

    property org_id
        Identifier of the organization this device belongs to. Read-only.

    property user_id
        Identifier of the user this device belongs to. Read-only.

    property version
        Latest reported Code42 client version number for this device. Read-only.
```

```
class py42.clients.settings.device_settings.DeviceSettings(device_dict)
Bases: py42.clients.settings.device_settings.DeviceSettingsDefaults

Class used to manage an individual device's settings.

property available_destinations
    Returns a dict of destinations available to be used by devices. Dict keys are destination guids and values are destination names.

backup_sets
    List of BackupSet objects used to manage this device's backup set configurations.

backup_status_email_enabled
    Determines if the regularly scheduled backup status email is enabled.

backup_status_email_frequency_days
    Determines the frequency of the regularly scheduled backup status email.

property computer_id
    Identifier of this device. Read-only.

critical_alert_days
    The number of days a device can go without any backup activity before "warning" alert threshold is passed.

critical_email_enabled
    Determines if backup "critical" threshold email alerts are configured for this device.

property device_id
    Identifier of this device (alias of .computer_id). Read only.

external_reference
    External reference field for this device.

property guid
    Globally unique identifier of this device. Read-only.

property java_memory_heap_max
    The maximum memory the client will use on its system

name
    Name for this device.

notes
    Notes field for this device.

property org_id
    Identifier of the organization this device belongs to. Read-only.

property user_id
    Identifier of the user this device belongs to. Read-only.

property version
    Latest reported Code42 client version number for this device. Read-only.

warning_alert_days
    The number of days a device can go without any backup activity before "warning" alert threshold is passed.

warning_email_enabled
    Determines if backup "warning" threshold email alerts are configured for this device.
```

2.11 Exceptions

exception `py42.exceptions.Py42ActiveLegalHoldError(exception, resource, resource_id)`
Bases: `py42.exceptions.Py42BadRequestError`

An exception raised when attempting to deactivate a user or device that is in an active legal hold.

property resource

The user or device resource.

property resource_id

The resource ID.

property response

The response prior to the error.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42ArchiveFileNotFoundException(response, device_guid, file_path)`
Bases: `py42.exceptions.Py42ResponseError`

An exception raised when a resource file is not found or the path is invalid.

property device_guid

The device GUID provided.

property file_path

The file path provided.

property response

The response prior to the error.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42BadRequestError(exception, message=None, *args)`
Bases: `py42.exceptions.Py42HTTPError`

A wrapper to represent an HTTP 400 error.

property response

The response prior to the error.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42BadRestoreRequestError(exception)`
Bases: `py42.exceptions.Py42BadRequestError`

An error raised when the given restore arguments are not compatible and cause a bad request.

property response

The response prior to the error.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42CaseAlreadyHasEventError(exception)`
Bases: `py42.exceptions.Py42BadRequestError`

An error raised when event is already associated to the case.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.Py42CaseNameExistsError(exception, case_name)

Bases: [py42.exceptions.Py42BadRequestError](#)

An error raised when trying to create a case with a name that already exists.

property case_name

The case name.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.Py42ChecksumNotFoundError(response, checksum_name, checksum_value)

Bases: [py42.exceptions.Py42ResponseError](#)

An exception raised when a user-supplied hash could not successfully locate its corresponding resource.

property checksum_name

The checksum name.

property checksum_value

The checksum value.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.Py42CloudAliasCharacterLimitExceededError

Bases: [py42.exceptions.Py42Error](#)

An exception raised when trying to add a cloud alias to a user that exceeds the max character limit.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.Py42CloudAliasLimitExceededError(exception, message=None)

Bases: [py42.exceptions.Py42BadRequestError](#)

An Exception raised when trying to add a cloud alias to a user when that user already has the max amount of supported cloud aliases.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.Py42ConflictError(exception, message=None, *args)

Bases: [py42.exceptions.Py42HTTPError](#)

A wrapper to represent an HTTP 409 error.

property response

The response prior to the error.

```
with_traceback()
    Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.Py42DescriptionLimitExceededError(exception)
    Bases: py42.exceptions.Py42BadRequestError

    An error raised when description of a case exceeds the allowed char length limit.

property response
    The response prior to the error.

with_traceback()
    Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.Py42DeviceNotConnectedError(response, device_guid)
    Bases: py42.exceptions.Py42ResponseError

    An exception raised when trying to push a restore to a device that is not connected to an Authority server.

property device_guid
    The device GUID.

property response
    The response prior to the error.

with_traceback()
    Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.Py42Error
    Bases: Exception

    A generic, Py42 custom base exception.

with_traceback()
    Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.Py42FeatureUnavailableError(response)
    Bases: py42.exceptions.Py42ResponseError

    An exception raised when a requested feature is not supported in your Code42 environment.

property response
    The response prior to the error.

with_traceback()
    Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.Py42ForbiddenError(exception, message=None, *args)
    Bases: py42.exceptions.Py42HTTPError

    A wrapper to represent an HTTP 403 error.

property response
    The response prior to the error.

with_traceback()
    Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception py42.exceptions.Py42HTTPError(exception, message=None, *args)
    Bases: py42.exceptions.Py42ResponseError

    A base custom class to manage all HTTP errors raised by an API endpoint.

property response
    The response prior to the error.
```

with_traceback()
Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42InternalServerError(exception, message=None, *args)`
Bases: `py42.exceptions.Py42HTTPError`
A wrapper to represent an HTTP 500 error.

property response
The response prior to the error.

with_traceback()
Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42InvalidArchiveEncryptionKey(exception)`
Bases: `py42.exceptions.Py42HTTPError`
An exception raised the encryption key for an archive is invalid.

property response
The response prior to the error.

with_traceback()
Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42InvalidArchivePassword(exception)`
Bases: `py42.exceptions.Py42HTTPError`
An exception raised when the password for unlocking an archive is invalid.

property response
The response prior to the error.

with_traceback()
Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42InvalidCaseUserError(exception, user_uid)`
Bases: `py42.exceptions.Py42BadRequestError`
An error raised when a case subject or assignee is not a valid user.

property response
The response prior to the error.

property user
The user UID.

with_traceback()
Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42InvalidEmailError(email, exception)`
Bases: `py42.exceptions.Py42InternalServerError`
An exception raised when trying to set an invalid email as a user's email.

property email
The email being assigned to a user.

property response
The response prior to the error.

with_traceback()
Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42InvalidPageTokenError(exception, page_token)`

Bases: `py42.exceptions.Py42BadRequestError`

An error raised when the page token given is invalid.

property `page_token`

The page token.

property `response`

The response prior to the error.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42InvalidPasswordError(exception)`

Bases: `py42.exceptions.Py42InternalServerError`

An exception raised when trying to set an invalid password as a user's password.

property `response`

The response prior to the error.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42InvalidRuleError(exception, rule_id)`

Bases: `py42.exceptions.Py42NotFoundError`

An exception raised when the observer rule ID does not exist.

property `response`

The response prior to the error.

property `rule_id`

The observer rule ID.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42InvalidRuleOperationError(exception, rule_id, source)`

Bases: `py42.exceptions.Py42HTTPError`

An exception raised when trying to add or remove users to a system rule.

property `response`

The response prior to the error.

property `rule_id`

The rule ID.

property `source`

The rule source.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42InvalidUsernameError(exception)`

Bases: `py42.exceptions.Py42InternalServerError`

An exception raised when trying to set an invalid username as a user's username.

property `response`

The response prior to the error.

with_traceback()
Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42InvalidWatchlistType(exception, watchlist_type)`
Bases: `py42.exceptions.Py42BadRequestError`

An exception raised when an invalid watchlist type is specified.

property response
The response prior to the error.

property watchlist_type
The specified watchlist type.

with_traceback()
Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42LegalHoldAlreadyActiveError(exception, legal_hold_matter_uid)`
Bases: `py42.exceptions.Py42BadRequestError`

An exception raised when trying to activate a Legal Hold Matter that is already active.

property legal_hold_matter_uid
The legal hold matter UID.

property response
The response prior to the error.

with_traceback()
Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42LegalHoldAlreadyDeactivatedError(exception, legal_hold_matter_uid)`
Bases: `py42.exceptions.Py42BadRequestError`

An exception raised when trying to deactivate a Legal Hold Matter that is already inactive.

property legal_hold_matter_uid
The legal hold matter UID.

property response
The response prior to the error.

with_traceback()
Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42LegalHoldCriteriaMissingError(exception)`
Bases: `py42.exceptions.Py42BadRequestError`

An exception raised when a bad request was made to a Legal Hold endpoint.

property response
The response prior to the error.

with_traceback()
Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42LegalHoldNotFoundOrPermissionDeniedError(exception, resource_uid, legal_hold_resource='matter')`
Bases: `py42.exceptions.Py42ForbiddenError`

An exception raised when a legal hold matter is inaccessible from your account or the matter ID is not valid.

property response

The response prior to the error.

property uid

The UID of the legal hold resource.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42MFARequiredError(exception, message=None)`

Bases: `py42.exceptions.Py42UnauthorizedError`

Deprecated: An exception raised when a request requires multi-factor authentication

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42NotFoundError(exception, message=None, *args)`

Bases: `py42.exceptions.Py42HTTPError`

A wrapper to represent an HTTP 404 error.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42OrgNotFoundError(exception, org_uid)`

Bases: `py42.exceptions.Py42BadRequestError`

An exception raised when a 400 HTTP error message indicates that an organization was not found.

property org_uid

” The org UID.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42ResponseError(response, message, *args)`

Bases: `py42.exceptions.Py42Error`

A base custom class to manage all errors raised because of an HTTP response.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42SessionInitializationError(exception)`

Bases: `py42.exceptions.Py42Error`

An exception raised when a user connection is invalid. A connection might be invalid due to connection timeout, invalid token, etc.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42StorageSessionInitializationError(exception, message)`
Bases: `py42.exceptions.Py42HTTPError`

An exception raised when the user is not authorized to initialize a storage session. This may occur when trying to restore a file or trying to get events for file activity on removable media, in cloud sync folders, and browser uploads.

property response

The response prior to the error.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42TooManyRequestsError(exception, message=None, *args)`
Bases: `py42.exceptions.Py42HTTPError`

A wrapper to represent an HTTP 429 error.

property response

The response prior to the error.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42TrustedActivityConflictError(exception, value)`
Bases: `py42.exceptions.Py42ConflictError`

An error raised when theres a conflict with a trusted activity domain URL.

property response

The response prior to the error.

property value

The domain, URL or workspace name.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42TrustedActivityIdNotFoundError(exception, resource_id)`
Bases: `py42.exceptions.Py42NotFoundError`

An exception raised when the trusted activity ID does not exist.

property resource_id

The resource ID.

property response

The response prior to the error.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42TrustedActivityInvalidChangeError(exception)`
Bases: `py42.exceptions.Py42BadRequestError`

An error raised when an invalid change is being made to a trusted activity.

property response

The response prior to the error.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42TrustedActivityInvalidCharacterError(exception)`

Bases: `py42.exceptions.Py42BadRequestError`

An error raised when an invalid character is in a trusted activity value.

property response

The response prior to the error.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42UnableToCreateProfileError(exception, username)`

Bases: `py42.exceptions.Py42BadRequestError`

An error raised when trying to call the method for creating a detection-list user when the user does not exist or is currently awaiting the profile to get created on the back-end. Note: you are no longer able to create detection-list profiles using the API; py42 only returns already existing profiles.

property response

The response prior to the error.

property username

The username of the user.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42UnauthorizedError(exception, message=None, *args)`

Bases: `py42.exceptions.Py42HTTPError`

A wrapper to represent an HTTP 401 error.

property response

The response prior to the error.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42UpdateClosedCaseError(exception)`

Bases: `py42.exceptions.Py42BadRequestError`

An error raised when trying to update a closed case.

property response

The response prior to the error.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

exception `py42.exceptions.Py42UserAlreadyAddedError(exception, user_id, list_name)`

Bases: `py42.exceptions.Py42BadRequestError`

An exception raised when the user is already added to group or list, such as the Departing Employee list.

property response

The response prior to the error.

property user_id

The user ID.

with_traceback()

`Exception.with_traceback(tb)` – set `self.__traceback__` to `tb` and return `self`.

```
exception py42.exceptions.Py42UserAlreadyExistsError(exception, message=None)
```

Bases: [py42.exceptions.Py42InternalServerError](#)

An exception raised when a user already exists

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

```
exception py42.exceptions.Py42UserNotOnListError(exception, user_id, list_name)
```

Bases: [py42.exceptions.Py42NotFoundError](#)

An exception raised when the user is not on a detection list.

property list_name

The list name.

property response

The response prior to the error.

property user_id

The user ID.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

```
exception py42.exceptions.Py42UserRiskProfileNotFound(exception, user_id, identifier='ID')
```

Bases: [py42.exceptions.Py42NotFoundError](#)

An exception raised when the user with the given ID for a user risk profile was not found.

property response

The response prior to the error.

property user

The user identifier.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

```
exception py42.exceptions.Py42UsernameMustBeEmailError(exception)
```

Bases: [py42.exceptions.Py42InternalServerError](#)

An exception raised when trying to set a non-email as a user's username in a cloud environment.

property response

The response prior to the error.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

```
exception py42.exceptions.Py42WatchlistNotFound(exception, resource_id)
```

Bases: [py42.exceptions.Py42NotFoundError](#)

An exception raised when the watchlist with the given ID was not found.

property response

The response prior to the error.

property watchlist_id

The watchlist ID.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

exception `py42.exceptions.Py42WatchlistOrUserNotFound(exception, watchlist_id, user_id)`

Bases: `py42.exceptions.Py42NotFoundError`

An exception raised when the watchlist ID or the User ID does not exist.

property response

The response prior to the error.

property user_id

The user ID.

property watchlist_id

The watchlist ID.

with_traceback()

Exception.with_traceback(tb) – set self.__traceback__ to tb and return self.

py42.exceptions.raise_py42_error(raised_error)

Raises the appropriate `py42.exceptions.Py42HttpError` based on the given `HTTPError`'s response status code.

2.12 File Event Queries - V1 (DEPRECATED)

Warning: V1 file events, saved searches, and queries are **deprecated**.

For details on using the new file event data model, see the [V2 File Events User Guide](#).

class `py42.sdk.queries.fileevents.file_event_query.FileEventQuery(*args, **kwargs)`

Bases: `py42.sdk.queries.BaseQuery`

Helper class for building V1 Code42 Forensic Search queries.

A `FileEventQuery` instance's `all()` and `any()` take one or more `FilterGroup` objects to construct a query that can be passed to the `FileEventService.search()` method. `all()` returns results that match all of the provided filter criteria, `any()` will return results that match any of the filters.

For convenience, the `FileEventQuery` constructor does the same as `all()`.

Usage example:

```
email_filter = EmailSender.is_in(["test.user@example.com", "test.sender@example.com  
↳"])  
exposure_filter = ExposureType.exists()  
query = FileEventQuery.all(email_filter, exposure_filter)
```

2.12.1 Saved Searches

```
class py42.services.savedsearch.SavedSearchService(connection, file_event_service)
    Bases: py42.services BaseService
```

A service to interact with saved search APIs.

execute(*search_id*, *page_number*=None, *page_size*=None, *use_v2*=False)

Executes a saved search for given search Id, returns up to the first 10,000 events.

Parameters

- **search_id** (*str*) – Unique search Id of the saved search.
- **page_number** (*int, optional*) – The consecutive group of results of size *page_size* in the result set to return. Defaults to None.
- **page_size** (*int, optional*) – The maximum number of results to be returned. Defaults to None.
- **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns *py42.response.Py42Response*

get(*use_v2*=False)

Fetch details of existing saved searches.

The existing data model for file events and saved searches is deprecated. To use the updated data model for file events, [update your settings](#). Retrieving saved searches with V2 settings enabled will convert existing saved search queries to the V2 data model. Existing V1 queries that cannot be properly converted will be excluded from the response.

Parameters **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns *py42.response.Py42Response*

get_by_id(*search_id*, *use_v2*=False)

Fetch the details of a saved search by its given search Id.

The existing data model for file events and saved searches is deprecated. To use the updated data model for file events, [update your settings](#). Retrieving saved searches with V2 settings enabled will convert existing saved search queries to the V2 data model. Existing V1 queries that cannot be properly converted will be excluded from the response.

Parameters

- **search_id** (*str*) – Unique search Id of the saved search.
- **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns *py42.response.Py42Response*

get_query(*search_id*, *page_number*=None, *page_size*=None, *use_v2*=False)

Get the saved search in form of a query(*py42.sdk.queries.fileevents.file_event_query*).

Parameters

- **search_id** (*str*) – Unique search Id of the saved search.
- **page_number** (*int, optional*) – The consecutive group of results of size *page_size* in the result set to return. Defaults to None.
- **page_size** (*int, optional*) – The maximum number of results to be returned. Defaults to None.
- **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns `py42.sdk.queries.fileevents.v2.file_event_query.FileEventQuery`

search_file_events(*search_id*, *page_number*=None, *page_size*=None, *use_v2*=False)
Alias method for `execute()`. Executes a saved search for given search Id, returns up to the first 10,000 events.

To view more than the first 10,000 events:

- pass the `search_id` to `get_query()`
- pass the resulting query (`FileEventQuery`) to `search_all_file_events()`, use that method as normal.

Parameters

- **search_id** (*str*) – Unique search Id of the saved search.
- **page_number** (*int, optional*) – The consecutive group of results of size `page_size` in the result set to return. Defaults to None.
- **page_size** (*int, optional*) – The maximum number of results to be returned. Defaults to None.
- **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns `py42.response.Py42Response`

2.12.2 Filter Classes

The following classes construct filters for file event queries. Each filter class corresponds to a file event detail. Call the appropriate classmethod on your desired filter class with the value you want to match and it will return a `FilterGroup` object that can be passed to `FileEventQuery`'s `all()` or `any()` methods to create complex queries that match multiple filter rules.

Example:

To search for events observed for certain set of documents, you can use the `FileName` and `MD5` filter classes to construct `FilterGroups` that will search for matching filenames or (in case someone renamed the sensitive file) the known MD5 hashes of the files:

```
filename_filter = FileName.is_in(['confidential_plans.docx', 'confidential_plan_
˓→projections.xlsx'])
md5_filter = MD5.is_in(['133765f4fff5e3038b9352a4d14e1532',
˓→'ea16f0cbfc76f6eba292871f8a8c794b'])
```

See [Executing Searches](#) for more on building search queries.

Event Filters

util.create_exists_filter_group()

Creates a `FilterGroup` to find events where filter data exists. Useful for creating EXISTS filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters `term` (*str*) – The term of the filter.

Returns `FilterGroup`

util.create_not_exists_filter_group()

Creates a `FilterGroup` to find events where filter data does not exist. Useful for creating DOES_NOT_EXIST filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters `term` (`str`) – The term of the filter.

Returns `FilterGroup`

`util.create_greater_than_filter_group(value)`

Creates a `FilterGroup` for matching file events where the value with key `term` is greater than the given value. Useful for creating GREATER_THAN filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- `term` (`str`) – The term of the filter.
- `value` (`str or int`) – The value used to filter file events.

Returns `FilterGroup`

`util.create_less_than_filter_group(value)`

Creates a `FilterGroup` for matching file events where the value with key `term` is less than the given value. Useful for creating LESS_THAN filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- `term` (`str`) – The term of the filter.
- `value` (`str or int`) – The value used to filter file events.

Returns `FilterGroup`

`class py42.sdk.queries.fileevents.filters.event_filter.EventTimestamp`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterTimestampField, py42.choices.Choices`

V1 filter class that filters events based on the timestamp of the event that occurred.

Available event timestamp constants are provided as class attributes. These constants should be used only with class method `within_the_last`:

- `EventTimestamp.FIFTEEN_MINUTES`
- `EventTimestamp.ONE_HOUR`
- `EventTimestamp.THREE_HOURS`
- `EventTimestamp.TWELVE_HOURS`
- `EventTimestamp.ONE_DAY`
- `EventTimestamp.THREE_DAYS`
- `EventTimestamp.SEVEN_DAYS`
- `EventTimestamp.FOURTEEN_DAYS`
- `EventTimestamp.THIRTY_DAYS`

Example:: `filter = EventTimestamp.within_the_last(EventTimestamp.SEVEN_DAYS)`

`classmethod choices()`

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (`list`)

classmethod `in_range(start_value, end_value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- `start_value (str or int or float or datetime)` – The start value used to filter results.
- `end_value (str or int or float or datetime)` – The end value used to filter results.

Returns `FilterGroup`

classmethod `on_or_after(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term`` is on or after the provided ``value``.

Parameters `value(str or int or float or datetime)` – The value used to filter results.

Returns `FilterGroup`

classmethod `on_or_before(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters `value(str or int or float or datetime)` – The value used to filter results.

Returns `FilterGroup`

classmethod `on_same_day(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters `value(str or int or float or datetime)` – The value used to filter results.

Returns `FilterGroup`

classmethod `within_the_last(value)`

Returns a `FilterGroup` that is useful for finding results where the key `self._term` is a timestamp-related term, such as `EventTimestamp._term`, and `value` is one of its accepted values, such as one of the values in `EventTimestamp.choices()`.

Parameters `value(str)` – The value used to filter file events.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.filters.event_filter.EventType`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField, py42.choices.Choices`

V1 filter class that filters file events based on event type.

Available event types are provided as class attributes:

- `EventType.CREATED`
- `EventType.DELETED`
- `EventType.EMAILED`
- `EventType.MODIFIED`
- `EventType.READ_BY_APP`
- `EventType.PRINTED`

Example:

```
filter = EventType.isin([EventType.READ_BY_APP, EventType.EMAILED])
```

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (list) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.event_filter.InsertionTimestamp`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterTimestampField`

V1 filter class that filters events based on the timestamp of when the event was actually added to the event store (which can be after the event occurred on the device itself).

`value` must be a POSIX timestamp. (see the *Dates* section of the Basics user guide for details on timestamp arguments in py42)

classmethod in_range(start_value, end_value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- **start_value** (*str or int or float or datetime*) – The start value used to filter results.
- **end_value** (*str or int or float or datetime*) – The end value used to filter results.

Returns *FilterGroup*

classmethod **on_or_after**(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is on or after the provided ``value``.

Parameters **value** (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod **on_or_before**(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters **value** (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod **on_same_day**(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters **value** (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod **within_the_last**(*value*)

Returns a *FilterGroup* that is useful for finding results where the key `self._term` is a timestamp-related term, such as `EventTimestamp._term`, and `value` is one of its accepted values, such as one of the values in `EventTimestamp.choices()`.

Parameters **value** (*str*) – The value used to filter file events.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.event_filter.Source`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`, `py42.choices.Choices`

V1 filter class that filters events by event source.

Available source types are provided as class attributes:

- `Source.ENDPOINT`
- `Source.GOOGLE_DRIVE`
- `Source.ONE_DRIVE`
- `Source.BOX`
- `Source.GMAIL`
- `Source.OFFICE_365`

Example:

```
filter = Source.is_in([Source.ENDPOINT, Source.BOX])
```

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.event_filter.MimeTypeMismatch`

Bases: `py42.sdk.queries.query_filter.QueryFilterBooleanField`

V1 filter class that filters events by whether or not a file's mime type matches its extension type.

classmethod is_false()

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is False.

Returns *FilterGroup*

classmethod is_true()

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is True.

Returns *FilterGroup*

```
class py42.sdk.queries.fileevents.filters.event_filter.OutsideActiveHours
Bases: py42.sdk.queries.query_filter.QueryFilterBooleanField

V1 filter class that filters events by whether or not they occurred outside a user's typical working hours

classmethod is_false()
    Returns a FilterGroup that is useful for finding results where the value with key self._term is False.

    Returns FilterGroup

classmethod is_true()
    Returns a FilterGroup that is useful for finding results where the value with key self._term is True.

    Returns FilterGroup
```

File Filters

```
class py42.sdk.queries.fileevents.filters.file_filter.FileCategory
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField, py42.choices.Choices

V1 filter class that filters events by category of the file observed.

Available file categories are provided as class attributes:

- FileCategory.AUDIO
- FileCategory.DOCUMENT
- FileCategory.EXECUTABLE
- FileCategory.IMAGE
- FileCategory.PDF
- FileCategory.PRESENTATION
- FileCategory.SCRIPT
- FileCategory.SOURCE_CODE
- FileCategory.SPREADSHEET
- FileCategory.VIDEO
- FileCategory.VIRTUAL_DISK_IMAGE
- FileCategory.ZIP

classmethod choices()
    Returns attribute values for the given class.

    Returns A list containing the attribute values of the given class.

    Return type (list)

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

        Parameters value (str) – The value to match on.

        Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.
```

Returns *FilterGroup*

classmethod **is_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists**()
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.file_filter.FileName`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by the name of the file observed.

classmethod **eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **exists**()
Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod **is_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

```
classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

    Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not
    in the provided value_list.

    Parameters value_list (list) – The list of values to exclude on.

    Returns FilterGroup

class py42.sdk.queries.fileevents.filters.file_filter.FileOwner
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V1 filter class that filters events by the owner of the file observed.

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the
    provided value.

    Parameters value (str) – The value to match on.

    Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.

    Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in
    the provided value_list.

    Parameters value_list (list) – The list of values to match on.

    Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not
    equal the provided value.

    Parameters value (str) – The value to exclude on.

    Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

    Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not
    in the provided value_list.

    Parameters value_list (list) – The list of values to exclude on.

    Returns FilterGroup

class py42.sdk.queries.fileevents.filters.file_filter.FilePath
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V1 filter class that filters events by path of the file observed.
```

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.file_filter.FileSize

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterComparableField`

V1 filter class that filters events by size of the file observed.

Size value must be bytes.

classmethod greater_than(value)

Returns a *FilterGroup* to find events where filter data is greater than the provided value.

Parameters `value (str or int or float)` – The value used to filter file events.

Returns *FilterGroup*

classmethod less_than(value)

Returns a *FilterGroup* to find events where filter data is less than than the provided value.

Parameters `value (str or int or float)` – The value used to filter file events.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.file_filter.MD5

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by the MD5 hash of the file observed.

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_exists()

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod not_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.filters.file_filter.SHA256`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by SHA256 hash of the file observed.

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`
 Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
 Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
 Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

Device Filters

```
class py42.sdk.queries.fileevents.filters.device_filter.DeviceUsername
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V1 filter class that filters events by the Code42 username of the device that observed the event.

classmethod eq(value)  

Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

Parameters value (str) – The value to match on.

Returns FilterGroup

classmethod exists()  

Returns a FilterGroup to find events where filter data exists.

Returns FilterGroup

classmethod is_in(value_list)  

Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.

Parameters value_list (list) – The list of values to match on.

Returns FilterGroup

classmethod not_eq(value)  

Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.

Parameters value (str) – The value to exclude on.

Returns FilterGroup

classmethod not_exists()  

Returns a FilterGroup to find events where filter data does not exist.

Returns FilterGroup
```

```
classmethod not_in(value_list)
```

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns *FilterGroup*

```
class py42.sdk.queries.fileevents.filters.device_filter.OSHostname
```

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by hostname of the device that observed the event.

```
classmethod eq(value)
```

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns *FilterGroup*

```
classmethod exists()
```

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

```
classmethod is_in(value_list)
```

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns *FilterGroup*

```
classmethod not_eq(value)
```

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns *FilterGroup*

```
classmethod not_exists()
```

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

```
classmethod not_in(value_list)
```

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns *FilterGroup*

```
class py42.sdk.queries.fileevents.filters.device_filter.PrivateIPAddress
```

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by private (LAN) IP address of the device that observed the event.

```
classmethod eq(value)
```

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod exists()
Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod is_in(value_list)
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod not_eq(value)
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod not_exists()
Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod not_in(value_list)
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.filters.device_filter.PublicIPAddress`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by public (WAN) IP address of the device that observed the event.

classmethod eq(value)
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod exists()
Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod is_in(value_list)
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod not_eq(value)
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.filters.device_filter.DeviceSignedInUserName`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by signed in user of the device that observed the event.

classmethod `eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `exists()`
Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

Cloud Filters

```
class py42.sdk.queries.fileevents.filters.cloud_filter.Actor
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

    V1 filter class that filters events by the cloud service username of the event originator (applies to cloud data source events only).

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

        Parameters value (str) – The value to match on.

        Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.

        Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.

        Parameters value_list (list) – The list of values to match on.

        Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.

        Parameters value (str) – The value to exclude on.

        Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

        Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.

        Parameters value_list (list) – The list of values to exclude on.

        Returns FilterGroup
```

class py42.sdk.queries.fileevents.filters.cloud_filter.DirectoryID
 Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V1 filter class that filters events by unique identifier of the cloud drive or folder where the event occurred (applies to cloud data source events only).

classmethod eq(value)
 Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

 Parameters `value` (`str`) – The value to match on.

 Returns *FilterGroup*

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_exists()

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod not_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.filters.cloud_filter.Shared`

Bases: `py42.sdk.queries.query_filter.QueryFilterBooleanField`

V1 filter class that filters events by the shared status of the file at the time the event occurred (applies to cloud data source events only).

classmethod is_false()

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is False.

Returns [FilterGroup](#)

classmethod is_true()

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is True.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.filters.cloud_filter.SharedWith`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by the list of users who had been granted access to the file at the time of the event (applies to cloud data source events only).

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns *FilterGroup*

classmethod **is_in**(*value_list*)
 Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq**(*value*)
 Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists**()
 Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in**(*value_list*)
 Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.cloud_filter.SharingTypeAdded`
 Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`, `py42.choices.Choices`

V1 filter class that filters results to include events where a file's sharing permissions were changed to a value that increases exposure (applies to cloud data source events only).

Available options provided as class attributes:

- `SharingTypeAdded.SHARED_VIA_LINK`
- `SharingTypeAdded.IS_PUBLIC`
- `SharingTypeAdded.OUTSIDE_TRUSTED_DOMAIN`

classmethod **choices**()
 Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (*list*)

classmethod **eq**(*value*)
 Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **exists**()
 Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns *FilterGroup*

Exposure Filters

class `py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`, `py42.choices.Choices`

V1 filter class that filters events based on exposure type.

Available options are provided as class attributes:

- `ExposureType.SHARED_VIA_LINK`
- `ExposureType.SHARED_TO_DOMAIN`
- `ExposureType.APPLICATION_READ`
- `ExposureType.CLOUD_STORAGE`
- `ExposureType.REMOVABLE_MEDIA`
- `ExposureType.IS_PUBLIC`

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (`list`)

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.exposure_filter.ProcessName

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the process name involved in the exposure (applies to read by browser or other app events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod *not_exists()*
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod *not_in(value_list)*
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.exposure_filter.ProcessOwner`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the process owner that was involved in the exposure (applies to read by browser or other app events only).

classmethod *eq(value)*
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod *exists()*
Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod *is_in(value_list)*
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod *not_eq(value)*
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod *not_exists()*
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod *not_in(value_list)*
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaName`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the name of the removable media involved in the exposure (applies to removable media events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaVendor`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the vendor of the removable media device involved in the exposure (applies to removable media events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

```
classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.
        Parameters value_list (list) – The list of values to match on.
        Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.
        Parameters value (str) – The value to exclude on.
        Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.
        Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.
        Parameters value_list (list) – The list of values to exclude on.
        Returns FilterGroup

class py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaMediaName
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

    V1 filter class that filters events based on the name of the removable media (as reported by the vendor/device, usually very similar to RemovableMediaName) involved in the exposure (applies to removable media events only).

    classmethod eq(value)
        Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.
            Parameters value (str) – The value to match on.
            Returns FilterGroup

    classmethod exists()
        Returns a FilterGroup to find events where filter data exists.
            Returns FilterGroup

    classmethod is_in(value_list)
        Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.
            Parameters value_list (list) – The list of values to match on.
            Returns FilterGroup

    classmethod not_eq(value)
        Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.
            Parameters value (str) – The value to exclude on.
            Returns FilterGroup
```

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaVolumeName

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the name of the formatted volume (as reported by the operating system) of the removable media device involved in the exposure (applies to `removable_media` events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaPartitionID

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the unique identifier assigned (by the operating system) to the removable media involved in the exposure (applies to `removable_media` events only).

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_exists()

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod not_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaSerialNumber`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the serial number of the connected hardware as reported by the operating system (applies to `removable media` events only).

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists**()
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.exposure_filter.SyncDestination`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`, `py42.choices.Choices`

V1 filter class that filters events based on the name of the cloud service the file is synced with (applies to synced to cloud service events only).

Available options are provided as class attributes:

- `SyncDestination.ICLOUD`
- `SyncDestination.BOX`
- `SyncDestination.BOX_DRIVE`
- `SyncDestination.GOOGLE_DRIVE`
- `SyncDestination.GOOGLE_BACKUP_AND_SYNC`
- `SyncDestination.DROPBOX`
- `SyncDestination.ONEDRIVE`

classmethod **choices**()
Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (*list*)

classmethod **eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **exists**()
Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists`()

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.filters.exposure_filter.SyncDestinationUsername`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the username associated with the cloud service the file is synced with (applies to `synced_to` cloud service events only).

classmethod `eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `exists`()

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists`()

Returns a `FilterGroup` to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.exposure_filter.TabURL`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on all the URLs of the browser tabs at the time the file contents were read by the browser (applies to `read by browser` or `other app` events only).

classmethod `eq(value)`
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`
Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.exposure_filter.WindowTitle`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events based on the name of all the browser tabs or application windows that were open when a browser or other app event occurred (applies to `read by browser` or `other app` events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

Email Filters

class py42.sdk.queries.fileevents.filters.email_filter.EmailPolicyName

Bases: *py42.sdk.queries.query_filter.QueryFilterStringField*

V1 filter class that filters events based on the email DLP policy that detected this file (applies to emails sent via Microsoft Office 365 only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.email_filter.EmailSubject`
Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`

V1 filter class that filters events based on the email's subject (applies to email events only).

classmethod **eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **is_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.email_filter.EmailRecipients`
Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`

V1 filter class that filters events based on the email's recipient list (applies to email events only).

classmethod **eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **is_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.email_filter.EmailSender`
Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`

V1 filter class that filters events based on the email's sender (applies to email events only).

classmethod **eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **is_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.filters.email_filter.EmailFrom`
Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`

V1 filter class that filters events based on the display name of the email's sender, as it appears in the "From:" field in the email (applies to email events only).

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns [FilterGroup](#)

Activity Filters

class py42.sdk.queries.fileevents.filters.activity_filter.TrustedActivity

Bases: [py42.sdk.queries.query_filter.QueryFilterBooleanField](#)

V1 filter class that filters events based on whether activity can be trusted.

classmethod is_false()

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is False.

Returns [FilterGroup](#)

classmethod is_true()

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is True.

Returns [FilterGroup](#)

class py42.sdk.queries.fileevents.filters.activity_filter.RemoteActivity

Bases: [py42.sdk.queries.query_filter.QueryFilterBooleanField](#)

V1 filter class that filters events based on whether the activity was remote (took place outside of corporate IP range).

classmethod is_false()

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` is False.

Returns [FilterGroup](#)

classmethod `is_true()`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` is True.

Returns `FilterGroup`

Printer Filters

`class py42.sdk.queries.fileevents.filters.print_filter.Printer`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by printer name.

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `exists()`

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

`class py42.sdk.queries.fileevents.filters.print_filter.PrintJobName`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V1 filter class that filters events by print job name.

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()
Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

Risk Filters

```
class py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

    V1 filter class that filters events by risk indicator.

    Available options are provided as class attributes:
        • RiskIndicator.CloudDataExposures.PUBLIC CORPORATE BOX
        • RiskIndicator.CloudDataExposures.PUBLIC CORPORATE GOOGLE DRIVE
        • RiskIndicator.CloudDataExposures.PUBLIC CORPORATE ONEDRIVE
        • RiskIndicator.CloudDataExposures.SENT CORPORATE GMAIL
        • RiskIndicator.CloudDataExposures.SHARED CORPORATE BOX
        • RiskIndicator.CloudDataExposures.SHARED CORPORATE GOOGLE DRIVE
        • RiskIndicator.CloudDataExposures.SHARED CORPORATE ONEDRIVE
        • RiskIndicator.CloudStorageUploads.AMAZON DRIVE
        • RiskIndicator.CloudStorageUploads.BOX
        • RiskIndicator.CloudStorageUploads.DROPBOX
        • RiskIndicator.CloudStorageUploads.GOOGLE DRIVE
```

- RiskIndicator.CloudStorageUploads.ICLOUD
- RiskIndicator.CloudStorageUploads.MEGA
- RiskIndicator.CloudStorageUploads.ONEDRIVE
- RiskIndicator.CloudStorageUploads.ZOHO
- RiskIndicator.CodeRepositoryUploads.BITBUCKET
- RiskIndicator.CodeRepositoryUploads.GITHUB
- RiskIndicator.CodeRepositoryUploads.GITLAB
- RiskIndicator.CodeRepositoryUploads.SOURCEFORGE
- RiskIndicator.CodeRepositoryUploads.STASH
- RiskIndicator.EmailServiceUploads.ONESIXTHREE_DOT_COM
- RiskIndicator.EmailServiceUploads.ONETWOSIX_DOT_COM
- RiskIndicator.EmailServiceUploads.AOL
- RiskIndicator.EmailServiceUploads.COMCAST
- RiskIndicator.EmailServiceUploads.GMAIL
- RiskIndicator.EmailServiceUploads.ICLOUD
- RiskIndicator.EmailServiceUploads.MAIL_DOT_COM
- RiskIndicator.EmailServiceUploads.OUTLOOK
- RiskIndicator.EmailServiceUploads.PROTONMAIL
- RiskIndicator.EmailServiceUploads.QQMAIL
- RiskIndicator.EmailServiceUploads.SINA_MAIL
- RiskIndicator.EmailServiceUploads.SOHU_MAIL
- RiskIndicator.EmailServiceUploads.YAHOO
- RiskIndicator.EmailServiceUploads.ZOHO_MAIL
- RiskIndicator.ExternalDevices.AIRDROP
- RiskIndicator.ExternalDevices.REMOVABLE_MEDIA
- RiskIndicator.FileCategories.AUDIO
- RiskIndicator.FileCategories.DOCUMENT
- RiskIndicator.FileCategories.EXECUTABLE
- RiskIndicator.FileCategories.IMAGE
- RiskIndicator.FileCategories.PDF
- RiskIndicator.FileCategories.PRESENTATION
- RiskIndicator.FileCategories.SCRIPT
- RiskIndicator.FileCategories.SOURCE_CODE
- RiskIndicator.FileCategories.SPREADSHEET
- RiskIndicator.FileCategories.VIDEO
- RiskIndicator.FileCategories.VIRTUAL_DISK_IMAGE

- RiskIndicator.FileCategories.ZIP
- RiskIndicator.MessagingServiceUploads.FACEBOOK_MESSENGER
- RiskIndicator.MessagingServiceUploads.MICROSOFT_TEAMS
- RiskIndicator.MessagingServiceUploads.SLACK
- RiskIndicator.MessagingServiceUploads.WHATSAPP
- RiskIndicator.Other.OTHER
- RiskIndicator.Other.UNKNOWN
- RiskIndicator.SocialMediaUploads.FACEBOOK
- RiskIndicator.SocialMediaUploads.LINKEDIN
- RiskIndicator.SocialMediaUploads.REDDIT
- RiskIndicator.SocialMediaUploads.TWITTER
- RiskIndicator.UserBehavior.FILE_MISMATCH
- RiskIndicator.UserBehavior.OFF_HOURS
- RiskIndicator.UserBehavior.REMOTE
- RiskIndicator.UserBehavior.FIRST_DESTINATION_USE
- RiskIndicator.UserBehavior.RARE_DESTINATION_USE

class CloudDataExposures
 Bases: py42.choices.Choices

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

class CloudStorageUploads
 Bases: py42.choices.Choices

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

class CodeRepositoryUploads
 Bases: py42.choices.Choices

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

class EmailServiceUploads
 Bases: py42.choices.Choices

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

class ExternalDevices
 Bases: py42.choices.Choices

```
classmethod choices()
    Returns attribute values for the given class.
    Returns A list containing the attribute values of the given class.
    Return type (list)

class FileCategories
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class MessagingServiceUploads
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class Other
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class SocialMediaUploads
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class UserBehavior
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

    classmethod eq(value)
        Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

        Parameters value (str) – The value to match on.
        Returns FilterGroup

    classmethod exists()
        Returns a FilterGroup to find events where filter data exists.

        Returns FilterGroup

    classmethod is_in(value_list)
        Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.
```

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

```
class py42.sdk.queries.fileevents.filters.risk_filter.RiskSeverity
    Bases:      py42.sdk.queries.fileevents.util.FileEventFilterStringField,  py42.choices.Choices
```

V1 filter class that filters events by risk severity.

Available options are provided as class attributes:

- `RiskSeverity.LOW`
- `RiskSeverity.MODERATE`
- `RiskSeverity.HIGH`
- `RiskSeverity.CRITICAL`
- `RiskSeverity.NO_RISK_INDICATED`

classmethod `choices()`

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (`list`)

classmethod `eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `exists()`

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.filters.risk_filter.RiskScore`

Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`, `py42.sdk.queries.fileevents.util.FileEventFilterComparableField`

V1 filter class that filters events by risk score.

classmethod `eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `greater_than`(`value`)

Returns a `FilterGroup` to find events where filter data is greater than the provided value.

Parameters `value` (`str or int or float`) – The value used to filter file events.

Returns `FilterGroup`

classmethod `is_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `less_than`(`value`)

Returns a `FilterGroup` to find events where filter data is less than than the provided value.

Parameters `value` (`str or int or float`) – The value used to filter file events.

Returns `FilterGroup`

classmethod `not_eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_in(value_list)`
 Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

2.13 File Event Queries - V2

For details on using the new file event data model, see the [V2 File Events User Guide](#).

```
class py42.sdk.queries.fileevents.v2.file_event_query.FileEventQuery(*args, **kwargs)
Bases: py42.sdk.queries.BaseQuery
```

Helper class for building V2 Code42 Forensic Search queries.

A `FileEventQuery` instance's `all()` and `any()` take one or more `FilterGroup` objects to construct a query that can be passed to the `FileEventService.search()` method. `all()` returns results that match all of the provided filter criteria, `any()` will return results that match any of the filters.

For convenience, the `FileEventQuery` constructor does the same as `all()`.

Usage example:

```
email_filter = EmailSender.is_in(["test.user@example.com", "test.sender@example.com
                                "])
exposure_filter = ExposureType.exists()
query = FileEventQuery.all(email_filter, exposure_filter)
```

2.13.1 Saved Searches

Important: Make sure to set the optional argument `use_v2=True` on saved search functions to get V2 file event data and queries.

```
class py42.services.savedsearch.SavedSearchService(connection, file_event_service)
Bases: py42.services BaseService
```

A service to interact with saved search APIs.

```
execute(search_id, page_number=None, page_size=None, use_v2=False)
Executes a saved search for given search Id, returns up to the first 10,000 events.
```

Parameters

- **search_id (str)** – Unique search Id of the saved search.
- **page_number (int, optional)** – The consecutive group of results of size `page_size` in the result set to return. Defaults to None.
- **page_size (int, optional)** – The maximum number of results to be returned. Defaults to None.
- **use_v2 (bool)** – Flag to use v2 file events and saved searches. Defaults to False.

Returns `py42.response.Py42Response`

get(use_v2=False)

Fetch details of existing saved searches.

The existing data model for file events and saved searches is deprecated. To use the updated data model for file events, [update your settings](#). Retrieving saved searches with V2 settings enabled will convert existing saved search queries to the V2 data model. Existing V1 queries that cannot be properly converted will be excluded from the response.

Parameters `use_v2 (bool)` – Flag to use v2 file events and saved searches. Defaults to False.

Returns `py42.response.Py42Response`

get_by_id(search_id, use_v2=False)

Fetch the details of a saved search by its given search Id.

The existing data model for file events and saved searches is deprecated. To use the updated data model for file events, [update your settings](#). Retrieving saved searches with V2 settings enabled will convert existing saved search queries to the V2 data model. Existing V1 queries that cannot be properly converted will be excluded from the response.

Parameters

- `search_id (str)` – Unique search Id of the saved search.
- `use_v2 (bool)` – Flag to use v2 file events and saved searches. Defaults to False.

Returns `py42.response.Py42Response`

get_query(search_id, page_number=None, page_size=None, use_v2=False)

Get the saved search in form of a query(`py42.sdk.queries.fileevents.file_event_query`).

Parameters

- `search_id (str)` – Unique search Id of the saved search.
- `page_number (int, optional)` – The consecutive group of results of size `page_size` in the result set to return. Defaults to None.
- `page_size (int, optional)` – The maximum number of results to be returned. Defaults to None.
- `use_v2 (bool)` – Flag to use v2 file events and saved searches. Defaults to False.

Returns `py42.sdk.queries.fileevents.v2.file_event_query.FileEventQuery`

search_file_events(search_id, page_number=None, page_size=None, use_v2=False)

Alias method for `execute()`. Executes a saved search for given search Id, returns up to the first 10,000 events.

To view more than the first 10,000 events:

- pass the `search_id` to `get_query()`
- pass the resulting query (`FileEventQuery`) to `search_all_file_events()`, use that method as normal.

Parameters

- `search_id (str)` – Unique search Id of the saved search.
- `page_number (int, optional)` – The consecutive group of results of size `page_size` in the result set to return. Defaults to None.
- `page_size (int, optional)` – The maximum number of results to be returned. Defaults to None.

- **use_v2** (*bool*) – Flag to use v2 file events and saved searches. Defaults to False.

Returns `py42.response.Py42Response`

2.13.2 Filter Classes

The following classes construct filters for file event queries. Each filter class corresponds to a file event detail. Call the appropriate class method on your desired filter class with the value you want to match and it will return a `FilterGroup` object that can be passed to `FileEventQuery`'s `all()` or `any()` methods to create complex queries that match multiple filter rules.

Example:

To search for events observed for certain set of documents, you can use the `file.Name` and `file.MD5` filter classes to construct `FilterGroups` that will search for matching filenames or (in case someone renamed the sensitive file) the known MD5 hashes of the files:

```
from py42.sdk.queries.fileevents.v2 import *
filename_filter = File.Name.is_in(['confidential_plans.docx', 'confidential_plan_
˓→projections.xlsx'])
md5_filter = File.MD5.is_in(['133765f4fff5e3038b9352a4d14e1532',
˓→'ea16f0cbfc76f6eba292871f8a8c794b'])
```

See [Executing Searches](#) for more on building search queries.

Destination Filters

```
class py42.sdk.queries.fileevents.v2.filters.destination.Category
Bases:    py42.sdk.queries.fileevents.util.FileEventFilterStringField, py42.choices.Choices
```

V2 filter class that filters events based on the category of the file event destination.

Available options are provided as class attributes:

- `destination.category.CLOUD_STORAGE`
- `destination.category.DEVICE`
- `destination.category.EMAIL`
- `destination.category.MESSAGING`
- `destination.category.MULTIPLE_POSSIBILITIES`
- `destination.category.SOCIAL_MEDIA`
- `destination.category.SOURCE_CODE_REPOSITORY`
- `destination.category.UNCATEGORIZED`
- `destination.category.UNKNOWN`
- `destination.category.BUSINESS_INTELLIGENCE_TOOLS`
- `destination.category.CIVIL_SERVICES`
- `destination.category.CLOUD_COMPUTING`
- `destination.category.CODING_TOOLS`
- `destination.category.CONTRACT_MANAGEMENT`

- destination.category.CRM_TOOLS
- destination.category.DESIGN_TOOLS
- destination.category.E_COMMERCE
- destination.category.FILE_CONVERSION_TOOLS
- destination.category.FINANCIAL_SERVICES
- destination.category.HEALTHCARE_AND_INSURANCE
- destination.category.HR_TOOLS
- destination.category.IMAGE_HOSTING
- destination.category.IT_SERVICES
- destination.category.JOB_LISTINGS
- destination.category.LEARNING_PLATFORMS
- destination.category.MARKETING_TOOLS
- destination.category.PDF_MANAGER
- destination.category.PHOTO_PRINTING
- destination.category.PRODUCTIVITY_TOOLS
- destination.category.PROFESSIONAL_SERVICES
- destination.category.REAL_ESTATE
- destination.category.SALES_TOOLS
- destination.category.SEARCH_ENGINE
- destination.category.SHIPPING
- destination.category.SOFTWARE
- destination.category.TRAVEL
- destination.category.WEB_HOSTING

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.destination.EmailRecipients`
Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`

V2 filter class that filters events based on the email's recipient list (applies to email events only).

classmethod `eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `is_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.destination.EmailSubject`
Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`

V2 filter class that filters events based on the email's subject (applies to email events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.destination.IpAddress

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by public (WAN) IP address of the destination device.

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

```

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

    Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not
    in the provided value_list.

    Parameters value_list (list) – The list of values to exclude on.

    Returns FilterGroup

class py42.sdk.queries.fileevents.v2.filters.destination.Name
Bases: py42.sdk.queries.query\_filter.QueryFilterStringField

V2 filter class that filters events based on the destination name.

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the
    provided value.

    Parameters value (str) – The value to match on.

    Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in
    the provided value_list.

    Parameters value_list (list) – The list of values to match on.

    Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not
    equal the provided value.

    Parameters value (str) – The value to exclude on.

    Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not
    in the provided value_list.

    Parameters value_list (list) – The list of values to exclude on.

    Returns FilterGroup

class py42.sdk.queries.fileevents.v2.filters.destination.OperatingSystem
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events by the operating system of the destination device.

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the
    provided value.

    Parameters value (str) – The value to match on.

    Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.

```

```
    Returns FilterGroup
classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.
        Parameters value_list (list) – The list of values to match on.
    Returns FilterGroup
classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.
        Parameters value (str) – The value to exclude on.
    Returns FilterGroup
classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.
    Returns FilterGroup
classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.
        Parameters value_list (list) – The list of values to exclude on.
    Returns FilterGroup
class py42.sdk.queries.fileevents.v2.filters.destination.PrintJobName
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField
    V2 filter class that filters events by print job name.
classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.
        Parameters value (str) – The value to match on.
    Returns FilterGroup
classmethod exists()
    Returns a FilterGroup to find events where filter data exists.
    Returns FilterGroup
classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.
        Parameters value_list (list) – The list of values to match on.
    Returns FilterGroup
classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.
        Parameters value (str) – The value to exclude on.
    Returns FilterGroup
```

```
classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

    Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not
    in the provided value_list.

    Parameters value_list (list) – The list of values to exclude on.

    Returns FilterGroup

class py42.sdk.queries.fileevents.v2.filters.destination.PrintedFilesBackupPath
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events by the printed file backup path.

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the
    provided value.

    Parameters value (str) – The value to match on.

    Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.

    Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in
    the provided value_list.

    Parameters value_list (list) – The list of values to match on.

    Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not
    equal the provided value.

    Parameters value (str) – The value to exclude on.

    Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

    Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not
    in the provided value_list.

    Parameters value_list (list) – The list of values to exclude on.

    Returns FilterGroup

class py42.sdk.queries.fileevents.v2.filters.destination.PrinterName
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events by printer name.
```

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.destination.PrivateIpAddress

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by private (LAN) IP address of the destination device.

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaBusType`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the bus type of the connected hardware as reported by the operating system (applies to removable media events only).

classmethod `eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `exists()`
Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaCapacity`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the capacity of the connected hardware as reported by the operating system (applies to removable media events only).

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `exists()`

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaMediaName`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the name of the removable media (as reported by the vendor/device, usually very similar to RemovableMediaName) involved in the exposure (applies to removable media events only).

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaName

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the name of the removable media involved in the exposure (applies to removable media events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

```
    Returns FilterGroup
classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

    Returns FilterGroup
classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.
        Parameters value_list (list) – The list of values to exclude on.
    Returns FilterGroup

class py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaPartitionID
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events based on the unique identifier assigned (by the operating system) to the removable media involved in the exposure (applies to removable media events only).

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.
        Parameters value (str) – The value to match on.
    Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.
    Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.
        Parameters value_list (list) – The list of values to match on.
    Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.
        Parameters value (str) – The value to exclude on.
    Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.
    Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.
        Parameters value_list (list) – The list of values to exclude on.
    Returns FilterGroup

class py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaSerialNumber
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField
```

V2 filter class that filters events based on the serial number of the connected hardware as reported by the operating system (applies to `removable media` events only).

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `exists()`

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaVendor`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the vendor of the removable media device involved in the exposure (applies to `removable media` events only).

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `exists()`

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.destination.RemovableMediaVolumeName`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the name of the formatted volume (as reported by the operating system) of the removable media device involved in the exposure (applies to `removable media` events only).

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `exists()`

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.destination.TabTitleErrors`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on destination tab title errors (for ‘browser or other app’ events).

classmethod `eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `exists()`
Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.destination.TabTitles`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the name of all the browser tabs or application windows that were open when a browser or other app event occurred (applies to `read` by `browser` or `other app` events only).

classmethod `eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `exists()`
Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.destination.TabUrlErrors`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on destination tab URL Errors (for ‘browser or other app’ events).

classmethod `eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `exists()`
Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.destination.TabUrls

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on all the URLs of the browser tabs at the time the file contents were read by the browser (applies to `read_by_browser` or `other` app events only).

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns *FilterGroup*

class py42.sdk.queries.fileevents.v2.filters.destination.UserEmail
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events by the signed in user email of the destination device.

classmethod eq(value)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()
Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

Event Filters

class py42.sdk.queries.fileevents.v2.filters.event.Action
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField, py42.choices.Choices

V2 filter class that filters events based on event action.

classmethod choices()
Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

```

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

    Parameters value (str) – The value to match on.

    Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.

    Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.

    Parameters value_list (list) – The list of values to match on.

    Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.

    Parameters value (str) – The value to exclude on.

    Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

    Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.

    Parameters value_list (list) – The list of values to exclude on.

    Returns FilterGroup

class py42.sdk.queries.fileevents.v2.filters.event.Id
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

    V2 filter class that filters events by event ID.

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

    Parameters value (str) – The value to match on.

    Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.

    Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.

    Parameters value_list (list) – The list of values to match on.

```

Returns *FilterGroup*

classmethod `not_eq(value)`
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.event.Inserted`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterTimestampField`

V2 filter class that filters events based on the timestamp of when the event was actually added to the event store (which can be after the event occurred on the device itself).

`value` must be a POSIX timestamp. (see the [Dates](#) section of the Basics user guide for details on timestamp arguments in py42)

classmethod `in_range(start_value, end_value)`
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- `start_value (str or int or float or datetime)` – The start value used to filter results.
- `end_value (str or int or float or datetime)` – The end value used to filter results.

Returns *FilterGroup*

classmethod `on_or_after(value)`
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term`` is on or after the provided `value`.

Parameters `value (str or int or float or datetime)` – The value used to filter results.

Returns *FilterGroup*

classmethod `on_or_before(value)`
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters `value (str or int or float or datetime)` – The value used to filter results.

Returns *FilterGroup*

classmethod `on_same_day(value)`
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters `value (str or int or float or datetime)` – The value used to filter results.

Returns `FilterGroup`

classmethod `within_the_last(value)`

Returns a `FilterGroup` that is useful for finding results where the key `self._term` is a timestamp-related term, such as `EventTimestamp._term`, and `value` is one of its accepted values, such as one of the values in `EventTimestamp.choices()`.

Parameters `value (str)` – The value used to filter file events.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.event.Observer`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField, py42.choices.Choices`

V2 filter class that filters events by event observer.

Available event observer types are provided as class attributes:

- `event.Observer.ENDPOINT`
- `event.Observer.GOOGLE_DRIVE`
- `event.Observer.ONE_DRIVE`
- `event.Observer.BOX`
- `event.Observer.GMAIL`
- `event.Observer.OFFICE_365`

Example:: `filter = Event.Observer.is_in([event.Observer.ENDPOINT, event.Observer.BOX])`

classmethod `choices()`

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `exists()`

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.event.ShareType`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by share type.

classmethod `eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `exists()`
Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

File Filters

```
class py42.sdk.queries.fileevents.v2.filters.file.Category
    Bases:    py42.sdk.queries.fileevents.util.FileEventFilterStringField,  py42.choices.Choices
```

V2 filter class that filters events by category of the observed file.

Available file categories are provided as class attributes:

- `file.Category.AUDIO`
- `file.Category.DOCUMENT`
- `file.Category.EXECUTABLE`
- `file.Category.IMAGE`
- `file.Category.PDF`
- `file.Category.PRESENTATION`
- `file.Category.SCRIPT`
- `file.Category.SOURCE_CODE`
- `file.Category.SPREADSHEET`
- `file.Category.VIDEO`
- `file.Category.VIRTUAL_DISK_IMAGE`
- `file.Category.ZIP`

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (str) – The value to match on.

Returns `FilterGroup`

classmethod exists()

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod is_in(value_list)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (list) – The list of values to match on.

Returns `FilterGroup`

classmethod not_eq(value)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (str) – The value to exclude on.

Returns *FilterGroup*

classmethod *not_exists()*
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod *not_in(value_list)*
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.CategoryByBytes`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters event by the category (by bytes) of the observed file

classmethod *eq(value)*
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod *exists()*
Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod *is_in(value_list)*
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod *not_eq(value)*
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod *not_exists()*
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod *not_in(value_list)*
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.CategoryByExtension`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters event by the category (by bytes) of the observed file

```
classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

    Parameters value (str) – The value to match on.

    Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.

    Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.

    Parameters value_list (list) – The list of values to match on.

    Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.

    Parameters value (str) – The value to exclude on.

    Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

    Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.

    Parameters value_list (list) – The list of values to exclude on.

    Returns FilterGroup
```

class `py42.sdk.queries.fileevents.v2.filters.file.Classification`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the classification of the observed file.

```
classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

    Parameters value (str) – The value to match on.

    Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.

    Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.

    Parameters value_list (list) – The list of values to match on.
```

Returns *FilterGroup*

classmethod **not_eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists**()
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.CloudDriveId`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters event by the cloud drive ID of the observed file.

classmethod **eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **exists**()
Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod **is_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists**()
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.file.Created`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterTimestampField`

V2 filter class that filters events by the creation timestamp of the observed file.

classmethod `in_range(start_value, end_value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- `start_value (str or int or float or datetime)` – The start value used to filter results.
- `end_value (str or int or float or datetime)` – The end value used to filter results.

Returns `FilterGroup`

classmethod `on_or_after(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term`` is on or after the provided `value`.

Parameters `value (str or int or float or datetime)` – The value used to filter results.

Returns `FilterGroup`

classmethod `on_or_before(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters `value (str or int or float or datetime)` – The value used to filter results.

Returns `FilterGroup`

classmethod `on_same_day(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters `value (str or int or float or datetime)` – The value used to filter results.

Returns `FilterGroup`

classmethod `within_the_last(value)`

Returns a `FilterGroup` that is useful for finding results where the key `self._term` is a timestamp-related term, such as `EventTimestamp._term`, and `value` is one of its accepted values, such as one of the values in `EventTimestamp.choices()`.

Parameters `value (str)` – The value used to filter file events.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.file.Directory`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by directory of the observed file.

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()
Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.DirectoryId`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the directory ID of the observed file.

classmethod eq(value)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()
Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
 Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
 Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.file.Id`
 Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the ID of the observed file.

classmethod `eq(value)`
 Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `exists()`
 Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`
 Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`
 Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
 Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
 Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.file.MD5`
 Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the MD5 hash of the observed file.

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_exists()

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod not_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByBytes`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters event by the mime type (by bytes) of the observed file

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByExtension`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters event by the mime type (by extension) of the observed file

classmethod `eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `exists()`

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.Modified`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterTimestampField`

V2 filter class that filters events by the modification timestamp of the observed file.

classmethod in_range(start_value, end_value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- `start_value (str or int or float or datetime)` – The start value used to filter results.
- `end_value (str or int or float or datetime)` – The end value used to filter results.

Returns *FilterGroup*

classmethod on_or_after(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term`` is on or after the provided ``value.

Parameters `value (str or int or float or datetime)` – The value used to filter results.

Returns *FilterGroup*

classmethod on_or_before(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters `value (str or int or float or datetime)` – The value used to filter results.

Returns *FilterGroup*

classmethod on_same_day(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters `value (str or int or float or datetime)` – The value used to filter results.

Returns *FilterGroup*

classmethod within_the_last(value)

Returns a *FilterGroup* that is useful for finding results where the key `self._term` is a timestamp-related term, such as `EventTimestamp._term`, and value is one of its accepted values, such as one of the values in `EventTimestamp.choices()`.

Parameters `value (str)` – The value used to filter file events.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.file.Name`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the name of the observed file.

```
classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

    Parameters value (str) – The value to match on.

    Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.

    Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.

    Parameters value_list (list) – The list of values to match on.

    Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.

    Parameters value (str) – The value to exclude on.

    Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

    Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.

    Parameters value_list (list) – The list of values to exclude on.

    Returns FilterGroup
```

class `py42.sdk.queries.fileevents.v2.filters.file.Owner`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the owner of the observed file.

```
classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

    Parameters value (str) – The value to match on.

    Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.

    Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.

    Parameters value_list (list) – The list of values to match on.
```

Returns `FilterGroup`

classmethod `not_eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.file.SHA256`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by SHA256 hash of the observed file.

classmethod `eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `exists()`
Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list(list)` – The list of values to exclude on.

Returns `FilterGroup`

`class py42.sdk.queries.fileevents.v2.filters.file.Size`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterTimestampField`

V2 filter class that filters events by size in bytes of the observed file.

Size value must be bytes.

`classmethod in_range(start_value, end_value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- `start_value(str or int or float or datetime)` – The start value used to filter results.
- `end_value(str or int or float or datetime)` – The end value used to filter results.

Returns `FilterGroup`

`classmethod on_or_after(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term`` is on or after the provided ``value.

Parameters `value(str or int or float or datetime)` – The value used to filter results.

Returns `FilterGroup`

`classmethod on_or_before(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters `value(str or int or float or datetime)` – The value used to filter results.

Returns `FilterGroup`

`classmethod on_same_day(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters `value(str or int or float or datetime)` – The value used to filter results.

Returns `FilterGroup`

`classmethod within_the_last(value)`

Returns a `FilterGroup` that is useful for finding results where the key `self._term` is a timestamp-related term, such as `EventTimestamp._term`, and value is one of its accepted values, such as one of the values in `EventTimestamp.choices()`.

Parameters `value(str)` – The value used to filter file events.

Returns `FilterGroup`

`class py42.sdk.queries.fileevents.v2.filters.file.Url`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the URL of the observed file.

`classmethod eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod exists()
Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod is_in(value_list)
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod not_eq(value)
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod not_exists()
Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod not_in(value_list)
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

Process Filters

class `py42.sdk.queries.fileevents.v2.filters.process.Executable`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the process name involved in the exposure (applies to read by browser or other app events only).

classmethod eq(value)
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod exists()
Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod is_in(value_list)
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`
 Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
 Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
 Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.process.Owner`
 Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the process owner that was involved in the exposure (applies to `read` by browser or other app events only).

classmethod `eq(value)`
 Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `exists()`
 Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`
 Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`
 Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
 Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
 Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

Report Filters

```
class py42.sdk.queries.fileevents.v2.filters.report.Count  
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField, py42.sdk.queries.  
fileevents.util.FileEventFilterComparableField
```

V2 filter class that filters events by the record count of the report.

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `exists()`

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `greater_than(value)`

Returns a `FilterGroup` to find events where filter data is greater than the provided value.

Parameters `value (str or int or float)` – The value used to filter file events.

Returns `FilterGroup`

classmethod `is_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `less_than(value)`

Returns a `FilterGroup` to find events where filter data is less than than the provided value.

Parameters `value (str or int or float)` – The value used to filter file events.

Returns `FilterGroup`

classmethod `not_eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

```
class py42.sdk.queries.fileevents.v2.filters.report.Description
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField
```

V2 filter class that filters events by the description of the report.

classmethod eq(value)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()
Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

```
class py42.sdk.queries.fileevents.v2.filters.report.Headers
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField
```

V2 filter class that filters events by the header(s) of the report.

classmethod eq(value)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()
Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.report.ID`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the ID of the report.

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `exists()`

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`
 Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.report.Name`
 Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the name of the report.

classmethod `eq(value)`
 Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`
 Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`
 Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`
 Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`
 Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`
 Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.report.Type`
 Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the type of the report.

Available options are provided as class attributes:

- `attr report.Type.AD_HOC`
- `attr report.Type.SAVED`

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

Risk Filters

class py42.sdk.queries.fileevents.v2.filters.risk.Indicators

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the type of risk indicator.

Available options are provided as class attributes:

- `risk.Indicators.FileCategories.AUDIO`
- `risk.Indicators.FileCategories.DOCUMENT`
- `risk.Indicators.FileCategories.EXECUTABLE`
- `risk.Indicators.FileCategories.IMAGE`
- `risk.Indicators.FileCategories.PDF`
- `risk.Indicators.FileCategories.PRESENTATION`
- `risk.Indicators.FileCategories.SCRIPT`
- `risk.Indicators.FileCategories.SOURCE_CODE`

- risk.Indicators.FileCategories.SPREADSHEET
- risk.Indicators.FileCategories.VIDEO
- risk.Indicators.FileCategories.VIRTUAL_DISK_IMAGE
- risk.Indicators.FileCategories.ZIP
- risk.Indicators.UserBehavior.FILE_MISMATCH
- risk.Indicators.UserBehavior.OFF_HOURS
- risk.Indicators.UserBehavior.REMOTE
- risk.Indicators.UserBehavior.FIRST_DESTINATION_USE
- risk.Indicators.UserBehavior.RARE_DESTINATION_USE
- risk.Indicators.UserBehavior.CONTRACT
- risk.Indicators.UserBehavior.DEPARTING
- risk.Indicators.UserBehavior.ELEVATED_ACCESS
- risk.Indicators.UserBehavior.FLIGHT_RISK
- risk.Indicators.UserBehavior.HIGH_IMPACT
- risk.Indicators.UserBehavior.HIGH_RISK
- risk.Indicators.UserBehavior.PERFORMANCE_CONCERNS
- risk.Indicators.UserBehavior.POOR_SECURITY_PRACTICES
- risk.Indicators.UserBehavior.SUSPICIOUS_SYSTEM_ACTIVITY
- risk.Indicators.CloudStorageUploads.AMAZON_DRIVE
- risk.Indicators.CloudStorageUploads.BAIDU_NET_DISK_UPLOAD
- risk.Indicators.CloudStorageUploads.BOX
- risk.Indicators.CloudStorageUploads.CRASHPLAN_UPLOAD
- risk.Indicators.CloudStorageUploads.DRAKE_PORTALS_UPLOAD
- risk.Indicators.CloudStorageUploads.DROPBOX
- risk.Indicators.CloudStorageUploads.FILE_DOT_IO_UPLOAD
- risk.Indicators.CloudStorageUploads.FILESTACK_UPLOAD
- risk.Indicators.CloudStorageUploads.GOOGLE_DRIVE
- risk.Indicators.CloudStorageUploads.OPEN_TEXT_HIGHTAIL_UPLOAD
- risk.Indicators.CloudStorageUploads.ICLOUD
- risk.Indicators.CloudStorageUploads.MEGA
- risk.Indicators.CloudStorageUploads.ONEDRIVE
- risk.Indicators.CloudStorageUploads.SECURE_FIRM_PORTAL_UPLOAD
- risk.Indicators.CloudStorageUploads.SHAREFILE_UPLOAD
- risk.Indicators.CloudStorageUploads.SMART_VAULT_UPLOAD
- risk.Indicators.CloudStorageUploads.SUGAR_SYNC_UPLOAD
- risk.Indicators.CloudStorageUploads.WE_TRANSFER_UPLOAD

- risk.Indicators.CloudStorageUploads.ZOHO
- risk.Indicators.EmailServiceUploads.ONESIXTHREE_DOT_COM
- risk.Indicators.EmailServiceUploads.ONETWOSIX_DOT_COM
- risk.Indicators.EmailServiceUploads.AOL
- risk.Indicators.EmailServiceUploads.COMCAST
- risk.Indicators.EmailServiceUploads.FASTMAIL_UPLOAD
- risk.Indicators.EmailServiceUploads.GMAIL
- risk.Indicators.EmailServiceUploads.GMX_UPLOAD
- risk.Indicators.EmailServiceUploads.ICLOUD
- risk.Indicators.EmailServiceUploads.LYCOS_UPLOAD
- risk.Indicators.EmailServiceUploads.MAIL_DOT_COM_UPLOAD
- risk.Indicators.EmailServiceUploads.OUTLOOK
- risk.Indicators.EmailServiceUploads.PROTONMAIL
- risk.Indicators.EmailServiceUploads.QQMAIL
- risk.Indicators.EmailServiceUploads.SINA_MAIL
- risk.Indicators.EmailServiceUploads.SOHU_MAIL
- risk.Indicators.EmailServiceUploads.TUTANOTA_UPLOAD
- risk.Indicators.EmailServiceUploads.YAHOO
- risk.Indicators.EmailServiceUploads.ZIX_UPLOAD
- risk.Indicators.EmailServiceUploads.ZOHO_MAIL
- risk.Indicators.ExternalDevices.AIRDROP
- risk.Indicators.ExternalDevices.SALESFORCE_DOWNLOAD
- risk.Indicators.ExternalDevices.REMOVABLE_MEDIA
- Indicators.CloudDataExposures.PUBLIC_CORPORATE_BOX
- Indicators.CloudDataExposures.PUBLIC_CORPORATE_GOOGLE_DRIVE
- Indicators.CloudDataExposures.PUBLIC_CORPORATE_ONEDRIVE
- Indicators.CloudDataExposures.SENT_CORPORATE_GMAIL
- Indicators.CloudDataExposures.SENT_CORPORATE_OFFICE365
- Indicators.CloudDataExposures.SHARED_CORPORATE_BOX
- Indicators.CloudDataExposures.SHARED_CORPORATE_GOOGLE_DRIVE
- Indicators.CloudDataExposures.SHARED_CORPORATE_ONEDRIVE
- risk.Indicators.FileConversionToolUploads.CLOUD_CONVERT_UPLOAD
- risk.Indicators.FileConversionToolUploads.COMPRESS_JPEG_UPLOAD
- risk.Indicators.FileConversionToolUploads.FREE_CONVERT_UPLOAD
- risk.Indicators.FileConversionToolUploads.HEIC_TO_JPEG_UPLOAD
- risk.Indicators.FileConversionToolUploads.TINY_PNG_UPLOAD

- risk.Indicators.MessagingServiceUploads.DISCORD_UPLOAD
- risk.Indicators.MessagingServiceUploads.FACEBOOK_MESSENGER
- risk.Indicators.MessagingServiceUploads.GOOGLE_MESSAGES_UPLOAD
- risk.Indicators.MessagingServiceUploads.GOOGLE_CHAT_UPLOAD
- risk.Indicators.MessagingServiceUploads.GOOGLE_HANGOUTS_UPLOAD
- risk.Indicators.MessagingServiceUploads.MICROSOFT_TEAMS
- risk.Indicators.MessagingServiceUploads.SLACK
- risk.Indicators.MessagingServiceUploads.TELEGRAM_UPLOAD
- risk.Indicators.MessagingServiceUploads.WEBEX_UPLOAD
- risk.Indicators.MessagingServiceUploads.WE_CHAT_UPLOAD
- risk.Indicators.MessagingServiceUploads.WHATSAPP
- risk.Indicators.MessagingServiceUploads.ZOOM_UPLOAD
- risk.Indicators.Other.OTHER_DESTINATION
- risk.Indicators.Other.UNKNOWN_DESTINATION
- risk.Indicators.PdfManagerUploads.ADOBE_ACROBAT_UPLOAD
- risk.Indicators.PdfManagerUploads.COMBINE_PDF_UPLOAD
- risk.Indicators.PdfManagerUploads.FREE_PDF_CONVERT_UPLOAD
- risk.Indicators.PdfManagerUploads.I_LOVE_PDF_UPLOAD
- risk.Indicators.PdfManagerUploads.JPG2_PDF_UPLOAD
- risk.Indicators.PdfManagerUploads.PDF24_TOOLS_UPLOAD
- risk.Indicators.PdfManagerUploads.PDF_ESCAPE_UPLOAD
- risk.Indicators.PdfManagerUploads.PDF_FILLER_UPLOAD
- risk.Indicators.PdfManagerUploads.PDF_SIMPLI_UPLOAD
- risk.Indicators.PdfManagerUploads.SEJDA_UPLOAD
- risk.Indicators.PdfManagerUploads.SMALL_PDF_UPLOAD
- risk.Indicators.PdfManagerUploads.SODA_PDF_UPLOAD
- risk.Indicators.ProductivityToolUploads.ADOBE_UPLOAD
- risk.Indicators.ProductivityToolUploads.CANVA_UPLOAD
- risk.Indicators.ProductivityToolUploads.EVERNOTE_UPLOAD
- risk.Indicators.ProductivityToolUploads.FIGMA_UPLOAD
- risk.Indicators.ProductivityToolUploads.GOOGLE_KEEP_UPLOAD
- risk.Indicators.ProductivityToolUploads.GOOGLE_JAMBOARD_UPLOAD
- risk.Indicators.ProductivityToolUploads.IMAGE_COLOR_PICKER_UPLOAD
- risk.Indicators.ProductivityToolUploads.KAPWING_UPLOAD
- risk.Indicators.ProductivityToolUploads.MIRO_UPLOAD
- risk.Indicators.ProductivityToolUploads.MONDAY_UPLOAD

- risk.Indicators.ProductivityToolUploads.MURAL_UPLOAD
- risk.Indicators.ProductivityToolUploads.NOTION_UPLOAD
- risk.Indicators.ProductivityToolUploads.OVERLEAF_UPLOAD
- risk.Indicators.ProductivityToolUploads.PHOTOPEA_UPLOAD
- risk.Indicators.ProductivityToolUploads.PIXLR_UPLOAD
- risk.Indicators.ProductivityToolUploads.REMOVE_DOT_BG_UPLOAD
- risk.Indicators.ProductivityToolUploads.TRELLO_UPLOAD
- risk.Indicators.ProductivityToolUploads.VEED_UPLOAD
- risk.Indicators.SocialMediaUploads.FOUR_CHAN_UPLOAD
- risk.Indicators.SocialMediaUploads.FACEBOOK
- risk.Indicators.SocialMediaUploads.IMGUR_UPLOAD
- risk.Indicators.SocialMediaUploads.LINKEDIN
- risk.Indicators.SocialMediaUploads.ODNOKLASSNIKI_UPLOAD
- risk.Indicators.SocialMediaUploads.OK_UPLOAD
- risk.Indicators.SocialMediaUploads.QZONE_UPLOAD
- risk.Indicators.SocialMediaUploads.REDDIT
- risk.Indicators.SocialMediaUploads.STACK_OVERFLOW_UPLOAD
- risk.Indicators.SocialMediaUploads.TUMBLR_UPLOAD
- risk.Indicators.SocialMediaUploads.TWITCH_UPLOAD
- risk.Indicators.SocialMediaUploads.TWITTER
- risk.Indicators.SocialMediaUploads.VIMEO_UPLOAD
- risk.Indicators.SocialMediaUploads.VK_UPLOAD
- risk.Indicators.SocialMediaUploads.WEIBO_UPLOAD
- risk.Indicators.SocialMediaUploads.YOU_TUBE_UPLOAD
- risk.Indicators.CodeRepositoryUploads.BITBUCKET_UPLOAD
- risk.Indicators.CodeRepositoryUploads.COLABORATORY_UPLOAD
- risk.Indicators.CodeRepositoryUploads.GITHUB
- risk.Indicators.CodeRepositoryUploads.GITLAB
- risk.Indicators.CodeRepositoryUploads.GOOGLE_APPS_SCRIPT_UPLOAD
- risk.Indicators.CodeRepositoryUploads.GOOGLE_CLOUD_SHELL_UPLOAD
- risk.Indicators.CodeRepositoryUploads.SOURCE_FORGE
- risk.Indicators.CodeRepositoryUploads.STASH
- risk.Indicators.WebHostingUploads.GIT_HUB_PAGES_UPLOAD
- risk.Indicators.WebHostingUploads.GOOGLE_SITES_UPLOAD
- risk.Indicators.WebHostingUploads.WIX_UPLOAD
- risk.Indicators.WebHostingUploads.WORD_PRESS_UPLOAD

```
class CloudDataExposures
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class CloudStorageUploads
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class CodeRepositoryUploads
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class EmailServiceUploads
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class ExternalDevices
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class FileCategories
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class FileConversionToolUploads
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
        Returns A list containing the attribute values of the given class.
        Return type (list)

class MessagingServiceUploads
    Bases: py42.choices.Choices

    classmethod choices()
        Returns attribute values for the given class.
```

Returns A list containing the attribute values of the given class.
Return type (list)

class Other
Bases: py42.choices.Choices

classmethod choices()
Returns attribute values for the given class.
Returns A list containing the attribute values of the given class.
Return type (list)

class PdfManagerUploads
Bases: py42.choices.Choices

classmethod choices()
Returns attribute values for the given class.
Returns A list containing the attribute values of the given class.
Return type (list)

class ProductivityToolUploads
Bases: py42.choices.Choices

classmethod choices()
Returns attribute values for the given class.
Returns A list containing the attribute values of the given class.
Return type (list)

class SocialMediaUploads
Bases: py42.choices.Choices

classmethod choices()
Returns attribute values for the given class.
Returns A list containing the attribute values of the given class.
Return type (list)

class UserBehavior
Bases: py42.choices.Choices

classmethod choices()
Returns attribute values for the given class.
Returns A list containing the attribute values of the given class.
Return type (list)

class WebHostingUploads
Bases: py42.choices.Choices

classmethod choices()
Returns attribute values for the given class.
Returns A list containing the attribute values of the given class.
Return type (list)

classmethod eq(value)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` – The value to match on.

Returns *FilterGroup*

classmethod exists()
Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod **is_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **not_eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters **value** (*str*) – The value to exclude on.

Returns *FilterGroup*

classmethod **not_exists**()
Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod **not_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.risk.IndicatorsWeight`
Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`, `py42.sdk.queries.fileevents.util.FileEventFilterComparableField`
V2 filter class that filters events by the risk indicator weight.

classmethod **eq**(*value*)
Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters **value** (*str*) – The value to match on.

Returns *FilterGroup*

classmethod **greater_than**(*value*)
Returns a *FilterGroup* to find events where filter data is greater than the provided value.

Parameters **value** (*str or int or float*) – The value used to filter file events.

Returns *FilterGroup*

classmethod **is_in**(*value_list*)
Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided *value_list*.

Parameters **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

classmethod **less_than**(*value*)
Returns a *FilterGroup* to find events where filter data is less than than the provided value.

Parameters **value** (*str or int or float*) – The value used to filter file events.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.risk.Score`

Bases: `py42.sdk.queries.query_filter.QueryFilterStringField`, `py42.sdk.queries.fileevents.util.FileEventFilterComparableField`

V2 filter class that filters events by risk score.

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod greater_than(value)

Returns a *FilterGroup* to find events where filter data is greater than the provided value.

Parameters `value (str or int or float)` – The value used to filter file events.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod less_than(value)

Returns a *FilterGroup* to find events where filter data is less than than the provided value.

Parameters `value (str or int or float)` – The value used to filter file events.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod not_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

```
class py42.sdk.queries.fileevents.v2.filters.risk.Severity
    Bases:      py42.sdk.queries.fileevents.util.FileEventFilterStringField,  py42.choices.Choices
```

V2 filter class that filters events by risk severity.

Available options are provided as class attributes:

- `risk.Severity.LOW`
- `risk.Severity.MODERATE`
- `risk.Severity.HIGH`
- `risk.Severity.CRITICAL`
- `risk.Severity.NO_RISK_INDICATED`

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (str) – The value to exclude on.

Returns *FilterGroup*

classmethod not_exists()

Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod not_in(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (list) – The list of values to exclude on.

Returns `FilterGroup`

```
class py42.sdk.queries.fileevents.v2.filters.risk.TrustReason
    Bases: py42.sdk.queries.query_filter.QueryFilterStringField, py42.choices.Choices
```

V2 filter class that filters events based on the trust reason for the activity.

Available options are provided as class attributes:

- `attr risk.TrustReason.TRUSTED_DOMAIN_BROWSER_URL`
- `attr risk.TrustReason.TRUSTED_BROWSER_URL_PATH`
- `attr risk.TrustReason.TRUSTED_DOMAIN_BROWSER_TAB_TITLE`
- `attr risk.TrustReason.TRUSTED_BROWSER_TAB_INFOS`
- `attr risk.TrustReason.TRUSTED_DOMAIN_EMAIL_RECIPIENT`
- `attr risk.TrustReason.TRUSTED_DOMAIN_CLOUD_SYNC_USERNAME`
- `attr risk.TrustReason.TRUSTED_SLACK_WORKSPACE`
- `attr risk.TrustReason.EVENT_PAIRING_SERVICE_MATCH`
- `attr risk.TrustReason.EVENT_PAIRING_SERVICE_ENDPOINT_MATCH`
- `attr risk.TrustReason.DOWNLOAD_TO_A_MANAGED_DEVICE`
- `attr risk.TrustReason.SHARED_WITH_TRUSTED_USERS`

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (str) – The value to match on.

Returns `FilterGroup`

classmethod is_in(value_list)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (list) – The list of values to match on.

Returns `FilterGroup`

classmethod not_eq(value)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (str) – The value to exclude on.

Returns `FilterGroup`

classmethod not_in(value_list)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (list) – The list of values to exclude on.

Returns *FilterGroup*

```
class py42.sdk.queries.fileevents.v2.filters.risk.Trusted
    Bases: py42.sdk.queries.query_filter.QueryFilterBooleanField
```

V2 filter class that filters events based on whether activity can be trusted.

classmethod is_false()

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is False.

Returns *FilterGroup*

classmethod is_true()

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is True.

Returns *FilterGroup*

Source Filters

```
class py42.sdk.queries.fileevents.v2.filters.source.Category
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField, py42.choices.Choices
```

V2 filter class that filters events based on source category.

Available options are provided as class attributes:

- `source.Category.BUSINESS_TOOLS`
- `source.Category.CLOUD_STORAGE`
- `source.Category.DEVICE`
- `source.Category.EMAIL`
- `source.Category.MESSAGING`
- `source.Category.MULTIPLE_POSSIBILITIES`
- `source.Category.SOCIAL_MEDIA`
- `source.Category.SOURCE_CODE_REPOSITORY`
- `source.Category.UNCATEGORIZED`
- `source.Category.UNKNOWN`
- `source.category.BUSINESS_INTELLIGENCE_TOOLS`
- `source.category.CIVIL_SERVICES`
- `source.category.CLOUD COMPUTING`
- `source.category.CODING_TOOLS`
- `source.category.CONTRACT_MANAGEMENT`
- `source.category.CRM_TOOLS`
- `source.category.DESIGN_TOOLS`
- `source.category.E_COMMERCE`
- `source.category.FILE_CONVERSION_TOOLS`
- `source.category.FINANCIAL_SERVICES`
- `source.category.HEALTHCARE_AND_INSURANCE`

- source.category.HR_TOOLS
- source.category.IMAGE_HOSTING
- source.category.IT_SERVICES
- source.category.JOB_LISTINGS
- source.category.LEARNING_PLATFORMS
- source.category.MARKETING_TOOLS
- source.category.PDF_MANAGER
- source.category.PHOTO_PRINTING
- source.category.PRODUCTIVITY_TOOLS
- source.category.PROFESSIONAL_SERVICES
- source.category.REAL_ESTATE
- source.category.SALES_TOOLS
- source.category.SEARCH_ENGINE
- source.category.SHIPPING
- source.category.SOFTWARE
- source.category.TRAVEL
- source.category.WEB_HOSTING

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (str) – The value to match on.

Returns *FilterGroup*

classmethod exists()

Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod is_in(value_list)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (list) – The list of values to match on.

Returns *FilterGroup*

classmethod not_eq(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (str) – The value to exclude on.

Returns *FilterGroup*

```

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

    Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not
    in the provided value_list.

    Parameters value_list (list) – The list of values to exclude on.

    Returns FilterGroup

class py42.sdk.queries.fileevents.v2.filters.source.Domain
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events by the domain of the source device.

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the
    provided value.

    Parameters value (str) – The value to match on.

    Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.

    Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in
    the provided value_list.

    Parameters value_list (list) – The list of values to match on.

    Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not
    equal the provided value.

    Parameters value (str) – The value to exclude on.

    Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

    Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not
    in the provided value_list.

    Parameters value_list (list) – The list of values to exclude on.

    Returns FilterGroup

class py42.sdk.queries.fileevents.v2.filters.source.EmailFrom
Bases: py42.sdk.queries.query\_filter.QueryFilterStringField

V2 filter class that filters events based on the display name of the email's sender, as it appears in the "From:" field in the email (applies to email events only).

```

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns [FilterGroup](#)

class `py42.sdk.queries.fileevents.v2.filters.source.EmailSender`

Bases: [py42.sdk.queries.query_filter.QueryFilterStringField](#)

V2 filter class that filters events based on the email's sender (applies to email events only).

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns *FilterGroup*

```
class py42.sdk.queries.fileevents.v2.filters.source.IpAddress
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

    V2 filter class that filters events by public (WAN) IP address of the source device.

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

        Parameters value (str) – The value to match on.

        Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.

        Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.

        Parameters value_list (list) – The list of values to match on.

        Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.

        Parameters value (str) – The value to exclude on.

        Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

        Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.

        Parameters value_list (list) – The list of values to exclude on.

        Returns FilterGroup
```

class py42.sdk.queries.fileevents.v2.filters.source.Name

Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events based on source name.

classmethod eq(*value*)
 Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

 Parameters *value* (*str*) – The value to match on.

 Returns *FilterGroup*

classmethod exists()
 Returns a *FilterGroup* to find events where filter data exists.

 Returns *FilterGroup*

classmethod `is_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists`()

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.source.OperatingSystem`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by the operating system of the source device.

classmethod `eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `exists`()

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists`()

Returns a `FilterGroup` to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`
 Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.source.PrivateIpAddress`
 Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events by private (LAN) IP address of the source device.

classmethod `eq(value)`
 Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns *FilterGroup*

classmethod `exists()`
 Returns a *FilterGroup* to find events where filter data exists.

Returns *FilterGroup*

classmethod `is_in(value_list)`
 Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns *FilterGroup*

classmethod `not_eq(value)`
 Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns *FilterGroup*

classmethod `not_exists()`
 Returns a *FilterGroup* to find events where filter data does not exist.

Returns *FilterGroup*

classmethod `not_in(value_list)`
 Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

class `py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBusType`
 Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the bus type of the connected hardware as reported by the operating system (applies to removable media events only).

classmethod `eq(value)`
 Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `exists()`
Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`
Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCapacity`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the capacity of the connected hardware as reported by the operating system (applies to removable media events only).

classmethod `eq(value)`
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `exists()`
Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

```

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.

    Parameters value (str) – The value to exclude on.

    Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

    Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.

    Parameters value_list (list) – The list of values to exclude on.

    Returns FilterGroup

class py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaMediaName
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

    V2 filter class that filters events based on the name of the removable media (as reported by the vendor/device, usually very similar to RemovableMediaName) involved in the exposure (applies to removable media events only).

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

    Parameters value (str) – The value to match on.

    Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.

    Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.

    Parameters value_list (list) – The list of values to match on.

    Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.

    Parameters value (str) – The value to exclude on.

    Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

    Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.

```

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaName`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the name of the removable media involved in the exposure (applies to `removable media` events only).

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `exists()`

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaPartitionID`
Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the unique identifier assigned (by the operating system) to the removable media involved in the exposure (applies to `removable media` events only).

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns [FilterGroup](#)

classmethod not_exists()

Returns a [FilterGroup](#) to find events where filter data does not exist.

Returns [FilterGroup](#)

classmethod not_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns [FilterGroup](#)

class py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaSerialNumber

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on the serial number of the connected hardware as reported by the operating system (applies to `removable media` events only).

classmethod eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns [FilterGroup](#)

classmethod exists()

Returns a [FilterGroup](#) to find events where filter data exists.

Returns [FilterGroup](#)

classmethod is_in(value_list)

Returns a [FilterGroup](#) that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns [FilterGroup](#)

classmethod not_eq(value)

Returns a [FilterGroup](#) that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

```
    Returns FilterGroup
classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.

    Returns FilterGroup
classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.
        Parameters value_list (list) – The list of values to exclude on.
        Returns FilterGroup
class py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVendor
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

V2 filter class that filters events based on the vendor of the removable media device involved in the exposure (applies to removable media events only).

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.
        Parameters value (str) – The value to match on.
        Returns FilterGroup
classmethod exists()
    Returns a FilterGroup to find events where filter data exists.
        Returns FilterGroup
classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.
        Parameters value_list (list) – The list of values to match on.
        Returns FilterGroup
classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.
        Parameters value (str) – The value to exclude on.
        Returns FilterGroup
classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.
        Returns FilterGroup
classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.
        Parameters value_list (list) – The list of values to exclude on.
        Returns FilterGroup
class py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVolumeName
Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField
```

V2 filter class that filters events based on the name of the formatted volume (as reported by the operating system) of the removable media device involved in the exposure (applies to `removable media` events only).

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `exists()`

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists()`

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on source tab title errors (for ‘browser or other app’ events).

classmethod `eq(value)`

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod `exists()`

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in(value_list)`

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists`()

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod `not_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to exclude on.

Returns `FilterGroup`

class `py42.sdk.queries.fileevents.v2.filters.source.TabTitles`

Bases: `py42.sdk.queries.fileevents.util.FileEventFilterStringField`

V2 filter class that filters events based on source tab titles (for ‘browser or other app’ events).

classmethod `eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value` (`str`) – The value to match on.

Returns `FilterGroup`

classmethod `exists`()

Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod `is_in`(`value_list`)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list` (`list`) – The list of values to match on.

Returns `FilterGroup`

classmethod `not_eq`(`value`)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value` (`str`) – The value to exclude on.

Returns `FilterGroup`

classmethod `not_exists`()

Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

```
classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.
        Parameters value_list (list) – The list of values to exclude on.
        Returns FilterGroup

class py42.sdk.queries.fileevents.v2.filters.source.TabUrlErrors
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField
    V2 filter class that filters events based on source tab URL Errors (for ‘browser or other app’ events).

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.
        Parameters value (str) – The value to match on.
        Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.
        Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.
        Parameters value_list (list) – The list of values to match on.
        Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.
        Parameters value (str) – The value to exclude on.
        Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.
        Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.
        Parameters value_list (list) – The list of values to exclude on.
        Returns FilterGroup

class py42.sdk.queries.fileevents.v2.filters.source.TabUrls
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField
    V2 filter class that filters events based on source tab URLs (for ‘browser or other app’ events).

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.
        Parameters value (str) – The value to match on.
```

Returns `FilterGroup`

classmethod exists()
Returns a `FilterGroup` to find events where filter data exists.

Returns `FilterGroup`

classmethod is_in(value_list)
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod not_eq(value)
Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod not_exists()
Returns a `FilterGroup` to find events where filter data does not exist.

Returns `FilterGroup`

classmethod not_in(value_list)
Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns `FilterGroup`

Timestamp Filters

```
class py42.sdk.queries.fileevents.v2.filters.timestamp.Timestamp
Bases: py42.sdk.queries.fileevents.util.FileEventFilterTimestampField, py42.choices.Choices
```

V2 filter class that filters events based on the timestamp of the event that occurred.

Available event timestamp constants are provided as class attributes. These constants should be used only with class method `within_the_last`:

- `timestamp.Timestamp.FIFTEEN_MINUTES`
- `timestamp.Timestamp.ONE_HOUR`
- `timestamp.Timestamp.THREE_HOURS`
- `timestamp.Timestamp.TWELVE_HOURS`
- `timestamp.Timestamp.ONE_DAY`
- `timestamp.Timestamp.THREE_DAYS`
- `timestamp.Timestamp.SEVEN_DAYS`
- `timestamp.Timestamp.FOURTEEN_DAYS`
- `timestamp.Timestamp.THIRTY_DAYS`

Example:: filter = timestamp.Timestamp.within_the_last(EventTimestamp.SEVEN_DAYS)

classmethod choices()

Returns attribute values for the given class.

Returns A list containing the attribute values of the given class.

Return type (list)

classmethod in_range(start_value, end_value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- **start_value** (str or int or float or datetime) – The start value used to filter results.
- **end_value** (str or int or float or datetime) – The end value used to filter results.

Returns *FilterGroup*

classmethod on_or_after(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term`` is on or after the provided ``value``.

Parameters `value` (str or int or float or datetime) – The value used to filter results.

Returns *FilterGroup*

classmethod on_or_before(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters `value` (str or int or float or datetime) – The value used to filter results.

Returns *FilterGroup*

classmethod on_same_day(value)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters `value` (str or int or float or datetime) – The value used to filter results.

Returns *FilterGroup*

classmethod within_the_last(value)

Returns a *FilterGroup* that is useful for finding results where the key `self._term` is a timestamp-related term, such as `EventTimestamp._term`, and value is one of its accepted values, such as one of the values in `EventTimestamp.choices()`.

Parameters `value` (str) – The value used to filter file events.

Returns *FilterGroup*

User Filters

```
class py42.sdk.queries.fileevents.v2.filters.user.DeviceUid
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

    V2 filter class that filters events by the device UID of the actor.

    classmethod eq(value)
        Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

            Parameters value (str) – The value to match on.

            Returns FilterGroup

    classmethod exists()
        Returns a FilterGroup to find events where filter data exists.

            Returns FilterGroup

    classmethod is_in(value_list)
        Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.

            Parameters value_list (list) – The list of values to match on.

            Returns FilterGroup

    classmethod not_eq(value)
        Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.

            Parameters value (str) – The value to exclude on.

            Returns FilterGroup

    classmethod not_exists()
        Returns a FilterGroup to find events where filter data does not exist.

            Returns FilterGroup

    classmethod not_in(value_list)
        Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.

            Parameters value_list (list) – The list of values to exclude on.

            Returns FilterGroup

class py42.sdk.queries.fileevents.v2.filters.user.Email
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField

    V2 filter class that filters events by the Code42 user email of the actor.

    classmethod eq(value)
        Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.

            Parameters value (str) – The value to match on.

            Returns FilterGroup

    classmethod exists()
        Returns a FilterGroup to find events where filter data exists.

            Returns FilterGroup
```

```
classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.
        Parameters value_list (list) – The list of values to match on.
        Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.
        Parameters value (str) – The value to exclude on.
        Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.
        Returns FilterGroup

classmethod not_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is not in the provided value_list.
        Parameters value_list (list) – The list of values to exclude on.
        Returns FilterGroup

class py42.sdk.queries.fileevents.v2.filters.user.Id
    Bases: py42.sdk.queries.fileevents.util.FileEventFilterStringField
    V2 filter class that filters events by the Code42 user ID of the actor.

classmethod eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term equals the provided value.
        Parameters value (str) – The value to match on.
        Returns FilterGroup

classmethod exists()
    Returns a FilterGroup to find events where filter data exists.
        Returns FilterGroup

classmethod is_in(value_list)
    Returns a FilterGroup that is useful for finding results where the value with the key self._term is in the provided value_list.
        Parameters value_list (list) – The list of values to match on.
        Returns FilterGroup

classmethod not_eq(value)
    Returns a FilterGroup that is useful for finding results where the value with key self._term does not equal the provided value.
        Parameters value (str) – The value to exclude on.
        Returns FilterGroup

classmethod not_exists()
    Returns a FilterGroup to find events where filter data does not exist.
```

Returns *FilterGroup*

classmethod **not_in**(*value_list*)

Returns a *FilterGroup* that is useful for finding results where the value with the key `self._term` is not in the provided *value_list*.

Parameters *value_list* (*list*) – The list of values to exclude on.

Returns *FilterGroup*

2.14 Legal Hold

class `py42.services.legalhold.LegalHoldService`(*connection*)

Bases: `py42.services BaseService`

A service for interacting with Code42 Legal Hold APIs.

The LegalHoldService provides the ability to manage Code42 Legal Hold Policies and Matters. It can: - Create, view, and list all existing Policies. - Create, view, deactivate, reactivate, and list all existing Matters. - Add/remove Custodians from a Matter.

add_to_matter(*user_uid*, *legal_hold_uid*)

Add a user (Custodian) to a Legal Hold Matter.

Parameters

- **user_uid** (*str*) – The identifier of the user.
- **legal_hold_uid** (*str*) – The identifier of the Legal Hold Matter.

Returns `py42.response.Py42Response`

create_matter(*name*, *hold_policy_uid*, *description=None*, *notes=None*, *hold_ext_ref=None*)

Creates a new, active Legal Hold Matter.

Parameters

- **name** (*str*) – The name of the new Legal Hold Matter.
- **hold_policy_uid** (*str*) – The identifier of the Preservation Policy that will apply to this Matter.
- **description** (*str, optional*) – An optional description of the Matter. Defaults to None.
- **notes** (*str, optional*) – Optional notes information. Defaults to None.
- **hold_ext_ref** (*str, optional*) – Optional external reference information. Defaults to None.

Returns `py42.response.Py42Response`

create_policy(*name*, *policy=None*)

Creates a new Legal Hold Preservation Policy.

Parameters

- **name** (*str*) – The name of the new Policy.
- **policy** (*dict, optional*) – The desired Preservation Policy settings as a dict. Defaults to None (where the server-default backup set is used).

Returns `py42.response.Py42Response`

deactivate_matter(*legal_hold_uid*)

Deactivates and closes a Legal Hold Matter.

Parameters **legal_hold_uid** (*str*) – The identifier of the Legal Hold Matter.

Returns *py42.response.Py42Response*

get_all_events(*legal_hold_uid=None, min_event_date=None, max_event_date=None*)

Gets an individual page of Legal Hold events.

Parameters

- **legal_hold_uid** (*str, optional*) – Find LegalHoldEvents for the Legal Hold Matter with this unique identifier. Defaults to None.
- **min_event_date** (*str or int or float or datetime, optional*) – Find LegalHoldEvents whose eventDate is equal to or after this time. E.g. yyyy-MM-dd HH:MM:SS. Defaults to None.
- **max_event_date** (*str or int or float or datetime, optional*) – Find LegalHoldEvents whose eventDate is equal to or before this time. E.g. yyyy-MM-dd HH:MM:SS. Defaults to None.

Returns An object that iterates over *py42.response.Py42Response* objects that each contain a page of LegalHoldEvent objects.

Return type generator

get_all_matter_custodians(*legal_hold_uid=None, user_uid=None, user=None, active=True*)

Gets all Legal Hold memberships.

Each user (Custodian) who has been added to a Legal Hold Matter is returned by the server as a LegalHoldMembership object in the response body. If the object's active state is "INACTIVE", they have been removed from the Matter and are no longer subject to the Legal Hold retention rules. Users can be Custodians of multiple Legal Holds at once (and thus would be part of multiple LegalHoldMembership objects).

Parameters

- **legal_hold_uid** (*str, optional*) – Find LegalHoldMemberships for the Legal Hold Matter with this unique identifier. Defaults to None.
- **user_uid** (*str, optional*) – Find LegalHoldMemberships for the user with this identifier. Defaults to None.
- **user** (*str, optional*) – Find LegalHoldMemberships by flexibly searching on username, email, extUserRef, or last name. Will find partial matches. Defaults to None.
- **active** (*bool or None, optional*) – Find LegalHoldMemberships by their active state. True returns active LegalHoldMemberships, False returns inactive LegalHoldMemberships, None returns all LegalHoldMemberships regardless of state. Defaults to True.

Returns An object that iterates over *py42.response.Py42Response* objects that each contain a page of LegalHoldMembership objects.

Return type generator

get_all_matters(*creator_user_uid=None, active=True, name=None, hold_ext_ref=None*)

Gets all existing Legal Hold Matters.

Parameters

- **creator_user_uid** (*str, optional*) – Find Matters by the identifier of the user who created them. Defaults to None.

- **active** (*bool or None, optional*) – Find Matters by their active state. True returns active Matters, False returns inactive Matters, None returns all Matters regardless of state. Defaults to True.
- **name** (*str, optional*) – Find Matters with a ‘name’ that either equals or contains this value. Defaults to None.
- **hold_ext_ref** (*str, optional*) – Find Matters having a matching external reference field. Defaults to None.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of Legal Hold Matters.

Return type generator

`get_custodians_page(page_num, legal_hold_membership_uid=None, legal_hold_uid=None, user_uid=None, user=None, active=True, page_size=None)`

Gets an individual page of Legal Hold memberships. One of the following optional args is required to determine which custodians to retrieve:

`legal_hold_membership_uid, legal_hold_uid, user_uid, user`

Parameters

- **page_num** (*int*) – The page number to request.
- **legal_hold_membership_uid** (*str, optional*) – Find LegalHoldMemberships with a specific membership UID. Defaults to None.
- **legal_hold_uid** (*str, optional*) – Find LegalHoldMemberships for the Legal Hold Matter with this unique identifier. Defaults to None.
- **user_uid** (*str, optional*) – Find LegalHoldMemberships for the user with this identifier. Defaults to None.
- **user** (*str, optional*) – Find LegalHoldMemberships by flexibly searching on username, email, extUserRef, or last name. Will find partial matches. Defaults to None.
- **active** (*bool or None, optional*) – Find LegalHoldMemberships by their active state. True returns active LegalHoldMemberships, False returns inactive LegalHoldMemberships, None returns all LegalHoldMemberships regardless of state. Defaults to True.
- **page_size** (*int, optional*) – The size of the page. Defaults to `py42.settings.items_per_page`.

Return type `py42.response.Py42Response`

`get_events_page(legal_hold_uid=None, min_event_date=None, max_event_date=None, page_num=1, page_size=None)`

Gets an individual page of Legal Hold events.

Parameters

- **legal_hold_uid** (*str, optional*) – Find LegalHoldEvents for the Legal Hold Matter with this unique identifier. Defaults to None.
- **min_event_date** (*str or int or float or datetime, optional*) – Find LegalHoldEvents whose eventDate is equal to or after this time. E.g. yyyy-MM-dd HH:MM:SS. Defaults to None.
- **max_event_date** (*str or int or float or datetime, optional*) – Find LegalHoldEvents whose eventDate is equal to or before this time. E.g. yyyy-MM-dd HH:MM:SS. Defaults to None.

- **page_num** (*int*) – The page number to request. Defaults to 1.
- **page_size** (*int, optional*) – The size of the page. Defaults to `py42.settings.items_per_page`.

Return type `py42.response.Py42Response`

get_matter_by_uid(*legal_hold_uid*)

Gets a single Legal Hold Matter.

Parameters `legal_hold_uid` (*str*) – The identifier of the Legal Hold Matter.

Returns A response containing the Matter.

Return type `py42.response.Py42Response`

get_matters_page(*page_num, creator_user_uid=None, active=True, name=None, hold_ext_ref=None, page_size=None*)

Gets a page of existing Legal Hold Matters.

Parameters

- **page_num** (*int*) – The page number to request.
- **creator_user_uid** (*str, optional*) – Find Matters by the identifier of the user who created them. Defaults to None.
- **active** (*bool or None, optional*) – Find Matters by their active state. True returns active Matters, False returns inactive Matters, None returns all Matters regardless of state. Defaults to True.
- **name** (*str, optional*) – Find Matters with a ‘name’ that either equals or contains this value. Defaults to None.
- **hold_ext_ref** (*str, optional*) – Find Matters having a matching external reference field. Defaults to None.
- **page_size** (*int, optional*) – The number of legal hold items to return per page. Defaults to `py42.settings.items_per_page`.

Return type `py42.response.Py42Response`

get_policy_by_uid(*legal_hold_policy_uid*)

Gets a single Preservation Policy.

Parameters `legal_hold_policy_uid` (*str*) – The identifier of the Preservation Policy.

Returns A response containing the Policy.

Return type `py42.response.Py42Response`

get_policy_list()

Gets a list of existing Preservation Policies.

Returns A response containing the list of Policies.

Return type `py42.response.Py42Response`

reactivate_matter(*legal_hold_uid*)

Reactivates and re-opens a closed Matter.

Parameters `legal_hold_uid` (*str*) – The identifier of the Legal Hold Matter.

Returns `py42.response.Py42Response`

remove_from_matter(*legal_hold_membership_uid*)

Remove a user (Custodian) from a Legal Hold Matter.

Parameters `legal_hold_membership_uid` (`str`) – The identifier of the LegalHoldMembership representing the Custodian to Matter relationship.

Returns `py42.response.Py42Response`

2.15 Orgs

```
class py42.services.orgs.OrgService(connection)
Bases: py42.services BaseService
```

A service for interacting with Code42 organization APIs.

Use the OrgService to create and retrieve organizations. You can also use it to block and deactivate organizations.

block(`org_id`)

Blocks the organization with the given org ID as well as its child organizations. A blocked organization will not allow any of its users or devices to log in. New registrations will be rejected and all currently logged in clients will be logged out. Backups continue for any devices that are still active.

Parameters `org_id` (`int`) – An ID for an organization.

Returns `py42.response.Py42Response`

create_org(`org_name`, `org_ext_ref=None`, `notes=None`, `parent_org_uid=None`)

Creates a new organization.

Parameters

- `org_name` (`str`) – The name of the new organization.
- `org_ext_ref` (`str, optional`) – External reference information, such as a serial number, asset tag, employee ID, or help desk issue ID. Defaults to None.
- `notes` (`str, optional`) – Descriptive information about the organization. Defaults to None.
- `parent_org_uid` (`int, optional`) – The org UID for the parent organization. Defaults to None.

Returns `py42.response.Py42Response`

deactivate(`org_id`)

Deactivates the organization with the given ID, including all users, plans, and devices. Backups stop and archives move to cold storage.

Parameters `org_id` (`int`) – An ID for an organization.

Returns `py42.response.Py42Response`

get_agent_full_disk_access_states(`org_id`)

Gets the full disk access status for devices in an org.

Parameters `org_id` (`str`) – The org's identifier.

Returns A response containing settings information.

Return type `py42.response.Py42Response`

get_agent_state(`org_id`, `property_name`)

Gets the agent state of the devices in the org.

Parameters

- **org_id** (*str*) – The org's identifier.
- **property_name** (*str*) – The name of the property to retrieve (e.g. *fullDiskAccess*).

Returns A response containing settings information.

Return type *py42.response.Py42Response*

get_all(***kwargs*)

Gets all organizations.

Returns An object that iterates over *py42.response.Py42Response* objects that each contain a page of organizations.

Return type generator

get_by_id(*org_id*, ***kwargs*)

Gets the organization with the given ID.

Parameters **org_id** (*int*) – An ID for an organization.

Returns A response containing the organization.

Return type *py42.response.Py42Response*

get_by_uid(*org_uid*, ***kwargs*)

Gets the organization with the given UID.

Parameters **org_uid** (*str*) – A UID for an organization.

Returns A response containing the organization.

Return type *py42.response.Py42Response*

get_current(***kwargs*)

Gets the organization for the currently signed-in user.

Returns A response containing the organization for the currently signed-in user.

Return type *py42.response.Py42Response*

get_page(*page_num*, *page_size=None*, ***kwargs*)

Gets an individual page of organizations.

Parameters

- **page_num** (*int*) – The page number to request.
- **page_size** (*int, optional*) – The number of organizations to return per page. Defaults to *py42.settings.items_per_page*.
- **kwargs** (*dict, optional*) – Additional advanced-user arguments. Defaults to None.

Returns *py42.response.Py42Response*

get_settings(*org_id*)

Gets setting data for an org and returns an *OrgSettingsManager* for the target org.

Parameters **org_id** (*int, str*) – The identifier of the org.

Returns A class to help manage org settings.

Return type *py42.clients._settings_managers.OrgSettings*

reactivate(*org_id*)

Reactivates the organization with the given ID. Backups are *not* restarted automatically.

Parameters **org_id** (*int*) – An ID for an organization.

Returns `py42.response.Py42Response`

unblock(*org_id*)

Removes a block, if one exists, on an organization and its descendants with the given ID. All users in the organization remain blocked until they are unblocked individually.

Parameters `org_id` (*int*) – An ID for an organization.

Returns `py42.response.Py42Response`

update_settings(*org_settings*)

Updates an org's settings based on changes to the passed in *OrgSettings* instance.

Parameters `org_settings` (*OrgSettings*) – An *OrgSettings* instance with desired modifications to settings.

Returns A namedtuple containing the result of the setting change api calls.

Return type `py42.services.orgs.OrgSettings`

2.16 Org Settings

class `py42.clients.settings.org_settings.OrgSettings`(*org_settings*, *t_settings*)

Bases: `collections.UserDict`

Class used to manage an Organization's settings.

archive_hold_days

Number of days backup archives are held in cold storage after deactivation or destination removal from any devices in this Org.

backup_alert_recipient_emails

List of email addresses that organization backup alert emails get sent to (org admin users get these automatically).

backup_critical_email_days

The number of days devices in this org can go without any backup before “critical” alerts get sent to org admins.

backup_warning_email_days

The number of days devices in this org can go without any backup before “warning” alerts get sent to org admins.

endpoint_monitoring_background_priority_enabled

Determines if devices in this org have reduced priority in some IO bound tasks. If enabled, devices may see improved general device performance at the expense of some Code42 backup/security tasks taking longer.

property endpoint_monitoring_browser_and_applications_enabled

Determines if browser and other application activity endpoint monitoring event capturing is enabled for this org.

property endpoint_monitoring_cloud_sync_enabled

Determines if cloud sync endpoint monitoring event capturing is enabled for this org.

endpoint_monitoring_custom_applications_mac

List of additional applications the Code42 client monitors for file exfiltration activity.

See [Support Documentation](#) for more details.

endpoint_monitoring_custom_applications_win

List of additional applications the Code42 client monitors for file exfiltration activity.

See [Support Documentation](#) for more details.

property endpoint_monitoring_enabled

Determines if endpoint monitoring settings are enabled for this org.

Disabling this property also disables “removable media”, “cloud sync”, “browser and application monitoring” and “printer detection” properties.

endpoint_monitoring_file_exfiltration_detection_exclusions

File types and file paths to exclude from file exfiltration detection.

See [Support Documentation](#) for more details on the shape of the body this setting expects.

property endpoint_monitoring_file_metadata_collection_enabled

Determines if file metadata collection is enabled for this org.

endpoint_monitoring_file_metadata_collection_exclusions

File types and file paths to exclude from file metadata collection.

See [Support Documentation](#) for more details on the shape of the body this setting expects.

endpoint_monitoring_file_metadata_ingest_scan_enabled

Determines if file metadata collection does an initial full scan when first enabled on devices.

endpoint_monitoring_file_metadata_scan_enabled

Determines if file metadata collection regular full scans are enabled for this org.

property endpoint_monitoring_printer_detection_enabled

Determines if printer endpoint monitoring event capturing is enabled for this org.

property endpoint_monitoring_removable_media_enabled

Determines if removable media endpoint monitoring event capturing is enabled for this org.

external_reference

External reference field for this Org.

maximum_user_subscriptions

Number of users allowed to consume a license in this Org. Set to -1 for unlimited.

notes

Notes field for this Org.

org_backup_quota

Backup storage quota (in GB) for this organization. Set to -1 for unlimited.

property org_id

The identifier for the org.

org_name

Name for this Org.

property packets

The setting packets for any modifications to be posted to the /api/v1/OrgSettings endpoint.

quota_settings_inherited

Determines if Org Quota settings (*maximum_user_subscriptions*, *org_backup_quota*, *user_backup_quota*, *archive_hold_days*) are inherited from parent organization.

Modifying one of the Org Quota attributes automatically sets this attribute to *False*.

property registration_key

The registration key for the org.

reporting_settings_inherited
Determines if Org Reporting settings (`backup_warning_email_days`, `backup_critical_email_days`, `backup_alert_recipient_emails`) are inherited from parent organization.

Modifying one of the Org Reporting attributes automatically sets this attribute to `False`.

user_backup_quota
Backup storage quota (in GB) for each user in this organization. Set to -1 for unlimited.

web_restore_admin_limit
Limit (in MB) to amount of data restorable by admin users via web restore.

web_restore_enabled
Determines if web restores are enabled for devices in this org.

web_restore_user_limit
Limit (in MB) to amount of data restorable by non-admin users via web restore.

class `py42.clients.settings.device_settings.DeviceSettingsDefaults(device_dict, org_settings)`
Bases: `collections.UserDict`

Class used for managing an Organization's Device Default settings. Also acts as a base class for `DeviceSettings` to manage individual device settings.

property available_destinations
Returns a dict of destinations available to be used by devices. Dict keys are destination guids and values are destination names.

backup_status_email_enabled
Determines if the regularly scheduled backup status email is enabled.

backup_status_email_frequency_days
Determines the frequency of the regularly scheduled backup status email.

critical_alert_days
The number of days a device can go without any backup activity before "warning" alert threshold is passed.

critical_email_enabled
Determines if backup "critical" threshold email alerts are configured for this device.

warning_alert_days
The number of days a device can go without any backup activity before "warning" alert threshold is passed.

warning_email_enabled
Determines if backup "warning" threshold email alerts are configured for this device.

2.17 Response

class `py42.response.Py42Response(requests_response)`
Bases: `object`

property encoding
The encoding used to decode the response text.

property headers
A case-insensitive dictionary of response headers.

iter_content(chunk_size=1, decode_unicode=False)
Iterates over the response data. When `stream=True` is set on the request, this avoids reading the content at once into memory for large responses.

Parameters

- **chunk_size** (*int, optional*) – The number of bytes it should read into memory. A value of None will function differently depending on the value of *stream*. *stream=True* will read data as it arrives in whatever size the chunks are received. If *stream=False*, data is returned as a single chunk. This is not necessarily the length of each item. Defaults to 1.
- **decode_unicode** (*bool, optional*) – If True, content will be decoded using the best available encoding based on the response. Defaults to False.

property raw_text

The `response.Response.text` property. It contains raw metadata that is not included in the `Py42Response.text` property.

property status_code

An integer code of the response HTTP Status, e.g. 404 or 200.

property text

The more useful parts of the HTTP response dumped into a dictionary.

property url

The final URL location of response.

2.18 Security Data

Warning: V1 file events, saved searches, and queries are **deprecated**.

For details on using the new file event data model, see the [V2 File Events User Guide](#).

```
class py42.clients.securitydata.SecurityDataClient(file_event_service, preservation_data_service,
                                                    saved_search_service, storage_service_factory)
```

Bases: `object`

property savedsearches

A collection of methods related to retrieving forensic search data.

Returns class: `py42.services.savedsearch.SavedSearchService`

search_all_file_events(query, page_token=“”)

Searches for all file events, returning a page of events with a token in the response to retrieve next page.
[REST Documentation](#)

Parameters

- **query** (*str or py42.sdk.queries.fileevents.v2.FileEventQuery*) – The file event query to filter search results.
- **page_token** (*str, optional*) – A token used to indicate the starting point for additional page results. For the first page, do not pass `page_token`. For all consecutive pages, pass the token from the previous response from field `nextPgToken`. Defaults to empty string.

Returns A response containing a page of events.

Return type `py42.response.Py42Response`

search_file_events(query)

Searches for file events, returns up to the first 10,000 events. [REST Documentation](#)

Parameters `query` (str or `py42.sdk.queries.fileevents.v2.FileEventQuery`) – The file event query to filter search results.

Returns A response containing the first 10,000 events.

Return type `py42.response.Py42Response`

stream_file_by_md5(`checksum`)
Stream file based on MD5 checksum.

Parameters `checksum`(str) – MD5 hash of the file.

Returns Returns a stream of the requested file.

stream_file_by_sha256(`checksum`)
Stream file based on SHA256 checksum.

Parameters `checksum`(str) – SHA256 hash of the file.

Returns Returns a stream of the requested file.

2.19 Shared Query Filters

```
class py42.sdk.queries.query_filter.FilterGroup(filter_list, filter_clause='AND')  
Bases: object
```

Class for constructing a logical sub-group of related filters from a list of `QueryFilter` objects. Takes a list of `QueryFilter` objects and combines them logically using the passed in filter clause (AND or OR).

When `str()` is called on a `FilterGroup` instance, the combined filter items are transformed into a JSON string to be used as part of a Forensic Search or Alert query.

When `dict()` is called on a `FilterGroup` instance, the combined filter items are transformed into the Python `dict` equivalent of their JSON representation. This can be useful for programmatically manipulating a `FilterGroup` after it's been created.

property filter_clause

The clause joining the filters, such as AND or OR.

property filter_list

The list of `QueryFilter` objects in this group.

classmethod from_dict(`_dict`)

Creates an instance of `FilterGroup` from the values found in `_dict`. `_dict` must contain keys `filters` and `filterClause`.

Parameters `_dict`(dict) – A dictionary containing keys `term`, `operator`, and `value`.

Returns `FilterGroup`

```
class py42.sdk.queries.query_filter.QueryFilter(term, operator, value=None)  
Bases: object
```

Class for constructing a single filter object for use in a search query.

When `str()` is called on a `QueryFilter` instance, the (`term`, `operator`, `value`) attribute combination is transformed into a JSON string to be used as part of a Forensic Search or Alert query.

When `dict()` is called on a `QueryFilter` instance, the (`term`, `operator`, `value`) attribute combination is transformed into the Python `dict` equivalent of their JSON representation. This can be useful for programmatically manipulating a `QueryFilter` after it's been created.

classmethod from_dict(_dict)

Creates an instance of `QueryFilter` from the values found in `_dict`. `_dict` must contain keys `term`, `operator`, and `value`.

Parameters `_dict (dict)` – A dictionary containing keys `term`, `operator`, and `value`.

Returns `QueryFilter`

property operator

The operator between `term` and `value`, such as `IS` or `IS_NOT`.

property term

The term of the filter, such as `actor` or `sharedWith`.

property value

The value used to filter results.

class py42.sdk.queries.query_filter.QueryFilterBooleanField

Bases: `object`

Helper class for creating filters where the search value is a boolean.

classmethod is_false()

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` is False.

Returns `FilterGroup`

classmethod is_true()

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` is True.

Returns `FilterGroup`

class py42.sdk.queries.query_filter.QueryFilterStringField

Bases: `object`

Helper class for creating filters where the search value is a string.

classmethod eq(value)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` equals the provided value.

Parameters `value (str)` – The value to match on.

Returns `FilterGroup`

classmethod is_in(value_list)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is in the provided `value_list`.

Parameters `value_list (list)` – The list of values to match on.

Returns `FilterGroup`

classmethod not_eq(value)

Returns a `FilterGroup` that is useful for finding results where the value with key `self._term` does not equal the provided value.

Parameters `value (str)` – The value to exclude on.

Returns `FilterGroup`

classmethod not_in(value_list)

Returns a `FilterGroup` that is useful for finding results where the value with the key `self._term` is not in the provided `value_list`.

Parameters `value_list (list)` – The list of values to exclude on.

Returns *FilterGroup*

```
class py42.sdk.queries.query_filter.QueryFilterTimestampField  
Bases: object
```

Helper class for creating filters where the search value is a timestamp.

classmethod *in_range*(*start_value*, *end_value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is in range between the provided `start_value` and `end_value`.

Parameters

- **`start_value`** (*str or int or float or datetime*) – The start value used to filter results.
- **`end_value`** (*str or int or float or datetime*) – The end value used to filter results.

Returns *FilterGroup*

classmethod *on_or_after*(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term`` is on or after the provided ``value``.

Parameters `value` (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod *on_or_before*(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is on or before the provided value.

Parameters `value` (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

classmethod *on_same_day*(*value*)

Returns a *FilterGroup* that is useful for finding results where the value with key `self._term` is within the same calendar day as the provided value.

Parameters `value` (*str or int or float or datetime*) – The value used to filter results.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_eq_filter_group(term, value)`

“Creates a *FilterGroup* for filtering results where the value with key `term` equals the given value. Useful for creating IS filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **`term`** – (str): The term of the filter, such as `actor` or `sharedWith`.
- **`value`** (str) – The value used to match on.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_filter_group(query_filter_list, filter_clause)`

Creates a *FilterGroup* object. Useful for programmatically crafting query filters, such as filters not yet defined in py42. Alternatively, if you want to create custom filter groups with already defined operators (such as `IS` or `IS_IN`), see the other methods in this module, such as `create_eq_filter_group()`.

Parameters

- **`query_filter_list`** (*list*) – a list of *QueryFilter* objects.

- **filter_clause** (*str*) – The clause joining the filters, such as AND or OR.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_in_range_filter_group(term, start_value, end_value)`

“Creates a *FilterGroup* for filtering results where the value with key `term` is in the given range. Examples include values describing dates. Useful for creating a combination of ON_OR_AFTER and ON_OR_BEFORE filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **term** – (*str*): The term of the filter, such as `eventTimestamp`.
- **start_value** (*str or int*) – The start value used to filter results.
- **end_value** (*str or int*) – The end value used to filter results.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_is_in_filter_group(term, value_list)`

“Creates a *FilterGroup* for filtering results where the value with key `term` is one of several values. Useful for creating IS_IN filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **term** – (*str*): The term of the filter, such as `actor` or `sharedWith`.
- **value_list** (*list*) – The list of values to match on.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_not_eq_filter_group(term, value)`

“Creates a *FilterGroup* for filtering results where the value with key `term` does not equal the given value. Useful for creating IS_NOT filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **term** – (*str*): The term of the filter, such as `actor` or `sharedWith`.
- **value** (*str*) – The value used to exclude on.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_not_in_filter_group(term, value_list)`

“Creates a *FilterGroup* for filtering results where the value with key `term` is not one of several values. Useful for creating NOT_IN filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **term** – (*str*): The term of the filter, such as `actor` or `sharedWith`.
- **value_list** (*list*) – The list of values to exclude on.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_on_or_after_filter_group(term, value)`

“Creates a *FilterGroup* for filtering results where the value with key `term` is on or after the given value. Examples include values describing dates. Useful for creating ON_OR_AFTER filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- **term** – (*str*): The term of the filter, such as `eventTimestamp`.
- **value** (*str or int*) – The value used to filter results.

Returns *FilterGroup*

`py42.sdk.queries.query_filter.create_on_or_before_filter_group(term, value)`

“Creates a `FilterGroup` for filtering results where the value with key `term` is on or before the given value. Examples include values describing dates. Useful for creating `ON_OR_BEFORE` filters that are not yet supported in py42 or programmatically crafting filter groups.

Parameters

- `term` – (str): The term of the filter, such as `eventTimestamp`.
- `value` (str or int) – The value used to filter results.

Returns `FilterGroup`

`py42.sdk.queries.query_filter.create_query_filter(term, operator, value=None)`

Creates a `QueryFilter` object. Useful for programmatically crafting query filters, such as filters not yet defined in py42.

Parameters

- `term` (str) – The term of the filter, such as `actor` or `sharedWith`.
- `operator` (str) – The operator between `term` and `value`, such as `IS` or `IS_NOT`.
- `value` (str) – The value used to filter results.

Returns `QueryFilter`

`py42.sdk.queries.query_filter.create_within_the_last_filter_group(term, value)`

Returns a `FilterGroup` that is useful for finding results where the key `term` is an `EventTimestamp._term` and the value is one of the `EventTimestamp` attributes as `value`.

Parameters `value` (str) – `EventTimestamp` attribute.

Returns `FilterGroup`

2.20 Trusted Activities

`class py42.clients.trustedactivities.TrustedActivityType`

Bases: `py42.choices.Choices`

Constants available for setting the type of a trusted activity.

- DOMAIN
- SLACK

`class py42.clients.trustedactivities.TrustedActivitiesClient(trusted_activities_service)`

Bases: `object`

A client to expose the trusted activities/data preferences API

Rest documentation

`create(type, value, description=None)`

Gets all trusted activities with the given type. Rest documentation

Parameters

- `type` (str) – Type of the trusted activity. Constants available at `py42.constants.TrustedActivityType`.
- `value` (str) – The URL of the domain or name of the Slack workspace.
- `description` (str, optional) – Description of the trusted activity.

Returns `py42.response.Py42Response`

delete(id)
Deletes a trusted activity by given resource number. [Rest documentation](#)

Parameters `id (int)` – Resource number of the trusted activity or domain.

Returns `py42.response.Py42Response`

get(id)
Retrieve trusted activity details by given resource number. [Rest documentation](#)

Parameters `id (int)` – Resource number of the trusted activity or domain.

Returns `py42.response.Py42Response`

get_all(type=None, page_size=None)
Gets all trusted activities. [Rest documentation](#)

Parameters

- `type (str, optional)` – Type of the trusted activity. Defaults to None. Constants available at `py42.constants.TrustedActivityType`.
- `page_size (int, optional)` – Number of results to return per page. Defaults to 100.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of cases.

Return type generator

update(id, value=None, description=None)
Updates trusted activity details by given resource number. [Rest documentation](#)

Parameters

- `id (int)` – Resource number of the trusted activity.
- `value (str, optional)` – The URL of the domain or name of the Slack workspace.
- `description (str, optional)` – Description of the trusted activity.

Returns `py42.response.Py42Response`

2.21 User Risk Profiles

```
class py42.clients.userriskprofile.UserRiskProfileClient(user_risk_profile_service)
```

Bases: `object`

A client to expose the user risk profile API.

[Rest Documentation](#)

add_cloud_aliases(user_id, cloud_alias)

Add cloud aliases to a user risk profile.

Parameters

- `user_id (str)` – The user UID.
- `cloud_alias (str or list(str))` – The alias(es) to add to the user risk profile. Each user starts with a default alias of their code42 username and can have one additional cloud alias.

Returns `py42.response.Py42Response`

delete_cloud_aliases(*user_id*, *cloud_aliases*)

Delete cloud aliases from a user risk profile.

Parameters

- **user_id** (*str*) – The user UID.
- **cloud_aliases** (*str or list(str)*) – The alias(es) to remove from the user risk profile. Each user starts with a default alias of their code42 username and can have one additional cloud alias.

Returns *py42.response.Py42Response***get_all**(*manager_id=None*, *title=None*, *division=None*, *department=None*, *employment_type=None*, *country=None*, *region=None*, *locality=None*, *active=None*, *deleted=None*, *support_user=None*)

Get all user risk profiles.

Parameters

- **manager_id** (*str, optional*) – Matches users whose manager has the given Code42 user UID. Defaults to None
- **title** (*str, optional*) – Matches users with the given job title. Defaults to None
- **division** (*str, optional*) – Matches users in the given division. Defaults to None
- **department** (*str, optional*) – Matches users in the given department. Defaults to None
- **employment_type** (*str, optional*) – Matches users with the given employment type. Defaults to None
- **country** (*str, optional*) – Matches users in the given country. Defaults to None
- **region** (*str, optional*) – Matches users the given region (state). Defaults to None
- **locality** (*str, optional*) – Matches users in the given locality (city). Defaults to None
- **active** (*boolean, optional*) – Matches users by whether the user is active. Defaults to None
- **deleted** (*boolean, optional*) – Matches users by whether the user is deleted. Defaults to None
- **support_user** (*boolean, optional*) – Matches users by whether the user is a support user. Defaults to None

Returns An object that iterates over *py42.response.Py42Response* objects that each contain a page of user risk profiles.

Return type generator**get_by_id**(*user_id*)

Get a user risk profile by a user UID.

Parameters **user_id** (*str*) – A unique user UID.

Returns *py42.response.Py42Response*

get_by_username(*username*)

Get a user risk profile by username.

Parameters **username** (*str*) – A username.

Returns *py42.response.Py42Response*

get_page(*page_num=1, page_size=None, manager_id=None, title=None, division=None, department=None, employment_type=None, country=None, region=None, locality=None, active=None, deleted=None, support_user=None*)

Get a page of user risk profiles.

Parameters

- **page_num** (*integer, optional*) – The desired page of user risk profile results to retrieve. Defaults to None
- **page_size** (*integer, optional*) – The desired number of results per page. Defaults to None
- **manager_id** (*str, optional*) – Matches users whose manager has the given Code42 user UID. Defaults to None
- **title** (*str, optional*) – Matches users with the given job title. Defaults to None
- **division** (*str, optional*) – Matches users in the given division. Defaults to None
- **department** (*str, optional*) – Matches users in the given department. Defaults to None
- **employment_type** (*str, optional*) – Matches users with the given employment type. Defaults to None
- **country** (*str, optional*) – Matches users in the given country. Defaults to None
- **region** (*str, optional*) – Matches users the given region (state). Defaults to None
- **locality** (*str, optional*) – Matches users in the given locality (city). Defaults to None
- **active** (*boolean, optional*) – Matches users by whether the user is active. Defaults to None
- **deleted** (*boolean, optional*) – Matches users by whether the user is deleted. Defaults to None
- **support_user** (*boolean, optional*) – Matches users by whether the user is a support user. Defaults to None

Returns `py42.response.Py42Response`

update(*user_id, start_date=None, end_date=None, notes=None*)

Update a user risk profile.

For each arg, if None is provided, the value will not be updated. Pass an empty string if you want to clear that value from the profile.

Parameters

- **user_id** (*str*) – The UID of the user to update.
- **start_date** (*str or datetime, optional*) – The start date of the user risk profile to be updated. Expects format of ‘YYYY-MM-DD’ or instance of datetime. Defaults to None.
- **end_date** (*str or datetime, optional*) – The departure date of the user risk profile to be updated. Expects format of ‘YYYY-MM-DD’ or instance of datetime. Defaults to None.
- **notes** (*str, optional*) – The notes field of the user risk profile to be updated. Defaults to None

Returns `py42.response.Py42Response`

2.22 Users

```
class py42.services.users.UserService(connection)
    Bases: py42.services BaseService
```

A service for interacting with Code42 user APIs. Use the UserService to create and retrieve users. You can also use it to block and deactivate users.

```
add_role(user_id, role_name)
```

Adds a role to a user.

Parameters

- **user_id** (*int*) – An ID for a user.
- **role_name** (*str*) – The name of the role to assign to the user.

Returns `py42.response.Py42Response`

```
block(user_id)
```

Blocks the user with the given ID. A blocked user is not allowed to log in or restore files. Backups will continue if the user is still active.

Parameters `user_id` (*int*) – An ID for a user.

Returns `py42.response.Py42Response`

```
change_org_assignment(user_id, org_id)
```

Assigns a user to a different organization.

Parameters

- **user_id** (*int*) – An ID for a user.
- **org_id** (*int*) – An ID for the organization to move the user to.

Returns `py42.response.Py42Response`

```
create_user(org_uid, username, email, password=None, first_name=None, last_name=None, notes=None)
```

Creates a new user. WARNING: If the provided username already exists for a user, it will be updated in the database instead.

Parameters

- **org_uid** (*str*) – The org UID for the organization the new user belongs to.
- **username** (*str*) – The username for the new user.
- **email** (*str*) – The email for the new user.
- **password** (*str, optional*) – The password for the new user. Defaults to None.
- **first_name** (*str, optional*) – The first name for the new user. Defaults to None.
- **last_name** (*str, optional*) – The last name for the new user. Defaults to None.
- **notes** (*str, optional*) – Descriptive information about the user. Defaults to None.

Returns `py42.response.Py42Response`

```
deactivate(user_id, block_user=None)
```

Deactivates the user with the given user ID. Backups discontinue for a deactivated user, and their archives go to cold storage.

Parameters

- **user_id** (*int*) – An ID for a user.

- **block_user** (*bool, optional*) – Blocks the user upon deactivation. Defaults to None.

Returns `py42.response.Py42Response`

get_all(*active=None, email=None, org_uid=None, role_id=None, q=None, **kwargs*)

Gets all users.

Parameters

- **active** (*bool, optional*) – True gets active users only, and false gets deactivated users only. Defaults to None.
- **email** (*str, optional*) – Limits users to only those with this email. Defaults to None.
- **org_uid** (*str, optional*) – Limits users to only those in the organization with this org UID. Defaults to None.
- **role_id** (*int, optional*) – Limits users to only those with a given role ID. Defaults to None.
- **q** (*str, optional*) – A generic query filter that searches across name, username, and email. Defaults to None.

Returns An object that iterates over `py42.response.Py42Response` objects that each contain a page of users.

Return type generator

get_available_roles()

Report the list of roles that are available for the authenticated user to assign to other users.

Returns `py42.response.Py42Response`

get_by_id(*user_id, **kwargs*)

Gets the user with the given ID. [Rest Documentation](#)

Parameters **user_id** (*int*) – An ID for a user.

Returns A response containing the user.

Return type `py42.response.Py42Response`

get_by_uid(*user_uid, **kwargs*)

Gets the user with the given UID.

Parameters **user_uid** (*str*) – A UID for a user.

Returns A response containing the user.

Return type `py42.response.Py42Response`

get_by_username(*username, **kwargs*)

Gets the user with the given username.

Parameters **username** (*str or unicode*) – A username for a user.

Returns A response containing the user.

Return type `py42.response.Py42Response`

get_current(***kwargs*)

Gets the currently signed in user.

Returns A response containing the user.

Return type `py42.response.Py42Response`

get_page(*page_num*, *active=None*, *email=None*, *org_uid=None*, *role_id=None*, *page_size=None*, *q=None*,
 ***kwargs*)

Gets an individual page of users.

Parameters

- **page_num** (*int*) – The page number to request.
- **active** (*bool, optional*) – True gets active users only, and false gets deactivated users only. Defaults to None.
- **email** (*str, optional*) – Limits users to only those with this email. Defaults to None.
- **org_uid** (*str, optional*) – Limits users to only those in the organization with this org UID. Defaults to None.
- **role_id** (*int, optional*) – Limits users to only those with a given role ID. Defaults to None.
- **page_size** (*int, optional*) – The number of items on the page. Defaults to *py42.settings.items_per_page*.
- **q** (*str, optional*) – A generic query filter that searches across name, username, and email. Defaults to None.

Returns *py42.response.Py42Response*

get_roles(*user_id*)

Return the list of roles that are currently assigned to the given user.

Parameters **user_id** (*int*) – An ID for a user.

Returns *py42.response.Py42Response*

get_scim_data_by_uid(*user_uid*)

Returns SCIM data such as division, department, and title for a given user.

Parameters **user_uid** (*str*) – A Code42 user uid.

Returns *py42.response.Py42Response*

reactivate(*user_id*, *unblock_user=None*)

Reactivates the user with the given ID.

Parameters

- **user_id** (*int*) – An ID for a user.
- **unblock_user** (*bool, optional*) – Whether or not to unblock the user. Defaults to None.

Returns *py42.response.Py42Response*

remove_role(*user_id*, *role_name*)

Removes a role from a user.

Parameters

- **user_id** (*int*) – An ID for a user.
- **role_name** (*str*) – The name of the role to unassign from the user.

Returns *py42.response.Py42Response*

unblock(*user_id*)

Removes a block, if one exists, on the user with the given user ID. Unblocked users are allowed to log in and restore.

Parameters `user_id` (`int`) – An ID for a user.

Returns `py42.response.Py42Response`

update_user (`user_uid`, `username=None`, `email=None`, `password=None`, `first_name=None`,
`last_name=None`, `notes=None`, `archive_size_quota_bytes=None`)

Updates an existing user.

Parameters

- `user_uid` (`str or int`) – A Code42 user UID.
- `username` (`str, optional`) – The username to which the user's username will be changed. Defaults to None.
- `email` (`str, optional`) – The email to which the user's email will be changed. Defaults to None.
- `password` (`str, optional`) – The password to which the user's password will be changed. Defaults to None.
- `first_name` (`str, optional`) – The first name to which the user's first name will be changed. Defaults to None.
- `last_name` (`str, optional`) – The last name to which the user's last name will be changed. Defaults to None.
- `notes` (`str, optional`) – Descriptive information about the user. Defaults to None.
- `archive_size_quota_bytes` (`int, optional`) – The quota in bytes that limits the user's archive size. Defaults to None.

Returns `py42.response.Py42Response`

class `py42.usercontext.UserContext(administration_client)`
Bases: `object`

An object representing the currently logged in user.

get_current_tenant_id()
Gets the currently signed in user's tenant ID.

2.23 Util

`py42.util.convert_datetime_to_timestamp_str(date)`

Converts the given datetime to a formatted date str. The format matches strftime directives `%Y-%m-%dT%H:%M:%S.%f`.

Parameters `date` (`datetime`) – The datetime object to convert.

Returns A str representing the given date. Example output looks like ‘2020-03-25T15:29:04.465Z’.

Return type (`str`)

`py42.util.convert_timestamp_to_str(timestamp)`

Converts the given POSIX timestamp to a date str. The format matches strftime directives `%Y-%m-%dT%H:%M:%S.%f`.

Parameters `timestamp` (`float or int`) – A POSIX timestamp.

Returns A str representing the given timestamp. Example output looks like ‘2020-03-25T15:29:04.465Z’.

Return type (str)

`py42.util.format_json(json_string)`

Converts a minified JSON str to a prettified JSON str.

Parameters `json_string (str)` – A str representing minified JSON.

Returns A str representing prettified JSON.

Return type (str)

`py42.util.get_attribute_values_from_class(cls)`

Returns attribute values for the given class.

Parameters `cls (class)` – The class to obtain attributes from.

Returns A list containing the attribute values of the given class.

Return type (list)

`py42.util.print_response(response, label=None)`

Prints a `py42.response.Py42Response` as prettified JSON. If unable to load, it prints the given response.

Parameters

- **response** (`py42.response.Py42Response`) – The response to print.
- **label** (str, optional) – A label at the beginning of the printed text. Defaults to None.

2.24 Watchlists

`class py42.clients.watchlists.WatchlistType`
Bases: `py42.choices.Choices`

Constants available for setting the type of watchlist.

- CONTRACT_EMPLOYEE
- DEPARTING_EMPLOYEE
- ELEVATED_ACCESS_PRIVILEGES
- FLIGHT_RISK
- HIGH_IMPACT_EMPLOYEE
- NEW_EMPLOYEE
- PERFORMANCE_CONCERN
- POOR_SECURITY_PRACTICES
- SUSPICIOUS_SYSTEM_ACTIVITY”

`class py42.clients.watchlists.WatchlistsClient(watchlists_service)`
Bases: `object`

A client to expose the watchlists API.

[Rest Documentation](#)

`add_included_users_by_watchlist_id(user_ids, watchlist_id)`

Explicitly include users on a watchlist.

Parameters

- **user_ids** (*list(str)*) – A list of user IDs to add to the watchlist
- **watchlist_id** (*str*) – A unique watchlist ID.

Returns *py42.response.Py42Response*

add_included_users_by_watchlist_type(*user_ids, watchlist_type*)

Explicitly include users on a watchlist.

Parameters

- **user_ids** (*list(str)*) – A list of user IDs to add to the watchlist
- **watchlist_type** (*str*) – Type of watchlist. Constants available at *py42.constants.WatchlistType*.

Returns *py42.response.Py42Response*

create(*watchlist_type*)

Create a new watchlist.

Parameters **watchlist_type** (*str*) – Type of watchlist. Constants available at *py42.constants.WatchlistType*.

Returns *py42.response.Py42Response*

delete(*watchlist_id*)

Delete a watchlist.

Parameters **watchlist_id** (*str*) – A unique watchlist ID.

Returns *py42.response.Py42Response*

get(*watchlist_id*)

Get a watchlist.

Parameters **watchlist_id** (*str*) – A unique watchlist ID.

Returns *py42.response.Py42Response*

get_all()

Get all watchlists.

Returns An object that iterates over *py42.response.Py42Response* objects that each contain a page of watchlists.

Return type generator

get_all_included_users(*watchlist_id*)

Get all users explicitly included on a watchlist.

Parameters **watchlist_id** (*str*) – A unique watchlist ID.

Returns An object that iterates over *py42.response.Py42Response* objects that each contain a page of included users that match the given query.

Return type generator

get_all_watchlist_members(*watchlist_id*)

Get all members of a watchlist.

Parameters **watchlist_id** (*str*) – A unique watchlist ID.

Returns An object that iterates over *py42.response.Py42Response* objects that each contain a page of watchlist members.

Return type generator

get_watchlist_member(*watchlist_id*, *user_id*)

Get a member of a watchlist.

Parameters

- **watchlist_id**(*str*) – A unique watchlist ID.
- **user_id**(*str*) – A unique user ID.

Returns *py42.response.Py42Response*

remove_included_users_by_watchlist_id(*user_ids*, *watchlist_id*)

Remove users that are explicitly included on a watchlist.

Parameters

- **user_ids**(*list(str)*) – A list of user IDs to remove from the watchlist
- **watchlist_id**(*str*) – A unique watchlist ID.

Returns *py42.response.Py42Response*

remove_included_users_by_watchlist_type(*user_ids*, *watchlist_type*)

Remove users that are explicitly included on a watchlist.

Parameters

- **user_ids**(*list(str)*) – A list of user IDs to remove from the watchlist
- **watchlist_type**(*str*) – Type of watchlist. Constants available at *py42.constants.WatchlistType*.

Returns *py42.response.Py42Response*

The main SDK object by which all other methods are accessed is created by calling `py42.sdk.from_local_account` or `py42.sdk.from_jwt_provider`. For example:

```
import py42.sdk

sdk = py42.sdk.from_local_account("console.us.code42.com", "john.doe@example.com", "my_pw"
                                   )
# access properties on 'sdk' to explore all the available methods
```

Important: *py42* only supports token-based authentication.

Explore the complete public documentation for *py42* below.

- *Alerts*
- *Alert Rules*
- *Archive*
- *Audit Logs*
- *Backup Sets*
- *Cases*
- *Constants*
- *Detection Lists*
- *Devices*

- *Device Settings*
- *Exceptions*
- *(DEPRECATED) File Event Queries - V1*
- *File Event Queries - V2*
- *Legal Hold*
- *Orgs*
- *Org Settings*
- *Response*
- *Security Data*
- *Shared Query Filters*
- *Trusted Activities*
- *Users*
- *User Risk Profiles*
- *Util*
- *Watchlists*

`py42.sdk.from_jwt_provider(host_address, jwt_provider)`

Creates a `SDKClient` object for accessing the Code42 REST APIs using a custom auth mechanism. User can use any authentication mechanism like that returns a JSON Web token on authentication which would then be used for all subsequent requests.

Parameters

- **host_address (str)** – The domain name of the Code42 instance being authenticated to, e.g. console.us.code42.com
- **jwt_provider (function)** – A function that accepts no parameters and on execution returns a JSON web token string.

Returns `py42.sdk.SDKClient`

`py42.sdk.from_local_account(host_address, username, password, totp=None)`

Creates a `SDKClient` object for accessing the Code42 REST APIs using the supplied credentials. This method supports only accounts created within the Code42 console or using the APIs (including py42). Username/passwords that are based on Active Directory, Okta, or other Identity providers cannot be used with this method.

Parameters

- **host_address (str)** – The domain name of the Code42 instance being authenticated to, e.g. console.us.code42.com
- **username (str)** – The username of the authenticating account.
- **password (str)** – The password of the authenticating account.
- **totp(callable or str, optional)** – The time-based one-time password of the authenticating account. Include only if the account uses Code42's two-factor authentication. Defaults to None.

Returns `py42.sdk.SDKClient`

```
class py42.sdk.SDKClient(main_connection, auth)
Bases: object

property alerts
    A collection of methods related to retrieving and updating alerts rules.

    Returns py42.clients.alertrules.AlertRulesClient

property archive
    A collection of methods for accessing Code42 storage archives. Useful for doing web-restores or finding a file on an archive.

    Returns py42.clients.archive.ArchiveClient

property auditlogs
    A collection of methods for retrieving audit logs.

    Returns py42.clients.auditlogs.AuditLogsClient

property cases
    A collection of methods and properties for managing cases and file events associated with the case.

    Returns py42.clients.cases.CaseClient

property detectionlists
    A collection of properties each containing methods for managing specific detection lists, such as departing employees.

    Returns py42.clients.detectionlists.DetectionListsClient

property devices
    A collection of methods for retrieving or updating data about devices in the Code42 environment.

    Returns py42.services.devices.DeviceService

classmethod from_jwt_provider(host_address, jwt_provider)

    Creates a SDKClient object for accessing the Code42 REST APIs using a custom auth mechanism.
    User can use any authentication mechanism like that returns a JSON Web token on authentication which would then be used for all subsequent requests.

Parameters

- host_address (str) – The domain name of the Code42 instance being authenticated to, e.g. console.us.code42.com
- jwt_provider (function) – A function that accepts no parameters and on execution returns a
- string. (JSON web token) –

Returns py42.sdk.SDKClient

classmethod from_local_account(host_address, username, password, totp=None)

    Creates a SDKClient object for accessing the Code42 REST APIs using the supplied credentials. This method supports only accounts created within the Code42 console or using the APIs (including py42). Username/passwords that are based on Active Directory, Okta, or other Identity providers should use the from_jwt_provider method.

Parameters

- host_address (str) – The domain name of the Code42 instance being authenticated to, e.g. console.us.code42.com

```

- **username** (*str*) – The username of the authenticating account.
- **password** (*str*) – The password of the authenticating account.
- **totp** (*callable or str, optional*) – The time-based one-time password of the authenticating account. Include only if the account uses Code42's two-factor authentication. Defaults to None.

Returns `py42.sdk.SDKClient`

property legalhold

A collection of methods for retrieving and updating legal-hold matters, policies, and custodians.

Returns `py42.services.legalhold.LegalHoldService`

property loginconfig

A collection of methods related to getting information about the login configuration of user accounts.

Returns `py42.clients.loginconfig.LoginConfigurationClient`

property orgs

A collection of methods for retrieving or updating data about organizations in the Code42 environment.

Returns `py42.services.orgs.OrgService`

property securitydata

A collection of methods and properties for getting security data such as:

- File events
- Security plan information

Returns `py42.clients.securitydata.SecurityDataClient`

property serveradmin

A collection of methods for getting server information for on-premise environments and tenant information for cloud environments.

Returns `py42.services.administration.AdministrationService`

property trustedactivities

A collection of methods and properties for managing trusted domains.

Returns `py42.clients.trustedactivities.TrustedActivitiesClient`

property usercontext

A collection of methods related to getting information about the currently logged in user, such as the tenant ID.

Returns `py42.usercontext.UserContext`

property userriskprofile

A collection of methods and properties for managing user risk profiles.

Returns `py42.clients.userriskprofile.UserRiskProfileClient`

property users

A collection of methods for retrieving or updating data about users in the Code42 environment.

Returns `py42.services.users.UserService`

property watchlists

A collection of methods and properties for managing watchlists.

Returns *py42.clients.watchlists.WatchlistsClient*

py42 is a Python wrapper around the Code42 REST APIs that also provides several utility methods. Use py42 to develop your own tools for working with Code42 data while avoiding the overhead of session / authentication management.

**CHAPTER
THREE**

FEATURES

- Managing users, organizations, and devices.
- Searching file events, alerts and auditlogs.
- Adding/Removing employees from detection lists.
- Managing cases.

**CHAPTER
FOUR**

CONTENT

- *User Guides*
- *Method Documentation*

PYTHON MODULE INDEX

p

py42.exceptions, 54
py42.sdk, 203
py42.sdk.queries.alerts.filters.alert_filter,
 25
py42.sdk.queries.fileevents.v2.filters.destination,
 107
py42.sdk.queries.fileevents.v2.filters.event,
 124
py42.sdk.queries.fileevents.v2.filters.file,
 129
py42.sdk.queries.fileevents.v2.filters.process,
 142
py42.sdk.queries.fileevents.v2.filters.report,
 144
py42.sdk.queries.fileevents.v2.filters.risk,
 148
py42.sdk.queries.fileevents.v2.filters.source,
 159
py42.sdk.queries.fileevents.v2.filters.timestamp,
 174
py42.sdk.queries.fileevents.v2.filters.user,
 176
py42.sdk.queries.query_filter, 188
py42.util, 199

INDEX

A

Action (*class in py42.sdk.queries.fileevents.v2.filters.event*), 26
Actor (*class in py42.sdk.queries.alerts.filters.alert_filter*), 25
Actor (*class in py42.sdk.queries.fileevents.filters.cloud_filter*), 81
add() (*py42.services.casesfileevents.CasesFileEventsService* method), 41
add() (*py42.services.detectionlists.departing_employee.DepartingEmployeeService* method), 46
add() (*py42.services.detectionlists.high_risk_employee.HighRiskEmployeeService* method), 48
add_cloud_aliases() (*py42.clients.userriskprofile.UserRiskProfileClient* method), 193
add_destination() (*py42.clients.settings.device_settings.BackupSet* method), 38
add_included_users_by_watchlist_id() (*py42.clients.watchlists.WatchlistsClient* method), 200
add_included_users_by_watchlist_type() (*py42.clients.watchlists.WatchlistsClient* method), 201
add_role() (*py42.services.users.UserService* method), 196
add_to_matter() (*py42.services.legalhold.LegalHoldService* method), 178
add_user() (*py42.clients.alertrules.AlertRulesClient* method), 21
add_user_cloud_alias() (*py42.clients.detectionlists.DetectionListsClient* method), 44
add_user_risk_tags() (*py42.clients.detectionlists.DetectionListsClient* method), 44
AlertQuery (*class in py42.sdk.queries.alerts.alert_query*), 32
AlertRulesClient (*class in py42.clients.alertrules*), 21
alerts (*py42.sdk.SDKClient* property), 204
AlertsClient (*class in py42.clients.alerts*), 23
AlertState (*class in py42.sdk.queries.alerts.filters.alert_filter*), 26
archive (*py42.sdk.SDKClient* property), 204
archive_hold_days (*py42.clients.settings.org_settings.OrgSettings* attribute), 184
ArchiveClient (*class in py42.clients.archive*), 33
auditlogs (*py42.sdk.SDKClient* property), 204
AuditLogsClient (*class in py42.clients.auditlogs*), 36
available_destinations (*py42.clients.settings.device_settings.DeviceSettings* property), 53
available_destinations (*py42.clients.settings.device_settings.DeviceSettingsDefaults* property), 186
available_destinations (*py42.clients.settings.org_settings.OrgSettings* attribute), 184
B

backup_alert_recipient_emails
backup_critical_email_days (*py42.clients.settings.org_settings.OrgSettings* attribute), 184
backup_sets (*py42.clients.settings.device_settings.DeviceSettings* attribute), 53
backup_status_email_enabled (*py42.clients.settings.device_settings.DeviceSettings* attribute), 53
backup_status_email_enabled (*py42.clients.settings.device_settings.DeviceSettingsDefaults* attribute), 186
backup_status_email_frequency_days (*py42.clients.settings.device_settings.DeviceSettings* attribute), 53
backup_status_email_frequency_days (*py42.clients.settings.device_settings.DeviceSettingsDefaults* attribute), 186
backup_warning_email_days (*py42.clients.settings.org_settings.OrgSettings* attribute), 184
BackupSet (*class in py42.clients.settings.device_settings*), 38
block() (*py42.services.devices.DeviceService* method), 49

block() (*py42.services.orgs.OrgService* method), 182
block() (*py42.services.users.UserService* method), 196

C

case_name (*py42.exceptions.Py42CaseNameExistsError* property), 55
cases (*py42.sdk.SDKClient* property), 204
CasesClient (class in *py42.clients.cases*), 39
CasesFileEventsService (class in *py42.services.casesfileevents*), 41
CaseStatus (class in *py42.clients.cases*), 39
CaseStatus (class in *py42.constants*), 42
Category (class in *py42.sdk.queries.fileevents.v2.filters.destination*), 107
Category (class in *py42.sdk.queries.fileevents.v2.filters.file*), 129
Category (class in *py42.sdk.queries.fileevents.v2.filters.source*), 159
CategoryByBytes (class in *py42.sdk.queries.fileevents.v2.filters.file*), 130
CategoryByExtension (class in *py42.sdk.queries.fileevents.v2.filters.file*), 130
change_org_assignment() (*py42.services.users.UserService* method), 196
checksum_name (*py42.exceptions.Py42ChecksumNotFoundError* property), 55
checksum_value (*py42.exceptions.Py42ChecksumNotFoundError* property), 55
choices() (*py42.sdk.queries.alerts.filters.alert_filter.AlertState* class method), 26
choices() (*py42.sdk.queries.alerts.filters.alert_filter.RuleSource* class method), 30
choices() (*py42.sdk.queries.alerts.filters.alert_filter.RuleType* class method), 31
choices() (*py42.sdk.queries.alerts.filters.alert_filter.Severity* class method), 32
choices() (*py42.sdk.queries.fileevents.filters.cloud_filter.SharingType* class method), 83
choices() (*py42.sdk.queries.fileevents.filters.event_filter.EventTimestamp* class method), 67
choices() (*py42.sdk.queries.fileevents.filters.event_filter.EventType* class method), 69
choices() (*py42.sdk.queries.fileevents.filters.event_filter.Source* class method), 71
choices() (*py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType* class method), 84
choices() (*py42.sdk.queries.fileevents.filters.exposure_filter.SyncDestination* class method), 91
choices() (*py42.sdk.queries.fileevents.filters.file_filter.FileCategory* class method), 72

choices() (*py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.CloudData* class method), 101
choices() (*py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.CloudStorage* class method), 101
choices() (*py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.Code* class method), 101
choices() (*py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.Email* class method), 101
in choices() (*py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.ExternalData* class method), 101
choices() (*py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.FileCategory* class method), 102
choices() (*py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.Message* class method), 102
choices() (*py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.Other* class method), 102
choices() (*py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.Social* class method), 102
in choices() (*py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator.User* class method), 102
choices() (*py42.sdk.queries.fileevents.filters.risk_filter.RiskSeverity* class method), 103
choices() (*py42.sdk.queries.fileevents.v2.filters.destination.Category* class method), 108
choices() (*py42.sdk.queries.fileevents.v2.filters.event.Action* class method), 124
choices() (*py42.sdk.queries.fileevents.v2.filters.event.Observer* class method), 127
choices() (*py42.sdk.queries.fileevents.v2.filters.file.Category* class method), 129
choices() (*py42.sdk.queries.fileevents.v2.filters.risk.Indicators.CloudData* class method), 153
choices() (*py42.sdk.queries.fileevents.v2.filters.risk.Indicators.CloudStorage* class method), 153
choices() (*py42.sdk.queries.fileevents.v2.filters.risk.Indicators.CodeRepository* class method), 153
choices() (*py42.sdk.queries.fileevents.v2.filters.risk.Indicators.EmailServer* class method), 153
choices() (*py42.sdk.queries.fileevents.v2.filters.risk.Indicators.ExternalData* class method), 153
choices() (*py42.sdk.queries.fileevents.v2.filters.risk.Indicators.FileCategory* class method), 153
choices() (*py42.sdk.queries.fileevents.v2.filters.risk.Indicators.FileConversion* class method), 153
choices() (*py42.sdk.queries.fileevents.v2.filters.risk.Indicators.Messaging* class method), 153
choices() (*py42.sdk.queries.fileevents.v2.filters.risk.Indicators.PdfManagement* class method), 154
choices() (*py42.sdk.queries.fileevents.v2.filters.risk.Indicators.Productivity* class method), 154
choices() (*py42.sdk.queries.fileevents.v2.filters.risk.Indicators.SocialMedia* class method), 154

choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.UserByRisk.query_filter), 191
 class method), 154
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators.WebHostedUpqueries.query_filter), 191
 class method), 154
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.Severity (py42.sdk.queries.fileevents.util method),
 class method), 157 67
 choices() (py42.sdk.queries.fileevents.v2.filters.risk.TrustReview.create_matter() (py42.services.legalhold.LegalHoldService
 class method), 158 method), 178
 choices() (py42.sdk.queries.fileevents.v2.filters.source.Category.create_not_eq_filter_group() (in module
 class method), 160 py42.sdk.queries.query_filter), 191
 choices() (py42.sdk.queries.fileevents.v2.filters.timestampDirective.create_not_exists_filter_group() (py42.sdk.queries.fileevents.util
 class method), 175 method), 66
 Classification (class in py42.sdk.queries.fileevents.v2.filters.file),
 131
 CloudDriveId (class in py42.sdk.queries.fileevents.v2.filters.file),
 132
 cloudshare (py42.clients.alertrules.AlertRulesClient property), 21
 CloudShareService (class in py42.services.alertrules),
 23
 computer_id (py42.clients.settings.device_settings.DeviceSettings method), 178
 property), 53
 computer_id (py42.clients.settings.device_settings.IncydrDeviceSetting.create_query_filter() (in module
 property), 52 py42.sdk.queries.query_filter), 192
 contains() (py42.sdk.queries.alerts.filters.alert_filter.Actor create_user() (py42.clients.detectionlists.DetectionListsClient
 class method), 25 method), 44
 contains() (py42.sdk.queries.alerts.filters.alert_filter.Description create_within_the_last_filter_group() (in mod-
 class method), 28ule py42.sdk.queries.query_filter), 192
 contains() (py42.sdk.queries.alerts.filters.alert_filter.RuleName Created (class in py42.sdk.queries.fileevents.v2.filters.file),
 class method), 29 133
 convert_datetime_to_timestamp_str() (in module critical_alert_days
 py42.util), 199 (py42.clients.settings.device_settings.DeviceSettings
 convert_timestamp_to_str() (in module py42.util), attribute), 53
 199
 Count (class in py42.sdk.queries.fileevents.v2.filters.report), critical_alert_days
 144 (py42.clients.settings.device_settings.DeviceSettingsDefaults
 create() (py42.clients.cases.CasesClient method), 39 attribute), 186
 create() (py42.clients.trustedactivities.TrustedActivitiesClient critical_email_enabled
 method), 192 (py42.clients.settings.device_settings.DeviceSettings
 create() (py42.clients.watchlists.WatchlistsClient attribute), 53
 method), 201 critical_email_enabled
 create_eq_filter_group() (in module (py42.clients.settings.device_settings.DeviceSettingsDefaults
 py42.sdk.queries.query_filter), 190 attribute), 186
 create_exists_filter_group() (py42.sdk.queries.fileevents.util
 method), 66 D
 DateObserved (class in module
 py42.sdk.queries.alerts.filters.alert_filter),
 27
 deactivate() (py42.services.devices.DeviceService
 method), 49
 deactivate() (py42.services.orgs.OrgService method),
 182

deactivate() (py42.services.users.UserService method), 196
deactivate_matter() (py42.services.legalhold.LegalHoldService method), 178
deauthenticate() (py42.services.devices.DeviceService method), 49
delete() (py42.clients.trustedactivities.TrustedActivitiesClient method), 193
delete() (py42.clients.watchlists.WatchlistsClient method), 201
delete() (py42.services.casesfileevents.CasesFileEventsSe
method), 42
delete_cloud_aliases() (py42.clients.userriskprofile.UserRiskProfileClient method), 194
DepartingEmployeeFilters (class in py42.constants), 43
DepartingEmployeeFilters (class in py42.services.detectionlists.departing_employee), 45
DepartingEmployeeService (class in py42.services.detectionlists.departing_employee), 45
Description (class in py42.sdk.queries.alerts.filters.alert_filter), 28
Description (class in py42.sdk.queries.fileevents.v2.filters.report), 145
destinations (py42.clients.settings.device_settings.BackupSet property), 38
detectionlists (py42.sdk.SDKClient property), 204
DetectionListsClient (class in py42.clients.detectionlists), 44
device_guid(py42.exceptions.Py42ArchiveFileNotFoundException property), 54
device_guid(py42.exceptions.Py42DeviceNotConnectedError property), 56
device_id(py42.clients.settings.device_settings.DeviceSettings property), 53
device_id(py42.clients.settings.device_settings.IncydrDeviceSetting property), 52
devices (py42.sdk.SDKClient property), 204
DeviceService (class in py42.services.devices), 49
DeviceSettings (class in py42.clients.settings.device_settings), 52
DeviceSettingsDefaults (class in py42.clients.settings.device_settings), 186
DeviceSignedInUserName (class in py42.sdk.queries.fileevents.filters.device_filter), 80
DeviceUid (class in py42.sdk.queries.fileevents.v2.filters.user), 176
DeviceUsername (class in py42.sdk.queries.fileevents.filters.device_filter), 77
Directory (class in py42.sdk.queries.fileevents.v2.filters.file), 133
DirectoryID (class in py42.sdk.queries.fileevents.filters.cloud_filter), 81
DirectoryId (class in py42.sdk.queries.fileevents.v2.filters.file), 134
Domain (class in py42.sdk.queries.fileevents.v2.filters.source), 161

E

Email (class in py42.sdk.queries.fileevents.v2.filters.user), 176
email (py42.exceptions.Py42InvalidEmailError property), 57
EmailFrom (class in py42.sdk.queries.fileevents.filters.email_filter), 96
EmailFrom (class in py42.sdk.queries.fileevents.v2.filters.source), 161
EmailPolicyName (class in py42.sdk.queries.fileevents.filters.email_filter), 94
EmailRecipients (class in py42.sdk.queries.fileevents.filters.email_filter), 95
EmailRecipients (class in py42.sdk.queries.fileevents.v2.filters.destination), 109
EmailSender (class in py42.sdk.queries.fileevents.filters.email_filter), 96
EmailSender (class in py42.sdk.queries.fileevents.v2.filters.source), 162
EmailSubject (class in py42.sdk.queries.fileevents.filters.email_filter), 95
EmailSubject (class in py42.sdk.queries.fileevents.v2.filters.destination), 109
encoding (py42.response.Py42Response property), 186
endpoint_monitoring_background_priority_enabled (py42.clients.settings.org_settings.OrgSettings attribute), 184
endpoint_monitoring_browser_and_applications_enabled (py42.clients.settings.org_settings.OrgSettings property), 184
endpoint_monitoring_cloud_sync_enabled (py42.clients.settings.org_settings.OrgSettings property), 184

endpoint_monitoring_custom_applications_mac
 (py42.clients.settings.org_settings.OrgSettings
 attribute), 184

endpoint_monitoring_custom_applications_win
 (py42.clients.settings.org_settings.OrgSettings
 attribute), 184

endpoint_monitoring_enabled
 (py42.clients.settings.org_settings.OrgSettings
 property), 185

endpoint_monitoring_file_exfiltration_detection_exclusionsmethod), 79
 eq() (py42.sdk.queries.fileevents.filters.device_filter.DeviceSignedInUserName
 class method), 80

endpoint_monitoring_file_metadata_collection_enabled
 (py42.clients.settings.org_settings.OrgSettings
 property), 185
 eq() (py42.sdk.queries.fileevents.filters.email_filter.EmailFrom
 class method), 97

endpoint_monitoring_file_metadata_collection_exclusionclass method), 95
 (py42.clients.settings.org_settings.OrgSettings
 attribute), 185
 eq() (py42.sdk.queries.fileevents.filters.email_filter.EmailPolicyName
 class method), 94

endpoint_monitoring_file_metadata_ingroup_enabled
 (py42.clients.settings.org_settings.OrgSettings
 attribute), 185
 eq() (py42.sdk.queries.fileevents.filters.event_filter.EventType
 class method), 69

endpoint_monitoring_file_metadata_scan_enabled
 (py42.clients.settings.org_settings.OrgSettings
 attribute), 185
 eq() (py42.sdk.queries.fileevents.filters.event_filter.Source
 class method), 71

endpoint_monitoring_printer_detection_enabled
 (py42.clients.settings.org_settings.OrgSettings
 property), 185
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType
 class method), 84

endpoint_monitoring_removable_media_enabled
 (py42.clients.settings.org_settings.OrgSettings
 property), 185
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.ProcessName
 class method), 85

eq() (py42.sdk.queries.alerts.filters.alert_filter.Actor
 class method), 26
 eq() (py42.sdk.queries.alerts.filters.alert_filter.AlertState
 class method), 27
 eq() (py42.sdk.queries.alerts.filters.alert_filter.Description
 class method), 28
 eq() (py42.sdk.queries.alerts.filters.alert_filter.RuleId
 class method), 29
 eq() (py42.sdk.queries.alerts.filters.alert_filter.RuleName
 class method), 29
 eq() (py42.sdk.queries.alerts.filters.alert_filter.RuleSource
 class method), 30
 eq() (py42.sdk.queries.alerts.filters.alert_filter.RuleType
 class method), 31
 eq() (py42.sdk.queries.alerts.filters.alert_filter.Severity
 class method), 32
 eq() (py42.sdk.queries.fileevents.filters.cloud_filter.Actor
 class method), 81
 eq() (py42.sdk.queries.fileevents.filters.cloud_filter.Directory
 class method), 81
 eq() (py42.sdk.queries.fileevents.filters.cloud_filter.SharedWith
 class method), 82
 eq() (py42.sdk.queries.fileevents.filters.cloud_filter.SharingType
 class method), 83
 eq() (py42.sdk.queries.fileevents.filters.device_filter.DeviceSignedInUserName
 class method), 80
 eq() (py42.sdk.queries.fileevents.filters.device_filter.DeviceUsername
 class method), 77
 eq() (py42.sdk.queries.fileevents.filters.device_filter.OSHostname
 class method), 78
 eq() (py42.sdk.queries.fileevents.filters.device_filter.PrivateIPAddress
 class method), 78
 eq() (py42.sdk.queries.fileevents.filters.device_filter.PublicIPAddress
 class method), 79
 eq() (py42.sdk.queries.fileevents.filters.email_filter.EmailRecipients
 class method), 95
 eq() (py42.sdk.queries.fileevents.filters.event_filter.EventSender
 class method), 96
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType
 class method), 84
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.ProcessName
 class method), 85
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.ProcessOwner
 class method), 86
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaName
 class method), 88
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaName
 class method), 87
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaPath
 class method), 89
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaSize
 class method), 90
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaVersion
 class method), 87
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMediaVolume
 class method), 89
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.SyncDestination
 class method), 91
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.SyncDestinationUsage
 class method), 92
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.TabURL
 class method), 93
 eq() (py42.sdk.queries.fileevents.filters.exposure_filter.WindowTitle
 class method), 93
 eq() (py42.sdk.queries.fileevents.filters.file_filter.FileCategory
 class method), 72
 eq() (py42.sdk.queries.fileevents.filters.file_filter.FileName
 class method), 73

eq() (py42.sdk.queries.fileevents.filters.file_filter.FileOwner eq() (py42.sdk.queries.fileevents.v2.filters.destination.TabTitleErrors
 class method), 74
eq() (py42.sdk.queries.fileevents.filters.file_filter.FilePath eq() (py42.sdk.queries.fileevents.v2.filters.destination.TabTitles
 class method), 74
eq() (py42.sdk.queries.fileevents.filters.file_filter.MD5 eq() (py42.sdk.queries.fileevents.v2.filters.destination.TabUrlErrors
 class method), 75
eq() (py42.sdk.queries.fileevents.filters.file_filter.SHA256 eq() (py42.sdk.queries.fileevents.v2.filters.destination.TabUrls
 class method), 76
eq() (py42.sdk.queries.fileevents.filters.print_filter.Printer eq() (py42.sdk.queries.fileevents.v2.filters.destination.UserEmail
 class method), 98
eq() (py42.sdk.queries.fileevents.filters.print_filter.PrintJobType eq() (py42.sdk.queries.fileevents.v2.filters.event.Action
 class method), 98
eq() (py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator eq() (py42.sdk.queries.fileevents.v2.filters.event.Id
 class method), 102
eq() (py42.sdk.queries.fileevents.filters.risk_filter.RiskScore eq() (py42.sdk.queries.fileevents.v2.filters.event.Observer
 class method), 104
eq() (py42.sdk.queries.fileevents.filters.risk_filter.RiskSeverity eq() (py42.sdk.queries.fileevents.v2.filters.event.ShareType
 class method), 103
eq() (py42.sdk.queries.fileevents.v2.filters.destination.Category eq() (py42.sdk.queries.fileevents.v2.filters.file.Category
 class method), 108
eq() (py42.sdk.queries.fileevents.v2.filters.destination.Email eq() (py42.sdk.queries.fileevents.v2.filters.file.CategoryByBytes
 class method), 109
eq() (py42.sdk.queries.fileevents.v2.filters.destination.Email eq() (py42.sdk.queries.fileevents.v2.filters.file.CategoryByExtension
 class method), 109
eq() (py42.sdk.queries.fileevents.v2.filters.destination.IpAddress eq() (py42.sdk.queries.fileevents.v2.filters.file.Classification
 class method), 110
eq() (py42.sdk.queries.fileevents.v2.filters.destination.Name eq() (py42.sdk.queries.fileevents.v2.filters.file.CloudDriveId
 class method), 111
eq() (py42.sdk.queries.fileevents.v2.filters.destination.Operation eq() (py42.sdk.queries.fileevents.v2.filters.file.Directory
 class method), 111
eq() (py42.sdk.queries.fileevents.v2.filters.destination.PrintedOn eq() (py42.sdk.queries.fileevents.v2.filters.file.DirectoryId
 class method), 113
eq() (py42.sdk.queries.fileevents.v2.filters.destination.PrintedOn eq() (py42.sdk.queries.fileevents.v2.filters.file.Id
 class method), 113
eq() (py42.sdk.queries.fileevents.v2.filters.destination.PrintedOn eq() (py42.sdk.queries.fileevents.v2.filters.file.MD5
 class method), 112
eq() (py42.sdk.queries.fileevents.v2.filters.destination.Private eq() (py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByBytes
 class method), 114
eq() (py42.sdk.queries.fileevents.v2.filters.destination.Removable eq() (py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByExtension
 class method), 115
eq() (py42.sdk.queries.fileevents.v2.filters.destination.Removable eq() (py42.sdk.queries.fileevents.v2.filters.file.Name
 class method), 116
eq() (py42.sdk.queries.fileevents.v2.filters.destination.Removable eq() (py42.sdk.queries.fileevents.v2.filters.file.Owner
 class method), 116
eq() (py42.sdk.queries.fileevents.v2.filters.destination.Removable eq() (py42.sdk.queries.fileevents.v2.filters.file.SHA256
 class method), 117
eq() (py42.sdk.queries.fileevents.v2.filters.destination.Removable eq() (py42.sdk.queries.fileevents.v2.filters.file.Url
 class method), 118
eq() (py42.sdk.queries.fileevents.v2.filters.destination.Removable eq() (py42.sdk.queries.fileevents.v2.filters.process.Executable
 class method), 119
eq() (py42.sdk.queries.fileevents.v2.filters.destination.Removable eq() (py42.sdk.queries.fileevents.v2.filters.process.Owner
 class method), 119
eq() (py42.sdk.queries.fileevents.v2.filters.destination.Removable eq() (py42.sdk.queries.fileevents.v2.filters.report.Count
 class method), 120

```

eq() (py42.sdk.queries.fileevents.v2.filters.report.Description eq() (py42.sdk.queries.fileevents.v2.filters.source.TabTitles
      class method), 145           class method), 172
eq() (py42.sdk.queries.fileevents.v2.filters.report.Headers eq() (py42.sdk.queries.fileevents.v2.filters.source.TabUrlErrors
      class method), 145           class method), 173
eq() (py42.sdk.queries.fileevents.v2.filters.report.ID   eq() (py42.sdk.queries.fileevents.v2.filters.source.TabUrls
      class method), 146           class method), 173
eq() (py42.sdk.queries.fileevents.v2.filters.report.Name eq() (py42.sdk.queries.fileevents.v2.filters.user.DeviceUid
      class method), 147           class method), 176
eq() (py42.sdk.queries.fileevents.v2.filters.report.Type eq() (py42.sdk.queries.fileevents.v2.filters.user.Email
      class method), 147           class method), 176
eq() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators eq() (py42.sdk.queries.fileevents.v2.filters.user.Id
      class method), 154           class method), 177
eq() (py42.sdk.queries.fileevents.v2.filters.risk.IndicatorsWeight eq() (py42.sdk.queries.query_filter.QueryFilterStringField
      class method), 155           class method), 189
eq() (py42.sdk.queries.fileevents.v2.filters.risk.Score   EventTimestamp           (class           in
      class method), 156           py42.sdk.queries.fileevents.filters.event_filter),
eq() (py42.sdk.queries.fileevents.v2.filters.risk.Severity EventTimestamp           67
      class method), 157           (class           in
eq() (py42.sdk.queries.fileevents.v2.filters.risk.TrustReason EventType (class in py42.sdk.queries.fileevents.filters.event_filter),
      class method), 158           68
eq() (py42.sdk.queries.fileevents.v2.filters.source.Category excluded_files (py42.clients.settings.device_settings.BackupSet
      class method), 160           property), 38
eq() (py42.sdk.queries.fileevents.v2.filters.source.Domain Executable (class in py42.sdk.queries.fileevents.filters.process),
      class method), 161           142
eq() (py42.sdk.queries.fileevents.v2.filters.source.EmailFrom execute() (py42.services.savedsearch.SavedSearchService
      class method), 161           method), 65
eq() (py42.sdk.queries.fileevents.v2.filters.source.EmailSender exfiltration (py42.clients.alertrules.AlertRulesClient
      class method), 162           property), 21
eq() (py42.sdk.queries.fileevents.v2.filters.source.IpAddress ExfiltrationService           (class           in
      class method), 163           py42.services.alertrules), 23
eq() (py42.sdk.queries.fileevents.v2.filters.source.Name exists() (py42.sdk.queries.fileevents.filters.cloud_filter.Actor
      class method), 163           class method), 81
eq() (py42.sdk.queries.fileevents.v2.filters.source.OperatingSystem exists() (py42.sdk.queries.fileevents.filters.cloud_filter.DirectoryID
      class method), 164           class method), 81
eq() (py42.sdk.queries.fileevents.v2.filters.source.PrivateIpAddress exists() (py42.sdk.queries.fileevents.filters.cloud_filter.SharedWith
      class method), 165           class method), 82
eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBusType exists() (py42.sdk.queries.fileevents.filters.cloud_filter.SharingTypeAdded
      class method), 165           class method), 83
eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCapability exists() (py42.sdk.queries.fileevents.filters.device_filter.DeviceSignedInU
      class method), 165           class method), 83
eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaMediaName exists() (py42.sdk.queries.fileevents.filters.device_filter.DeviceUsername
      class method), 167           class method), 77
eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaNameless exists() (py42.sdk.queries.fileevents.filters.device_filter.OSHostname
      class method), 168           class method), 78
eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaPartitionID exists() (py42.sdk.queries.fileevents.filters.device_filter.PrivateIPAddress
      class method), 168           class method), 79
eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaSerialNumber exists() (py42.sdk.queries.fileevents.filters.device_filter.PublicIPAddress
      class method), 169           class method), 79
eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVendorID exists() (py42.sdk.queries.fileevents.filters.event_filter.EventType
      class method), 170           class method), 69
eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVolumeName exists() (py42.sdk.queries.fileevents.filters.event_filter.Source
      class method), 171           class method), 71
eq() (py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType
      class method), 171           class method), 84
eq() (py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors exists() (py42.sdk.queries.fileevents.filters.exposure_filter.ProcessName
      class method), 171           class method), 84

```

```
    class method), 85
exists() (py42.sdk.queries.fileevents.filters.exposure_filter.Exists() (py42.sdk.queries.v2.filters.destination.PrivateIpAddress
    class method), 86
exists() (py42.sdk.queries.fileevents.filters.exposure_filter.Exists() (py42.sdk.queries.v2.filters.destination.RemovableMedia
    class method), 88
exists() (py42.sdk.queries.fileevents.filters.exposure_filter.Exists() (py42.sdk.queries.v2.filters.destination.RemovableMedia
    class method), 87
exists() (py42.sdk.queries.fileevents.filters.exposure_filter.Exists() (py42.sdk.queries.v2.filters.destination.RemovableMedia
    class method), 90
exists() (py42.sdk.queries.fileevents.filters.exposure_filter.Exists() (py42.sdk.queries.v2.filters.destination.RemovableMedia
    class method), 90
exists() (py42.sdk.queries.fileevents.filters.exposure_filter.Exists() (py42.sdk.queries.v2.filters.destination.RemovableMedia
    class method), 90
exists() (py42.sdk.queries.fileevents.filters.exposure_filter.Exists() (py42.sdk.queries.v2.filters.destination.RemovableMedia
    class method), 91
exists() (py42.sdk.queries.fileevents.filters.exposure_filter.Exists() (py42.sdk.queries.v2.filters.destination.RemovableMedia
    class method), 92
exists() (py42.sdk.queries.fileevents.filters.exposure_filter.Exists() (py42.sdk.queries.v2.filters.destination.TabTitleErrors
    class method), 93
exists() (py42.sdk.queries.fileevents.filters.exposure_filter.Exists() (py42.sdk.queries.v2.filters.destination.TabTitles
    class method), 94
exists() (py42.sdk.queries.fileevents.filters.file_filter.FileExists() (py42.sdk.queries.v2.filters.destination.TabUrls
    class method), 72
exists() (py42.sdk.queries.fileevents.filters.file_filter.FileExists() (py42.sdk.queries.v2.filters.destination.TabUrls
    class method), 73
exists() (py42.sdk.queries.fileevents.filters.file_filter.FileExists() (py42.sdk.queries.v2.filters.destination.UserEmail
    class method), 74
exists() (py42.sdk.queries.fileevents.filters.file_filter.FileExists() (py42.sdk.queries.v2.filters.event.Action
    class method), 75
exists() (py42.sdk.queries.fileevents.filters.file_filter.MD5Exists() (py42.sdk.queries.v2.filters.event.Id
    class method), 76
exists() (py42.sdk.queries.fileevents.filters.file_filter.SHA256Exists() (py42.sdk.queries.v2.filters.event.Observer
    class method), 76
exists() (py42.sdk.queries.fileevents.filters.print_filter.PrintExists() (py42.sdk.queries.v2.filters.event.ShareType
    class method), 98
exists() (py42.sdk.queries.fileevents.filters.print_filter.PrintExists() (py42.sdk.queries.v2.filters.file.Category
    class method), 99
exists() (py42.sdk.queries.fileevents.filters.risk_filter.RiskExists() (py42.sdk.queries.v2.filters.file.CategoryByBytes
    class method), 102
exists() (py42.sdk.queries.fileevents.filters.risk_filter.RiskExists() (py42.sdk.queries.v2.filters.file.CategoryByExtension
    class method), 103
exists() (py42.sdk.queries.fileevents.v2.filters.destination.Exists() (py42.sdk.queries.v2.filters.file.Classification
    class method), 108
exists() (py42.sdk.queries.fileevents.v2.filters.destination.Exists() (py42.sdk.queries.v2.filters.file.CloudDriveId
    class method), 110
exists() (py42.sdk.queries.fileevents.v2.filters.destination.Exists() (py42.sdk.queries.v2.filters.file.Directory
    class method), 111
exists() (py42.sdk.queries.fileevents.v2.filters.destination.Exists() (py42.sdk.queries.v2.filters.file.DirectoryId
    class method), 113
exists() (py42.sdk.queries.fileevents.v2.filters.destination.Exists() (py42.sdk.queries.v2.filters.file.Id
    class method), 114
exists() (py42.sdk.queries.fileevents.v2.filters.destination.Exists() (py42.sdk.queries.v2.filters.file.MD5
```

```

    class method), 136
exists() (py42.sdk.queries.fileevents.v2.filters.file.MimeType exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaSource
    class method), 136                                         class method), 169
exists() (py42.sdk.queries.fileevents.v2.filters.file.MimeType exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVe
    class method), 137                                         class method), 170
exists() (py42.sdk.queries.fileevents.v2.filters.file.Name  exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVo
    class method), 139                                         class method), 171
exists() (py42.sdk.queries.fileevents.v2.filters.file.Owner exists() (py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors
    class method), 139                                         class method), 171
exists() (py42.sdk.queries.fileevents.v2.filters.file.SHA256exists() (py42.sdk.queries.fileevents.v2.filters.source.TabTitles
    class method), 140                                         class method), 172
exists() (py42.sdk.queries.fileevents.v2.filters.file.Url  exists() (py42.sdk.queries.fileevents.v2.filters.source.TabUrlErrors
    class method), 142                                         class method), 173
exists() (py42.sdk.queries.fileevents.v2.filters.process.Exe exists() (py42.sdk.queries.fileevents.v2.filters.source.TabUrls
    class method), 142                                         class method), 174
exists() (py42.sdk.queries.fileevents.v2.filters.process.Ow exists() (py42.sdk.queries.fileevents.v2.filters.user.DeviceUid
    class method), 143                                         class method), 176
exists() (py42.sdk.queries.fileevents.v2.filters.report.Count exists() (py42.sdk.queries.fileevents.v2.filters.user.Email
    class method), 144                                         class method), 176
exists() (py42.sdk.queries.fileevents.v2.filters.report.Descri exists() (py42.sdk.queries.fileevents.v2.filters.user.Id
    class method), 145                                         class method), 177
exists() (py42.sdk.queries.fileevents.v2.filters.report.Header export_summary() (py42.clients.cases.CasesClient
    class method), 145                                         method), 39
exists() (py42.sdk.queries.fileevents.v2.filters.report.ID   ExposureType          (class           in
    class method), 146                                         py42.sdk.queries.fileevents.filters.exposure_filter),
exists() (py42.sdk.queries.fileevents.v2.filters.report.Name  external_reference (py42.clients.settings.device_settings.DeviceSetting
    class method), 147                                         attribute), 84
exists() (py42.sdk.queries.fileevents.v2.filters.report.Type  external_reference (py42.clients.settings.device_settings.IncydrDevices
    class method), 148                                         attribute), 53
exists() (py42.sdk.queries.fileevents.v2.filters.risk.Indicators external_reference (py42.clients.settings.org_settings.OrgSettings
    class method), 154                                         attribute), 52
exists() (py42.sdk.queries.fileevents.v2.filters.risk.Severity  external_reference (py42.clients.settings.org_settings.OrgSettings
    class method), 157                                         attribute), 185
exists() (py42.sdk.queries.fileevents.v2.filters.source.Category F
    class method), 160                                         file_events (py42.clients.cases.CasesClient property),
exists() (py42.sdk.queries.fileevents.v2.filters.source.Domain   39
    class method), 161                                         file_path (py42.exceptions.Py42ArchiveFileNotFoundException)
exists() (py42.sdk.queries.fileevents.v2.filters.source.IpAddress  property), 54
    class method), 163                                         FileCategory          (class           in
exists() (py42.sdk.queries.fileevents.v2.filters.source.Name   py42.sdk.queries.fileevents.filters.file_filter), 72
    class method), 163                                         FileEventQuery        (class           in
exists() (py42.sdk.queries.fileevents.v2.filters.source.OperatingSystem  py42.sdk.queries.fileevents.file_event_query),
    class method), 164                                         64
exists() (py42.sdk.queries.fileevents.v2.filters.source.PrivateFingerprint  (class in py42.sdk.queries.fileevents.filters.file_filter),
    class method), 165                                         73
exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaSource  FileOwner (class in py42.sdk.queries.fileevents.filters.file_filter),
    class method), 166                                         FileNameExclusions
exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCapacity  (py42.clients.settings.device_settings.BackupSet
    class method), 166                                         property), 38
exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaPropertyName  FileOwner (class in py42.sdk.queries.fileevents.filters.file_filter),
    class method), 167                                         FileNameExclusions
exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaPartitionID  FilePath (class in py42.sdk.queries.fileevents.filters.file_filter),
    class method), 168                                         FileNameExclusions
exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaPartitionID  FileSize (class in py42.sdk.queries.fileevents.filters.file_filter),
    class method), 169                                         FileNameExclusions

```

```
filetypeismatch(py42.clients.alertrules.AlertRulesClient      23
                property), 21
FileTypeMismatchService      (class      in      get_all()  (py42.clients.alertrules.AlertRulesClient
                py42.services.alertrules), 23                           method), 21
filter_clause(py42.sdk.queries.query_filter.FilterGroup      get_all()  (py42.clients.auditlogs.AuditLogsClient
                property), 188                                         method), 36
filter_list(py42.sdk.queries.query_filter.FilterGroup      get_all()  (py42.clients.cases.CasesClient method), 39
                property), 188                                         method), 193
FilterGroup (class in py42.sdk.queries.query_filter),     get_all()  (py42.clients.trustedactivities.TrustedActivitiesClient
                188                                         method), 194
format_json() (in module py42.util), 200
from_dict() (py42.sdk.queries.query_filter.FilterGroup      get_all()  (py42.clients.watchlists.WatchlistsClient
                class method), 188                                         method), 201
from_dict() (py42.sdk.queries.query_filter.QueryFilter      get_all()  (py42.services.casesfileevents.CasesFileEventsService
                class method), 188                                         method), 42
from_jwt_provider() (in module py42.sdk), 203
from_jwt_provider() (py42.sdk.SDKClient  class      get_all()  (py42.services.detectionlists.departing_employee.DepartingEm
                method), 204                                         method), 46
from_local_account() (in module py42.sdk), 203
from_local_account() (py42.sdk.SDKClient  class      get_all()  (py42.services.detectionlists.high_risk_employee.HighRiskEmp
                method), 204                                         method), 48
get_all() (py42.services.devices.DeviceService method), 50
get_all() (py42.services.orgs.OrgService method), 183
get_all() (py42.services.users.UserService method), 197
get_all_alert_details() (py42.clients.alerts.AlertsClient      method), 97
get_all_by_device_guid() (py42.clients.archive.ArchiveClient  method), 33
get_all_by_name() (py42.clients.alertrules.AlertRulesClient  method), 22
get_all_device_restore_history() (py42.clients.archive.ArchiveClient  method), 33
get_all_events() (py42.services.legalhold.LegalHoldService  method), 179
get_all_included_users() (py42.clients.watchlists.WatchlistsClient  method), 201
get_all_matter_custodians() (py42.services.legalhold.LegalHoldService  method), 179
get_all_matters() (py42.services.legalhold.LegalHoldService  method), 179
get_all_org_cold_storage_archives() (py42.clients.archive.ArchiveClient  method), 33
get_all_org_restore_history() (py42.clients.archive.ArchiveClient  method), 34
get_all_user_restore_history() (py42.clients.archive.ArchiveClient  method), 34
get_all_watchlist_members()
```

(`py42.clients.watchlists.WatchlistsClient method`), 201
`get_attribute_values_from_class()` (*in module `py42.util`*), 200
`get_available_roles()`
 (`py42.services.users.UserService method`), 197
`get_backup_sets()` (`py42.clients.archive.ArchiveClient method`), 34
`get_by_archive_guid()`
 (`py42.clients.archive.ArchiveClient method`), 34
`get_by_guid()` (`py42.services.devices.DeviceService method`), 50
`get_by_id()` (`py42.clients.userriskprofile.UserRiskProfileClient method`), 194
`get_by_id()` (`py42.services.devices.DeviceService method`), 50
`get_by_id()` (`py42.services.orgs.OrgService method`), 183
`get_by_id()` (`py42.services.savedsearch.SavedSearchService method`), 65
`get_by_id()` (`py42.services.users.UserService method`), 197
`get_by_observer_id()`
 (`py42.clients.alertrules.AlertRulesClient method`), 22
`get_by_uid()` (`py42.services.orgs.OrgService method`), 183
`get_by_uid()` (`py42.services.users.UserService method`), 197
`get_by_username()` (`py42.clients.userriskprofile.UserRiskProfileClient method`), 194
`get_by_username()` (`py42.services.users.UserService method`), 197
`get_current()` (`py42.services.orgs.OrgService method`), 183
`get_current()` (`py42.services.users.UserService method`), 197
`get_current_tenant_id()`
 (`py42.usercontext.UserContext method`), 199
`get_custodians_page()`
 (`py42.services.legalhold.LegalHoldService method`), 180
`get_details()` (`py42.clients.alerts.AlertsClient method`), 24
`get_events_page()` (`py42.services.legalhold.LegalHoldService method`), 180
`get_matter_by_uid()`
 (`py42.services.legalhold.LegalHoldService method`), 181
`get_matters_page()` (`py42.services.legalhold.LegalHoldService method`), 181
`get_page()` (`py42.clients.alertrules.AlertRulesClient method`), 22
`get_page()` (`py42.clients.auditlogs.AuditLogsClient method`), 37
`get_page()` (`py42.clients.cases.CasesClient method`), 40
`get_page()` (`py42.clients.userriskprofile.UserRiskProfileClient method`), 194
`get_page()` (`py42.services.detectionlists.departing_employee.DepartingEmployeeClient method`), 46
`get_page()` (`py42.services.detectionlists.high_risk_employee.HighRiskEmployeeClient method`), 48
`get_page()` (`py42.services.devices.DeviceService method`), 51
`get_page()` (`py42.services.orgs.OrgService method`), 183
`get_page()` (`py42.services.users.UserService method`), 197
`get_policy_by_uid()`
 (`py42.services.legalhold.LegalHoldService method`), 181
`get_policy_list()` (`py42.services.legalhold.LegalHoldService method`), 181
`get_query()` (`py42.services.savedsearch.SavedSearchService method`), 65
`get_roles()` (`py42.services.users.UserService method`), 198
`get_scim_data_by_uid()`
 (`py42.services.users.UserService method`), 198
`get_settings()` (`py42.services.devices.DeviceService method`), 51
`get_settings()` (`py42.services.orgs.OrgService method`), 183
`get_user()` (`py42.clients.detectionlists.DetectionListsClient method`), 44
`get_user_by_id()` (`py42.clients.detectionlists.DetectionListsClient method`), 44
`get_watchlist_member()`
 (`py42.clients.watchlists.WatchlistsClient method`), 201
`greater_than()` (`py42.sdk.queries.filerevents.filters.file_filter.FileSize class method`), 75
`greater_than()` (`py42.sdk.queries.filerevents.filters.risk_filter.RiskScore class method`), 104
`greater_than()` (`py42.sdk.queries.filerevents.v2.filters.report.Count class method`), 144
`greater_than()` (`py42.sdk.queries.filerevents.v2.filters.risk.IndicatorsWeight class method`), 155
`greater_than()` (`py42.sdk.queries.filerevents.v2.filters.risk.Score class method`), 156
`guid` (`py42.clients.settings.device_settings.DeviceSettings property`), 53
`guid` (`py42.clients.settings.device_settings.IncydrDeviceSettings property`), 52

H

Headers (class in `py42.sdk.queries.fileevents.v2.filters.report`), 145
headers (`py42.response.Py42Response` property), 186
HighRiskEmployeeFilters (class in `py42.constants`), 43
HighRiskEmployeeFilters (class in `py42.services.detectionlists.high_risk_employee`), 47
HighRiskEmployeeService (class in `py42.services.detectionlists.high_risk_employee`), 47

I

Id (class in `py42.sdk.queries.fileevents.v2.filters.event`), 125
Id (class in `py42.sdk.queries.fileevents.v2.filters.file`), 135
ID (class in `py42.sdk.queries.fileevents.v2.filters.report`), 146
Id (class in `py42.sdk.queries.fileevents.v2.filters.user`), 177
`in_range()` (`py42.sdk.queries.alerts.filters.alert_filter.DateObserved` class method), 27
`in_range()` (`py42.sdk.queries.fileevents.filters.event_filter.EventTimestamp` class method), 67
`in_range()` (`py42.sdk.queries.fileevents.filters.event_filter.InsertionTimestamp` class method), 69
`in_range()` (`py42.sdk.queries.fileevents.v2.filters.event.Inserted` class method), 126
`in_range()` (`py42.sdk.queries.fileevents.v2.filters.file.Created` class method), 133
`in_range()` (`py42.sdk.queries.fileevents.v2.filters.file.Modified` class method), 138
`in_range()` (`py42.sdk.queries.fileevents.v2.filters.file.Size` class method), 141
`in_range()` (`py42.sdk.queries.fileevents.v2.filters.timestamp.Timestamp` class method), 175
`in_range()` (`py42.sdk.queries.query_filter.QueryFilterTimestampField` class method), 190
included_files (`py42.clients.settings.device_settings.BackupSet` property), 38
IncydrDeviceSettings (class in `py42.clients.settings.device_settings`), 52
Indicators (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 148
Indicators.CloudDataExposures (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 152
Indicators.CloudStorageUploads (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 153
Indicators.CodeRepositoryUploads (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 153

Indicators.EmailServiceUploads (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 153
Indicators.ExternalDevices (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 153
Indicators.FileCategories (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 153
Indicators.FileConversionToolUploads (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 153
Indicators.MessagingServiceUploads (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 153
Indicators.Other (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 154
Indicators.PdfManagerUploads (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 154
Indicators.ProductivityToolUploads (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 154
Indicators.SocialMediaUploads (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 154
Indicators.UserBehavior (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 154
Indicators.WebHostingUploads (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 154
IndicatorsWeight (class in `py42.sdk.queries.fileevents.v2.filters.risk`), 155
Inserted (class in `py42.sdk.queries.fileevents.v2.filters.event`), 126
InsertionTimestamp (class in `py42.sdk.queries.fileevents.filters.event_filter`), 69
IpAddress (class in `py42.sdk.queries.fileevents.v2.filters.destination`), 110
IpAddress (class in `py42.sdk.queries.fileevents.v2.filters.source`), 163
is_false() (`py42.sdk.queries.fileevents.filters.activity_filter.RemoteActivity` class method), 97
is_false() (`py42.sdk.queries.fileevents.filters.activity_filter.TrustedActivity` class method), 97
is_false() (`py42.sdk.queries.fileevents.filters.cloud_filter.Shared` class method), 82
is_false() (`py42.sdk.queries.fileevents.filters.event_filter.MimeTypeMismatch` class method), 71
is_false() (`py42.sdk.queries.fileevents.filters.event_filter.OutsideActiveHours` class method), 72
is_false() (`py42.sdk.queries.fileevents.v2.filters.risk.Trusted` class method), 159

```

is_false() (py42.sdk.queries.query_filter.QueryFilterBookmarksFilter) (py42.sdk.queries.fileevents.filters.exposure_filter.ProcessOwner
    class method), 189
                                         class method), 86
is_in() (py42.sdk.queries.alerts.filters.alert_filter.Actor  is_in() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMedia
    class method), 26
                                         class method), 88
is_in() (py42.sdk.queries.alerts.filters.alert_filter.AlertStates_in() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMedia
    class method), 27
                                         class method), 87
is_in() (py42.sdk.queries.alerts.filters.alert_filter.Description_is_in() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMedia
    class method), 28
                                         class method), 90
is_in() (py42.sdk.queries.alerts.filters.alert_filter.RuleId  is_in() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMedia
    class method), 29
                                         class method), 90
is_in() (py42.sdk.queries.alerts.filters.alert_filter.RuleName_is_in() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMedia
    class method), 29
                                         class method), 87
is_in() (py42.sdk.queries.alerts.filters.alert_filter.RuleSource_is_in() (py42.sdk.queries.fileevents.filters.exposure_filter.RemovableMedia
    class method), 30
                                         class method), 89
is_in() (py42.sdk.queries.alerts.filters.alert_filter.RuleType_is_in() (py42.sdk.queries.fileevents.filters.exposure_filter.SyncDestination
    class method), 31
                                         class method), 91
is_in() (py42.sdk.queries.alerts.filters.alert_filter.Severity_is_in() (py42.sdk.queries.fileevents.filters.exposure_filter.SyncDestination
    class method), 32
                                         class method), 92
is_in() (py42.sdk.queries.fileevents.filters.cloud_filter.Actor_is_in() (py42.sdk.queries.fileevents.filters.exposure_filter.TabURL
    class method), 81
                                         class method), 93
is_in() (py42.sdk.queries.fileevents.filters.cloud_filter.Directory_is_in() (py42.sdk.queries.fileevents.filters.exposure_filter.WindowTitle
    class method), 82
                                         class method), 94
is_in() (py42.sdk.queries.fileevents.filters.cloud_filter.ShareType_is_in() (py42.sdk.queries.fileevents.filters.file_filter.FileCategory
    class method), 83
                                         class method), 73
is_in() (py42.sdk.queries.fileevents.filters.cloud_filter.SharingType_is_in() (py42.sdk.queries.fileevents.filters.file_filter.FileName
    class method), 83
                                         class method), 73
is_in() (py42.sdk.queries.fileevents.filters.device_filter.DeviceSignature_is_in() (py42.sdk.queries.fileevents.filters.file_filter.FileOwner
    class method), 80
                                         class method), 74
is_in() (py42.sdk.queries.fileevents.filters.device_filter.DeviceType_is_in() (py42.sdk.queries.fileevents.filters.file_filter.FilePath
    class method), 77
                                         class method), 75
is_in() (py42.sdk.queries.fileevents.filters.device_filter.OSHost_is_in() (py42.sdk.queries.fileevents.filters.file_filter.MD5
    class method), 78
                                         class method), 76
is_in() (py42.sdk.queries.fileevents.filters.device_filter.PrivateIPAddr_is_in() (py42.sdk.queries.fileevents.filters.file_filter.SHA256
    class method), 79
                                         class method), 76
is_in() (py42.sdk.queries.fileevents.filters.device_filter.PublicIPAddr_is_in() (py42.sdk.queries.fileevents.filters.print_filter.Printer
    class method), 79
                                         class method), 98
is_in() (py42.sdk.queries.fileevents.filters.email_filter.EmailFrom_is_in() (py42.sdk.queries.fileevents.filters.print_filter.PrintJobName
    class method), 97
                                         class method), 99
is_in() (py42.sdk.queries.fileevents.filters.email_filter.EmailPolicy_is_in() (py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator
    class method), 94
                                         class method), 102
is_in() (py42.sdk.queries.fileevents.filters.email_filter.EmailRecipient_is_in() (py42.sdk.queries.fileevents.filters.risk_filter.RiskScore
    class method), 96
                                         class method), 104
is_in() (py42.sdk.queries.fileevents.filters.email_filter.EmailSender_is_in() (py42.sdk.queries.fileevents.filters.risk_filter.RiskSeverity
    class method), 96
                                         class method), 103
is_in() (py42.sdk.queries.fileevents.filters.email_filter.EmailSubject_is_in() (py42.sdk.queries.fileevents.v2.filters.destination.Category
    class method), 95
                                         class method), 108
is_in() (py42.sdk.queries.fileevents.filters.event_filter.EventType_is_in() (py42.sdk.queries.fileevents.v2.filters.destination.EmailRecipients
    class method), 69
                                         class method), 109
is_in() (py42.sdk.queries.fileevents.filters.event_filter.Source_is_in() (py42.sdk.queries.fileevents.v2.filters.destination.EmailSubject
    class method), 71
                                         class method), 110
is_in() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType_is_in() (py42.sdk.queries.fileevents.v2.filters.destinationIpAddress
    class method), 85
                                         class method), 110
is_in() (py42.sdk.queries.fileevents.filters.exposure_filter.Location_is_in() (py42.sdk.queries.fileevents.v2.filters.destination.Name
    class method), 85
                                         class method), 111

```

is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.Operation*)
 (*py42.sdk.queries.fileevents.v2.filters.file.Directory*
 class method), 112
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.PossibleFileTypes*)
 (*py42.sdk.queries.fileevents.v2.filters.file.DirectoryId*
 class method), 134
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.PossibleName*)
 (*py42.sdk.queries.fileevents.v2.filters.file.Id*
 class method), 135
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.PossibleName*)
 (*py42.sdk.queries.fileevents.v2.filters.file.MD5*
 class method), 136
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.PossibleName*)
 (*py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByBytes*
 class method), 136
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.Resolvable*)
 (*py42.sdk.queries.fileevents.v2.filters.file.MimeTypeByExtension*
 class method), 137
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.Resolvable*)
 (*py42.sdk.queries.fileevents.v2.filters.file.Name*
 class method), 139
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.Resolvable*)
 (*py42.sdk.queries.fileevents.v2.filters.file.Owner*
 class method), 139
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.Resolvable*)
 (*py42.sdk.queries.fileevents.v2.filters.file.SHA256*
 class method), 140
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.Resolvable*)
 (*py42.sdk.queries.fileevents.v2.filters.file.Url*
 class method), 142
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.Resolvable*)
 (*py42.sdk.queries.fileevents.v2.filters.process.Executable*
 class method), 142
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.Resolvable*)
 (*py42.sdk.queries.fileevents.v2.filters.process.Owner*
 class method), 143
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.Resolvable*)
 (*py42.sdk.queries.fileevents.v2.filters.report.Count*
 class method), 144
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.TabTitle*)
 (*py42.sdk.queries.fileevents.v2.filters.report.Description*
 class method), 145
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.TabTitle*)
 (*py42.sdk.queries.fileevents.v2.filters.report.Headers*
 class method), 145
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.TabTitle*)
 (*py42.sdk.queries.fileevents.v2.filters.report.ID*
 class method), 146
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.TabTitle*)
 (*py42.sdk.queries.fileevents.v2.filters.report.Name*
 class method), 147
is_in() (*py42.sdk.queries.fileevents.v2.filters.destination.UserId*)
 (*py42.sdk.queries.fileevents.v2.filters.report.Type*
 class method), 148
is_in() (*py42.sdk.queries.fileevents.v2.filters.event.Action*)
 is_in() (*py42.sdk.queries.fileevents.v2.filters.risk.Indicators*
 class method), 155
is_in() (*py42.sdk.queries.fileevents.v2.filters.event.Id*)
 is_in() (*py42.sdk.queries.fileevents.v2.filters.risk.IndicatorsWeight*
 class method), 155
is_in() (*py42.sdk.queries.fileevents.v2.filters.event.Observers*)
 is_in() (*py42.sdk.queries.fileevents.v2.filters.risk.Score*
 class method), 156
is_in() (*py42.sdk.queries.fileevents.v2.filters.event.ShareType*)
 is_in() (*py42.sdk.queries.fileevents.v2.filters.risk.Severity*
 class method), 157
is_in() (*py42.sdk.queries.fileevents.v2.filters.file.Category*)
 is_in() (*py42.sdk.queries.fileevents.v2.filters.risk.TrustReason*
 class method), 158
is_in() (*py42.sdk.queries.fileevents.v2.filters.file.Category*)
 is_in() (*py42.sdk.queries.fileevents.v2.filters.source.Category*
 class method), 160
is_in() (*py42.sdk.queries.fileevents.v2.filters.file.Category*)
 is_in() (*py42.sdk.queries.fileevents.v2.filters.source.Domain*
 class method), 161
is_in() (*py42.sdk.queries.fileevents.v2.filters.file.Classification*)
 is_in() (*py42.sdk.queries.fileevents.v2.filters.source.EmailFrom*
 class method), 162
is_in() (*py42.sdk.queries.fileevents.v2.filters.file.CloudDrive*)
 is_in() (*py42.sdk.queries.fileevents.v2.filters.source.EmailSender*
 class method), 162

J
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.IpAddressContent) (py42.response.Py42Response
 class method), 163
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.Name
 class method), 163
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.OperatingSystemJavaMemory_heap_max
 class method), 164
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.PrivateIpAddressProperty), 53
 class method), 165
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBusType
 class method), 166
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCapacity
 class method), 166
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCapacity
 class method), 167
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCapacity
 class method), 168
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCapacity
 class method), 169
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCapacity
 class method), 170
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCapacity
 class method), 171
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors
 class method), 171
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.TabTitles
 class method), 172
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.TabUrls
 class method), 173
 is_in() (py42.sdk.queries.fileevents.v2.filters.source.TabUrls
 class method), 174
 is_in() (py42.sdk.queries.fileevents.v2.filters.user.DeviceUid
 class method), 176
 is_in() (py42.sdk.queries.fileevents.v2.filters.user.Email
 class method), 176
 is_in() (py42.sdk.queries.fileevents.v2.filters.user.Id
 class method), 177
M
 is_in() (py42.sdk.queries.query_filter.QueryFilterStringField
 class method), 189
 is_true() (py42.sdk.queries.fileevents.filters.activity_filter.RemoteActivity
 class method), 97
 is_true() (py42.sdk.queries.fileevents.filters.activity_filter.TrustedActivity
 class method), 97
 is_true() (py42.sdk.queries.fileevents.filters.cloud_filter.Shared
 class method), 82
 is_true() (py42.sdk.queries.fileevents.filters.event_filter.MimeTypeMismatch
 class method), 71
 is_true() (py42.sdk.queries.fileevents.filters.event_filter.OutsideActiveHours
 class method), 72
 is_true() (py42.sdk.queries.fileevents.v2.filters.risk.Trusted
 class method), 159
 is_true() (py42.sdk.queries.query_filter.QueryFilterBooleanField
 class method), 189
N
 less_than() (py42.sdk.queries.fileevents.filters.file_filter.FileSize
 class method), 75
 less_than() (py42.sdk.queries.fileevents.filters.risk_filter.RiskScore
 class method), 104
 less_than() (py42.sdk.queries.fileevents.v2.filters.report.Count
 class method), 144
 less_than() (py42.sdk.queries.fileevents.v2.filters.risk.IndicatorsWeight
 class method), 155
 less_than() (py42.sdk.queries.fileevents.v2.filters.risk.Score
 class method), 156
 list_name (py42.exceptions.Py42UserNotOnListError
 property), 63
 lock_destination() (py42.clients.settings.device_settings.BackupSet
 method), 38
 locked (py42.clients.settings.device_settings.BackupSet
 property), 38
 loginconfig (py42.sdk.SDKClient property), 205
P
 maximum_user_subscriptions (py42.clients.settings.org_settings.OrgSettings
 attribute), 185
 MD5 (class in py42.sdk.queries.fileevents.filters.file_filter),
 75
 MD5 (class in py42.sdk.queries.fileevents.v2.filters.file),
 135
 MimeByBytes (class in py42.sdk.queries.fileevents.v2.filters.file),
 136
 MimeByExtension (class in py42.sdk.queries.fileevents.v2.filters.file),
 137
 MimeMismatch (class in py42.sdk.queries.fileevents.v2.filters.file),
 71
R
 py42.sdk.queries.fileevents.filters.event_filter)

Modified (*class* in `py42.sdk.queries.fileevents.v2.filters.file`) `not_eq()` (*py42.sdk.queries.alerts.filters.alert_filter.RuleId class method*), 29
138
module
 `py42.exceptions`, 54
 `py42.sdk`, 203
 `py42.sdk.queries.alerts.filters.alert_filter`, *class method*), 31
 25
 `py42.sdk.queries.fileevents.v2.filters.destination`*class method*), 31
 107
 `py42.sdk.queries.fileevents.v2.filters.event`, *class method*), 32
 124
 `py42.sdk.queries.fileevents.v2.filters.file`, *class method*), 81
 129
 `py42.sdk.queries.fileevents.v2.filters.process`, *class method*), 82
 142
 `py42.sdk.queries.fileevents.v2.filters.report`, *class method*), 83
 144
 `py42.sdk.queries.fileevents.v2.filters.risk`, *class method*), 84
 148
 `py42.sdk.queries.fileevents.v2.filters.source`, *class method*), 80
 159
 `py42.sdk.queries.fileevents.v2.filters.timestamp`, *class method*), 77
 174
 `py42.sdk.queries.fileevents.v2.filters.user`, *class method*), 78
 176
 `py42.sdk.queries.query_filter`, 188
 `py42.util`, 199

N

`Name` (*class* in `py42.sdk.queries.fileevents.v2.filters.destination`), *class method*), 97
111
`Name` (*class* in `py42.sdk.queries.fileevents.v2.filters.file`), *class method*), 95
138
`Name` (*class* in `py42.sdk.queries.fileevents.v2.filters.report`), *class method*), 96
147
`Name` (*class* in `py42.sdk.queries.fileevents.v2.filters.source`), *class method*), 96
163
`name` (`py42.clients.settings.device_settings.DeviceSettings attribute`), 53
 class method), 53
`name` (`py42.clients.settings.device_settings.IncydrDeviceSettings property`), 52
 class method), 52
`not_contains()` (`py42.sdk.queries.alerts.filters.alert_filter.Actor` *class method*), 71
 class method), 26
`not_contains()` (`py42.sdk.queries.alerts.filters.alert_filter.Description` *class method*), 85
 class method), 28
`not_contains()` (`py42.sdk.queries.alerts.filters.alert_filter.RuleName` *class method*), 85
 class method), 30
`not_eq()` (`py42.sdk.queries.alerts.filters.alert_filter.Actor` *class method*), 86
 class method), 26
`not_eq()` (`py42.sdk.queries.alerts.filters.alert_filter.AlertState` *class method*), 88
 class method), 27
`not_eq()` (`py42.sdk.queries.alerts.filters.alert_filter.Description` *class method*), 87
 class method), 28
`not_eq()` (`py42.sdk.queries.alerts.filters.alert_filter.Description` *class method*), 90
 class method), 90

not_eq() (py42.sdk.queries.fileevents.filters.exposure_filter.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.destination.PrivateIpAddress.
class method), 91
 class method), 115

not_eq() (py42.sdk.queries.fileevents.filters.exposure_filter.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia.
class method), 88
 class method), 115

not_eq() (py42.sdk.queries.fileevents.filters.exposure_filter.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia.
class method), 89
 class method), 116

not_eq() (py42.sdk.queries.fileevents.filters.exposure_filter.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia.
class method), 92
 class method), 117

not_eq() (py42.sdk.queries.fileevents.filters.exposure_filter.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia.
class method), 92
 class method), 117

not_eq() (py42.sdk.queries.fileevents.filters.exposure_filter.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia.
class method), 93
 class method), 118

not_eq() (py42.sdk.queries.fileevents.filters.exposure_filter.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia.
class method), 94
 class method), 119

not_eq() (py42.sdk.queries.fileevents.filters.file_filter.FileContent.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia.
class method), 73
 class method), 120

not_eq() (py42.sdk.queries.fileevents.filters.file_filter.FileContent.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia.
class method), 73
 class method), 120

not_eq() (py42.sdk.queries.fileevents.filters.file_filter.FileContent.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.destination.TabTitleErrors.
class method), 74
 class method), 121

not_eq() (py42.sdk.queries.fileevents.filters.file_filter.FilePath.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.destination.TabTitles.
class method), 75
 class method), 122

not_eq() (py42.sdk.queries.fileevents.filters.file_filter.MD5.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.destination.TabUrlErrors.
class method), 76
 class method), 122

not_eq() (py42.sdk.queries.fileevents.filters.file_filter.SHA256.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.destination.TabUrls.
class method), 77
 class method), 123

not_eq() (py42.sdk.queries.fileevents.filters.print_filter.Print.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.destination.UserEmail.
class method), 98
 class method), 124

not_eq() (py42.sdk.queries.fileevents.filters.print_filter.Print.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.event.Action.
class method), 99
 class method), 125

not_eq() (py42.sdk.queries.fileevents.filters.risk_filter.RiskNotice.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.event.Id.
class method), 103
 class method), 126

not_eq() (py42.sdk.queries.fileevents.filters.risk_filter.RiskNotice.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.event.Observer.
class method), 104
 class method), 127

not_eq() (py42.sdk.queries.fileevents.filters.risk_filter.RiskNotice.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.event.ShareType.
class method), 104
 class method), 128

not_eq() (py42.sdk.queries.fileevents.v2.filters.destination.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.file.Category.
class method), 109
 class method), 129

not_eq() (py42.sdk.queries.fileevents.v2.filters.destination.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.file.CategoryByBytes.
class method), 109
 class method), 130

not_eq() (py42.sdk.queries.fileevents.v2.filters.destination.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.file.CategoryByExtension.
class method), 110
 class method), 131

not_eq() (py42.sdk.queries.fileevents.v2.filters.destination.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.file.Classification.
class method), 110
 class method), 132

not_eq() (py42.sdk.queries.fileevents.v2.filters.destination.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.file.CloudDriveId.
class method), 111
 class method), 132

not_eq() (py42.sdk.queries.fileevents.v2.filters.destination.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.file.Directory.
class method), 112
 class method), 134

not_eq() (py42.sdk.queries.fileevents.v2.filters.destination.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.file.DirectoryId.
class method), 113
 class method), 134

not_eq() (py42.sdk.queries.fileevents.v2.filters.destination.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.file.Id.
class method), 114
 class method), 135

not_eq() (py42.sdk.queries.fileevents.v2.filters.destination.**not_eq()** (py42.sdk.queries.fileevents.v2.filters.file.MD5.
class method), 112
 class method), 136

not_eq() (py42.sdk.queries.fileevents.v2.filters.file.MimeType) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (class method), 137
not_eq() (py42.sdk.queries.fileevents.v2.filters.file.MimeType) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (class method), 137
not_eq() (py42.sdk.queries.fileevents.v2.filters.file.Name) not_eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (class method), 139
not_eq() (py42.sdk.queries.fileevents.v2.filters.file.Owner) not_eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (class method), 140
not_eq() (py42.sdk.queries.fileevents.v2.filters.file.SHA256) not_eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (class method), 140
not_eq() (py42.sdk.queries.fileevents.v2.filters.file.Url) not_eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (class method), 142
not_eq() (py42.sdk.queries.fileevents.v2.filters.process.Exe) not_eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (class method), 143
not_eq() (py42.sdk.queries.fileevents.v2.filters.process.Owner) not_eq() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBucket) (class method), 143
not_eq() (py42.sdk.queries.fileevents.v2.filters.report.Count) not_eq() (py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors) (py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors) (class method), 144
not_eq() (py42.sdk.queries.fileevents.v2.filters.report.Description) not_eq() (py42.sdk.queries.fileevents.v2.filters.source.TabTitles) (py42.sdk.queries.fileevents.v2.filters.source.TabTitles) (class method), 145
not_eq() (py42.sdk.queries.fileevents.v2.filters.report.Header) not_eq() (py42.sdk.queries.fileevents.v2.filters.source.TabUrlErrors) (py42.sdk.queries.fileevents.v2.filters.source.TabUrlErrors) (class method), 146
not_eq() (py42.sdk.queries.fileevents.v2.filters.report.ID) not_eq() (py42.sdk.queries.fileevents.v2.filters.source.TabUrls) (py42.sdk.queries.fileevents.v2.filters.source.TabUrls) (class method), 146
not_eq() (py42.sdk.queries.fileevents.v2.filters.report.Name) not_eq() (py42.sdk.queries.fileevents.v2.filters.user.DeviceUid) (py42.sdk.queries.fileevents.v2.filters.user.DeviceUid) (class method), 147
not_eq() (py42.sdk.queries.fileevents.v2.filters.report.Type) not_eq() (py42.sdk.queries.fileevents.v2.filters.user.Email) (py42.sdk.queries.fileevents.v2.filters.user.Email) (class method), 148
not_eq() (py42.sdk.queries.fileevents.v2.filters.risk.Indicator) not_eq() (py42.sdk.queries.fileevents.v2.filters.user.Id) (py42.sdk.queries.fileevents.v2.filters.user.Id) (class method), 155
not_eq() (py42.sdk.queries.fileevents.v2.filters.risk.Indicator) not_weight() (py42.sdk.queries.query_filter.QueryFilterStringField) (py42.sdk.queries.query_filter.QueryFilterStringField) (class method), 155
not_eq() (py42.sdk.queries.fileevents.v2.filters.risk.Score) not_exists() (py42.sdk.queries.fileevents.filters.cloud_filter.Actor) (py42.sdk.queries.fileevents.filters.cloud_filter.Actor) (class method), 156
not_eq() (py42.sdk.queries.fileevents.v2.filters.risk.Severity) not_exists() (py42.sdk.queries.fileevents.filters.cloud_filter.DirectoryID) (py42.sdk.queries.fileevents.filters.cloud_filter.DirectoryID) (class method), 157
not_eq() (py42.sdk.queries.fileevents.v2.filters.risk.TrustReason) not_exists() (py42.sdk.queries.fileevents.filters.cloud_filter.SharedWith) (py42.sdk.queries.fileevents.filters.cloud_filter.SharedWith) (class method), 158
not_eq() (py42.sdk.queries.fileevents.v2.filters.source.Category) not_exists() (py42.sdk.queries.fileevents.filters.cloud_filter.SharingType) (py42.sdk.queries.fileevents.filters.cloud_filter.SharingType) (class method), 160
not_eq() (py42.sdk.queries.fileevents.v2.filters.source.Domain) not_exists() (py42.sdk.queries.fileevents.filters.device_filter.DeviceSignature) (py42.sdk.queries.fileevents.filters.device_filter.DeviceSignature) (class method), 161
not_eq() (py42.sdk.queries.fileevents.v2.filters.source.Email) not_exists() (py42.sdk.queries.fileevents.filters.device_filter.DeviceUsernames) (py42.sdk.queries.fileevents.filters.device_filter.DeviceUsernames) (class method), 162
not_eq() (py42.sdk.queries.fileevents.v2.filters.source.Email) not_exists() (py42.sdk.queries.fileevents.filters.device_filter.OSHostname) (py42.sdk.queries.fileevents.filters.device_filter.OSHostname) (class method), 162
not_eq() (py42.sdk.queries.fileevents.v2.filters.source.IpAddress) not_exists() (py42.sdk.queries.fileevents.filters.device_filter.PrivateIPAddresses) (py42.sdk.queries.fileevents.filters.device_filter.PrivateIPAddresses) (class method), 163
not_eq() (py42.sdk.queries.fileevents.v2.filters.source.Name) not_exists() (py42.sdk.queries.fileevents.filters.device_filter.PublicIPAddresses) (py42.sdk.queries.fileevents.filters.device_filter.PublicIPAddresses) (class method), 164
not_eq() (py42.sdk.queries.fileevents.v2.filters.source.OpenFile) not_exists() (py42.sdk.queries.fileevents.filters.event_filter.EventType) (py42.sdk.queries.fileevents.filters.event_filter.EventType) (class method), 164
not_eq() (py42.sdk.queries.fileevents.v2.filters.source.PrivateIpAddress) not_exists() (py42.sdk.queries.fileevents.filters.event_filter.Source) (py42.sdk.queries.fileevents.filters.event_filter.Source) (class method), 165

```

not_exists() (py42.sdk.queries.fileevents.filters.exposure.filterExists()filterExistsForType(py42.sdk.queries.fileevents.v2.filters.destination.PrinterName)
    class method), 85
    class method), 114
not_exists() (py42.sdk.queries.fileevents.filters.exposure.filterExists()filterExistsByName(py42.sdk.queries.fileevents.v2.filters.destination.PrintJobName)
    class method), 86
    class method), 112
not_exists() (py42.sdk.queries.fileevents.filters.exposure.filterExists()filterExistsByIp(py42.sdk.queries.fileevents.v2.filters.destination.PrivateIpAddress)
    class method), 86
    class method), 115
not_exists() (py42.sdk.queries.fileevents.filters.exposure.filterExists()filterExistsByMediaMedium(py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia)
    class method), 88
    class method), 115
not_exists() (py42.sdk.queries.fileevents.filters.exposure.filterExists()filterExistsByMediaName(py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia)
    class method), 87
    class method), 116
not_exists() (py42.sdk.queries.fileevents.filters.exposure.filterExists()filterExistsByMediaPlanId(py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia)
    class method), 90
    class method), 117
not_exists() (py42.sdk.queries.fileevents.filters.exposure.filterExists()filterExistsByMediaScriptName(py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia)
    class method), 91
    class method), 118
not_exists() (py42.sdk.queries.fileevents.filters.exposure.filterExists()filterExistsByMediaSqlQuery(py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia)
    class method), 88
    class method), 118
not_exists() (py42.sdk.queries.fileevents.filters.exposure.filterExists()filterExistsByMediaSqlName(py42.sdk.queries.fileevents.v2.filters.destination.RemovableMedia)
    class method), 89
    class method), 119
not_exists() (py42.sdk.queries.fileevents.filters.exposure.filterExists()filterExistsByTabTitle(py42.sdk.queries.fileevents.v2.filters.destination.TabTitleError)
    class method), 92
    class method), 120
not_exists() (py42.sdk.queries.fileevents.filters.exposure.filterExists()filterExistsByTabTitleName(py42.sdk.queries.fileevents.v2.filters.destination.TabTitleError)
    class method), 92
    class method), 120
not_exists() (py42.sdk.queries.fileevents.filters.exposure.filterExists()filterExistsForTabTitle(py42.sdk.queries.fileevents.v2.filters.destination.TabTitleError)
    class method), 93
    class method), 121
not_exists() (py42.sdk.queries.fileevents.filters.exposure.filterExists()filterExistsForTabTitles(py42.sdk.queries.fileevents.v2.filters.destination.TabTitles)
    class method), 94
    class method), 122
not_exists() (py42.sdk.queries.fileevents.filters.file_filter.filterExists()filterExistsForFile(py42.sdk.queries.fileevents.v2.filters.destination.TabUrlError)
    class method), 73
    class method), 123
not_exists() (py42.sdk.queries.fileevents.filters.file_filter.filterExists()filterExistsForFile(py42.sdk.queries.fileevents.v2.filters.destination.TabUrls)
    class method), 73
    class method), 123
not_exists() (py42.sdk.queries.fileevents.filters.file_filter.filterExists()filterExistsForFile(py42.sdk.queries.fileevents.v2.filters.destination.UserEmail)
    class method), 74
    class method), 124
not_exists() (py42.sdk.queries.fileevents.filters.file_filter.filterExists()filterExistsForFile(py42.sdk.queries.fileevents.v2.filters.event.Action)
    class method), 75
    class method), 125
not_exists() (py42.sdk.queries.fileevents.filters.file_filter.filterExists()filterExistsForFile(py42.sdk.queries.fileevents.v2.filters.event.Id)
    class method), 76
    class method), 126
not_exists() (py42.sdk.queries.fileevents.filters.file_filter.filterExists()filterExistsForFile(py42.sdk.queries.fileevents.v2.filters.event.Observer)
    class method), 77
    class method), 128
not_exists() (py42.sdk.queries.fileevents.filters.print_filter.filterExists()filterExistsForPrint(py42.sdk.queries.fileevents.v2.filters.event.ShareType)
    class method), 98
    class method), 128
not_exists() (py42.sdk.queries.fileevents.filters.print_filter.filterExists()filterExistsForPrint(py42.sdk.queries.fileevents.v2.filters.file.Category)
    class method), 99
    class method), 130
not_exists() (py42.sdk.queries.fileevents.filters.risk_filter.filterExists()filterExistsForRisk(py42.sdk.queries.fileevents.v2.filters.file.CategoryByBytes)
    class method), 103
    class method), 130
not_exists() (py42.sdk.queries.fileevents.filters.risk_filter.filterExists()filterExistsForRisk(py42.sdk.queries.fileevents.v2.filters.file.CategoryByExtension)
    class method), 104
    class method), 131
not_exists() (py42.sdk.queries.fileevents.v2.filters.destination.notExists()notExistsForDestination(py42.sdk.queries.fileevents.v2.filters.file.Classification)
    class method), 109
    class method), 132
not_exists() (py42.sdk.queries.fileevents.v2.filters.destination.notExists()notExistsForDestination(py42.sdk.queries.fileevents.v2.filters.file.CloudDriveId)
    class method), 110
    class method), 132
not_exists() (py42.sdk.queries.fileevents.v2.filters.destination.notExists()notExistsForDestination(py42.sdk.queries.fileevents.v2.filters.file.Directory)
    class method), 112
    class method), 134
not_exists() (py42.sdk.queries.fileevents.v2.filters.destination.notExists()notExistsForDestination(py42.sdk.queries.fileevents.v2.filters.file.DirectoryId)
    class method), 113
    class method), 135

```

```
not_exists() (py42.sdk.queries.fileevents.v2.filters.file.Id not_exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMedia
    class method), 135                                         class method), 168
not_exists() (py42.sdk.queries.fileevents.v2.filters.file.MD5 not_exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMedia
    class method), 136                                         class method), 169
not_exists() (py42.sdk.queries.fileevents.v2.filters.file.MinifyType not_exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMedia
    class method), 137                                         class method), 170
not_exists() (py42.sdk.queries.fileevents.v2.filters.file.MinifyType not_exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMedia
    class method), 137                                         class method), 170
not_exists() (py42.sdk.queries.fileevents.v2.filters.file.Nan not_exists() (py42.sdk.queries.fileevents.v2.filters.source.RemovableMedia
    class method), 139                                         class method), 171
not_exists() (py42.sdk.queries.fileevents.v2.filters.file.Owner not_exists() (py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors
    class method), 140                                         class method), 172
not_exists() (py42.sdk.queries.fileevents.v2.filters.file.SHA256 not_exists() (py42.sdk.queries.fileevents.v2.filters.source.TabTitles
    class method), 140                                         class method), 172
not_exists() (py42.sdk.queries.fileevents.v2.filters.file.Url not_exists() (py42.sdk.queries.fileevents.v2.filters.source.TabUrlErrors
    class method), 142                                         class method), 173
not_exists() (py42.sdk.queries.fileevents.v2.filters.processedTime not_exists() (py42.sdk.queries.fileevents.v2.filters.source.TabUrls
    class method), 143                                         class method), 174
not_exists() (py42.sdk.queries.fileevents.v2.filters.processedTime not_exists() (py42.sdk.queries.fileevents.v2.filters.user.DeviceUid
    class method), 143                                         class method), 176
not_exists() (py42.sdk.queries.fileevents.v2.filters.reporter not_exists() (py42.sdk.queries.fileevents.v2.filters.user.Email
    class method), 144                                         class method), 177
not_exists() (py42.sdk.queries.fileevents.v2.filters.reporter not_exists() (py42.sdk.queries.fileevents.v2.filters.user.Id
    class method), 145                                         class method), 177
not_exists() (py42.sdk.queries.fileevents.v2.filters.reporter not_exists() (py42.sdk.queries.alerts.filters.alert_filter.Actor
    class method), 146                                         class method), 26
not_exists() (py42.sdk.queries.fileevents.v2.filters.reporter not_exists() (py42.sdk.queries.alerts.filters.alert_filter.AlertState
    class method), 146                                         class method), 27
not_exists() (py42.sdk.queries.fileevents.v2.filters.reporter not_exists() (py42.sdk.queries.alerts.filters.alert_filter.Description
    class method), 147                                         class method), 28
not_exists() (py42.sdk.queries.fileevents.v2.filters.reporter not_exists() (py42.sdk.queries.alerts.filters.alert_filter.RuleId
    class method), 148                                         class method), 29
not_exists() (py42.sdk.queries.fileevents.v2.filters.risk.Infection not_exists() (py42.sdk.queries.alerts.filters.alert_filter.RuleName
    class method), 155                                         class method), 30
not_exists() (py42.sdk.queries.fileevents.v2.filters.risk.Sensitivity not_exists() (py42.sdk.queries.alerts.filters.alert_filter.RuleSource
    class method), 157                                         class method), 31
not_exists() (py42.sdk.queries.fileevents.v2.filters.sourceContainer not_exists() (py42.sdk.queries.alerts.filters.alert_filter.RuleType
    class method), 160                                         class method), 31
not_exists() (py42.sdk.queries.fileevents.v2.filters.sourceContainer not_exists() (py42.sdk.queries.alerts.filters.alert_filter.Severity
    class method), 161                                         class method), 32
not_exists() (py42.sdk.queries.fileevents.v2.filters.sourceContainer not_exists() (py42.sdk.queries.filters.cloud_filter.Actor
    class method), 163                                         class method), 81
not_exists() (py42.sdk.queries.fileevents.v2.filters.sourceContainer not_exists() (py42.sdk.queries.filters.cloud_filter.DirectoryID
    class method), 164                                         class method), 82
not_exists() (py42.sdk.queries.fileevents.v2.filters.sourceContainer not_exists() (py42.sdk.queries.filters.cloud_filter.SharedWith
    class method), 164                                         class method), 83
not_exists() (py42.sdk.queries.fileevents.v2.filters.sourceContainer not_exists() (py42.sdk.queries.filters.cloud_filter.SharingTypeAdded
    class method), 165                                         class method), 84
not_exists() (py42.sdk.queries.fileevents.v2.filters.sourceContainer not_exists() (py42.sdk.queries.filters.device_filter.DeviceSignedInUser
    class method), 166                                         class method), 80
not_exists() (py42.sdk.queries.fileevents.v2.filters.sourceContainer not_exists() (py42.sdk.queries.filters.device_filter.DeviceUsername
    class method), 167                                         class method), 77
not_exists() (py42.sdk.queries.fileevents.v2.filters.sourceContainer not_exists() (py42.sdk.queries.filters.device_filter.OSHostname
    class method), 167                                         class method), 78
```

not_in() (py42.sdk.queries.fileevents.filters.device_filter.PrioritizeDDos) (py42.sdk.queries.fileevents.filters.file_filter.SHA256 class method), 79
 not_in() (py42.sdk.queries.fileevents.filters.device_filter.PrioritizeDDos) (py42.sdk.queries.fileevents.filters.print_filter.Printer class method), 77
 not_in() (py42.sdk.queries.fileevents.filters.device_filter.PrioritizeDDos) (py42.sdk.queries.fileevents.filters.print_filter.Printer class method), 80
 not_in() (py42.sdk.queries.fileevents.filters.email_filter.EmailFrom) (py42.sdk.queries.fileevents.filters.print_filter.PrintJobName class method), 97
 not_in() (py42.sdk.queries.fileevents.filters.email_filter.EmailFrom) (py42.sdk.queries.fileevents.filters.risk_filter.RiskIndicator class method), 98
 not_in() (py42.sdk.queries.fileevents.filters.email_filter.EmailFrom) (py42.sdk.queries.fileevents.filters.risk_filter.RiskScore class method), 99
 not_in() (py42.sdk.queries.fileevents.filters.email_filter.EmailFrom) (py42.sdk.queries.fileevents.filters.risk_filter.RiskSeverity class method), 103
 not_in() (py42.sdk.queries.fileevents.filters.email_filter.EmailRecipient) (py42.sdk.queries.fileevents.filters.risk_filter.RiskScore class method), 96
 not_in() (py42.sdk.queries.fileevents.filters.email_filter.EmailRecipient) (py42.sdk.queries.fileevents.filters.risk_filter.RiskSeverity class method), 105
 not_in() (py42.sdk.queries.fileevents.filters.email_filter.EmailSender) (py42.sdk.queries.fileevents.filters.risk_filter.RiskSeverity class method), 96
 not_in() (py42.sdk.queries.fileevents.filters.email_filter.EmailSubject) (py42.sdk.queries.v2.filters.destination.Category class method), 109
 not_in() (py42.sdk.queries.fileevents.filters.event_filter.EventTyping) (py42.sdk.queries.v2.filters.destination.EmailRecipient class method), 69
 not_in() (py42.sdk.queries.fileevents.filters.event_filter.SomewhatIn) (py42.sdk.queries.v2.filters.destination.EmailSubject class method), 71
 not_in() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType) (py42.sdk.queries.v2.filters.destination.IpAddress class method), 85
 not_in() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType) (py42.sdk.queries.v2.filters.destination.Name class method), 86
 not_in() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType) (py42.sdk.queries.v2.filters.destination.OperatingSystem class method), 86
 not_in() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType) (py42.sdk.queries.v2.filters.destination.PrintedFilesBackups class method), 89
 not_in() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType) (py42.sdk.queries.v2.filters.destination.PrinterName class method), 87
 not_in() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType) (py42.sdk.queries.v2.filters.destination.PrintJobName class method), 90
 not_in() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType) (py42.sdk.queries.v2.filters.destination.PrivateIpAddress class method), 91
 not_in() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType) (py42.sdk.queries.v2.filters.destination.RemovableMediaBackups class method), 88
 not_in() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType) (py42.sdk.queries.v2.filters.destination.RemovableMediaBackups class method), 89
 not_in() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType) (py42.sdk.queries.v2.filters.destination.RemovableMediaBackups class method), 92
 not_in() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType) (py42.sdk.queries.v2.filters.destination.RemovableMediaBackups class method), 93
 not_in() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType) (py42.sdk.queries.v2.filters.destination.RemovableMediaBackups class method), 93
 not_in() (py42.sdk.queries.fileevents.filters.exposure_filter.ExposureType) (py42.sdk.queries.v2.filters.destination.RemovableMediaBackups class method), 94
 not_in() (py42.sdk.queries.fileevents.filters.file_filter.FileCategory) (py42.sdk.queries.v2.filters.destination.RemovableMediaBackups class method), 73
 not_in() (py42.sdk.queries.fileevents.filters.file_filter.FileCategory) (py42.sdk.queries.v2.filters.destination.RemovableMediaBackups class method), 74
 not_in() (py42.sdk.queries.fileevents.filters.file_filter.FileCategory) (py42.sdk.queries.v2.filters.destination.RemovableMediaBackups class method), 121
 not_in() (py42.sdk.queries.fileevents.filters.file_filter.FileCategory) (py42.sdk.queries.v2.filters.destination.TabTitleErrors class method), 74
 not_in() (py42.sdk.queries.fileevents.filters.file_filter.FilePath) (py42.sdk.queries.v2.filters.destination.TabTitles class method), 75
 not_in() (py42.sdk.queries.fileevents.filters.file_filter.MD5not_in) (py42.sdk.queries.v2.filters.destination.TabUrlErrors class method), 76
 not_in() (py42.sdk.queries.fileevents.filters.file_filter.MD5not_in) (py42.sdk.queries.v2.filters.destination.TabUrlErrors class method), 123

not_in() (py42.sdk.queries.fileevents.v2.filters.destination.**NotIn**) (py42.sdk.queries.fileevents.v2.filters.report.Name
class method), 123
not_in() (py42.sdk.queries.fileevents.v2.filters.destination.**NotIn**) (py42.sdk.queries.fileevents.v2.filters.report.Type
class method), 148
not_in() (py42.sdk.queries.fileevents.v2.filters.event.Action.**not_in**) (py42.sdk.queries.fileevents.v2.filters.risk.Indicators
class method), 125
not_in() (py42.sdk.queries.fileevents.v2.filters.event.Id not_in) (py42.sdk.queries.fileevents.v2.filters.risk.IndicatorsWeight
class method), 126
not_in() (py42.sdk.queries.fileevents.v2.filters.event.Observation.**not_in**) (py42.sdk.queries.fileevents.v2.filters.risk.Score
class method), 128
not_in() (py42.sdk.queries.fileevents.v2.filters.event.Share.**not_in**) (py42.sdk.queries.fileevents.v2.filters.risk.Severity
class method), 128
not_in() (py42.sdk.queries.fileevents.v2.filters.file.Category.**not_in**) (py42.sdk.queries.fileevents.v2.filters.risk.TrustReason
class method), 130
not_in() (py42.sdk.queries.fileevents.v2.filters.file.Category.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.Category
class method), 130
not_in() (py42.sdk.queries.fileevents.v2.filters.file.Category.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.Domain
class method), 131
not_in() (py42.sdk.queries.fileevents.v2.filters.file.Classification.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.EmailFrom
class method), 132
not_in() (py42.sdk.queries.fileevents.v2.filters.file.CloudDrive.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.EmailSender
class method), 132
not_in() (py42.sdk.queries.fileevents.v2.filters.file.Directory.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.IpAddress
class method), 134
not_in() (py42.sdk.queries.fileevents.v2.filters.file.Directory.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.Name
class method), 135
not_in() (py42.sdk.queries.fileevents.v2.filters.file.Id not_in) (py42.sdk.queries.fileevents.v2.filters.source.OperatingSystem
class method), 135
not_in() (py42.sdk.queries.fileevents.v2.filters.file.MD5 not_in) (py42.sdk.queries.fileevents.v2.filters.source.PrivateIpAddress
class method), 136
not_in() (py42.sdk.queries.fileevents.v2.filters.file.MimeType.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaBu
class method), 137
not_in() (py42.sdk.queries.fileevents.v2.filters.file.MimeType.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaCa
class method), 137
not_in() (py42.sdk.queries.fileevents.v2.filters.file.Name not_in) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaMe
class method), 139
not_in() (py42.sdk.queries.fileevents.v2.filters.file.Owner not_in) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaNa
class method), 140
not_in() (py42.sdk.queries.fileevents.v2.filters.file.SHA256.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaPa
class method), 140
not_in() (py42.sdk.queries.fileevents.v2.filters.file.Url not_in) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaSe
class method), 142
not_in() (py42.sdk.queries.fileevents.v2.filters.process.Exe.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVe
class method), 143
not_in() (py42.sdk.queries.fileevents.v2.filters.process.Own.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.RemovableMediaVo
class method), 143
not_in() (py42.sdk.queries.fileevents.v2.filters.report.Count.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.TabTitleErrors
class method), 144
not_in() (py42.sdk.queries.fileevents.v2.filters.report.Description.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.TabTitles
class method), 145
not_in() (py42.sdk.queries.fileevents.v2.filters.report.Header.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.TabUrlErrors
class method), 146
not_in() (py42.sdk.queries.fileevents.v2.filters.report.ID not_in) (py42.sdk.queries.fileevents.v2.filters.source.TabUrls
class method), 147
not_in() (py42.sdk.queries.fileevents.v2.filters.report.Name.**not_in**) (py42.sdk.queries.fileevents.v2.filters.source.TabUrls
class method), 147

not_in() (py42.sdk.queries.fileevents.v2.filters.user.DeviceId same_day() (py42.sdk.queries.alerts.filters.alert_filter.DateObserved class method), 176
not_in() (py42.sdk.queries.fileevents.v2.filters.user.Email on_same_day() (py42.sdk.queries.fileevents.filters.event_filter.EventTimestamp class method), 177
not_in() (py42.sdk.queries.fileevents.v2.filters.user.Id on_same_day() (py42.sdk.queries.fileevents.filters.event_filter.InsertionTime class method), 178
not_in() (py42.sdk.queries.query_filter.QueryFilterStringFinal same_day() (py42.sdk.queries.fileevents.v2.filters.event.Inserted class method), 189
notes (py42.clients.settings.device_settings.DeviceSettings on_same_day() (py42.sdk.queries.fileevents.v2.filters.file.Created class method), 53
notes (py42.clients.settings.device_settings.IncydrDeviceSetting on_same_day() (py42.sdk.queries.fileevents.v2.filters.file.Modified class method), 52
notes (py42.clients.settings.org_settings.OrgSettings attribute), 185
on_same_day() (py42.sdk.queries.fileevents.v2.filters.file.Size class method), 141
on_same_day() (py42.sdk.queries.fileevents.v2.filters.timestamp.Timestamp class method), 175
O
Observer (class in py42.sdk.queries.fileevents.v2.filters.event), 127
on_or_after() (py42.sdk.queries.alerts.filters.alert_filter.OperatingSystem (class in py42.sdk.queries.fileevents.v2.filters.destination), 27
on_or_after() (py42.sdk.queries.fileevents.filters.event_filter.EventTimestamp 111 OperatingSystem (class in py42.sdk.queries.fileevents.v2.filters.destination), 68
on_or_after() (py42.sdk.queries.fileevents.filters.event_filter.InsertionTimestamp 111 (py42.sdk.queries.fileevents.v2.filters.source), 164
on_or_after() (py42.sdk.queries.fileevents.v2.filters.event.Inserted operator (py42.sdk.queries.query_filter.QueryFilter property), 189
on_or_after() (py42.sdk.queries.fileevents.v2.filters.file.Created org_backup_quota (py42.clients.settings.org_settings.OrgSettings attribute), 185
on_or_after() (py42.sdk.queries.fileevents.v2.filters.file.Modified org_id (py42.clients.settings.device_settings.DeviceSettings property), 53
on_or_after() (py42.sdk.queries.fileevents.v2.filters.file.Size org_id (py42.clients.settings.device_settings.IncydrDeviceSettings property), 52
on_or_after() (py42.sdk.queries.fileevents.v2.filters.timestamp.org_id (py42.clients.settings.org_settings.OrgSettings property), 185
on_or_after() (py42.sdk.queries.fileevents.v2.filters.timestamp.org_id (py42.clients.settings.org_settings.OrgSettings property), 175
on_or_after() (py42.sdk.queries.query_filter.QueryFilter org_name (py42.clients.settings.org_settings.OrgSettings attribute), 185
on_or_before() (py42.sdk.queries.alerts.filters.alert_filter.DateObserved(py42.exceptions.Py42NotFoundError property), 60
on_or_before() (py42.sdk.queries.fileevents.filters.event_filter.event_timestamp (py42.sdk.SDKClient property), 205
on_or_before() (py42.sdk.queries.fileevents.filters.event_filter.event_timestamp (py42.services.orgs.OrgService (class in py42.services.orgs), 182
on_or_before() (py42.sdk.queries.fileevents.filters.event_filter.InsertionTimestamp (class in py42.clients.settings.org_settings), 184
on_or_before() (py42.sdk.queries.fileevents.v2.filters.event.Inserted OSHostname (class in py42.sdk.queries.fileevents.filters.device_filter), 78
on_or_before() (py42.sdk.queries.fileevents.v2.filters.file.Created outsideActiveHours (class in py42.sdk.queries.fileevents.filters.event_filter), 133
on_or_before() (py42.sdk.queries.fileevents.v2.filters.file.Modified 71 Owner (class in py42.sdk.queries.fileevents.v2.filters.file), 138
on_or_before() (py42.sdk.queries.fileevents.v2.filters.file.Size 139 Owner (class in py42.sdk.queries.fileevents.v2.filters.process), 141
on_or_before() (py42.sdk.queries.fileevents.v2.filters.timestamp.Timestamp 143
P
on_or_before() (py42.sdk.queries.query_filter.QueryFilterTimestampField packets (py42.clients.settings.org_settings.OrgSettings class method), 190

property), 185
page_token(py42.exceptions.Py42InvalidPageTokenError property), 58
print_response() (in module py42.util), 200
PrintedFilesBackupPath (class) in py42.sdk.queries.fileevents.v2.filters.destination), 113
Printer (class in py42.sdk.queries.fileevents.filters.print_filter), 98
PrinterName (class) in py42.sdk.queries.fileevents.v2.filters.destination), 113
PrintJobName (class) in py42.sdk.queries.fileevents.filters.print_filter), 98
PrintJobName (class) in py42.sdk.queries.fileevents.v2.filters.destination), 112
PrivateIPAddress (class) in py42.sdk.queries.fileevents.filters.device_filter), 78
PrivateIpAddress (class) in py42.sdk.queries.fileevents.v2.filters.destination), 114
PrivateIpAddress (class) in py42.sdk.queries.fileevents.v2.filters.source), 165
ProcessName (class) in py42.sdk.queries.fileevents.filters.exposure_filter), 85
ProcessOwner (class) in py42.sdk.queries.fileevents.filters.exposure_filter), 86
PublicIPAddress (class) in py42.sdk.queries.fileevents.filters.device_filter), 79
py42.exceptions module, 54
py42.sdk module, 203
py42.sdk.queries.alerts.filters.alert_filter module, 25
py42.sdk.queries.fileevents.v2.filters.destination module, 107
py42.sdk.queries.fileevents.v2.filters.event module, 124
py42.sdk.queries.fileevents.v2.filters.file module, 129
py42.sdk.queries.fileevents.v2.filters.process module, 142
py42.sdk.queries.fileevents.v2.filters.report module, 144
py42.sdk.queries.fileevents.v2.filters.risk module, 148
py42.sdk.queries.fileevents.v2.filters.source module, 159
py42.sdk.queries.fileevents.v2.filters.timestamp module, 174
py42.sdk.queries.fileevents.v2.filters.user module, 176
py42.sdk.queries.query_filter
py42.util module, 199
Py42ActiveLegalHoldError, 54
Py42ArchiveNotFoundError, 54
Py42BadRequestError, 54
Py42BadRestoreRequestError, 54
Py42CaseAlreadyHasEventError, 54
Py42CaseNameExistsError, 55
Py42ChecksumNotFoundError, 55
Py42CloudAliasCharacterLimitExceededError, 55
Py42CloudAliasLimitExceededError, 55
Py42ConflictError, 55
Py42DescriptionLimitExceededError, 56
Py42DeviceNotConnectedError, 56
Py42Error, 56
Py42FeatureUnavailableError, 56
Py42ForbiddenError, 56
Py42HTTPError, 56
Py42InternalServerError, 57
Py42InvalidArchiveEncryptionKey, 57
Py42InvalidArchivePassword, 57
Py42InvalidCaseUserError, 57
Py42InvalidEmailError, 57
Py42InvalidPageTokenError, 57
Py42InvalidPasswordError, 58
Py42InvalidRuleError, 58
Py42InvalidRuleOperationError, 58
Py42InvalidUsernameError, 58
Py42InvalidWatchlistType, 59
Py42LegalHoldAlreadyActiveError, 59
Py42LegalHoldAlreadyDeactivatedError, 59
Py42LegalHoldCriteriaMissingError, 59
Py42LegalHoldNotFoundOrPermissionDeniedError, 59
Py42MFARquiredError, 60
Py42NotFoundError, 60
Py42OrgNotFoundError, 60
Py42Response (class in py42.response), 186
Py42ResponseError, 60
Py42SessionInitializationError, 60
Py42StorageSessionInitializationError, 60
Py42TooManyRequestsError, 61
Py42TrustedActivityConflictError, 61
Py42TrustedActivityIdNotFoundError, 61
Py42TrustedActivityInvalidChangeError, 61
Py42TrustedActivityInvalidCharacterError, 61

Py42UnableToCreateProfileError, 62
 Py42UnauthorizedError, 62
 Py42UpdateClosedCaseError, 62
 Py42UserAlreadyAddedError, 62
 Py42UserAlreadyExistsError, 62
 Py42UsernameMustBeEmailError, 63
 Py42UserNotOnListError, 63
 Py42UserRiskProfileNotFound, 63
 Py42WatchlistNotFound, 63
 Py42WatchlistOrUserNotFound, 64

Q

QueryFilter (*class* in *py42.sdk.queries.query_filter*), 188
 QueryFilterBooleanField (*class* in *py42.sdk.queries.query_filter*), 189
 QueryFilterStringField (*class* in *py42.sdk.queries.query_filter*), 189
 QueryFilterTimestampField (*class* in *py42.sdk.queries.query_filter*), 190
 quota_settings_inherited (*py42.clients.settings.org_settings.OrgSettings attribute*), 185

R

raise_py42_error() (*in module py42.exceptions*), 64
 raw_text (*py42.response.Py42Response property*), 187
 reactivate() (*py42.services.devices.DeviceService method*), 51
 reactivate() (*py42.services.orgs.OrgService method*), 183
 reactivate() (*py42.services.users.UserService method*), 198
 reactivate_matter() (*py42.services.legalhold.LegalHoldService method*), 181
 refresh_user_scim_attributes() (*py42.clients.detectionlists.DetectionListsClient method*), 44
 registration_key (*py42.clients.settings.org_settings.OrgSettings property*), 185
 RemoteActivity (*class* in *py42.sdk.queries.fileevents.filters.activity_filter*), 97
 RemovableMediaBusType (*class* in *py42.sdk.queries.fileevents.v2.filters.destination*), 115
 RemovableMediaBusType (*class* in *py42.sdk.queries.fileevents.v2.filters.source*), 165
 RemovableMediaCapacity (*class* in *py42.sdk.queries.fileevents.v2.filters.destination*), 116

RemovableMediaCapacity (*class* in *py42.sdk.queries.fileevents.v2.filters.source*), 166
 RemovableMediaMediaName (*class* in *py42.sdk.queries.fileevents.filters.exposure_filter*), 88
 RemovableMediaMediaName (*class* in *py42.sdk.queries.fileevents.v2.filters.destination*), 116
 RemovableMediaMediaName (*class* in *py42.sdk.queries.fileevents.v2.filters.source*), 167
 RemovableMediaName (*class* in *py42.sdk.queries.fileevents.filters.exposure_filter*), 86
 RemovableMediaName (*class* in *py42.sdk.queries.fileevents.v2.filters.destination*), 117
 RemovableMediaName (*class* in *py42.sdk.queries.fileevents.v2.filters.source*), 168
 RemovableMediaPartitionID (*class* in *py42.sdk.queries.fileevents.filters.exposure_filter*), 89
 RemovableMediaPartitionID (*class* in *py42.sdk.queries.fileevents.v2.filters.destination*), 118
 RemovableMediaPartitionID (*class* in *py42.sdk.queries.fileevents.v2.filters.source*), 168
 RemovableMediaSerialNumber (*class* in *py42.sdk.queries.fileevents.filters.exposure_filter*), 90
 RemovableMediaSerialNumber (*class* in *py42.sdk.queries.fileevents.v2.filters.destination*), 118
 RemovableMediaSerialNumber (*class* in *py42.sdk.queries.fileevents.v2.filters.source*), 169
 RemovableMediaVendor (*class* in *py42.sdk.queries.fileevents.filters.exposure_filter*), 87
 RemovableMediaVendor (*class* in *py42.sdk.queries.fileevents.v2.filters.destination*), 119
 RemovableMediaVendor (*class* in *py42.sdk.queries.fileevents.v2.filters.source*), 170
 RemovableMediaVolumeName (*class* in *py42.sdk.queries.fileevents.filters.exposure_filter*), 89
 RemovableMediaVolumeName (*class* in *py42.sdk.queries.fileevents.v2.filters.destination*), 120

RemovableMediaVolumeName (class in response (py42.exceptions.Py42ChecksumNotFoundError
py42.sdk.queries.fileevents.v2.filters.source),
170
remove() (py42.services.detectionlists.departing_employee.DepartingEmployeeService
method), 46
remove() (py42.services.detectionlists.high_risk_employee.HighRiskEmployeeService
method), 49
remove_all_users() (py42.clients.alertrules.AlertRulesClient
method), 22
remove_destination()
(py42.clients.settings.device_settings.BackupSet
method), 38
remove_from_matter()
(py42.services.legalhold.LegalHoldService
method), 181
remove_included_users_by_watchlist_id()
(py42.clients.watchlists.WatchlistsClient
method), 202
remove_included_users_by_watchlist_type()
(py42.clients.watchlists.WatchlistsClient
method), 202
remove_role() (py42.services.users.UserService
method), 198
remove_user() (py42.clients.alertrules.AlertRulesClient
method), 22
remove_user_cloud_alias()
(py42.clients.detectionlists.DetectionListsClient
method), 45
remove_user_risk_tags()
(py42.clients.detectionlists.DetectionListsClient
method), 45
reopen() (py42.clients.alerts.AlertsClient method), 24
reporting_settings_inherited
(py42.clients.settings.org_settings.OrgSettings
attribute), 185
resolve() (py42.clients.alerts.AlertsClient method), 24
resource (py42.exceptions.Py42ActiveLegalHoldError
property), 54
resource_id (py42.exceptions.Py42ActiveLegalHoldError
property), 54
resource_id (py42.exceptions.Py42TrustedActivityIdNotFoundError
property), 61
response (py42.exceptions.Py42ActiveLegalHoldError
property), 54
response (py42.exceptions.Py42ArchiveFileNotFoundException
property), 54
response (py42.exceptions.Py42BadRequestError prop-
erty), 54
response (py42.exceptions.Py42BadRestoreRequestError
property), 54
response (py42.exceptions.Py42CaseAlreadyHasEventError
property), 54
response (py42.exceptions.Py42CaseNameExistsError
property), 55
in response (py42.exceptions.Py42ChecksumNotFoundError
property), 55
response (py42.exceptions.Py42CloudAliasLimitExceededError
response (py42.exceptions.Py42ConflictError prop-
erty), 55
response (py42.exceptions.Py42DescriptionLimitExceededError
property), 56
response (py42.exceptions.Py42DeviceNotConnectedError
property), 56
response (py42.exceptions.Py42FeatureUnavailableError
property), 56
response (py42.exceptions.Py42ForbiddenError prop-
erty), 56
response (py42.exceptions.Py42HTTPSError property),
56
response (py42.exceptions.Py42InternalServerError
property), 57
response (py42.exceptions.Py42InvalidArchiveEncryptionKey
property), 57
response (py42.exceptions.Py42InvalidArchivePassword
property), 57
response (py42.exceptions.Py42InvalidCaseUserError
property), 57
response (py42.exceptions.Py42InvalidEmailError
property), 57
response (py42.exceptions.Py42InvalidPageTokenError
property), 58
response (py42.exceptions.Py42InvalidPasswordError
property), 58
response (py42.exceptions.Py42InvalidRuleError prop-
erty), 58
response (py42.exceptions.Py42InvalidRuleOperationError
property), 58
response (py42.exceptions.Py42InvalidUsernameError
property), 58
response (py42.exceptions.Py42InvalidWatchlistType
property), 59
response (py42.exceptions.Py42LegalHoldAlreadyActiveError
property), 59
response (py42.exceptions.Py42LegalHoldAlreadyDeactivatedError
property), 59
response (py42.exceptions.Py42LegalHoldCriteriaMissingError
property), 59
response (py42.exceptions.Py42LegalHoldNotFoundOrPermissionDenied
property), 59
response (py42.exceptions.Py42MFARequiredError
property), 60
response (py42.exceptions.Py42NotFoundError prop-
erty), 60
response (py42.exceptions.Py42OrgNotFoundError
property), 60
response (py42.exceptions.Py42ResponseError prop-
erty), 60

```

response (py42.exceptions.Py42StorageSessionInitializationError  in py42.sdk.queries.fileevents.filters.risk_filter),
         property), 61
102
response (py42.exceptions.Py42TooManyRequestsError  RiskIndicator.Other      (class      in
         property), 61
py42.sdk.queries.fileevents.filters.risk_filter),
102
response (py42.exceptions.Py42TrustedActivityConflictError   RiskIndicator.SocialMediaUploads  (class      in
         property), 61
py42.sdk.queries.fileevents.filters.risk_filter),
102
response (py42.exceptions.Py42TrustedActivityInvalidCharacterError RiskIndicator.UserBehavior    (class      in
         property), 61
py42.sdk.queries.fileevents.filters.risk_filter),
102
response (py42.exceptions.Py42TrustedActivityInvalidCharacterError RiskScore (class in py42.sdk.queries.fileevents.filters.risk_filter),
         property), 62
104
response (py42.exceptions.Py42UnableToCreateProfileError   RiskSeverity      (class      in
         property), 62
py42.sdk.queries.fileevents.filters.risk_filter),
103
response (py42.exceptions.Py42UnauthorizedError   rule_id (py42.exceptions.Py42InvalidRuleError prop-
         property), 62
erty), 58
response (py42.exceptions.Py42UserAlreadyAddedError   rule_id (py42.exceptions.Py42InvalidRuleOperationError
         property), 63
property), 58
response (py42.exceptions.Py42UsernameMustBeEmailError RuleId (class in py42.sdk.queries.alerts.filters.alert_filter),
         property), 63
29
response (py42.exceptions.Py42UserNotOnListError   RuleName (class in py42.sdk.queries.alerts.filters.alert_filter),
         property), 63
29
response (py42.exceptions.Py42UserRiskProfileNotFound rules (py42.clients.alerts.AlertsClient property), 24
         property), 63
RuleSource (class in py42.sdk.queries.alerts.filters.alert_filter),
30
RuleType (class in py42.sdk.queries.alerts.filters.alert_filter),
31
response (py42.exceptions.Py42WatchlistOrUserNotFound   S
         property), 64
RiskIndicator      (class      in
                  py42.sdk.queries.fileevents.filters.risk_filter),
99
RiskIndicator.CloudDataExposures (class in
                  py42.sdk.queries.fileevents.filters.risk_filter),
101
RiskIndicator.CloudStorageUploads (class in
                  py42.sdk.queries.fileevents.filters.risk_filter),
101
RiskIndicator.CodeRepositoryUploads (class in
                  py42.sdk.queries.fileevents.filters.risk_filter),
101
RiskIndicator.EmailServiceUploads (class in
                  py42.sdk.queries.fileevents.filters.risk_filter),
101
RiskIndicator.ExternalDevices (class in
                  py42.sdk.queries.fileevents.filters.risk_filter),
101
RiskIndicator.FileCategories (class in
                  py42.sdk.queries.fileevents.filters.risk_filter),
102
RiskIndicator.MessagingServiceUploads (class
                  in
py42.clients.securitydata.SecurityDataClient
property), 187
SavedSearchService      (class      in
py42.services.savedsearch), 65
Score (class in py42.sdk.queries.fileevents.v2.filters.risk),
156
SDKClient (class in py42.sdk), 203
search() (py42.clients.alerts.AlertsClient method), 24
search_all_file_events()
         (py42.clients.securitydata.SecurityDataClient
method), 187
search_all_pages() (py42.clients.alerts.AlertsClient
method), 25
search_file_events()
         (py42.clients.securitydata.SecurityDataClient
method), 187
search_file_events()
         (py42.services.savedsearch.SavedSearchService
method), 66
securitydata (py42.sdk.SDKClient property), 205

```

SecurityDataClient (class in <code>py42.clients.securitydata</code>), 187 serveradmin (<code>py42.sdk.SDKClient</code> property), 205 set_alerts_enabled() (<code>py42.services.detectionlists.departing_employee.DepartingEmployeeService</code> method), 47 set_alerts_enabled() (<code>py42.services.detectionlists.high_risk_employee.HighRiskEmployeeService</code> method), 49 Severity (class in <code>py42.sdk.queries.alerts.filters.alert_filter</code>), 32 Severity (class in <code>py42.sdk.queries.fileevents.v2.filters.risk</code>), 157 SHA256 (class in <code>py42.sdk.queries.fileevents.filters.file_filter</code>), 76 SHA256 (class in <code>py42.sdk.queries.fileevents.v2.filters.file</code>), 140 Shared (class in <code>py42.sdk.queries.fileevents.filters.cloud_filter</code>), 82 SharedWith (class in <code>py42.sdk.queries.fileevents.filters.cloud_filter</code>), 82 ShareType (class in <code>py42.sdk.queries.fileevents.v2.filters.event</code>), 128 SharingTypeAdded (class in <code>py42.sdk.queries.fileevents.filters.cloud_filter</code>), 83 Size (class in <code>py42.sdk.queries.fileevents.v2.filters.file</code>), 141 SortDirection (class in <code>py42.constants</code>), 42 Source (class in <code>py42.sdk.queries.fileevents.filters.event_filter</code>), 70 source (<code>py42.exceptions.Py42InvalidRuleOperationError</code> property), 58 status_code (<code>py42.response.Py42Response</code> property), 187 stream_file_by_md5() (<code>py42.clients.securitydata.SecurityDataClient</code> method), 188 stream_file_by_sha256() (<code>py42.clients.securitydata.SecurityDataClient</code> method), 188 stream_from_backup() (<code>py42.clients.archive.ArchiveClient</code> method), 34 stream_to_device() (<code>py42.clients.archive.ArchiveClient</code> method), 35 SyncDestination (class in <code>py42.sdk.queries.fileevents.filters.exposure_filter</code>), 91 SyncDestinationUsername (class in <code>py42.sdk.queries.fileevents.filters.exposure_filter</code>), 92	T TabTitleErrors (class in <code>py42.sdk.queries.fileevents.v2.filters.destination</code>), 121 TabTitleErrors (<code>py42.sdk.queries.fileevents.v2.filters.source</code>), 171 TabTitles (class in <code>py42.sdk.queries.fileevents.v2.filters.destination</code>), 121 TabTitles (class in <code>py42.sdk.queries.fileevents.v2.filters.source</code>), 172 TabURL (class in <code>py42.sdk.queries.fileevents.filters.exposure_filter</code>), 93 TabUrlErrors (class in <code>py42.sdk.queries.fileevents.v2.filters.destination</code>), 122 TabUrlErrors (class in <code>py42.sdk.queries.fileevents.v2.filters.source</code>), 173 TabUrls (class in <code>py42.sdk.queries.fileevents.v2.filters.destination</code>), 123 TabUrls (class in <code>py42.sdk.queries.fileevents.v2.filters.source</code>), 173 term (<code>py42.sdk.queries.query_filter.QueryFilter</code> property), 189 text (<code>py42.response.Py42Response</code> property), 187 Timestamp (class in <code>py42.sdk.queries.fileevents.v2.filters.timestamp</code>), 174 Trusted (class in <code>py42.sdk.queries.fileevents.v2.filters.risk</code>), 159 trustedactivities (<code>py42.sdk.SDKClient</code> property), 205 TrustedActivitiesClient (class in <code>py42.clients.trustedactivities</code>), 192 TrustedActivity (class in <code>py42.sdk.queries.fileevents.filters.activity_filter</code>), 97 TrustedActivityType (class in <code>py42.clients.trustedactivities</code>), 192 TrustedActivityType (class in <code>py42.constants</code>), 43 TrustReason (class in <code>py42.sdk.queries.fileevents.v2.filters.risk</code>), 158 Type (class in <code>py42.sdk.queries.fileevents.v2.filters.report</code>), 147	U uid (<code>py42.exceptions.Py42LegalHoldNotFoundOrPermissionDeniedError</code> property), 60 unblock() (<code>py42.services.devices.DeviceService</code> method), 51 unblock() (<code>py42.services.orgs.OrgService</code> method), 184 unblock() (<code>py42.services.users.UserService</code> method), 198
--	---	---

unlock_destination()
 (py42.clients.settings.device_settings.BackupSet
 method), 38

update() (py42.clients.cases.CasesClient method), 41

update() (py42.clients.trustedactivities.TrustedActivitiesClient
 method), 193

update() (py42.clients.userriskprofile.UserRiskProfileClient
 method), 195

update_cold_storage_purge_date()
 (py42.clients.archive.ArchiveClient
 method), 36

update_departure_date()
 (py42.services.detectionlists.departing_employee
 method), 47

update_note() (py42.clients.alerts.AlertsClient
 method), 25

update_settings() (py42.services.devices.DeviceService
 method), 52

update_settings() (py42.services.orgs.OrgService
 method), 184

update_state() (py42.clients.alerts.AlertsClient
 method), 25

update_user() (py42.services.users.UserService
 method), 199

update_user_notes()
 (py42.clients.detectionlists.DetectionListsClient
 method), 45

upgrade() (py42.services.devices.DeviceService
 method), 52

Url (class in py42.sdk.queries.fleevents.v2.filters.file),
 141

url (py42.response.Py42Response property), 187

user (py42.exceptions.Py42InvalidCaseUserError prop-
 erty), 57

user (py42.exceptions.Py42UserRiskProfileNotFound
 property), 63

user_backup_quota (py42.clients.settings.org_settings.OrgSettings
 attribute), 186

user_id (py42.clients.settings.device_settings.DeviceSettings
 property), 53

user_id (py42.clients.settings.device_settings.IncydrDeviceSettings
 property), 52

user_id (py42.exceptions.Py42UserAlreadyAddedError
 property), 62

user_id (py42.exceptions.Py42UserNotOnListError
 property), 63

user_id (py42.exceptions.Py42WatchlistOrUserNotFound
 property), 64

UserContext (class in py42.usercontext), 199

usercontext (py42.sdk.SDKClient property), 205

UserEmail (class in py42.sdk.queries.flevents.v2.filters.destination)
 124

username (py42.exceptions.Py42UnableToCreateProfileError
 property), 62

userriskprofile (py42.sdk.SDKClient property), 205

UserRiskProfileClient (class in
 py42.clients.userriskprofile), 193

users (py42.sdk.SDKClient property), 205

UserService (class in py42.services.users), 196

V

value (py42.exceptions.Py42TrustedActivityConflictError
 property), 61

value (py42.sdk.queries.query_filter.QueryFilter prop-
 erty), 189

version (py42.clients.settings.device_settings.DeviceSettings
 DepartingEmployeeService)

version (py42.clients.settings.device_settings.IncydrDeviceSettings
 property), 52

W

warning_alert_days (py42.clients.settings.device_settings.DeviceSetting
 attribute), 53

warning_alert_days (py42.clients.settings.device_settings.DeviceSetting
 attribute), 186

warning_email_enabled
 (py42.clients.settings.device_settings.DeviceSettings
 attribute), 53

warning_email_enabled
 (py42.clients.settings.device_settings.DeviceSettingsDefaults
 attribute), 186

watchlist_id (py42.exceptions.Py42WatchlistNotFound
 property), 63

watchlist_id (py42.exceptions.Py42WatchlistOrUserNotFound
 property), 64

watchlist_type (py42.exceptions.Py42InvalidWatchlistType
 property), 59

watchlists (py42.sdk.SDKClient property), 205

WatchlistsClient (class in py42.clients.watchlists),
 200

WatchlistType (class in py42.clients.watchlists), 200

WatchlistType (class in py42.constants), 43

web_restore_admin_limit
 (py42.clients.settings.org_settings.OrgSettings
 attribute), 186

web_restore_enabled
 (py42.clients.settings.org_settings.OrgSettings
 attribute), 186

web_restore_user_limit
 (py42.clients.settings.org_settings.OrgSettings
 attribute), 186

WindowTitle (class in
 py42.sdk.queries.flevents.filters.exposure_filter),
 93

with_traceback() (py42.exceptions.Py42ActiveLegalHoldError
 method), 54

with_traceback() (py42.exceptions.Py42ArchiveFileNotFoundException
 method), 54

```
with_traceback() (py42.exceptions.Py42BadRequestError with_traceback() (py42.exceptions.Py42LegalHoldCriteriaMissingError
    method), 54                                         method), 59
with_traceback() (py42.exceptions.Py42BadRestoreRequest with_traceback() (py42.exceptions.Py42LegalHoldNotFoundOrPermission
    method), 54                                         method), 60
with_traceback() (py42.exceptions.Py42CaseAlreadyHas with_traceback() (py42.exceptions.Py42MFARequiredError
    method), 55                                         method), 60
with_traceback() (py42.exceptions.Py42CaseNameExists with_traceback() (py42.exceptions.Py42NotFoundError
    method), 55                                         method), 60
with_traceback() (py42.exceptions.Py42ChecksumNotFound with_traceback() (py42.exceptions.Py42OrgNotFoundError
    method), 55                                         method), 60
with_traceback() (py42.exceptions.Py42CloudAliasCh with_traceback() (py42.exceptions.Py42ResponseError
    method), 55                                         method), 60
with_traceback() (py42.exceptions.Py42CloudAliasLimit with_traceback() (py42.exceptions.Py42SessionInitializationError
    method), 55                                         method), 60
with_traceback() (py42.exceptions.Py42ConflictError with_traceback() (py42.exceptions.Py42StorageSessionInitializationError
    method), 55                                         method), 61
with_traceback() (py42.exceptions.Py42DescriptionLimit with_traceback() (py42.exceptions.Py42TooManyRequestsError
    method), 56                                         method), 61
with_traceback() (py42.exceptions.Py42DeviceNotConn with_traceback() (py42.exceptions.Py42TrustedActivityConflictError
    method), 56                                         method), 61
with_traceback() (py42.exceptions.Py42Error with_traceback() (py42.exceptions.Py42TrustedActivityIdNotFoundError
    method), 56                                         method), 61
with_traceback() (py42.exceptions.Py42FeatureUnavail with_traceback() (py42.exceptions.Py42TrustedActivityInvalidChangeError
    method), 56                                         method), 61
with_traceback() (py42.exceptions.Py42ForbiddenError with_traceback() (py42.exceptions.Py42TrustedActivityInvalidCharacter
    method), 56                                         method), 62
with_traceback() (py42.exceptions.Py42HTTPError with_traceback() (py42.exceptions.Py42UnableToCreateProfileError
    method), 56                                         method), 62
with_traceback() (py42.exceptions.Py42InternalServerError with_traceback() (py42.exceptions.Py42UnauthorizedError
    method), 57                                         method), 62
with_traceback() (py42.exceptions.Py42InvalidArchive with_traceback() (py42.exceptions.Py42UpdateClosedCaseError
    method), 57                                         method), 62
with_traceback() (py42.exceptions.Py42InvalidArchiveP with_traceback() (py42.exceptions.Py42UserAlreadyAddedError
    method), 57                                         method), 62
with_traceback() (py42.exceptions.Py42InvalidCaseUser with_traceback() (py42.exceptions.Py42UserAlreadyExistsError
    method), 57                                         method), 63
with_traceback() (py42.exceptions.Py42InvalidEmailEr with_traceback() (py42.exceptions.Py42UsernameMustBeEmailError
    method), 57                                         method), 63
with_traceback() (py42.exceptions.Py42InvalidPageTok with_traceback() (py42.exceptions.Py42UserNotOnListError
    method), 58                                         method), 63
with_traceback() (py42.exceptions.Py42InvalidPassword with_traceback() (py42.exceptions.Py42UserRiskProfileNotFound
    method), 58                                         method), 63
with_traceback() (py42.exceptions.Py42InvalidRuleError with_traceback() (py42.exceptions.Py42WatchlistNotFound
    method), 58                                         method), 63
with_traceback() (py42.exceptions.Py42InvalidRuleOpen with_traceback() (py42.exceptions.Py42WatchlistOrUserNotFound
    method), 58                                         method), 64
with_traceback() (py42.exceptions.Py42InvalidUsername with_in_the_last() (py42.sdk.queries.fileevents.filters.event_filter.EventT
    method), 58                                         class method), 68
with_traceback() (py42.exceptions.Py42InvalidWatchlist with_in_the_last() (py42.sdk.queries.fileevents.filters.event_filter.Inserti
    method), 59                                         class method), 70
with_traceback() (py42.exceptions.Py42LegalHoldAlready with_in_the_last() (py42.sdk.queries.fileevents.v2.filters.event.Inserted
    method), 59                                         class method), 127
with_traceback() (py42.exceptions.Py42LegalHoldAlready with_in_the_Last() (py42.sdk.queries.fileevents.v2.filters.file.Created
    method), 59                                         class method), 133
```

`within_the_last()` (*py42.sdk.queries.fileevents.v2.filters.file.Modified class method*), 138
`within_the_last()` (*py42.sdk.queries.fileevents.v2.filters.file.Size class method*), 141
`within_the_last()` (*py42.sdk.queries.fileevents.v2.filters.timestamp.Timestamp class method*), 175